samtec

QSTRIP®

(0,80mm) .0315"

QSE SERIES



HIGH SPEED GROUND PLANE SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?QSE

Insulator Material:
Liquid Crystal Polymer

Terminal Material:
Phosphor Bronze

Plating:
Au or Sn over 50µ" (1,27µm) Ni

Current Rating:
Contacts: 1.3A @ 95°C
Ground Plane: 10.1A @ 95°C

Operating Temp Range:
-55°C to +125°C

Voltage Rating:
225 VAC (5mm Stack Height)

Max Cycles:
100

Unmating Force (-RT1 option):
-RT1 option increases unmating force up to 50%

RoHS Compliant:
Yes

Processing:

Lead–Free Solderable:
Yes

SMT Lead Coplanarity:
(0,10mm) .004" max (020-060)
(0,15mm) .006" max (080)

Board Stacking:
For applications requiring more than two connectors per board or 4 banks or more, contact ipg@samtec.com

APPLICATION SPECIFIC OPTION

- 14mm, 15mm, 22mm and 30mm stack height (Caution: Some automatic placement/inspection machines may have component height restrictions. Please consult machinery specifications.)
- 30µ" (0,76µm) Gold (Specify -H plating for Data Rate cable mating applications.)
- Edge Mount
- 100 positions per row
- Guide Posts and Friction Lock options.

Call Samtec.

***Note:** –C Plating passes 10 year MFG testing

Note: Some lengths, styles and options are non-standard, non-returnable.

Board Mates:
QTE

Cable Mates:
EQCD, EQSD, EQDP, EQRF
(See Application Specific note)

E.L.P.™ EXTENDED LIFE PRODUCT
10 year Mixed Flowing Gas with 50µ" Gold
Call Samtec for maximum cycles mated with QTE



Final inch® Break Out Region Performance Certified finalinch.com

Protocols Supported
XAUI
PCI Express®
SATA
MGT (Rocket I/O)
InfiniBand™
Download app notes at www.samtec.com/appnote
Contact SIG @ samtec.com for questions on protocols

QTE/QSE 5mm Stack Height	Type	Rated @ 3dB Insertion Loss	
		with PCB effects*	w/o PCB effects**
Single-Ended Signaling	–D	9 GHz / 18 Gbps	7.5 GHz / 15 Gbps
Differential Pair Signaling	–D	8 GHz / 16 Gbps	8.5 GHz / 17 Gbps
Differential Pair Signaling	–DP	8.5 GHz / 17 Gbps	——

*Performance data includes effects of a non-optimized PCB.
**Test board losses de-embedded from performance data.

Performance data for other stack heights and complete test data available at www.samtec.com?QSE or contact sig@samtec.com

ALSO AVAILABLE
Board Spacing Standoffs. See SO Series.

QSE – PINS PER ROW NO. OF PAIRS – 01 – PLATING OPTION – TYPE – A – OTHER OPTION

–020, –040, –060, –080
(40 total pins per bank = –D)

–014, –028, –042, –056
(14 pairs per bank = –D–DP)



–F
= Gold Flash on Signal Pins and Ground Plane, Matte Tin on tails

–L
= 10µ" (0,25µm) Gold on Signal Pins and Ground Plane, Matte Tin on tails

–C*
= Electro-Polished Selective 50µ" (1,27µm) min Au over 150µ" (3,81µm) Ni on Signal Pins in contact area, 10µ" (0,25µm) min Au over 50µ" (1,27µm) Ni on Ground Plane in contact area, Matte Tin over 50µ" (1,27µm) min Ni on all solder tails

–D
= Single-Ended

–D–DP
= Differential Pair (–01 only)

QTE LEAD STYLE	MATED HEIGHT WITH QSE*
–01	(5,00) .197
–02	(8,00) .315
–03	(11,00) .433
–04	(16,00) .630
–05	(19,00) .748
–07	(25,00) .984

*Processing conditions will affect mated height.

–K
= (8,25mm) .325" DIA Polyimide Film Pick & Place Pad

–TR
= Tape & Reel Packaging (N/A on 56 & 80 positions)

–RT1
= Retention Option (N/A on 56 & 80 positions or –L (latch) option)

–L
= Latching Option (N/A on 42, 56, 60 & 80 positions or –RT1 option)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292
SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766
SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683