Operating System Security

Day 1: Operating System & Linux Fundamentals

The Heart of Your Computer

- **Core Manager:** manages memory, processes, and all hardware and software components.
- **Digital Translator:** acts as an intermediary, translating user commands into the computer's language so you can communicate without knowing **complex** code.
- **Resource Coordinator:** Without an OS, hardware remains a collection of disconnected parts; the OS provides the interface and manages resources efficiently.
- **Windows:** The most popular desktop OS, known for its user-friendly GUI.
- **Linux:** An open-source powerhouse, favored by developers and cybersecurity professionals.
- **macOS:** Apple's proprietary OS, valued for its design and ecosystem integration.



Linux

- **Open-Source Kernel:** Linux serves as the foundation for a massive ecosystem of distributions, born from a movement that makes code free to use, modify, and distribute.
- **Security Through Transparency**: A vibrant global community constantly reviews and improves the code, ensuring a higher standard of security through open collaboration.
- **The Defender’s Choice**: Its robust security features and command-line interface make it an indispensable tool for both offensive and defensive cybersecurity operations.
- **Deep Customization:** The inherent flexibility of Linux allows for specialized environments and the development of custom security tools.

Linux distributions commonly used for cybersecurity

- **Kali Linux:** The industry standard for penetration testing and ethical hacking, featuring hundreds of pre-installed tools.
- **Parrot Security OS:** A lightweight and cloud-friendly distribution designed for security auditing, forensics, and privacy.
- **BlackArch Linux:** Built for expert users, this Arch-based distro contains over 2,800 specialized cybersecurity tools.
- **Tails (The Amnesic Incognito Live System):** A security-focused OS aimed at preserving privacy and anonymity by routing all traffic through the Tor network.
- **CAINE (Computer Aided Investigative Environment):** A specialized distribution specifically created for digital forensics and data recovery.

Linux vs. Windows Security Architecture

- **User Permissions:** Linux utilizes a strict "Root" vs. "User" hierarchy where administrative changes require explicit authorization (sudo).
- **Access Controls:** Windows uses User Account Control (UAC) to prompt for permission, but historically, more users operate with full administrative rights by default.
- **Kernel Design:** Linux is an open-source kernel, meaning a global community identifies and patches vulnerabilities transparently.
- **Attack Surface:** Windows has a larger market share in the consumer sector, making it a more frequent target for malware and ransomware developers.

Why Operating System Security is Your Priority

- **The Foundation of Trust:** The OS is the core layer that sits between your hardware and applications; if the foundation is compromised, nothing running above it can be considered secure.
- **Gatekeeper of Data:** The operating system manages file permissions, memory access, and user authentication, making it the primary line of defense for sensitive information.
- **Centralized Control:** Because the OS coordinates all system resources, an attacker with OS-level access (Root or Admin) gains total control over the entire device.
- **Primary Attack Surface:** Most malware, from ransomware to spyware, is specifically designed to exploit OS vulnerabilities to gain persistence and execute malicious code.
- **Security Updates & Patching:** Maintaining OS security through regular updates is the most effective way to close "backdoors" and protect against newly discovered exploits.

Common OS Vulnerabilities & Exploits

- **Privilege Escalation:** Exploiting a bug to jump from a "Standard User" to "Admin/Root" status, gaining full system control.
- **Buffer Overflow:** Overwhelming a system's memory with excess data to crash it or force it to execute malicious code.
- **Kernel Exploits:** Targeting the core of the OS to bypass all security software and remain invisible to the user.
- **Insecure Defaults:** Unnecessary services or weak default passwords that leave "unlocked doors" for attackers.
- **Zero-Days:** Exploiting unknown flaws that the software developer hasn't had the chance to patch yet.

Linux in Practice: A Dual-Edged Sword

- Linux's power and flexibility make it a tool of choice for both ethical hackers (defenders) and malicious actors (attackers). Its open-source nature means vulnerabilities are often discovered and patched quickly, but also that exploit techniques can be widely shared.

- **Attackers**
  - Leverage its command-line power for scripting and automation of attacks.
  - Utilize specialized tools available in distributions like Kali Linux for reconnaissance, exploitation, and post-exploitation.
  - Exploit kernel vulnerabilities or misconfigurations to gain unauthorized access.

- **Defenders**
  - Use it for building secure servers and network infrastructure.
  - Employ forensics tools to analyze compromised systems and recover data.
  - Conduct penetration testing to identify and patch vulnerabilities before attackers can exploit them.