Payroll ESS API Manual

API Manual for accessing ESS API using JSONRPC standard.

/ess-api/mfa-request

Requests for a new MFA code to be sent via email.

Parameters:

```
{'employee-email': 'rberdin@eztechsoft.com'}
```

Result:

```
{'params': {'employee-email': 'rberdin@eztechsoft.com'},
 'res': True}
```

/ess-api/mfa-validate

Validates MFA code and returns employee ID and hash defined for email address.

Parameters:

```
{'employee-email': 'rberdin@eztechsoft.com', 'mfa': '413908'}
```

Valid Results:

```
{'employee_id': 19,
'hash': 'b3cd5c78c3d12153fe3d360a1c02ccbd',
'msg': 'Success',
'res': True}
```

Error or Invalid Results:

```
{'msg': 'Invalid email or MFA.', 'res': False}
```

/ess-api/attendance/next-process/[int:employee_id]/[string:hash]

Get next process for attendance log.

Sample call:

```
https://demo-ezpay.odoo17.eztechsoft.com/ess-api/attendance/check_in/19/b3cd5c78c3d12153fe3d360a1c02ccb
```

Parameters:

- employee_id - employee ID taken from mfa-validate
- hash - taken from mfa-validate

Successful Results:

```
{'msg': 'Success.', 'next-process': 'check_out', 'res': True}
```

or

```
{'msg': 'Success.', 'next-process': 'check_in', 'res': True}
```

Error or Invalid Results:

```
{'msg': 'Invalid parameters.', 'res': False}
```

/ess-api/attendance/check_in/[int:employee_id]/[string:hash]

Check in employee at attendance module.

Sample call:

```
https://demo-ezpay.odoo17.eztechsoft.com/ess-api/attendance/check_in/19/b3cd5c78c3d12153fe3d360a1c02ccb
```

Parameters:

- employee_id - employee ID, from mfa-validate
- hash - from validate, from mfa-validate

```
{'check_in': '2025-03-05 08:19:39',
 'in_latitude': 10.29998,
 'in_longitude': 123.95216}
```

Successful Results:

```
{'msg': 'Success.', 'res': True}
```

Error or Invalid s:

```
{'msg': 'Invalid parameters.', 'res': False}
```

or

```
{'msg': 'Invalid location.', 'res': False}
```

/ess-api/attendance/check_out/[int:employee_id]/[string:hash]

Check out employee at attendance module.

Sample call:

```
https://demo-ezpay.odoo17.eztechsoft.com/ess-api/attendance/check_out/19/b3cd5c78c3d12153fe3d360a1c02cc
```

Parameters:

- employee_id - employee ID, from mfa-validate
- hash - from validate, from mfa-validate
- date/time is in UTC

```
{'check_out': '2025-03-05 08:05:04',
 'out_latitude': 10.29998,
 'out_longitude': 123.95216}
```

Successful Results:

```
{'msg': 'Success.', 'res': True}
```

Error or Invalid Results:

```
{'msg': 'Invalid parameters.', 'res': False}
```

or

```
{'msg': 'Invalid location.', 'res': False}
```

set_geofence_check_in

Using JSON RPC and with user login with HR admin rights, sets the valid check in location of an employee.

Sample call:

```
uid = login(URL,DB,USER,PASS)
model_name = "hr.employee"
res = call(url, "object", "execute", DB, uid, PASS, model_name,
    'set_geofence_check_in', 19, 10.1, 100.1)
```

Parameters:

- employee_id - (19)
- latitude - (10.1)
- longitude - (100.1)

Results:

```
{'res': True}
```

set_geofence_check_out

Using JSONRPC and with user login with HR admin rights, sets the valid check out location of an employee.

Sample call:

```
uid = login(URL,DB,USER,PASS)
model_name = "hr.employee"
res = call(url, "object", "execute", DB, uid, PASS, model_name,
    'set_geofence_check_out', 19, 10.1, 100.1)
```

Parameters:

- employee_id - (19)
- latitude - (10.1)
- longitude - (100.1)

Results:

```
{'res': True}
```