

Package ‘aRtsy’

August 11, 2021

Title Generative Art with 'ggplot2'

Description Provides various algorithms for creating artworks in the 'ggplot2' language that incorporate some form of randomness.

Version 0.1.0

Date 2021-08-11

BugReports <https://github.com/koenderks/aRtsy/issues>

URL <https://koenderks.github.io/aRtsy/>, <https://github.com/koenderks/aRtsy>, https://twitter.com/aRtsy_package

Imports dplyr, ggplot2, ggpubr, Rcpp, reshape2

LinkingTo Rcpp, RcppArmadillo

Language en-US

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.1

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

R topics documented:

aRtsy-package	2
canvas_ant	2
canvas_arcs	3
canvas_circlemap	4
canvas_collatz	5
canvas_diamonds	6
canvas_function	7
canvas_mandelbrot	7
canvas_planet	8
canvas_polylines	9
canvas_ribbons	10
canvas_segments	11
canvas_squares	12
canvas_strokes	13
canvas_turmite	14
colorPalette	15

saveCanvas	16
themeCanvas	16

Index	18
--------------	-----------

aRtsy-package	<i>aRtsy — Generative Art using ggplot2</i>
---------------	---

Description

aRtsy is an attempt at making generative art available for the masses in a simple and standardized format. The package provides various algorithms for creating artworks in ggplot2 that incorporate some form of randomness (depending on the set seed). Each type of artwork is implemented in a separate function.

For documentation on aRtsy itself, including the manual and user guide for the package, worked examples, and other tutorial information visit the [package website](#).

Author(s)

Koen Derks (maintainer, author) <koen-derks@hotmail.com>

Please use the citation provided by R when citing this package. A BibTex entry is available from `citation("aRtsy")`.

See Also

Useful links:

- The [twitter feed](#) to check the artwork of the day.
- The [issue page](#) to submit a bug report or feature request.

canvas_ant	<i>Paint Langton's Ant on a Canvas</i>
------------	--

Description

This function paints Langton's Ant. Langton's ant is a two-dimensional universal Turing machine with a very simple set of rules but complex emergent behavior.

Usage

```
canvas_ant(colors, background = '#fafafa', iterations = 1e7,
           width = 200, height = 200)
```

Arguments

colors	a character (vector) specifying the colors for the ant.
background	a character specifying the color of the background.
iterations	the number of iterations of the ant.
width	the width of the artwork in pixels.
height	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

References

https://en.wikipedia.org/wiki/Langtons_ant

Examples

```
## Not run:
canvas_ant(colors = '#000000', background = '#fafafa')

## End(Not run)
```

canvas_arcs	<i>Paint Arcs on a Canvas</i>
-------------	-------------------------------

Description

Inspired by the work of @ijeamaka_a, this type of artwork mimics her beautiful [Arc Series](#). For private use only.

Usage

```
canvas_arcs(colors, background = '#fdf5e6', n = 1, nrow = NULL, ncol = NULL,
            dir = 'right', starts = 'clockwise')
```

Arguments

colors	a character vector specifying the 3 colors used for the arcs.
background	a character string specifying the color used for the background.
n	an integer specifying how many arcs should be put on the canvas.
nrow	an (optional) integer specifying the number of rows on the canvas.
ncol	an (optional) integer specifying the number of columns on the canvas.
dir	a character string specifying which direction the arcs turn. Can be one of "right" (default) or "left".
starts	a character sting specifying where the arcs should start. Can be one of "clockwise" (default) or "random".

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
aRtsy:::canvas_arcs(colors = c('darkgreen', 'goldenrod', 'firebrick'), n = 9)

## End(Not run)
```

canvas_circlemap

Paint a Circle Map on a Canvas

Description

This function is my attempt at a circle map.

Usage

```
canvas_circlemap(colors, x_min = 0, x_max = 12.56, y_min = 0, y_max = 1,
  iterations = 10, width = 1500, height = 1500)
```

Arguments

colors	a character specifying the color used for the function shape.
x_min	a numeric value specifying the minimum value for the x-axis.
x_max	a numeric value specifying the maximum value for the x-axis.
y_min	a numeric value specifying the minimum value for the y-axis.
y_max	a numeric value specifying the maximum value for the y-axis.
iterations	the number of iterations.
width	the width of the artwork in pixels.
height	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

References

<https://linas.org/art-gallery/circle-map/circle-map.html>

Examples

```
## Not run:
canvas_circlemap(colors = colorPalette('tuscan2'))

## End(Not run)
```

canvas_collatz

Paint the Collatz Conjecture on Canvas

Description

This function draws the Collatz conjecture on the canvas.

Usage

```
canvas_collatz(colors, background = '#fafafa', n = 200,
               angle.even = 0.0075, angle.odd = 0.0145, side = FALSE)
```

Arguments

colors	a character (vector) specifying the colors used for the artwork.
background	a character specifying the color used for the background.
n	the number of numbers to sample for the lines. Can also be a vector of numbers to use.
angle.even	the angle (radials) to use after odd numbers.
angle.odd	the angle (radials) to use after even numbers.
side	logical. Whether to put the artwork on its side.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
set.seed(1)
canvas_collatz(colors = colorPalette('dark1'), n = 100)

## End(Not run)
```

`canvas_diamonds`*Paint A Diamond on Canvas*

Description

This function draws many diamonds on the canvas and places two lines behind them. The diamonds can be transparent or have a random color sampled from the input.

Usage

```
canvas_diamonds(colors, background = '#fafafa', col.line = 'black',
               radius = 10, alpha = 1, p = 0.2,
               width = 500, height = 500)
```

Arguments

<code>colors</code>	a character (vector) specifying the colors used for the strokes.
<code>background</code>	a character specifying the color used for the background.
<code>col.line</code>	color of the lines.
<code>radius</code>	radius of the diamonds.
<code>alpha</code>	transparency of the diamonds. If NULL, added layers become increasingly more transparent.
<code>p</code>	takeover probability.
<code>width</code>	the width of the artwork in pixels.
<code>height</code>	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
set.seed(1)
canvas_diamonds(colors = colorPalette('house'), radius = 10)

## End(Not run)
```

canvas_function	<i>Paint Functions on a Canvas</i>
-----------------	------------------------------------

Description

This function paints functions with random parameters and mimics the functionality of the `generativeart` package.

Usage

```
canvas_function(color, background = '#fafafa')
```

Arguments

color	a character specifying the color used for the function shape.
background	a character specifying the color used for the background.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

References

<https://github.com/cutterkom/generativeart>

Examples

```
## Not run:  
set.seed(10)  
canvas_function(color = '#000000', background = '#fafafa')  
  
## End(Not run)
```

canvas_mandelbrot	<i>Paint the Mandelbrot Set on Canvas</i>
-------------------	---

Description

This function draws the Mandelbrot set on the canvas.

Usage

```
canvas_mandelbrot(colors, n = 100, xmin = -1.7, xmax = -0.2, ymin = -0.2999,  
                  ymax = 0.8001, zoom = 1, width = 500, height = 500)
```

Arguments

colors	a character (vector) specifying the colors used for the artwork.
n	the number of iterations.
xmin	the minimum x value.
xmax	the maximum x value.
ymin	the minimum y value.
ymax	the maximum y value.
zoom	the amount of zoom to apply.
width	the width of the artwork in pixels.
height	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:  
set.seed(1)  
canvas_mandelbrot(colors = colorPalette('dark1'), n = 100)  
  
## End(Not run)
```

canvas_planet

Paint a Planet on a Canvas

Description

This function paints one or multiple planets.

Usage

```
canvas_planet(colors, threshold = 4, iterations = 200,  
              starprob = 0.01, fade = 0.2,  
              radius = NULL, center.x = NULL, center.y = NULL,  
              light.right = TRUE, width = 1500, height = 1500)
```


Arguments

colors	a character specifying the colors used for the planet(s). Can also be a list where each entry is a vector of colors for each planet.
threshold	a character specifying the threshold for a color take.
iterations	the number of iterations of the planets
starprob	the probability of drawing a star in outer space.
fade	the fading factor.
radius	a numeric (vector) specifying the radius of the planet(s).
center.x	the x-axis coordinate(s) for the center(s) of the planet(s).
center.y	the y-axis coordinate(s) for the center(s) of the planet(s).
light.right	whether to draw the light from the right or the left.
width	the width of the artwork in pixels.
height	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
# Sun behind Earth and Moon
set.seed(1)
colors <- list(c("khaki1", "lightcoral", "lightsalmon"),
               c("dodgerblue", "forestgreen", "white"),
               c("gray", "darkgray", "beige"))
canvas_planet(colors, radius = c(800, 400, 150),
              center.x = c(1, 500, 1100),
              center.y = c(1400, 500, 1000),
              starprob = 0.005)

## End(Not run)
```

canvas_polylines

Paint Polygons and Lines on Canvas

Description

This function draws many points on the canvas and connects these points into a polygon. After repeating this for all the colors, the edges of all polygons are drawn on top of the artwork.

Usage

```
canvas_polylines(colors, background = '#fafafa', ratio = 0.5, iterations = 1000,
                 alpha = NULL, size = 0.1, width = 500, height = 500)
```

Arguments

colors	a character (vector) specifying the colors used for the strokes.
background	a character specifying the color used for the borders.
ratio	width of the polygons. Larger ratios cause more overlap.
iterations	the number of points for each polygon.
alpha	transparency of the polygons. If NULL, added layers become increasingly more transparent.
size	size of the borders.
width	the width of the artwork in pixels.
height	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
set.seed(1)
canvas_polylines(colors = colorPalette('retro2'))

## End(Not run)
```

canvas_ribbons

Paint Ribbons on a Canvas

Description

This function paints ribbons and (optionally) a triangle in the middle.

Usage

```
canvas_ribbons(colors, background = '#fdf5e6', triangle = TRUE)
```

Arguments

colors	a character (vector) specifying the colors for the ribbons. Colors determine the number of ribbons.
background	a character specifying the color of the background.
triangle	logical. Whether to draw the triangle that breaks the ribbon polygons.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
set.seed(1)
canvas_ribbons(colors = colorPalette('tuscan1'))

## End(Not run)
```

canvas_segments

Paint Line Segments on Canvas

Description

This function draws many line segments on the canvas.

Usage

```
canvas_segments(colors, background = '#fafafa', n = 100,
                p = 0.5, H = 0.1, size = 0.2)
```

Arguments

colors	a character (vector) specifying the colors used for the line segments.
background	a character specifying the color used for the background.
n	the number of line segments to draw.
p	probability of drawing a vetical line segment.
H	scaling factor for the line segments.
size	line width of the segments.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:
set.seed(1)
canvas_segments(colors = 'black', background = '#fafafa')

## End(Not run)
```

`canvas_squares`*Paint Squares on a Canvas*

Description

This function paints a squares. It works by repeatedly cutting into the canvas at random locations and coloring the area that these cuts create.

Usage

```
canvas_squares(colors, background = '#000000', cuts = 50, ratio = 1.618,  
               width = 100, height = 100)
```

Arguments

<code>colors</code>	a character vector specifying the colors used in the squares.
<code>background</code>	a character specifying the color used for the background (borders).
<code>cuts</code>	the number of cuts to make.
<code>ratio</code>	the 1:1 ratio for each cut.
<code>width</code>	the width of the artwork in pixels.
<code>height</code>	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:  
set.seed(6)  
canvas_squares(colors = colorPalette('tuscan1'))  
  
## End(Not run)
```

canvas_strokes*Paint Strokes on a Canvas*

Description

This function creates an artwork that resembles paints strokes. The algorithm is based on the simple idea that each next point on the grid has a chance to take over the color of an adjacent colored point but also has a change of generating a new color.

Usage

```
canvas_strokes(colors, neighbors = 1, p = 0.01, iterations = 1,  
              width = 500, height = 500, side = FALSE)
```

Arguments

colors	a character (vector) specifying the colors used for the strokes.
neighbors	the number of neighbors a block considers when taking over a color. More neighbors fades the artwork.
p	the probability of selecting a new color at each block. A higher probability adds more noise to the artwork.
iterations	the number of iterations on the artwork. More iterations fade the artwork.
width	the width of the artwork in pixels.
height	the height of the artwork in pixels.
side	whether to turn the artwork on its side.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
## Not run:  
set.seed(1)  
canvas_strokes(colors = colorPalette('tuscany3'))  
  
## End(Not run)
```

`canvas_turmite`*Paint a Turmite on a Canvas*

Description

This function paints a turmite. A turmite is a Turing machine which has an orientation in addition to a current state and a "tape" that consists of a two-dimensional grid of cells. The algorithm is simple: 1) turn on the spot (left, right, up, down) 2) change the color of the square 3) move forward one square.

Usage

```
canvas_turmite(color, background = '#fafafa', p = 0.5, iterations = 1e7,  
               width = 1500, height = 1500)
```

Arguments

<code>color</code>	a character specifying the color used for the turmite.
<code>background</code>	a character specifying the color used for the background.
<code>p</code>	the probability of a state switch within the turmite.
<code>iterations</code>	the number of iterations of the turmite.
<code>width</code>	the width of the artwork in pixels.
<code>height</code>	the height of the artwork in pixels.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

References

<https://en.wikipedia.org/wiki/Turmite>

Examples

```
## Not run:  
set.seed(1)  
canvas_turmite(color = "#000000", background = "#fafafa")  
  
## End(Not run)
```

colorPalette*Color palette generator.*

Description

This function creates a random color palette, or allows the user to select a pre-implemented palette.

Usage


```
colorPalette(name, n = NULL)
```

Arguments

- | | |
|------|--|
| name | name of the color palette. Can be random for random colors, but can also be the name of a pre-implemented palette. See the details section for a list of pre-implemented palettes. |
| n | the number of colors to select from the palette. Required if name = 'random'. Otherwise, if NULL, automatically selects all colors from the chosen palette. |

Details

The following color palettes are implemented:



Value

A vector of colors.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Examples

```
colorPalette('random', 5)
```

saveCanvas

Save a canvas to an external device.

Description

This function is a wrapper around `ggplot2::ggsave`. It provides a suggested export with square dimensions for a canvas created using the `aRtsy` package.

Usage

```
saveCanvas(plot, filename, width = 7, height = 7, resolution)
```

Arguments

plot	a ggplot2 object to be saved.
filename	the filename of the export.
width	the width of the artwork in cm.
height	the height of the artwork in cm.
resolution	the dpi of the export.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

themeCanvas

Canvas theme for ggplot2 objects

Description

Add a canvas theme to the plot. The canvas theme by default has no margins and fills any empty canvas with a background color.

Usage

```
themeCanvas(x, background = '#fafafa', margin = -1.25)
```

Arguments

x	a ggplot2 object.
background	a character specifying the color used for the empty canvas.
margin	margins of the plot.

Value

A ggplot object containing the artwork.

Author(s)

Koen Derks, <koen-derks@hotmail.com>

Index

- * **aRtsy**
 - aRtsy-package, [2](#)
- * **artwork**
 - canvas_ant, [2](#)
 - canvas_arcs, [3](#)
 - canvas_circlemap, [4](#)
 - canvas_collatz, [5](#)
 - canvas_diamonds, [6](#)
 - canvas_function, [7](#)
 - canvas_mandelbrot, [7](#)
 - canvas_planet, [8](#)
 - canvas_polylines, [9](#)
 - canvas_ribbons, [10](#)
 - canvas_segments, [11](#)
 - canvas_squares, [12](#)
 - canvas_strokes, [13](#)
 - canvas_turmite, [14](#)
- * **canvas**
 - canvas_ant, [2](#)
 - canvas_arcs, [3](#)
 - canvas_circlemap, [4](#)
 - canvas_collatz, [5](#)
 - canvas_diamonds, [6](#)
 - canvas_function, [7](#)
 - canvas_mandelbrot, [7](#)
 - canvas_planet, [8](#)
 - canvas_polylines, [9](#)
 - canvas_ribbons, [10](#)
 - canvas_segments, [11](#)
 - canvas_squares, [12](#)
 - canvas_strokes, [13](#)
 - canvas_turmite, [14](#)
 - colorPalette, [15](#)
 - saveCanvas, [16](#)
 - themeCanvas, [16](#)
- * **package**
 - aRtsy-package, [2](#)
- * **palette**
 - colorPalette, [15](#)
- * **save**
 - saveCanvas, [16](#)
- * **theme**
 - themeCanvas, [16](#)
- aRtsy (aRtsy-package), [2](#)
- aRtsy-package, [2](#)
- canvas_ant, [2](#)
- canvas_arcs, [3](#)
- canvas_circlemap, [4](#)
- canvas_collatz, [5](#)
- canvas_diamonds, [6](#)
- canvas_function, [7](#)
- canvas_mandelbrot, [7](#)
- canvas_planet, [8](#)
- canvas_polylines, [9](#)
- canvas_ribbons, [10](#)
- canvas_segments, [11](#)
- canvas_squares, [12](#)
- canvas_strokes, [13](#)
- canvas_turmite, [14](#)
- colorPalette, [15](#)
- saveCanvas, [16](#)
- themeCanvas, [16](#)