

Universität Leipzig

# MAG Import

## Documentation

Johannes Leupold, Philip Fritzsche, Timo Adameit

July 28, 2017

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Microsoft Academic Graph</b>	<b>2</b>
2.1	Dimensions Of The Dataset . . . . .	2
2.2	Primitive Types . . . . .	3
2.2.1	Node . . . . .	4
2.2.2	Edge . . . . .	4
2.2.3	Hyperedge . . . . .	4
2.2.4	Multi Attribute . . . . .	5
<b>3</b>	<b>Parsing</b>	<b>5</b>
<b>4</b>	<b>Import Into Gradoop</b>	<b>6</b>
4.1	Primitive Representation . . . . .	6
4.1.1	NODE . . . . .	6
4.1.2	EDGE . . . . .	6
4.1.3	EDGE_3 . . . . .	7
4.1.4	MULTI_ATTRIBUTE . . . . .	7
4.2	Graph Creation . . . . .	7
<b>5</b>	<b>Schema Extraction</b>	<b>7</b>
5.1	General Procedure . . . . .	7
5.2	Microsoft Academic Graph . . . . .	7
5.3	DBLP Graph . . . . .	7
<b>6</b>	<b>Schema Matching</b>	<b>7</b>

# 1 Introduction

Microsoft Academic Graph (MAG) is a large scale publication dataset. It contains information about scientific articles published in both journals and conferences paired with information about their authors and affiliations. This project aims to import Microsoft Academic Graph into Gradoop, the open source graph processing framework created by the Database Group at Universität Leipzig. Therefore, the MAG model must be converted to make it compatible with the extended property graph model (EPGM) used in Gradoop. We are trying to extract the schema graph from the MAG dataset to match the schema with the one of DBLP Graph, another academic publication dataset. The goal of this schema matching is creating a consolidated graph containing both the information from MAG and DBLP to combine advantages of both datasets. For instance, MAG has affiliation information and connects publications to a field of study hierarchy, while DBLP contains information about publication types and enables the creation of co-author relations.

The following sections contain information on the MAG dataset itself and the considerations in creating the parser and the importer. Finally, we will provide our schema matching of both datasets.

## 2 Microsoft Academic Graph

The Microsoft Academic Graph<sup>1</sup> “is a heterogeneous graph containing scientific publication records, citation relationships between those publications, as well as authors, institutions, journals, conferences, and fields of study”. [2] It is used to support user experience in Bing, Cortana and Microsoft Academic. It can be accessed through the Microsoft Cognitive Services Academic Knowledge API. [2]

For our project, we are using an older dump of the MAG, created in February 2016. The parser will still be applicable to a current dump of the graph, because the schema hasn’t changed since. The only problem in obtaining a current dump is that it is nowhere to be found. Since at the moment the graph can only be accessed through the Academic Knowledge API, it is very difficult to create such dumps.

### 2.1 Dimensions Of The Dataset

The MAG dataset contains a big number of publications and other information. Herrmannova and Knoth write [1]

“ It is also the largest publicly available dataset of citation data. As such, it is an important resource for scholarly communications research.”

---

<sup>1</sup><https://www.microsoft.com/en-us/research/project/microsoft-academic-graph>

<b>Papers</b>	126,909,021
<b>Authors</b>	114,698,044
<b>Institutions</b>	19,843
<b>Journals</b>	23,404
<b>Conferences</b>	1,283
<b>Conference Instances</b>	50,202
<b>Fields Of Study</b>	50,266

Table 1: Number of nodes in the MAG dataset, grouped by entity type, as of September 2016




Figure 1: The current schema of the MAG dataset.

In their analysis of September 2016, they present their findings about the dimensions of the MAG (see Table 1).

The current schema of the MAG can be viewed in Figure 1.

## 2.2 Primitive Types

Different types of primitives (such as Node, Edge etc.) are found in the MAG. To successfully parse the graph, we need to analyse the primitive types and find a way to represent them using Gradoop primitives (**Vertex**, **Edge**, **Properties**). MAG contains four different types of primitives.

### 2.2.1 Node

A node represents an entity in the graph, for instance a paper. It has properties, which may contain foreign keys referencing other entity types. In the EPGM, a node can be represented as a **Vertex**.

**Files containing node primitives:**

- `Affiliations.txt`
- `Authors.txt`
- `ConferenceInstances.txt`
- `Conferences.txt`
- `FieldsOfStudy.txt`
- `Journals.txt`
- `Papers.txt`

### 2.2.2 Edge

An edge creates a connection between exactly two nodes and encodes a relationship between the entities represented by these nodes. The edge may have properties. The EPGM representation of an edge would be **Edge**.

**Files containing edge primitives:**

- `FieldOfStudyHierarchy.txt`
- `PaperKeywords.txt`
- `PaperReferences.txt`

### 2.2.3 Hyperedge

A hyperedge is a connection between three or more nodes to encode polyvalent relationships between these entities. The MAG contains only one hyperedge representing the three-side relationship between authors, papers and affiliations, expressing “The author writes the paper while working at the affiliation”. In the EPGM, a hyperedge can be represented by one **Vertex** representing the relationship and multiple **Edges** to the involved nodes or by multiple **Edges** which can be clearly assigned to each other.

**Files containing hyperedge primitives:**

- `PaperAuthorAffiliations.txt`

### 2.2.4 Multi Attribute

A multi attribute is an additional property for a node. Other than basic properties it can have multiple values for the same entity. Therefore, it can't be stored in the same file due to the tsv format. The EPGM equivalent of a multi attribute should be single property.

**Files containing multi attribute primitives:**

- `PaperUrls.txt`

## 3 Parsing

The MAG parser aims to create an internal representation of the graph independent from further processing, e.g. the import into Gradoop. Therefore, we pursue a separation of concerns approach. We created a callback interface to allow the user of our project to specify further processing themselves. The parser takes an implementation of this interface as a constructor argument and passes all parsed objects to this `ElementProcessor` for further consideration. The processor could be our own Gradoop importer or a simple statistics tool, for example.

The input files get processed line-wise, while the lines are splitted at tabs, like you would a tsv parser expect to do.

All primitives contained in the MAG are abstracted into the class `MagObject`. Each `MagObject` has a `TableSchema` containing a description of the objects structure (property names and types). The schema also contains the object type, a representation of the primitive type described in Section 2.2. Possible values of this values are defined as `enum ObjectType {NODE, EDGE, EDGE_3, MULTI_ATTRIBUTE}`. For each input file, there is a `TableSchema` which is named after the input file. In the callback implementation all of these information can be accessed.

There are multiple property types, some of which are basic types, others have special meanings for hyperedges. The basic types are

- **ID**: The unique key for an entity. Only used in nodes.
- **ATTRIBUTE**: A generic property. Can be used in all primitive types.
- **KEY**: A foreign key, therefore contains the ID of an entity. This field type is used in nodes as a foreign key and in edges and hyperedges as link partners for the edge.
- **IGNORE**: The field is not needed (redundant information) and is ignored in parsing. Can be used on all primitive types.

Some field types are created solely for the purpose of parsing hyperedges.

- **ATTRIBUTE\_1**: When the hyperedge is split into two edges, this field gets used as **ATTRIBUTE** only for the first of those edges.
- **KEY\_1**: This field is a link partner only for the first edge created. It is attached as an **ATTRIBUTE** to the second edge to connect both edges.

- **KEY\_2**: The field is a link partner only for the second edge created. In the creation of the first edge, it is ignored.

All needed **TableSchemas** are bundled into one **InputSchema** for easier access. The parsing order is defined by primitive type. **EDGEs** are processed first, with **EDGE\_3** following. After that, we process all **NODEs** and at last the **MULTI\_ATTRIBUTES**. The parsing order inside one of those groups is non-deterministic.

## 4 Import Into Gradoop

The Gradoop importer is an implementation of the MAG parser **ElementProcessor** callback. It takes care of all primitive types and creates the graph as JSON output in the Gradoop format once parsing is finished. The parsed **MagObjects** are processed regardless of schema name, only the object type is taken into consideration. The corresponding package contains two classes: **ImportMain**, which takes care of the full import process, and **GradoopElementProcessor** which creates the EPGM elements from the parsed **MsagObjects**. The following section covers the process of creating EPGM elements from the different object types.

### 4.1 Primitive Representation

#### 4.1.1 NODE

The transformation of a **NODE** to the corresponding EPGM **Vertex** isn't very complicated. The processor creates an **InputVertex** and uses the schema name of the **NODE** as its label. All fields marked **ATTRIBUTE** are joined into a single **Properties** object which is assigned to the vertex. The **ID** field of the node is used as vertex ID. All vertices are kept in an **ArrayList** for later creation of datasets.

The **KEY** fields are extracted from the node using the helper function **getForeignKeys**. Each foreign key is transformed into an **ImportEdge**, going from the just created node to the referenced node. The edge is labeled **[schema name] | [target schema name]**. The edge id is **[ID] | [target ID]**.

Papers' properties are additionally inserted into a **HashMap**, using their ID as the key for later addition of the **Urls** multi attribute.

#### 4.1.2 EDGE

An **EDGE** gets directly transformed into an **InputEdge**. The edge gets labeled with the schema name and uses the ID **[source ID] | [target ID]**. The **ATTRIBUTE** fields are extracted and converted into a **Properties** object which is attached to the **ImportEdge**. All edges are kept in an **ArrayList**.

### 4.1.3 EDGE\_3

For the processing of `EDGE_3`, the hyperedges are split into two single edges, one connecting papers and authors and the second connecting authors to affiliations. The second one is annotated with the paper ID to maintain the relationship between both edges.

Here, the additional field types are taken into consideration. A modified helper function, `convertAttributesEdge3`, is used to extract `Properties` from the `MsagObject`. It pays attention to the context (first or second run) and only returns the correct attributes. A similar process is applied to the link partners: the function `getForeignKeysEdge3` returns only those references, needed in the edge currently created.

Both edges are transformed into `ImportEdges` and labeled like normal edges, but with `_1` and `_2` suffices.

### 4.1.4 MULTI\_ATTRIBUTE

A `MULTI_ATTRIBUTE` must be added to the `Vertex` it is associated with. The association is determined using the single `KEY` field of the attribute. After that, the associated paper's properties are loaded from the previously created map. The property is added to a `List<PropertyValue>` which is stored in the `Properties` object.

## 4.2 Graph Creation

After parsing is finished, the resulting lists of vertices and edges are retrieved from `GradoopElementProcessor` and converted into Flink `DataSets`. The datasets are used to create a `LogicalGraph` which is then written to a `JSONDataSink`.

## 5 Schema Extraction

### 5.1 General Procedure

### 5.2 Microsoft Academic Graph

### 5.3 DBLP Graph

## 6 Schema Matching

## References

- [1] Drahomira Herrmannova and Petr Knuth. An analysis of the microsoft academic graph. *D-Lib Magazine*, 22(9/10), 2016.
- [2] Microsoft Research. Microsoft academic graph. <https://www.microsoft.com/en-us/research/project/microsoft-academic-graph/>, July 2017.