USB-A plug, ESD
USB-212-BCW
TPD1E05U06PYR
TPD1E10B06PYR
Power path: TPS2116 priority mux (VBUS_A first) + TLV75733P 3.3 V LDO
TPS2116DRLR
TLV75733PDYDR
USB D+/D- switch (follows powering plug; OE pulled high = disconnected)
TS3USB221ARSER
ESP32-S3 (R16V / plain / R8 variants)
ESP32-S3
ESP32-S3 supplies, reset, straps, UART
SUPERVISOR_3V0_SC70_TBD
40 MHz crystal
XRCGB40M000F1S1BR0
RF: chip-side C-L-C, 0R break, antenna-side pi, Johanson 2450AT18D (thin edge)
2450AT18D0100001E
16 MB QSPI flash (1.8 V on N16R16 / N16)
GD25LQ128EWIGR
USB-C plug (sink mount), ESD, CC Rd, VBUS_C sense
TYPE-C-31-G-07
Recovery button, status LED
Bottom-side pogo test pads

Generated by hardware/scripts/gen_schematic.py from the board + tscircuit netlist (source of truth: hardware/index.circuit.tsx). Net labels connect pins; all pins passive. Variants: N16R16 = ESP32-S3R16V + GD25LQ128E (1.8 V), R9 fitted; N16 = ESP32-S3 + same flash, R9 fitted; N16R8 = ESP32-S3R8 + 3.3 V flash (W25Q128JVPIQ), R9 NOT fitted.

Generated from the PCB netlist; all pins passive

Sheet: /
File: esp32s3_dongle.kicad_sch

Title: ESP32-S3 dual-plug USB dongle

Size: User
Date:
Rev: A
KiCad E.D.A. 10.0.8
Id: 1/1