

CS4670: Computer Vision


Noah Snavely

Image Resampling




Image

This image is too big to fit on the screen. How can we generate a half-sized version?



Source: S. Seitz

Image sub-sampling




1/4



1/8

Throw away every other row and column to create a 1/2 size image
- called *image sub-sampling*

Image sub-sampling



1/2



1/4 (2x zoom)




1/8 (4x zoom)


Why does this look so cruffy?

Source: S. Seitz


Image sub-sampling



Even worse for synthetic images



Aliasing




- Occurs when your sampling rate is not high enough to capture the amount of detail in your image
- Can give you the wrong signal/image—an *alias*
- To do sampling right, need to understand the structure of your signal/image
- Enter Monsieur Fourier...
- To avoid aliasing:
 - sampling rate $\geq 2 * \text{max frequency in the image}$
 - said another way: \geq two samples per cycle
 - This minimum sampling rate is called the **Nyquist rate**

Wagon-wheel effect

Imagine a spoked wheel moving to the right (rotating clockwise).



Mark wheel with dot so we can see what's happening.

If camera shutter is only open for a fraction of a frame time (frame time = $1/30$ sec. for video, $1/24$ sec. for film):





Without dot, wheel appears to be rotating slowly backwards!
(counterclockwise)

Nyquist limit – 2D example



Good sampling




Bad sampling

Aliasing

- When downsampling by a factor of two
 - Original image has frequencies that are too high
- How can we fix this?

Gaussian pre-filtering



Gaussian 1/2



G 1/4



G 1/8

- Solution: filter the image, *then* subsample

Subsampling with Gaussian pre-filtering



Gaussian 1/2



G 1/4



G 1/8

- Solution: filter the image, *then* subsample

Compare with...



1/2




1/4 (2x zoom)





1/8 (4x zoom)

Gaussian pre-filtering



- Solution: filter the image, *then* subsample



...



*Gaussian
pyramid*



blur



subsample




blur



subsample


...



Gaussian pyramids

[Burt and Adelson, 1983]

Idea: Represent $N \times N$ image as a “pyramid” of $1 \times 1, 2 \times 2, 4 \times 4, \dots, 2^k \times 2^k$ images (assuming $N=2^k$)




- In computer graphics, a *mip map* [Williams, 1983]
- A precursor to *wavelet transform*

Gaussian Pyramids have all sorts of applications in computer vision

Gaussian pyramids


[Burt and Adelson, 1983]

Idea: Represent $N \times N$ image as a “pyramid” of $1 \times 1, 2 \times 2, 4 \times 4, \dots, 2^k \times 2^k$ images (assuming $N = 2^k$)



- How much space does a Gaussian pyramid take compared to the original image?

Gaussian Pyramid




The Laplacian Pyramid

$$L_i = G_i - \text{expand}(G_{i+1})$$

Gaussian Pyramid

$$G_i = L_i + \text{expand}(G_{i+1})$$

Laplacian Pyramid







Fig. 10. A summary of the steps in Laplacian pyramid coding and decoding. First, the original image g_0 (lower left) is used to generate Gaussian pyramid levels g_1, g_2, \dots through repeated local averaging. Levels of the Laplacian pyramid L_0, L_1, \dots are then computed as the differences between adjacent Gaussian levels. Laplacian pyramid elements are quantized to yield the Laplacian pyramid code C_0, C_1, C_2, \dots . Finally, a reconstructed image r_0 is generated by summing levels of the code pyramid.

Questions?

CS4670: Computer Vision

Noah Snaveley


Image Interpolation



Image

Last time:

This image is too big to fit on the screen. How can we generate a half-sized version?



Source: S. Seitz

Upsampling



- This image is too small for this screen: 
- How can we make it 10 times as big?
- Simplest approach:
 - repeat each row
 - and column 10 times
- (“Nearest neighbor interpolation”)



Image interpolation




$d = 1$ in this example

Recall how a digital image is formed

$$F[x, y] = \text{quantize}\{f(xd, yd)\}$$

- It is a discrete point-sampling of a continuous function
- If we could somehow reconstruct the original function, any new image could be generated, at any resolution and scale

Image interpolation




$d = 1$ in this example

Recall how a digital image is formed

$$F[x, y] = \text{quantize}\{f(xd, yd)\}$$

- It is a discrete point-sampling of a continuous function
- If we could somehow reconstruct the original function, any new image could be generated, at any resolution and scale

Image interpolation



$d = 1$ in this example

- What if we don't know f ?


- Guess an approximation: \tilde{f}
- Can be done in a principled way: filtering
- Convert F to a continuous function:

$$f_F(x) = F\left(\frac{x}{d}\right) \text{ when } \frac{x}{d} \text{ is an integer, } 0 \text{ otherwise}$$


- Reconstruct by convolution with a *reconstruction filter*, h

$$\tilde{f} = h * f_F$$


Image interpolation




“Ideal” reconstruction




Nearest-neighbor interpolation



Linear interpolation




Gaussian reconstruction




Reconstruction filters

- What does the 2D version of this hat function look like?



$h(x, y)$




(tent function) performs
bilinear interpolation

Often implemented without cross-correlation

- E.g., http://en.wikipedia.org/wiki/Bilinear_interpolation

Better filters give better resampled images

- Bicubic** is common choice



Cubic reconstruction filter

$$r(x) = \frac{1}{6} \begin{cases} (12 - 9B - 6C)|x|^3 + (-18 + 12B + 6C)|x|^2 + (6 - 2B) & |x| < 1 \\ ((-B - 6C)|x|^3 + (6B + 30C)|x|^2 + (-12B - 48C)|x| + (8B + 24C)) & 1 \leq |x| < 2 \\ 0 & \text{otherwise} \end{cases}$$

Image interpolation

Original image:  x 10



Nearest-neighbor interpolation




Bilinear interpolation




Bicubic interpolation

Image interpolation

Also used for *resampling*



Raster to Vector Graphics

vector**magic**

Easily Convert Bitmap Images To Clean Vector Art

Log In | Sign Up
Forgot Password

Home | Online | Hand-Tracing | Desktop | Pricing | Support

Welcome | Comparisons | Examples | Buzz

Search

Easily Convert Bitmap Images To Clean Vector Art


Automatically convert bitmap images like JPEGs, GIFs and PNGs to the crisp, clean, scalable vector art of EPS, SVG, and PDF with the world's best auto-tracing software.

Use the convenient service online by uploading your image below, or start tracing images offline with the [Desktop Edition](#).

Save time and money getting your artwork ready to print, embroider, cut and more!



The diagram illustrates the conversion process. It starts with a 'Bitmap Image' (a pixelated yellow and black graphic). An arrow points to a 'Traced Image' (the same graphic with visible vector paths). Another arrow points to the final 'Vector Image' (a clean, scalable version of the graphic).




Online

Upload your bitmap image to convert it to a vector image (EPS, SVG and PDF).

Free to try, no signup necessary, and results ready right away. [Learn more](#)

 **Upload Image To Trace...**

[Subscribe](#) | [Pricing](#)





Desktop

Convert images offline to EPS, SVG, PDF, AI, DXF and EMF. Works seamlessly with Illustrator, Corel, and others.

Learn More

[Buy](#) | [Pricing](#)

Your product is AMAZING!
- Shawn, Reminderband

Featured in

The New York Times Communication Arts

Customers



Vector Magic is

- More accurate
- Easier to use
- Faster

than the alternatives.
[See comparisons](#)

Downloads

 [Desktop Application](#)

Languages: [English](#), [Deutsch](#), [Español](#), and [Français](#)

Support

- [FAQ](#)
 - [What Are Vectors?](#)
 - [What Are Bitmaps?](#)
 - [Why Use Vectors?](#)
 - [What Is Vectorization?](#)
- [Uses For Vector Images](#)
- [Useful Tools](#)
- [File Formats](#)


Tutorials

- [How To Use Vector Magic](#)
- [Vectorizing Artwork/Logos](#)
- [Vectorizing Photos](#)
- [Vectorizing Scans](#)
- [Tips And Tricks](#)
- [Building a New Font](#)

Need help?

- [Online contact form](#)

Depixelating Pixel Art



Questions?