

Load protocol

SMA Wires:

#	Description	Excitation	Properties
01	Wire 1	Strain driven cycles	0-5%
02	Wire 2	Strain driven cycles	0-5%
03	Wire 3	Strain driven cycles	0-5%
04	Wire 4	Strain driven cycles	0-5%
05	Wire 5	Strain driven cycles	0-5%
06	Wire 6	Strain driven cycles	0-5%
07	Wire 7	Strain driven cycles	0-5%
08	Wire 8	Strain driven cycles	0-5%
09	Wire 9	Strain driven cycles	0-5%
10	Wire 10	Strain driven cycles	0-5%
11	Wire 11	Strain driven cycles	0-5%
12	Wire 12	Strain driven cycles	0-5%
13	Wire 13	Strain driven cycles	0-5%
14	Wire 14	Strain driven cycles	0-5%
15	Wire 15	Strain driven cycles	0-5%
16	Wire 16	Strain driven cycles	0-5%
17	Wire 17	Strain driven cycles	0-5%
18	Wire 18	Strain driven cycles	0-5%
19	Wire 19	Strain driven cycles	0-5%

SMAWD:

#	Description	Excitation	Properties
01	1x SMAWD, 8 wires	Sinusoidal	20 mm, 0.1 Hz
02	1x SMAWD, 8 wires	Sinusoidal	20 mm, 0.5 Hz
03	1x SMAWD, 8 wires	Sinusoidal	20 mm, 1.0 Hz
04	1x SMAWD, 8 wires	Sinusoidal	40 mm, 0.1 Hz
05	1x SMAWD, 8 wires	Sinusoidal	40 mm, 0.5 Hz
06	1x SMAWD, 8 wires	Sinusoidal	40 mm, 1.0 Hz
07	2x SMAWDs, 4 wires each	Sinusoidal	20 mm, 0.5 Hz
08	2x SMAWDs, 4 wires each	Sinusoidal	40 mm, 1.0 Hz
09	2x SMAWDs, 4 wires each	Sinusoidal	20 mm, 0.5 Hz post EQ testing
10	2x SMAWDs, 4 wires each	Sinusoidal	40 mm, 1.0 Hz post EQ testing
11	2D RTHS, 1 SMAWD, Config. 1	Northridge (1994)	0.15 g
12	2D RTHS, 1 SMAWD, Config. 1	Kreta (2021)	0.15 g
13	2D RTHS, 1 SMAWD, Config. 1	Kobe (1995)	0.15 g
14	2D RTHS, 1 SMAWD, Config. 1	Northridge (1994)	0.30 g
15	2D RTHS, 1 SMAWD, Config. 1	Kreta (2021)	0.30 g
16	2D RTHS, 2 SMAWDs, Config. 2	Northridge (1994)	0.15 g
17	2D RTHS, 2 SMAWDs, Config. 2	Kreta (2021)	0.15 g
18	2D RTHS, 2 SMAWDs, Config. 2	Kobe (1995)	0.15 g
19	3D RTHS, 2 SMAWDs, Config. 1	Northridge (1994)	0.15 g
20	3D RTHS, 2 SMAWDs, Config. 1	Kreta (2021)	0.15 g
21	3D RTHS, 2 SMAWDs, Config. 2	Northridge (1994)	0.15 g
22	3D RTHS, 2 SMAWDs, Config. 2	Kreta (2021)	0.15 g