

BS API DOC

TABLE OF CONTENTS

Information.....	2
Methods.....	2
Fetch series list (Alphabetical)	2
Fetch series list (Genres)	2
Fetch season.....	2
Fetch episode.....	3
Fetch link.....	4
Login.....	4
Logout.....	4
Version.....	5
Error messages	5
Using login sessions.....	5

INFORMATION

Base URL	https://www.burning-seri.es/api (Only HTTPS!)
Response	JSON

METHODS

FETCH SERIES LIST (ALPHABETICAL)

URI	/series
Description	Fetches an array with all series, ordered alphabetically
Parameters	-
Response	<pre>array [object (string series, Series name int id Series ID), ...]</pre>

FETCH SERIES LIST (GENRES)

URI	/series:genre
Description	Fetches an array with all series, ordered by genre
Parameters	-
Response	<pre>Object ("Genre": object: (int id, Genre ID array series [object (string name, Series name int id Series ID), ...]), ...)</pre>

FETCH SEASON

URI	/series/[id]/[season]
Description	Fetches the episodes of a specified season of a specified series

Parameters	id: series ID season: season to fetch
Response	<pre> object (object series: (int id, Series ID string series, Series name string description, Series description int movies, Number of movies int seasons Number of seasons int start series start (year) int end Series end (year) object data (array producer [string, ...] Producers array author [string, ...] Authors array genre [string, ...] Genres array director [string, ...] Directors string genre Main genre)), int season, Season array epi [object (string german, German title string english, English title int epi, Episode number bool watched Already watched by user?), ...]) </pre>

FETCH EPISODE

URI	/series/[id]/[season]/[episode]
Description	Fetches information on a specified episode
Parameters	id: series ID season: season to fetch episode: episode number to fetch
Response	<pre> object (string series, Series name </pre>

	<pre> object epi (string german, German title string english, English title string description, Episode description int id Episode ID), array links [object (string hoster, Hoster int part, Part int id Link ID), ...]) </pre>
--	--

FETCH LINK

URI	/watch/[id]
Description	Fetches a specified link
Parameters	id: link ID
Response	<pre> object (string hoster, Hoster string url, URI identifier of the video string fullurl Full URL of the video int part Part) </pre>

LOGIN

URI	/login
Description	Starts a new session and returns the session id unless the login information is invalid.
Parameters	-
POST	<pre> login[user], User name login[pass] Password </pre>
Response	<pre> object (string user, User name string session Session ID) </pre>

LOGOUT

URI	/logout
-----	---------

Description	Ends a session
Parameters	-
Response	object (<i>bool</i> logout Logout succeeded)

VERSION

URI	/version/[system]
Description	Get the newest version number for a specific system for a software updater
Parameters	system: selected system, e.g. <i>android</i> or <i>ios</i>
Response	object (<i>int</i> version newest version)

ERROR MESSAGES

If the request is malformed or any other error occurs, an object containing the error message will be returned instead of the given response.

USING LOGIN SESSIONS

The session ID can always be sent in the GET argument 's' to fetch user-specific data, for example watched episodes.