- Client netplan config file

```
GNU nano 7.2                    /etc/netplan/50-cloud-init.yaml
# This file is generated from information provided by the datasource.  Changes
# to it will not persist across an instance reboot.  To disable cloud-init's
# network configuration capabilities, write a file
# /etc/cloud/cloud.cfg.d/99-disable-network-config.cfg with the following:
# network: {config: disabled}
network:
    ethernets:
        enp0s3:
            dhcp4: true
        enp0s8:
            dhcp4: false
            addresses:
                - 192.168.0.2/24
    version: 2

                                [ Read 14 lines ]
^G Help    ^O Write Out  ^W Where Is   ^K Cut       ^T Execute   ^C Location  M-U Undo    M-A Set Mark
^X Exit    ^R Read File  ^\ Replace    ^U Paste     ^J Justify   ^/ Go To Line M-E Redo    M-6 Copy
```

- Server netplan config file

```
GNU nano 7.2                    50-cloud-init.yaml
# This file is generated from information provided by the datasource.  Changes
# to it will not persist across an instance reboot.  To disable cloud-init's
# network configuration capabilities, write a file
# /etc/cloud/cloud.cfg.d/99-disable-network-config.cfg with the following:
# network: {config: disabled}
network:
    ethernets:
        enp0s3:
            dhcp4: true
        enp0s8:
            dhcp4: false
            addresses:
                - 192.168.0.1/24
    version: 2

                                [ Read 14 lines ]
^G Help    ^O Write Out  ^W Where Is   ^K Cut       ^T Execute   ^C Location  M-U Undo    M-A Set Mark
^X Exit    ^R Read File  ^\ Replace    ^U Paste     ^J Justify   ^/ Go To Line M-E Redo    M-6 Copy
```

- - Server pings client

```
administrator@administrator:/etc/netplan$ ping 192.168.0.2
PING 192.168.0.2 (192.168.0.2) 56(84) bytes of data.
64 bytes from 192.168.0.2: icmp_seq=1 ttl=64 time=0.678 ms
64 bytes from 192.168.0.2: icmp_seq=2 ttl=64 time=0.569 ms
64 bytes from 192.168.0.2: icmp_seq=3 ttl=64 time=0.594 ms
64 bytes from 192.168.0.2: icmp_seq=4 ttl=64 time=0.679 ms
64 bytes from 192.168.0.2: icmp_seq=5 ttl=64 time=0.729 ms
64 bytes from 192.168.0.2: icmp_seq=6 ttl=64 time=0.443 ms
64 bytes from 192.168.0.2: icmp_seq=7 ttl=64 time=0.552 ms
64 bytes from 192.168.0.2: icmp_seq=8 ttl=64 time=0.751 ms
^C
--- 192.168.0.2 ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 8134ms
rtt min/avg/max/mdev = 0.443/0.624/0.751/0.096 ms
administrator@administrator:/etc/netplan$
```

- - Client pings server

```
administrator@administrator:~$ ping 192.168.0.1
PING 192.168.0.1 (192.168.0.1) 56(84) bytes of data.
64 bytes from 192.168.0.1: icmp_seq=1 ttl=64 time=0.597 ms
64 bytes from 192.168.0.1: icmp_seq=2 ttl=64 time=0.576 ms
64 bytes from 192.168.0.1: icmp_seq=3 ttl=64 time=0.361 ms
64 bytes from 192.168.0.1: icmp_seq=4 ttl=64 time=0.382 ms
64 bytes from 192.168.0.1: icmp_seq=5 ttl=64 time=0.656 ms
64 bytes from 192.168.0.1: icmp_seq=6 ttl=64 time=0.347 ms
^C
--- 192.168.0.1 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5081ms
rtt min/avg/max/mdev = 0.347/0.486/0.656/0.125 ms
administrator@administrator:~$
```