"Schutzvermerk nach DIN ISO 16016 beachten" "Please pay attention to copyright note DIN ISO 16016"

A



A–A (1 : 1)



ISO (1 : 1)



B

A

Unterteil/
Base



B

B–B (1 : 1)



C

Oberteil/
Lid



C

C–C (1 : 1)





Z (2 : 1)



Y (2 : 1)



X (2 : 1)



Für Version mit Einlegedichtung:
Schutzart IP40. Um Schutzart IP65 zu erreichen,
muss die beiliegende Dichtung korrekt montiert werden.
Die Dichtung darf in den Ecken weder gestreckt noch gestaucht werden.
Stoßstelle schräg geschnitten und verklebt, sodaß die
Schnittstellen durch den Federdruck aufeinander gedrückt werden.

For Version with enclosed gasket
Protection class IP40. To achieve protection class IP65,
the enclosed gasket must be mounted correctly. The gasket must not be
stretched or compressed in the corners. Ends cut obliquely and glued,
so that the cut ends are pressed together by the spring pressure.

BOX4U

		Datum/*Date*	Name/*name*
Gezeichnet		10.05.2022	ES
Kontrolliert			
Norm			

Status	Ä.Nr/*Alt.No*	Datum/*Date*	Name

Zeichnungs-Nr. / *Drawing-No.:* 2K 5455.077.01

6U-110704

Katalogzeichnung/Catalogue drawing

2504626.idw

1:1 (2:1)

A2