

Sphinx-process-graph... 1/1

src / sphinx-graph / init.py :

→ uses Pydantic's Base Model for Data

→ `model-config = ConfigDict (extra="forbid")`

↓
unknown fields are an error

→ captures :

objects : A python object

events : sphinx events

transforms : transform for a sphinx event

more on ←
next page

post-transforms :

There might be other stuff to capture as well.

build-main → uses `sphinx-graph-tool`
to build the graph & then converts
to svg.

↓
build-graph) 



The sphinx-graph.toml is used to
create the ~~graph~~ final graph.svg.
Where does it come from?
→ ~~get-it~~ get-info.py (~~maybe~~)

Transforms

- A class in docutils
- sphinx reads .rst file &
creates a AST (doctree)

Transform → walks through the
doctree & improve it

Multiple (different kinds of)
transforms are applied before
converting those into HTML.

Each transform has a priority--
lower-numbered priority transforms
are applied first.

• xst

Apples

See :ref: 'quickstart'.

.. contents ::

Apples are red. [#]_

.. [#] and also green.

doctree

Document

↳ section

↳ Title ("Apples")

↳ Paragraph

↳ Text ("see ")

↳ Pending Xref (target="quickstart")

↳ Pending Contents

↳ Paragraph

↳ Text ("Apples are red.")

↳ Footnote Reference

↳ Footnote

↳ paragraph ("and also green.")



 After applying ~~diff~~ multiple transforms:

Document

↳ Title ("Apples")

↳ Paragraph

↳ Text ("see")

↳ Reference (href = "quickest.html")

↳ Table of Contents

↳ Paragraph

↳ Text ("Apples are red.")

↳ FootnoteReference (refid = "footnote-1")

↳ Footnote (id = "footnote-1")

↳ Paragraph ("and also green")

⊛ PendingXRef → Reference (sphinx cross-reference resolution) happens during sphinx's post processing of doctree instead through a Docutils transform class.

get-info.py

```
from sphinx.application import Sphinx
app = Sphinx(src dir "testes", conf dir None, out dir "testes/build",
doctreedir "testes", buildername "html")
```



roughly,

sphinx-build -b html testes
testes/build

benchmarking phases or events?
which events make a phase?