

# OptiFit: a fast method for fitting amplicon sequences to existing OTUs

2021-04-06

Kelly L. Sovacool<sup>1</sup>, Sarah L. Westcott<sup>2</sup>, M. Brodie Mumphrey<sup>1</sup>, Gabrielle A. Dotson<sup>1</sup>,  
Patrick D. Schloss<sup>2†</sup>

<sup>1</sup> Department of Computational Medicine and Bioinformatics, University of Michigan, Ann Arbor, MI 48109

<sup>2</sup> Department of Microbiology and Immunology, University of Michigan, Ann Arbor, MI 48109

† To whom correspondence should be addressed: [pschloss@umich.edu](mailto:pschloss@umich.edu)

- start paragraph with question, end with why we should care. transitions to move the story along.
- AND, BUT, THEREFORE, structure

## Abstract

Assigning amplicon sequences to Operational Taxonomic Units (OTUs) is an important step in characterizing the composition of microbial communities across large datasets. OptiClust, a *de novo* OTU clustering method in the mothur program, has been shown to produce higher quality OTU assignments than other methods and at comparable or faster speeds (1, 2). A notable difference between *de novo* clustering and database-dependent methods is that OTU assignments clustered with *de novo* methods are not stable when new sequences are added to a dataset (3). However, in some cases one may wish to incorporate new samples into a previously clustered dataset without performing clustering again on all sequences, such as when deploying a machine learning model where OTUs are features (4). To provide an efficient and robust method to fit amplicon sequence data to existing OTUs, we developed the OptiFit algorithm as a new component of the mothur program.

**TODO: summarize results & conclusion**

**Importance**

**TODO**

## Introduction

Amplicon sequencing has become a mainstay of microbial ecology and host-associated microbiome research. Researchers can affordably generate millions of sequences to characterize the composition of hundreds of samples from culture-independent microbial communities. In a typical analysis pipeline, 16S rRNA gene sequences are assigned to Operational Taxonomic Units (OTUs) to facilitate comparison of taxonomic composition between communities. A distance threshold of 3% (or sequence similarity of 97%) is commonly used to cluster sequences into OTUs based on either a reference database or pairwise comparisons of the sequences within the dataset. The method chosen for clustering affects the quality of OTU assignments and thus may impact downstream analyses of community composition (1, 3, 5).

There are three main categories of OTU clustering algorithms: closed reference, open reference, and *de novo* clustering. Closed reference methods assign sequences to a set of pre-made OTUs generated from reference sequences. If a query sequence is not within the distance threshold to any of the reference sequences, it is discarded. While reference-based clustering is generally fast, it is limited by the diversity of the reference database. Rare or novel sequences in the sample will be lost if they are not represented by a similar sequence in the database. *De novo* methods cluster sequences based on their distance to each other, without the use of an external reference. *De novo* clustering overcomes the limitations of reference databases by considering only sequences in the dataset, but is more computationally intensive and generates different OTU assignments when new sequences are introduced. Unstable OTU assignments make it difficult to use *de novo* clustering to compare taxonomic composition of communities between studies or to use machine learning models trained with *de novo* OTUs to make predictions on new data. Open reference methods take a hybrid approach, first performing closed reference clustering, then any sequences that cannot be assigned to reference OTUs are

clustered *de novo* to create additional OTUs. Previous studies found that the OptiClust *de novo* clustering algorithm created the highest quality OTU assignments of all clustering methods based on the Matthews correlation coefficient (MCC) (1). As a result, we have recommended OptiClust as the preferred method for OTU clustering whenever OTU stability is not required.

- **TODO: current method for open/closed is vsearch against greengenes.**
- **TODO: use word “map” for what vsearch does, “fit” for what optifit does.**
- **TODO: 2 categories of clustering: *de novo* and reference based.** separate paragraphs. describe opticlust first in *de novo* paragraph. 2nd paragraph: ref methods are good cause they’re fast and don’t use much ram. dependent on order of db. people use greengenes, which are rep seqs from 3% otus from full length.
- reader should know what opticlust is, closed & open ref clustering is, strengths & weakness are of each. then we solve these problems.
- **TODO: note that greengenes is defunct now?!**

To overcome the limitations of *de novo* clustering while maintaining OTU quality, we developed OptiFit, a reference-based clustering algorithm in the mothur program which takes existing OTUs as the reference to fit new sequences to. **TODO: more words here?** Here, we tested the OptiFit algorithm with the reference as a database or *de novo* OTUs and compared the performance to existing tools. To evaluate the OptiFit algorithm and compare to existing methods, we used four published datasets isolated from soil (6), marine (7), mouse gut (8), and human gut (9) samples.

## Results

### The OptiFit algorithm

OptiFit leverages the method employed by OptiClust of iteratively assigning sequences to OTUs to produce the highest quality OTUs possible, and extends this method for reference-based clustering. OptiFit begins where OptiClust ends, starting with a list of reference OTUs and their sequences, a list of query sequences to assign to the reference OTUs, and the sequence pairs that are within the distance threshold (e.g. 0.03). Initially, query sequences are placed in singleton OTUs. Then, the algorithm iteratively reassigns the query sequences to the reference OTUs to optimize the Matthews correlation coefficient (MCC). A sequence will remain unassigned if the MCC value is maximized when the sequence is a singleton rather than assigned to a reference OTU. This process is repeated until the MCC stabilizes, changing by no more than 0.0001 by default, or until a maximum number of iterations is reached (default: 100). In closed-reference mode, any query sequences that cannot be assigned to reference OTUs are discarded, and the results will only contain OTUs that exist in the original reference. In open-reference mode, unassigned query sequences are clustered *de novo* using OptiClust to generate additional OTUs. The final quality score is reported with the best OTU assignments. There are two strategies for generating OTUs with OptiFit: 1) fit sequences to reference OTUs of an independent database, or 2) split the dataset into a reference and query fraction, cluster the reference sequences *de novo*, then fit the query sequences to the reference OTUs.

### Reference clustering with public databases

While *de novo* clustering produces high quality OTUs, researchers may prefer to perform reference clustering to a public database because reference-based methods produce stable OTUs and are generally faster than *de novo* methods. In closed reference mode, sequences that cannot be assigned to reference OTUs are thrown out, so that the final

clustering contains only OTUs that exist in the reference. To test how OptiFit performs for this purpose, we fit each dataset to three databases of reference OTUs; the Greengenes database, the SILVA non-redundant database, and the Ribosomal Database Project (RDP) (10–12). Reference OTUs for each database were created by performing *de novo* clustering with OptiClust at a distance threshold of 3%. Fitting sequences to Greengenes and SILVA in closed reference mode performed similarly, with median MCC scores of 0.80 and 0.72 respectively, while when fitting to RDP the median MCC dropped to 0.33. For comparison to the state of the art, clustering datasets *de novo* with OptiClust produced an average MCC score of 0.83. This gap in OTU quality mostly disappears when clustering in open reference mode, which produced median MCCs of 0.82 with greengenes, 0.81 with Silva, and 0.82 with RDP. Thus, open reference OptiFit produces OTUs of very similar quality as *de novo* clustering, and closed reference OptiFit follows closely behind as long as a suitable reference database is chosen.

Since closed reference clustering throws out query sequences that cannot be assigned to reference OTUs, an additional measure of clustering performance to consider is the fraction of query sequences that were able to be assigned. On average, more sequences were assigned with Greengenes as the reference (`r_frac_fit_gg%`) than with Silva (36.35%) or RDP (7.15%). This mirrors the result reported above that Greengenes produced better OTUs in terms of MCC score than either Silva or RDP. Note that *De novo* and open reference clustering methods always assign 100% of sequences to OTUs. The database chosen affects the final OTU assignments considerably in terms of both MCC score and fraction of query sequences fit.

Despite the drawbacks, closed reference methods have been used when fast execution speed is required such as when using very large datasets. To compare performance in terms of speed, we repeated each OptiFit and OptiClust run 100 times and measured the execution time. Closed reference OptiFit outperformed OptiClust by 28.92% and

VSEARCH by 77.75%. In open reference mode, OptiFit ran faster than VSEARCH by 181.05%, but slower than OptiClust by 22.11%.

To compare to the reference clustering method used by QIIME2, we clustered each dataset with VSEARCH against the Greengenes database of OTUs clustered at 97% similarity. **TODO note vsearch otu definition vs. ours.** *De novo* clustering with OptiClust produced 56.08% higher quality OTUs than VSEARCH, but performed 48.79% slower than VSEARCH. VSEARCH was able to map 41.83% more query sequences than OptiFit to the Greengenes reference database in closed reference mode. OptiFit produced higher quality OTUs than VSEARCH when open reference clustering against the Greengenes database, with median MCC scores of 0.82 and 0.52 (respectively).

## Reference clustering with split datasets

- **TODO**; start with problem with current state of the art.
- tied to reference dbs that may be unrelated to samples studying. can we use our own data as a reference?
- lay out the use case and how this is a benefit over ref-db clustering.
- we wanted to use x% of data as ref, weren't sure what size to use and strategy for selecting.
- important result: it works!

A split dataset strategy was employed to assess how well OptiFit performs for tasks where new sequences are added to existing OTUs, such as when comparing OTUs across studies or making predictions with machine learning models. Datasets were randomly split into a reference fraction and a query fraction. Reference sizes from 10% to 80% of the sequences were created, with the remaining sequences used for the query. Reference sequences were clustered *de novo* with OptiClust, then query sequences were fit to the *de novo* OTUs with OptiFit.

**TODO; ref weight simple only here.** OTU quality from the split dataset strategy with OptiFit was highly similar to that from *de novo* clustering the whole dataset with OptiClust regardless of mode (0.90% difference in median MCC). OTU quality was remarkably stable across reference fraction sizes within parameter sets (Fig. **XX**). For example, splitting the human dataset 100 times yielded a coefficient of variation of 0.07 for the MCC score. In terms of runtime, closed and open reference OptiFit performed faster than OptiClust on whole datasets by 33.65% and 24.08 respectively. The split dataset strategy performed 6.66% faster than the database strategy in closed reference mode and 40.87% in open reference mode. **TODO: fraction mapped.**

**TODO: pick a fraction (e.g. 50%). this part is less important. figure would be supplemental.** We also tested three methods for selecting the fraction of sequences to be used as the reference; a simple random sample, weighting sequences by relative abundance, and weighting by similarity to other sequences in the dataset. OTU quality was similar with the simple and abundance-weighted sampling (median MCCs 0.82 and 0.84 respectively), but worse for similarity-weighted sampling with a median MCC of 0.71. In closed reference mode, the fraction of query sequences that can be fit to the reference OTUs increases as the reference fraction increases; from 53.80% of query sequences fit when using 10% of the dataset as the reference, to 75.20% of query sequences fit when using 80% of the dataset as the reference.

## Discussion

We developed a new algorithm for fitting sequences to existing OTUs and have demonstrated its suitability for reference-based clustering. OptiFit makes the iterative method employed by OptiClust available for tasks where reference-based clustering is required. We have shown that OTU quality is similar between OptiClust and OptiFit in open reference mode, regardless of strategy employed. Open reference OptiFit performs



168 slower than OptiClust due to the additional *de novo* clustering step, so users may prefer  
169 OptiClust for tasks that do not require reference OTUs.

170 When fitting to public databases, OTU quality dropped in closed reference mode to different  
171 degrees depending on the database and dataset source, and no more than half of query  
172 sequences were able to be fit to OTUs across any dataset/database combination. This  
173 may reflect limitations of reference databases, which are unlikely to contain sequences  
174 from rare and novel microbes. This drop in quality was most notable with RDP, which  
175 contains only about 21,000 sequences compared to over 200,000 sequences in SILVA and  
176 Greengenes each at the time of this writing. We recommend that users who require an  
177 independent reference database opt for large databases with good coverage of microbial  
178 diversity. Since OptiClust performs faster than open reference OptiFit and creates higher  
179 quality OTUs than closed reference OptiFit with the database strategy, we recommend  
180 using OptiClust rather than fitting to a database whenever stable OTUs are not required for  
181 the study at hand.

182 The OptiClust and OptiFit algorithms provided by mothur produced higher quality OTUs  
183 than VSEARCH in open reference, closed reference, or *de novo* modes. However,  
184 VSEARCH was able to map more sequences to OTUs than OptiFit in closed reference  
185 mode. While both mothur and VSEARCH use a distance or similarity threshold for  
186 determining how to assign sequences to OTUs, VSEARCH is more permissive than  
187 mothur. The OptiFit and OptiClust algorithms use all of the sequences to define an OTU,  
188 requiring that all pairs of sequences (including reference and query sequences) in an OTU  
189 are within the distance threshold without penalizing the MCC. In contrast, VSEARCH only  
190 requires each query sequence to be similar to the single sequence that seeded the OTU.  
191 In this way, VSEARCH sacrifices OTU quality in order to allow more sequences to fit to  
192 OTUs. Users who require closed reference clustering to the Greengenes database may  
193 prefer to use VSEARCH if they wish to maximize the fraction of sequences that can be fit

at the cost of OTU quality. However, mothur's OptiClust or OptiFit are recommended for *de novo* or open reference clustering to produce OTUs of the highest possible quality.

When fitting with the split dataset strategy, OTU quality was remarkably similar when reference sequences were selected by a simple random sample or weighted by abundance, but quality was slightly worse when sequences were weighted by similarity. We recommend using a simple random sample since the more sophisticated reference selection methods do not offer any benefit. The similarity in OTU quality between OptiClust and OptiFit with this strategy demonstrates the suitability of using OptiFit to fit sequences to existing OTUs, such as when using already-trained machine learning models to make predictions on new data or comparing OTUs across studies. However, when stable OTUs are not required, we recommend using OptiClust for *de novo* clustering over the split strategy with OptiFit since OptiClust is simpler to execute but performs similarly in terms of both run time and OTU quality.

**TODO: big picture concluding paragraph.** We have developed a new clustering algorithm that allows users to produce high quality OTUs using already existing OTUs as a reference. **TODO: Point to courtney's paper metaphorically. wow what a cool application someone should do *wink wink*.**

## Materials and Methods

### Data Processing Steps

We downloaded 16S rRNA gene amplicon sequences from four published datasets isolated from soil (6), marine (7), mouse gut (8), and human gut (9) samples. Raw sequences were processed using mothur according to the Schloss Lab MiSeq SOP as described in the mothur wiki and accompanying study by Kozich *et al.* (13, 14). These steps included trimming and filtering for quality, aligning to the SILVA reference alignment (11), discarding

sequences that aligned outside the V4 region, removing chimeric reads with UCHIME (15), and calculating distances between all pairs of sequences within each dataset prior to clustering.

## **Reference database clustering**

To generate reference OTUs from independent databases, we downloaded sequences from the Greengenes database (v13\_8\_99) (10), SILVA non-redundant database (v132) (11), and the Ribosomal Database Project (v16) (12). These sequences were processed using the same steps outlined above followed by clustering sequences into *de novo* OTUs with OptiClust. Processed reads from each of the four datasets were clustered with OptiFit to the reference OTUs generated from each of the three databases. When reference clustering with VSEARCH, processed datasets were fit directly to the unprocessed Greengenes reference alignment, since this method is how VSEARCH is typically used by the QIIME2 software reference-based clustering (16, 17).

## **Split dataset clustering**

For each dataset, a fraction of the sequences was selected to be clustered *de novo* into reference OTUs with OptiClust. We used three methods for selecting the fraction of sequences to be used as the reference; a simple random sample, weighting sequences by relative abundance, and weighting by similarity to other sequences in the dataset. Dataset splitting was repeated with reference fractions ranging from 10% to 80% of the dataset and for 100 random seeds. For each dataset split, the remaining sequences were assigned to the reference OTUs with OptiFit.

## **Benchmarking**

Since OptiClust and OptiFit employ a random number generator to break ties when OTU assignments are of equal quality, they produce slightly different OTU assignments when

repeated with different random seeds. To capture any variation in OTU quality or execution time, clustering was repeated with 100 random seeds for each combination of parameters and input datasets. We used the benchmark feature provided by Snakemake to measure the run time of every clustering job. We calculated the MCC on each set of OTUs to quantify the quality of clustering, as described by Westcott *et al.* (1).

## Data and Code Availability

We implemented the analysis workflow in Snakemake (18) and wrote scripts in R (19), Python (20), and GNU bash (21). Software used includes mothur v1.45.0 (2), VSEARCH v2.13.3 (22), numpy (23), the Tidyverse metapackage (24), R Markdown (25), the SRA toolkit (26), and the conda environment manager (27). The complete workflow, manuscript, and conda environment are available at **TODO: UPDATED REPO LINK**.

## Acknowledgements

KLS received support from the NIH Training Program in Bioinformatics (T32 GM070449).

PDS received support from **TODO: Pat's grant(s)**.

The funders had no role in study design, data collection and interpretation, or the decision to submit the work for publication.

## Author Contributions

KLS wrote the analysis code, evaluated the algorithm, and wrote the original draft of the manuscript. SLW designed and implemented the OptiFit algorithm and assisted in debugging the analysis code. MBM and GAD contributed analysis code. PDS conceived the study, supervised the project, and assisted in debugging the analysis code. All authors

reviewed and edited the manuscript.

1. **Westcott SL, Schloss PD.** 2017. OptiClust, an Improved Method for Assigning Amplicon-Based Sequence Data to Operational Taxonomic Units. *mSphere* **2**:e00073–17. doi:10.1128/mSphereDirect.00073-17.

2. **Schloss PD, Westcott SL, Ryabin T, Hall JR, Hartmann M, Hollister EB, Lesniewski RA, Oakley BB, Parks DH, Robinson CJ, Sahl JW, Stres B, Thallinger GG, Van Horn DJ, Weber CF.** 2009. Introducing mothur: Open-source, platform-independent, community-supported software for describing and comparing microbial communities. *Applied and Environmental Microbiology* **75**:7537–7541. doi:10.1128/AEM.01541-09.

3. **Westcott SL, Schloss PD.** 2015. De novo clustering methods outperform reference-based methods for assigning 16S rRNA gene sequences to operational taxonomic units. *PeerJ* **3**:e1487. doi:10.7717/peerj.1487.

4. **Topçuoğlu BD, Lesniak NA, Ruffin M, Wiens J, Schloss PD.** 2019. Effective application of machine learning to microbiome-based classification problems. *bioRxiv* 816090. doi:10.1101/816090.

5. **Schloss PD.** 2016. Application of a Database-Independent Approach To Assess the Quality of Operational Taxonomic Unit Picking Methods. *mSystems* **1**:e00027–16. doi:10.1128/mSystems.00027-16.

6. **Johnston ER, Rodriguez-R LM, Luo C, Yuan MM, Wu L, He Z, Schuur EAG, Luo Y, Tiedje JM, Zhou J, Konstantinidis KT.** 2016. Metagenomics Reveals Pervasive Bacterial Populations and Reduced Community Diversity across the Alaska Tundra Ecosystem. *Front Microbiol* **7**. doi:10.3389/fmicb.2016.00579.

7. **Henson MW, Pitre DM, Weckhorst JL, Lanclos VC, Webber AT, Thrash JC.** 2016. Artificial Seawater Media Facilitate Cultivating Members of the Microbial Majority from the

- 287 Gulf of Mexico. *mSphere* **1**. doi:10.1128/mSphere.00028-16.
- 288 8. **Schloss PD, Schubert AM, Zackular JP, Iverson KD, Young VB, Petrosino JF**. 2012.  
289 Stabilization of the murine gut microbiome following weaning. *Gut Microbes* **3**:383–393.  
290 doi:10.4161/gmic.21008.
- 291 9. **Baxter NT, Ruffin MT, Rogers MAM, Schloss PD**. 2016. Microbiota-based model  
292 improves the sensitivity of fecal immunochemical test for detecting colonic lesions. *Genome*  
293 *Med* **8**:37. doi:10.1186/s13073-016-0290-3.
- 294 10. **DeSantis TZ, Hugenholtz P, Larsen N, Rojas M, Brodie EL, Keller K, Huber**  
295 **T, Dalevi D, Hu P, Andersen GL**. 2006. Greengenes, a Chimera-Checked 16S  
296 rRNA Gene Database and Workbench Compatible with ARB. *AEM* **72**:5069–5072.  
297 doi:10.1128/AEM.03006-05.
- 298 11. **Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glöckner**  
299 **FO**. 2013. The SILVA ribosomal RNA gene database project: Improved data processing  
300 and web-based tools. *Nucleic Acids Research* **41**:D590–D596. doi:10.1093/nar/gks1219.
- 301 12. **Cole JR, Wang Q, Fish JA, Chai B, McGarrell DM, Sun Y, Brown CT, Porras-Alfaro**  
302 **A, Kuske CR, Tiedje JM**. 2014. Ribosomal Database Project: Data and tools for high  
303 throughput rRNA analysis. *Nucl Acids Res* **42**:D633–D642. doi:10.1093/nar/gkt1244.
- 304 13. **Schloss PD, Westcott SL**. MiSeq SOP. [https://mothur.org/MiSeq\\_SOP](https://mothur.org/MiSeq_SOP).
- 305 14. **Kozich JJ, Westcott SL, Baxter NT, Highlander SK, Schloss PD**. 2013.  
306 Development of a Dual-Index Sequencing Strategy and Curation Pipeline for Analyzing  
307 Amplicon Sequence Data on the MiSeq Illumina Sequencing Platform. *Appl Environ*  
308 *Microbiol* **79**:5112–5120. doi:10.1128/AEM.01043-13.
- 309 15. **Edgar RC, Haas BJ, Clemente JC, Quince C, Knight R**. 2011. UCHIME

improves sensitivity and speed of chimera detection. *Bioinformatics* **27**:2194–2200.  
doi:10.1093/bioinformatics/btr381.

16. **Bolyen E, Rideout JR, Dillon MR, Bokulich NA, Abnet CC, Al-Ghalith GA, Alexander H, Alm EJ, Arumugam M, Asnicar F, Bai Y, Bisanz JE, Bittinger K, Brejnrod A, Brislawn CJ, Brown CT, Callahan BJ, Caraballo-Rodríguez AM, Chase J, Cope EK, Da Silva R, Diener C, Dorrestein PC, Douglas GM, Durall DM, Duvallet C, Edwardson CF, Ernst M, Estaki M, Fouquier J, Gauglitz JM, Gibbons SM, Gibson DL, Gonzalez A, Gorlick K, Guo J, Hillmann B, Holmes S, Holste H, Huttenhower C, Huttley GA, Janssen S, Jarmusch AK, Jiang L, Kaehler BD, Kang KB, Keefe CR, Keim P, Kelley ST, Knights D, Koester I, Kosciulek T, Kreps J, Langille MGI, Lee J, Ley R, Liu Y-X, Lottfield E, Lozupone C, Maher M, Marotz C, Martin BD, McDonald D, McIver LJ, Melnik AV, Metcalf JL, Morgan SC, Morton JT, Naimey AT, Navas-Molina JA, Nothias LF, Orchanian SB, Pearson T, Peoples SL, Petras D, Preuss ML, Priesse E, Rasmussen LB, Rivers A, Robeson MS, Rosenthal P, Segata N, Shaffer M, Shiffer A, Sinha R, Song SJ, Spear JR, Swafford AD, Thompson LR, Torres PJ, Trinh P, Tripathi A, Turnbaugh PJ, Ul-Hasan S, van der Hooft JJJ, Vargas F, Vázquez-Baeza Y, Vogtmann E, von Hippel M, Walters W, Wan Y, Wang M, Warren J, Weber KC, Williamson CHD, Willis AD, Xu ZZ, Zaneveld JR, Zhang Y, Zhu Q, Knight R, Caporaso JG.** 2019. Reproducible, interactive, scalable and extensible microbiome data science using QIIME 2. *Nat Biotechnol* **37**:852–857. doi:10.1038/s41587-019-0209-9.

17. Clustering sequences into OTUs using q2-vsearch QIIME 2 2021.2.0 documentation. <https://docs.qiime2.org/2021.2/tutorials/otu-clustering/>.

18. **Köster J, Rahmann S.** 2012. Snakemake a scalable bioinformatics workflow engine. *Bioinformatics* **28**:2520–2522. doi:10.1093/bioinformatics/bts480.

19. **R Core Team.** 2020. R: A language and environment for statistical computing. Manual,

R Foundation for Statistical Computing, Vienna, Austria.

20. **Van Rossum G, Drake FL.** 2009. Python 3 Reference Manual | Guide books.

21. Bash Reference Manual. <https://www.gnu.org/software/bash/manual/bash.html>.

22. **Rognes T, Flouri T, Nichols B, Quince C, Mahé F.** 2016. VSEARCH: A versatile open source tool for metagenomics. *PeerJ* **4**:e2584. doi:10.7717/peerj.2584.

23. **Harris CR, Millman KJ, van der Walt SJ, Gommers R, Virtanen P, Cournapeau D, Wieser E, Taylor J, Berg S, Smith NJ, Kern R, Picus M, Hoyer S, van Kerkwijk MH, Brett M, Haldane A, del Río JF, Wiebe M, Peterson P, Gérard-Marchant P, Sheppard K, Reddy T, Weckesser W, Abbasi H, Gohlke C, Oliphant TE.** 2020. Array programming with NumPy. *Nature* **585**:357–362. doi:10.1038/s41586-020-2649-2.

24. **Wickham H, Averick M, Bryan J, Chang W, McGowan LD, François R, Golemund G, Hayes A, Henry L, Hester J, Kuhn M, Pedersen TL, Miller E, Bache SM, Müller K, Ooms J, Robinson D, Seidel DP, Spinu V, Takahashi K, Vaughan D, Wilke C, Woo K, Yutani H.** 2019. Welcome to the Tidyverse. *Journal of Open Source Software* **4**:1686. doi:10.21105/joss.01686.

25. **Xie Y, Allaire JJ, Golemund G.** 2018. R Markdown: The Definitive Guide. Taylor & Francis, CRC Press.

26. SRA-Tools - NCBI. <http://ncbi.github.io/sra-tools/>.

27. 2016. Anaconda Software Distribution. Anaconda Documentation. Anaconda Inc.

## References