

# Boosting

## Introduction & Gradient Boosting

# Objectives

After this lecture you will be able to:

- Describe conceptually what boosting is
- Describe the Gradient Boosting algorithm
- List Gradient Boosting hyperparameters
- Be able to use GridSearchCV to find the best hyperparameters for a model
- List a couple of *useful* non-sklearn based boosting algorithms


# Setting the stage

Test time!

10 students have 1 hour to take the test.

Think of each student taking the test as a machine learning model (say decision tree).

After the test, and by using all the tests, is there some way the **students could work together** to submit **one exam** with the **answers mostly right**?




# Working apart, then aggregating results...

Assuming the students are *strong learners* (low bias) but make occasional mistakes (high variance), for each multiple choice question take the majority vote from the class.

That majority vote should be right (and will have less variance than an answer by an individual student.)

It's like the ensemble method **bagging** (but without the bootstrap - all students took the same test).




# An unconventional strategy...

But what if students could work differently during the test?

Instead of working in parallel (each student working independently on their own during the hour), they could work **sequentially**?

Student 1 fills in the test quickly (only has 6 minutes!), then passes the test to Student 2 for editing, who passes it to Student 3 for editing, etc. all the way to student 10.




# ...but it's not cheating in the machine learning world...

But what if students could work differently during the test?

Instead of working in parallel (each student working independently on their own during the hour), they could work **sequentially**?

Student 1 fills in the test quickly (only has 6 minutes!), then passes the test to Student 2 for editing, who passes it to Student 3 for editing, etc. all the way to student 10.




An important detail: each time the test is passed from one student to another, the teacher rushes in with a red pen and marks all the wrong answers for the next student to see.

# That test was boosted!

Even though each student didn't have much time with the test (*weak learner with high bias*), the ability to focus on the questions the previous student got wrong in the end gives good results!

A+



# Ensemble methods

The goal of **ensemble methods** is to combine the predictions of several models of a given learning algorithm to improve generalizability / robustness over a single model.

Two families of ensemble models:

In **averaging methods**, high variance models are built and then their predictions are averaged. The combined model is usually better than any single model because its variance is reduced. (ex. bagging, random forests)

In **boosting methods**, high bias models are built sequentially on top of each other. The motivation is to combine many weak models to produce a powerful ensemble low-bias model in the end. (ex. boosted trees)

In both cases, the goal is to arrive at a low bias, low variance model.



# Boosting - general idea

- In Boosting, an ensemble of trees is grown *sequentially*, based on information learned in the previous tree.
- Specifically, each new tree (after the first) is fit on some **modified version of the training set** based on results from the previous tree.
- In **Adaboost**, the data associated with the largest residuals are *weighted the most* in the new training set.
- In **Gradient Boosting**, the new training set **is the residuals**. (Makes “new” training sets)
- Can think of each boosted tree as a weak “rule of thumb,” where the final prediction is a combination of these increasingly specific rules-of-thumb to yield good prediction accuracy in the end.
- We want our weak learners: in this case high bias, low variance. By sequential addition of models the bias is decreased to get a low bias, low variance model.

# How is fitting on the residual gradient descent?

**TABLE 10.2.** *Gradients for commonly used loss functions.*

Setting	Loss Function	$-\partial L(y_i, f(x_i))/\partial f(x_i)$
Regression	$\frac{1}{2}[y_i - f(x_i)]^2$	$y_i - f(x_i)$
Regression	$ y_i - f(x_i) $	$\text{sign}[y_i - f(x_i)]$
Regression	Huber	$y_i - f(x_i)$ for $ y_i - f(x_i)  \leq \delta_m$ $\delta_m \text{sign}[y_i - f(x_i)]$ for $ y_i - f(x_i)  > \delta_m$ where $\delta_m = \alpha\text{th-quantile}\{ y_i - f(x_i) \}$
Classification	Deviance	$k\text{th component: } I(y_i = \mathcal{G}_k) - p_k(x_i)$

# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

Algorithm:


1. Initialize model with a constant value:

$$F_0(x) = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, \gamma).$$

*Find the initial simple model with the least loss*

# The Gradient Descent Regressor Visually

The Zero'th Boosting Stage



# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

Algorithm:

1. Initialize model with a constant value:

$$F_0(x) = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, \gamma).$$

*Find the initial simple model with the least loss*

2. For  $m = 1$  to  $M$ :

1. Compute so-called *pseudo-residuals*:


$$r_{im} = - \left[ \frac{\partial L(y_i, F(x_i))}{\partial F(x_i)} \right]_{F(x)=F_{m-1}(x)} \quad \text{for } i = 1, \dots, n.$$

*For each tree  $m = 1..M$*

*Compute the residuals for all the data  $i=1..n$  for model  $m-1$*


# The Gradient Descent Regressor Visually

The First Boosting Stage With Residuals  $y_i - f_0(x_i)$



# The Gradient Descent Regressor Visually

Residuals  $y - f_0(x)$  : Training Data For First Tree





# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

Algorithm:

1. Initialize model with a constant value:

$$F_0(x) = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, \gamma).$$

*Find the initial simple model with the least loss*

2. For  $m = 1$  to  $M$ :

*For each tree  $m = 1..M$*

1. Compute so-called *pseudo-residuals*:

$$r_{im} = - \left[ \frac{\partial L(y_i, F(x_i))}{\partial F(x_i)} \right]_{F(x)=F_{m-1}(x)} \quad \text{for } i = 1, \dots, n.$$

*Compute the residuals for all the data  $i=1..n$  for model  $m-1$*

2. Fit a base learner (e.g. tree)  $h_m(x)$  to pseudo-residuals, i.e. train it using the training set  $\{(x_i, r_{im})\}_{i=1}^n$ .

*Fit a model,  $h_m$ , to residuals*

# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

Algorithm:

1. Initialize model with a constant value:

$$F_0(x) = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, \gamma).$$

*Find the initial simple model with the least loss*

2. For  $m = 1$  to  $M$ :

*For each tree  $m = 1..M$*

1. Compute so-called *pseudo-residuals*:

$$r_{im} = - \left[ \frac{\partial L(y_i, F(x_i))}{\partial F(x_i)} \right]_{F(x)=F_{m-1}(x)} \quad \text{for } i = 1, \dots, n.$$

*Compute the residuals for all the data  $i=1..n$  for model  $m-1$*

2. Fit a base learner (e.g. tree)  $h_m(x)$  to pseudo-residuals, i.e. train it using the training set  $\{(x_i, r_{im})\}_{i=1}^n$ .

*Fit a model,  $h_m$ , to residuals*

3. Compute multiplier  $\gamma_m$  by solving the following **one-dimensional optimization** problem:

$$\gamma_m = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, F_{m-1}(x_i) + \gamma h_m(x_i)).$$

*Determine the weighting factor  $\gamma$  for  $h_m$  that reduces the loss the most*

# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

Algorithm:

1. Initialize model with a constant value:

$$F_0(x) = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, \gamma).$$

*Find the initial simple model with the least loss*

2. For  $m = 1$  to  $M$ :

*For each tree  $m = 1..M$*

1. Compute so-called *pseudo-residuals*:

$$r_{im} = - \left[ \frac{\partial L(y_i, F(x_i))}{\partial F(x_i)} \right]_{F(x)=F_{m-1}(x)} \quad \text{for } i = 1, \dots, n.$$

*Compute the residuals for all the data  $i=1..n$  for model  $m-1$*

2. Fit a base learner (e.g. tree)  $h_m(x)$  to pseudo-residuals, i.e. train it using the training set  $\{(x_i, r_{im})\}_{i=1}^n$ .

*Fit a model,  $h_m$ , to residuals*

3. Compute multiplier  $\gamma_m$  by solving the following **one-dimensional optimization** problem:

$$\gamma_m = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, F_{m-1}(x_i) + \gamma h_m(x_i)).$$

*Determine the weighting factor  $\gamma$  for  $h_m$  that reduces the loss the most*


4. Update the model:

$$F_m(x) = F_{m-1}(x) + \gamma_m h_m(x).$$

*Model  $m$  is defined as model  $m-1$  plus the weighting factor times the fit to the residuals*


# The Gradient Descent Regressor Visually

The Second Boosting Stage




# The Gradient Descent Regressor Visually


The Second Boosting Stage With Residuals  $y_i - f_0(x_i) - f_1(x_i)$




# The Gradient Descent Regressor Visually



# The Gradient Descent Regressor Visually




# The Gradient Descent Regressor Visually





# The Gradient Descent Regressor Visually



# The Gradient Descent Regressor Algorithm

Input: training set  $\{(x_i, y_i)\}_{i=1}^n$ , a differentiable loss function  $L(y, F(x))$ , number of iterations  $M$ .

*M - number of trees*

Algorithm:

1. Initialize model with a constant value:

$$F_0(x) = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, \gamma).$$

*Find the initial simple model with the least loss*

2. For  $m = 1$  to  $M$ :

*For each tree  $m = 1..M$*

1. Compute so-called *pseudo-residuals*:

$$r_{im} = - \left[ \frac{\partial L(y_i, F(x_i))}{\partial F(x_i)} \right]_{F(x)=F_{m-1}(x)} \quad \text{for } i = 1, \dots, n.$$

*Compute the residuals for all the data  $i=1..n$  for model  $m-1$*

2. Fit a base learner (e.g. tree)  $h_m(x)$  to pseudo-residuals, i.e. train it using the training set  $\{(x_i, r_{im})\}_{i=1}^n$ .

*Fit a model,  $h_m$ , to residuals*

3. Compute multiplier  $\gamma_m$  by solving the following **one-dimensional optimization** problem:

$$\gamma_m = \arg \min_{\gamma} \sum_{i=1}^n L(y_i, F_{m-1}(x_i) + \gamma h_m(x_i)).$$

*Determine the weighting factor  $\gamma$  for  $h_m$  that reduces the loss the most*

4. Update the model:

$$F_m(x) = F_{m-1}(x) + \gamma_m h_m(x).$$

*Model  $m$  is defined as model  $m-1$  plus the weighting factor times the fit to the residuals*

3. Output  $F_M(x)$ .

*Model  $M$  is the weighted sum of models  $1..M-1$*


*adapted from Wikipedia*

# Breakout - Part 1

Pair up and ask your partner the following questions:

1. What is a *weak learner*?
2. How do bias & variance relate to a *weak learner*?
3. How are *weak learners* used in boosting?
4. Describe how a decision tree can be a *weak learner*.


# Breakout - Part 2



## With a partner:

1. How many leaf nodes are in *tree 1*? Draw the full tree including the values that determine the splits. Assume a max depth of 2.

# Breakout - Part 2




**With a partner:**

2. In [ISLR](#), the prediction of a boosted model is represented as  $\hat{f}(x) = \sum_{b=1}^B \lambda \hat{f}^b(x)$

Looking at the diagram above, what are:  $b$   $B$   $\lambda$   $\hat{f}^b(x)$

# Breakout - Part 2



## With a partner:

3. Calculate the predicted y-value from the full 3-tree model, for new data points:  $x=2$  and  $x=6$ , what assumptions are required to make your predictions?

# Gradient boosting in sklearn - and hyperparameters

```
class sklearn.ensemble. GradientBoostingRegressor (loss='ls', learning_rate=0.1, n_estimators=100,  
subsample=1.0, min_samples_split=2, min_samples_leaf=1, min_weight_fraction_leaf=0.0, max_depth=3, init=None,  
random_state=None, max_features=None, alpha=0.9, verbose=0, max_leaf_nodes=None, warm_start=False,  
presort='auto') ¶
```

[\[source\]](#)

```
class sklearn.ensemble. GradientBoostingClassifier (loss='deviance', learning_rate=0.1, n_estimators=100,  
subsample=1.0, min_samples_split=2, min_samples_leaf=1, min_weight_fraction_leaf=0.0, max_depth=3, init=None,  
random_state=None, max_features=None, verbose=0, max_leaf_nodes=None, warm_start=False, presort='auto') ¶
```

Gradient boosted trees have all the same hyperparameters as decision trees, but with a few more:

- `learning_rate`
- `subsample`
- `max_features`

# Hyperparameter: `learning_rate`

Also known as the shrinkage parameter, it is applied when one model is added onto another model. Typically  $\sim 0.2$ . Highly related to `n_estimators` to get a desired test error. In cross-validation we usually set either the `learning_rate` or `n_estimators` and then vary the other.

No shrinkage:

$$F_m(x) = F_{m-1}(x) + \gamma_m h_m(x).$$

With shrinkage:

$$F_m(x) = F_{m-1}(x) + \nu \cdot \gamma_m h_m(x), \quad 0 < \nu \leq 1$$

where parameter  $\nu$  is called the "learning rate".

*"Empirically it has been found that using small learning rates (such as  $\nu < 0.1$ ) yields dramatic improvements in model's generalization ability over gradient boosting without shrinking. However, it comes at the price of increasing computational time both during training and querying: lower learning rate requires more iterations." - Wikipedia*



# Hyperparameters: `subsample` & `max_features`

To build randomness similar to random forest methods, we may choose to build each tree on a **`subsample`** of our data.

Unlike in random forests, we sample without replacement.

We might also subset our feature space using **`max_features`** similar to random forests.

Building in randomness in the above ways creates a method known as Stochastic Gradient Descent, which has been shown to work faster and better in many cases, and provide some regularization.

# Selection of hyperparameters

GridsearchCV looks exhaustively through the parameters you give it to find the set that does the best on your scoring metric.

By default  $k=3$ , see documentation.

```
from sklearn.model_selection import GridSearchCV

random_forest_grid = {'max_depth': [3, None],
                      'max_features': ['sqrt', 'log2', None],
                      'min_samples_split': [1, 2, 4],
                      'min_samples_leaf': [1, 2, 4],
                      'bootstrap': [True, False],
                      'n_estimators': [20, 40, 60, 80, 100, 120],
                      'random_state': [42]}

rf_gridsearch = GridSearchCV(RandomForestClassifier(),
                             random_forest_grid,
                             n_jobs=-1, verbose=True,
                             scoring='f1_weighted')
rf_gridsearch.fit(X_train, y_train)
print "best parameters:", rf_gridsearch.best_params_
```

```
best parameters: {'bootstrap': True, 'min_samples_leaf': 1, '
n_estimators': 100, 'min_samples_split': 1, 'random_state': 42, '
max_features': 'sqrt', 'max_depth': None}
```

# Types of Grid Search

- Exhaustive Grid Search ([GridSearchCV](#))  
Looks through every combination of hyperparameters.

```
param_grid = {'C': [1, 10, 100, 1000], 'gamma': [0.001, 0.0001], 'kernel': ['rbf']}
```

# Types of Grid Search

- Exhaustive Grid Search ([GridSearchCV](#))  
Looks through every combination of hyperparameters.

```
param_grid = {'C': [1, 10, 100, 1000], 'gamma': [0.001, 0.0001], 'kernel': ['rbf']}
```

How many models would this Grid Search cause to be trained?

# Types of Grid Search

- Exhaustive Grid Search ([GridSearchCV](#))  
Looks through every combination of hyperparameters.

```
param_grid = {'C': [1, 10, 100, 1000], 'gamma': [0.001, 0.0001], 'kernel': ['rbf']}
```

How many models would this Grid Search cause to be trained?

$4 * 2 * 1 = 8$  \* number of folds! (default is 3), so 24!

# Types of Grid Search

- Exhaustive Grid Search ([GridSearchCV](#))  
Looks through every combination of hyperparameters.

```
param_grid = {'C': [1, 10, 100, 1000], 'gamma': [0.001, 0.0001], 'kernel': ['rbf']}
```

- Randomized Parameter Optimization ([RandomizedSearchCV](#))  
Implements a randomized search over parameters, where each setting is sampled from a distribution over possible parameter values.


```
{'C': scipy.stats.expon(scale=100), 'gamma': scipy.stats.expon(scale=.1),  
 'kernel': ['rbf'], 'class_weight':['balanced', None]}
```

[Comparing the two...](#)

# Boosting tips

Overfitting can be a problem with boosting (debatable). To prevent this:

- Keep the base estimator simple (limit its `max_depth` to 2-8).
- Limit `M`, the maximum number of iterations. Use `staged_predict` (a method on a Gradient Boosting Regressor object) to monitor the train and test errors as they evolve with each iteration.
- Use shrinkage
- Use Stochastic Gradient Boosting using `subsample` and `max_features`
- Use large values for `min_samples_leaf` (also limits the depth of the tree)



# Boosting - algorithms of note

XGBoost - A top performing algorithm on Kaggle.

note: installation on Mac involved - wait until you have time to debug

CatBoost - For only categorical features



# Objectives

After this lecture you will be able to:

- Describe conceptually what boosting is
- Describe the Gradient Boosting algorithm
- List Gradient Boosting hyperparameters
- Be able to use GridSearchCV to find the best hyperparameters for a model
- List a couple of *useful* non-sklearn based boosting algorithms

# Jupyter notebook demo

```
boosting_drury.ipynb
```