

Runtime (and Memory) Analysis

Problem

- ▶ Code can take an unfeasibly long time to run.
- ▶ (Code can require more memory than available.)

Solution

- ▶ Analyze the runtime of your code to make it more efficient.
- ▶ (Analyze the memory requirement of your code to make it more efficient.)

Example 1

How long does this take to run?

```
for i in range(n):  
    print(i)
```

Runtime is expressed as a function of n , the size of the code's input.

Example 1

```
for i in range(n):  
    print(i)
```

Example 1

```
for i in range(n): # 1 + n steps  
    print(i)       # n steps
```

$1 \text{ step} + 2n \text{ steps} \approx 2n \text{ steps}$ for large value of n

Example 2

How long does this take to run?

```
for i in range(n):  
    for j in range(n):  
        print(i, j)
```

Example 2

```
for i in range(n):  
    for j in range(n):  
        print(i, j)
```


Example 2

```
for i in range(n):      # 1 + n steps
    for j in range(n):  # n * (1 + n) steps
        print(i, j)     # n^2 steps
```

$1 \text{ step} + 2n \text{ steps} + 2n^2 \text{ steps} \approx 2n^2 \text{ steps}$ for large value of n

Example 3

How long does this take to run?

```
def find_anagrams(words):  
    anagrams = []  
    for word1 in words:  
        for word2 in words:  
            if word1 != word2:  
                for word in permutations(word1):  
                    if word == list(word2):  
                        anagrams.append(word1)  
    return anagrams
```

Example 3

```
def find_anagrams(words):  
    anagrams = []  
    for word1 in words:  
        for word2 in words:  
            if word1 != word2:  
                for word in permutations(word1):  
                    if word == list(word2):  
                        anagrams.append(word1)  
    return anagrams
```

Example 3

```
def find_anagrams(words):  
    anagrams = []  
    for word1 in words:  
        for word2 in words:  
            if word1 != word2:  
                for word in permutations(word1):  
                    if word == list(word2):  
                        anagrams.append(word1)  
    return anagrams
```

1
1 + n
n * (1 + n)
n^2 * k
n^2 * k!
n^2 * k! * k
n^2 * k! * k
1

$$3 + 2n + n^2 + n^2k + n^2k! + 2n^2(k+1)! \text{ steps}$$

Is this a useful expression?

$$3 + 2n + n^2 + n^2k + n^2k! + 2n^2(k+1)! \text{ steps}$$

- ▶ $(n, k) = (10, 5)$
 - ▶ $3 + 20 + 1E2 + 5E2 + 12E4 + \mathbf{12E5}$
- ▶ $(n, k) = (100, 10)$
 - ▶ $3 + 200 + 1E4 + 1E5 + 4E10 + \mathbf{8E11}$

With large inputs, only the largest terms of the expression are relevant.

Simplifying Runtime Analysis: Big O Notation

- ▶ Often, a single term dominates the runtime expression.
- ▶ Runtime analysis can be simplified by eliminating lower order terms.
- ▶ Big O notation provides a principled way to do this.

Big O Definition

Let f and g be two functions: $\mathbb{N} \rightarrow \mathbb{R}^+$. We say that

$$f(n) \in O(g(n))$$

(read f is Big-"O" of g)

if there exists a constant $c \in \mathbb{R}^+$ and $n_0 \in \mathbb{N}$ such that for every integer $n \geq n_0$,

$$f(n) \leq cg(n)$$

Big O Intuitive Summary

$$f = O(g)$$

"f is bounded by g" (roughly speaking)

- ▶ f is bounded by some constant multiple of g
- ▶ (only true for sufficiently large input values)

Practical runtime analysis only cares about large input values and approximate bounds.

Big O Conventions

Be Precise

- ▶ Technically, if a function is $O(n)$, then it is also $O(n^2)$.
 - ▶ But a more precise upper bound is more useful.
- ▶ Therefore, give the lowest upper bound possible.
 - ▶ I.e., don't say $O(n^2)$ when you could instead say $O(n)$.

Ignore Constants

- ▶ If a function is $O(n)$, then it is also $O(2n)$.
- ▶ Saying $O(2n)$ is highly unconventional.

Big O Example

What's the big O analysis of this expression? (from the earlier anagrams example)

$$3 + 2n + n^2 + n^2k + n^2k! + 2n^2(k+1)! \text{ steps}$$

Big O Example

Example 4

How long does this take to run?

```
def find_anagrams(words):  
    anagrams = []  
    d = defaultdict(list)  
    for word in words:  
        d[tuple(sorted(word))].append(word)  
    for _, words in d.items():  
        if len(words) > 1:  
            anagrams.extend(words)  
    return anagrams
```

Example 4

```
def find_anagrams(words):  
    anagrams = []  
    d = defaultdict(list)  
    for word in words:  
        d[tuple(sorted(word))].append(word)  
    for _, words in d.items():  
        if len(words) > 1:  
            anagrams.extend(words)  
    return anagrams
```

Example 4

```
def find_anagrams(words):  
    anagrams = []                                #  $O(1)$   
    d = defaultdict(list)                       #  $O(1)$   
    for word in words:                          #  $O(n)$   
        d[tuple(sorted(word))].append(word)    #  $O(n * k * \log(k))$   
        # line is executed  $n$  times; then in series,  
        # - sorted() is  $O(k * \log(k))$   
        # - d[] is  $O(1)$   
        # - .append() is  $O(1)$   
    for _, words in d.items():                  #  $v$   
        if len(words) > 1:                     #  $v$   
            anagrams.extend(words)             #  $O(n)$   
    return anagrams                            #  $O(1)$ 
```

Common runtimes to remember

- ▶ $O(1)$ - constant
- ▶ $O(n)$ - linear
- ▶ $O(n \log(n))$ - “n log n”
- ▶ $O(n^2)$ - quadratic
- ▶ $O(n^3)$ - cubic
- ▶ $O(2^n)$ - exponential (base is not necessarily 2)
- ▶ $O(n!)$ - factorial

Runtime in practical terms

n	Linear runtime	Quadratic runtime
100	1 s	1s
1000	10 s	100 s
10,000	100 s	10,000 s = 167 min
100,000	1000 s = 17 min	1,000,000 s = 11 days

Quadratic (n^2) algorithms are already really slow.

Linear (n) or $n\log(n)$ are ideal; anything bigger is usually too slow for large data.

Back to example 1

How much memory does this take to run?

```
for i in range(n):  
    print(i)
```

Memory is expressed as a function of n , the size of the code's input.

Back to example 2

How much memory does this take to run?

```
for i in range(n):  
    for j in range(n):  
        print(i, j)
```

Back to example 3

How much memory does this take to run?

```
def find_anagrams(words):  
    anagrams = []  
    for word1 in words:  
        for word2 in words:  
            if word1 != word2:  
                for word in permutations(word1):  
                    if word == list(word2):  
                        anagrams.append(word1)  
    return anagrams
```

Back to example 4

How long does this take to run?

```
def find_anagrams(words):  
    anagrams = []  
    d = defaultdict(list)  
    for word in words:  
        d[tuple(sorted(word))].append(word)  
    for _, words in d.items():  
        if len(words) > 1:  
            anagrams.extend(words)  
    return anagrams
```

Important data structures

- ▶ Lists
- ▶ Dictionaries
- ▶ Graphs
 - ▶ Trees

Runtime of typical Python list functions

- ▶ Appending
- ▶ Adding to the beginning or middle
- ▶ Popping from the end
- ▶ Popping from the beginning or middle
- ▶ Looking up by index
- ▶ Searching an unsorted list
- ▶ Searching a sorted list

Runtime of typical Python list functions (Time Complexity)

- ▶ Appending:
 - ▶ $O(1)$
- ▶ Adding to the beginning or middle:
 - ▶ $O(n)$ (have to shift elements over!)
- ▶ Popping from the end:
 - ▶ $O(1)$
- ▶ Popping from the beginning or middle:
 - ▶ $O(n)$ (again, have to shift elements over!)
- ▶ Looking up by index:
 - ▶ $O(1)$
- ▶ Searching an unsorted list:
 - ▶ $O(n)$ (have to look at every item)
- ▶ Searching a sorted list:
 - ▶ $O(\log n)$ (binary search)

Runtime of typical Python dictionary functions

- ▶ Inserting an item
- ▶ Removing an item
- ▶ Looking up by key
- ▶ Looking up by value

Runtime of typical Python dictionary functions (Time Complexity)

- ▶ Inserting an item:
 - ▶ $O(1)$
- ▶ Removing an item:
 - ▶ $O(1)$
- ▶ Looking up by key:
 - ▶ $O(1)$
- ▶ Looking up by value:
 - ▶ $O(n)$ (have to look at every item)

More

Algorithms Notes for Professionals book

- ▶ Chapter 2: Algorithm Complexity
- ▶ Chapter 22: Big-O Notation

Important algorithms: Sorting

Algorithm	Best	Average	Worst	Memory
Bubble sort	n	n^2	n^2	1
Selection sort	n^2	n^2	n^2	1
Insertion sort	n^2	n^2	n^2	1
Merge sort	$n \log(n)$	$n \log(n)$	$n \log(n)$	n (worst)
In-place merge sort	-	-	$n(\log(n))^2$	1
Quicksort	$n \log(n)$	$n \log(n)$	n^2	$\log n$ (average) n (worst)
Heapsort	$n \log(n)$	$n \log(n)$	$n \log(n)$	1

Important algorithms: Sorting

Algorithms Notes for Professionals book

- ▶ Chapters 23: Sorting
 - ▶ Chapters 24: Bubble Sort
 - ▶ Chapters 25: Merge Sort
 - ▶ Chapters 26: Insertion Sort
 - ▶ Chapters 27: Bucket Sort
 - ▶ Chapters 28: Quick Sort
 - ▶ Chapters 29: Counting Sort
 - ▶ Chapters 30: Heap Sort
 - ▶ Chapters 31: Cycle Sort
 - ▶ Chapters 32: Odd-Even Sort
 - ▶ Chapters 33: Selection Sort

Other important algorithms

Algorithms Notes for Professionals book

- ▶ Chapter 3: Graph
 - ▶ Chapter 4: Graph Traversals
 - ▶ Chapter 5: Dijkstra's Algorithm
- ▶ Chapter 34: Trees
 - ▶ Chapter 35: Binary Search Trees
 - ▶ Chapter 37: Binary Tree traversals
 - ▶ Chapter 41: Breadth-First Search
 - ▶ Chapter 41: Depth First Search