



DarwinTM API User Manual

A SparkCognitionTM Education Document

v 1.3.1 - June 2018

This document contains copyrighted and proprietary information of SparkCognition and is protected by United States copyright laws and international treaty provisions. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning or otherwise, except as permitted under such laws or with the prior written permission of SparkCognition Inc.

SparkCognition[™], the sparkcognition logo, Darwin[™], DeepArmor[®], DeepNLP[™], MindFabric[®], SparkSecure[®], and SparkPredict[™], are trademarks of SparkCognition, Inc. and/or its affiliates and may not be used without written permission. All other trademarks are the property of their respective owners.

©SparkCognition, Inc. 2017-2018. All rights reserved.

SparkCognition Darwin API User Guide

Contents

About this guide	1
Darwin overview	2
Accessing the API	2
Expectation	2
Technical routes	2
analyze	2
auth	6
download	9
job	10
lookup	12
risk	18
run	20
train	20
upload	24
Examples	25
Login	25
Train a model - supervised	26
Train a model - unsupervised	28
Create risk data	28
Analyze a dataset	29
Analyze a model	30
Model uses	30
Revision Table	31

About this guide

This manual describes the Darwin™ API and its use in automated model building. It is intended for data scientists, software engineers, and analysts who want to use the Darwin API to interact with Darwin to create and train models, monitor jobs, and perform analysis.

Darwin overview

Darwin is a SparkCognition™ tool that automates model building processes to solve specific problems. This tool enhances data scientist potential because it automates various tasks that are often manually performed. These tasks include data cleaning, latent relationship extraction, and optimal model determination. Darwin promotes rapid and accurate feature generation through both automated windowing and risk generation. Darwin quickly creates highly-accurate, dynamic models using both supervised and unsupervised learning methods.

For additional information on Darwin, contact your local SparkCognition partner for access to the white paper titled: *Darwin - A Neurogenesis Platform*.

Accessing the API

The Darwin API can normally be accessed through one of three methods:

- the Darwin Python SDK (preferred, recommended)
- the `https://darwin-api.sparkcognition.com/v1` end point
- optionally, through user-created `curl` commands

For additional information on the Darwin SDK, see the *SparkCognition Darwin Python SDK Guide*.

Expectation

This document assumes the experience of a data scientist or software engineer that is knowledgeable of data science techniques and associated programming tasks.

Technical routes

The Darwin API includes the following api operations:

- `analyze` - analyze a model or dataset
- `auth` - register and authenticate
- `download` - download or delete a generated artifact
- `job` - return status on jobs
- `lookup` - get model or dataset metadata
- `risk` - create risk information for a dataset
- `run` - run a model on a dataset
- `train` - train a model
- `upload` - upload or delete a dataset

analyze

Request Type: POST

URI: /v1/analyze/model/{*model_name*}

Headers:

- Authorization: Bearer token

Form Data:

- *model_name*: The name of the model to be analyzed
- *job_name*: (optional) If not specified, a uuid is created as the *job_name*.
- *artifact_name*: (optional) If not specified, a uuid is created as the *artifact_name*.
- *category_name*: (optional) The name of the class for supervised or cluster for unsupervised to get feature importances for. If this is not specified, the feature importance will be over all class/clusters.

Description: Analyze the universal feature importances for a particular model given the model name.

Note: This API is capable of returning the structure of the model in the form of a pandas Series.

Response Codes: 201, 400, 401, 403, 422

Successful Response:

```
{
  "job_name": "string",
  "artifact_name": "string"
}
```

Request Type: POST

URI: /v1/analyze/model/predictions/{*model_name*}/{*dataset_name*}

Headers:

- Authorization: Bearer token

Form Data:

- *dataset_name*: The name of the dataset containing the data to analyze predictions for. This is a new dataset that was not used during training for which you want feature importance scores for each row of this dataset. This dataset has a limit of 500 rows. There is no limit for columns.
- *model_name*: The name of the model to be analyzed
- *job_name*: (optional) If not specified, a uuid is created as the *job_name*.
- *artifact_name*: (optional) If not specified, a uuid is created as the *artifact_name*.

Description: Analyze specific feature importances for a particular sample or samples given the model name and sample data.

Response Codes: 201, 400, 401, 403, 422

Successful Response:

```
{
  "job_name": "string",
  "artifact_name": "string"
}
```

Request Type: POST

URI: /v1/analyze/data/{dataset_name}

Headers:

- Authorization: Bearer token

Description: Analyze a dataset and return statistics/metadata concerning designated data.

Parameter Descriptions:

- *dataset_name*: The name of the dataset to analyze and return statistics/metadata for
- *target*: String denoting target prediction column in input data.
- *job_name*: The job name
- *artifact_name*: The artifact name.
- *impute*: String alias that indicates how to fill in missing values in input data. Descriptions in following table.

ALIAS	DESCRIPTION	COMPLEXITY
'genetic'	Genetic Fill: Automatically determines the most appropriate fast imputation method using evolutionary methods.	Linear Fast
'ffill'	(Default) Forward Fill: Propagate values forward from one example into the missing cell of the next example. Can be useful for timeseries data, but also applicable for both numerical and categorical data.	Linear Fast
'bfill'	Backward Fill: Propagate values backward from one example into the missing cell of the previous example. Can be useful for timeseries data, but also applicable for both numerical and categorical data.	Linear Fast
'mean'	Mean Fill: Computes the mean value of all non-missing examples in a column to fill in missing examples. The result might not be interpretable in terms of the input space for categorical variables.	Linear Fast
'median'	Median Fill: Computes the median value of all non-missing examples in a column to fill in missing examples. Note: Although the result is interpretable in terms of the input space for categorical variables, the approach might not be appropriate for non-ordinal data.	Linear Fast
'linear'	Linear Interpolation Fill: Interpolation using a linear function. Can be useful for timeseries or sequential data.	Linear Fast

- *drop*: Enables automatic pruning of input columns based on different criteria such as amount of missing data, number of unique values, and standard deviation. Possible values are: 'hard', 'soft', or 'no'.

Note: This automatically drops identifier columns (unique value for each sample) and columns that do not contain sufficient data to aid prediction.

- *max_int_uniques*: Threshold for automatic encoding of categorical variables. If a column contains at least *max_int_uniques* unique values, it is treated as categorical and one hot encoded during preprocessing.
- *max_unique_values*: Threshold for automatic pruning of categorical columns prior to one hot encoding based on the number of unique values.
Note: If a categorical column contains at least *max_unique_values*, it is dropped during preprocessing prior to one hot encoding.
- *feature_eng*: Enables automatic feature generation. Identifies an appropriate time window and augments input with new features derived in the frequency and time domains.

Notes:

- Can be applied only to timeseries data.
- String aliases specify methods for window computation.

Alias	Description
'mi'	Uses mutual information to estimate the window length.
'auc'	(Default) Uses autocorrelation to estimate the window length.
'user'	User specified window length: see <i>window_len</i> .

- *window_len*: User specified window length for feature generation.
Note: This parameter is used only if *user* is provided for the *feature_eng* parameter.
- *feature_select*: A number in [0,1] that specifies the percentage of numerical features to maintain based on their dependency to the target. Ranks all features using mutual information and drops (1 - *feature_select*)% of the lowest-ranking features. Default is **1** (keep all features).
- *outlier*: A string alias that indicates that outlier detection be applied during preprocessing.
Note: Outliers are removed and later filled using imputation.

Alias	Description
'mad'	Uses Median Absolute Deviation (mad) to detect outliers.
'perc'	Uses Percentile-based outlier detection.
'isol'	Uses Isolation Forest to detect outliers.

Payload:

```
{
  "target": "string",
  "job_name": "string",
  "artifact_name": "string",
  "impute": "mean",
  "drop": "no",
  "max_int_uniques": 15,
  "max_unique_values": 50,
  "feature_eng": "auc",
  "window_len": 10
}
```

```
"feature_select": 1,  
"outlier": "mad"  
}
```

Response Codes: 201, 400, 401, 403, 422

Successful Response:

```
{  
  "job_name": "string",  
  "artifact_name": "string"  
}
```

auth

Request Type: PATCH

URI: /v1/auth/email

Headers:

- Authorization: Bearer token

Description: Add or change an email address.

Form Data:

- *email*: Email address

Response Codes: 204, 400, 401, 422

Successful Response:

```
{  
  'access_token': 'token_string'  
}
```

Request Type: POST

URI: /v1/auth/login

Headers:

- Authorization: Bearer token

Description: Login as a service.

Form Data:

- *api_key*: The api key of the service
- *pass1*: The service level password

Response Codes: 201, 400, 401

Successful Response:

```
{
  'access_token': 'token_string'
}
```

Request Type: POST

URI: /v1/auth/login/user

Description: Login as a user.

Form Data:

- *username*: The end user name
- *pass1*: The end user level password

Response Codes: 201, 400, 401, 422

Successful Response:

```
{
  'access_token': 'token_string'
}
```

Request Type: PATCH

URI: /v1/auth/password

Headers:

- Authorization: Bearer token

Description: Change the password.

Form Data:

- *curpass*: Current password
- *newpass1*: New password
- *newpass2*: Confirmation of new password

Response Codes: 204, 400, 401, 422

Successful Response:

```
{
  'access_token': 'token_string'
}
```

Request Type: PATCH

URI: /v1/auth/password/reset

Headers:

Description: Reset a user's password. An email will be sent to the user's email address with a temporary password and instructions for changing it.

Form Data:

- *username*: The username of the user whose password needs resetting

Response Codes: 201, 400, 401, 422

Successful Response:

```
{
  'access_token': 'token_string'
}
```

Request Type: POST

URI: /v1/auth/register

Headers:

Description: Register as a service.

Form Data:

- *api_key*: The api key of the service
- *pass1*: The service level password
- *pass2*: The service level password confirmation
- *email*: Email address

Response Codes: 201, 400, 401, 403

Successful Response:

```
{
  'access_token': 'token_string'
}
```

Request Type: POST

URI: /v1/auth/register/user

Headers:

- Authorization: Bearer token

Description: Register a user for your service.

Form Data:

- *username*: The end user's name
- *pass1*: The end user's password
- *pass2*: The end user's password confirmation
- *email*: The end user's email address

Response Codes: 201, 400, 401, 422

Successful Response:

```
{
  'access_token': 'token_string'
}
```

Request Type: DELETE

URI: /v1/auth/register/user/{username}

Headers:

- Authorization: Bearer token

Description: Remove/Unregister a user.

Form Data:

- *username*: The username of the user to remove

Response Codes: 201, 401, 403

Successful Response: None

download

Request Type: GET

URI: /v1/download/artifacts/{artifact_name}

Headers:

- Authorization: Bearer token

Description: Download an artifact by name.

Form Data:

- *artifact_name*: Name of the artifact to download

Response Codes: 201, 401, 404, 408, 422

Successful Response:

```
{
  'artifact': 'artifact_name'
}
```

Request Type: DELETE

URI: /v1/download/artifacts/{*artifact_name*}

Headers:

- Authorization: Bearer token

Description: Delete an artifact.

Form Data:

- *artifact_name*: Name of the artifact to download

Response Codes: 204, 401, 404, 408, 422

Successful Response: None

job

Request Type: GET

URI: /v1/job/status

Headers:

- Authorization: Bearer token

Query Parameters:

- *age*: List jobs that are less than X units old (for example, 3 weeks, 2 days)
- *status*: List job of a particular status, for example *Running*

Description: Get the status for all jobs.

Response Codes: 200, 400, 401, 422

Successful Response:

```
[
  {
    "job_name": "job1_name",
    "status": "Requested",
    "starttime": "2018-01-30T13:27:46.449865",
    "endtime": "2018-01-30T13:28:46.449865",
    "percent_complete": 0,
    "job_type": "TrainModel",
    "loss": 0,
    "generations": 0,
    "dataset_names": [
      "phone_data"
    ],
  },
]
```

```
    "artifact_names": [
      "art1"
    ],
    "model_name": null,
  },
  {
    "job_name": "job2_name",
    "status": "Running",
    "starttime": "2018-01-30T13:27:46.449865",
    "endtime": "2018-01-30T13:28:46.449865",
    "percent_complete": 23,
    "job_type": "UpdateModel",
    "loss": 0.92,
    "generations": 50,
    "dataset_names": [
      "language_data"
    ],
    "artifact_names": null,
    "model_name": "test_model",
  }
]
```

Request Type: GET**URI:** /v1/job/status/{*job_name*}**Headers:**

- Authorization: Bearer token

Description: Get the status for a particular job.**Form Data:**

- *job_name*: The job name you want status on.

Response Codes: 200, 400, 401, 403, 404, 422**Successful Response:**

```
{
  "status": "Requested",
  "starttime": "2018-01-30T13:27:46.449865",
  "endtime": "2018-01-30T13:28:46.449865",
  "percent_complete": 0,
  "job_type": "TrainModel",
  "loss": 0,
  "generations": 0,
  "dataset_names": [
    "language_data"
  ]
}
```

```
],  
  "artifact_names": null,  
  "model_name": None  
}
```

Request Type: PATCH

URI: /v1/job/status/{*job_name*}

Headers:

- Authorization: Bearer token

Description: Stop a running job.

Form Data:

- *job_name*: The job name you want to stop.

Response Codes: 200, 400, 401, 403, 404, 422

Successful Response:

```
"Job is scheduled to stop"
```

Request Type: DELETE

URI: /v1/job/status/{*job_name*}

Headers:

- Authorization: Bearer token

Description: Soft delete a running job

Form Data:

- *job_name*: The job name you want to delete.

Response Codes: 200, 400, 401, 403, 404, 422

Successful Response:

None

lookup

Request Type: GET

URI: /v1/lookup/limits

Headers:

- Authorization: Bearer token

Description: Get a client's usage limit metadata.

Response Codes: 200, 401, 422

Successful Response:

```
{
  "username": "string",
  "tier": 0,
  "model_limit": 0,
  "job_limit": 0,
  "upload_limit": 0,
  "user_limit": 0
}
```

Request Type: GET

URI: /v1/lookup/artifact

Headers:

- Authorization: Bearer token

Query Parameters:

- *type*: filter on the type of artifact (for example, Model, Dataset, Test, Run, or Risk)

Description: Get artifact metadata

Response Codes: 200, 401, 422

Successful Response:

```
[
  {
    "id": "string",
    "name": "string",
    "type": "string",
    "created_at": "2018-01-22T19:00:39.863Z",
    "mbytes": 0
  }
]
```

Request Type: GET

URI: /v1/lookup/artifact/{*artifact_name*}

Headers:

- Authorization: Bearer token

Description: Get artifact metadata for a single artifact

Form Data:

- *artifact_name*: The artifact name you want to look up.

Response Codes: 200, 401, 404, 422

Successful Response:

```
{
  "name": "string",
  "type": "string",
  "created_at": "2018-01-22T19:00:39.869Z",
  "mbytes": 0
}
```

Request Type: GET

URI: /v1/lookup/model

Headers:

- Authorization: Bearer token

Description: Get the model metadata for a user. This is useful if a user has forgotten certain model names.

Response Codes: 200, 401, 422

Successful Response:

```
[
  {
    "name": "model1_name",
    "type": "Supervised",
    "updated_at": "2017-02-03T073000",
    "trained_on": ["dataset1_id", "dataset2_id"],
    "generations": 100,
    "loss": 0.8,
    "parameters": {},
  },
  {
    "name": "model2_name",
    "type": "Ensembled",
    "updated_at": "2017-08-22T175022",
    "trained_on": ["dataset3_id"],
    "loss": 0.82,
    "generations": 80,
    "parameters": {
      "target": "target1"
    },
  },
]
```

Request Type: GET

URI: /v1/lookup/model/{*model_name*}

Headers:

- Authorization: Bearer token

Description: Get all of the model metadata for a particular model.

Form Data:

- *model_name*: The model name you want to look up.

Response Codes: 200, 401, 404, 422

Successful Response:

```
{
  "type": "Unsupervised",
  "updated_at": "2017-02-03T073000",
  "trained_on": ["dataset1_id", "dataset2_id"],
  "generations": 100,
  "loss": 0.8,
  "parameters": {},
}
```

Request Type: GET

URI: /v1/lookup/dataset

Headers:

- Authorization: Bearer token

Description: Get the dataset metadata for a user. This is useful if a user has forgotten certain dataset names.

Response Codes: 200, 401, 422

Successful Response:

```
[
  {
    "name": "dataset1_name",
    "mbytes": 0.2,
    "updated_at": "20170924T000000",
    "categorical": False,
    "sequential": True,
    "imbalanced": True,
  },
  {
    "name": "dataset2_name",
    "mbytes": 3.5,
```

```
    "updated_at": "20170902T010101",
    "categorical": True,
    "sequential": False,
    "imbalanced": False,
  }
]
```

Request Type: GET**URI:** /v1/lookup/dataset/{*dataset_name*}**Headers:**

- Authorization: Bearer token

Description: Get all of the metadata for a particular dataset.**Form Data:**

- *dataset_name*: The dataset name for which you want the metadata.

Response Codes: 200, 401, 404, 422**Successful Response:**

```
{
  'mbytes': 0.2,
  'updated_at': '20170924T000000',
  'categorical': False,
  'sequential': True,
  'imbalanced': True,
}
```

Request Type: GET**URI:** /v1/lookup/tier**Headers:**

- Authorization: Bearer token

Description: Get all of the tier metadata.**Response Codes:** 200, 401, 422**Successful Response:**

```
[
  {
    "tier": 0,
    "model_limit": 0,
    "job_limit": 0,
```

```
    "upload_limit": 0,  
    "user_limit": 0  
  }  
]
```

Request Type: GET**URI:** /v1/lookup/tier/{*tier_num*}**Headers:**

- Authorization: Bearer token

Description: Get the metadata for a particular tier.**Form Data:**

- *tier_num*: Tier for which you want metadata.

Response Codes: 200, 401, 404, 422**Successful Response:**

```
{  
  "tier": 0,  
  "model_limit": 0,  
  "job_limit": 0,  
  "upload_limit": 0,  
  "user_limit": 0  
}
```

Request Type: GET**URI:** /v1/lookup/user**Headers:**

- Authorization: Bearer token

Description: Get user metadata for all users.**Response Codes:** 200, 401, 422**Successful Response:**

```
[  
  {  
    "user_id": "string",  
    "internal_name": "string",  
    "username": "string",  
    "tier": 0,  
    "created_at": "string",  
    "client_api_key": "string",
```

```
"parent_id": "string"
}
```

Request Type: GET

URI: /v1/lookup/user/{username}

Headers:

- Authorization: Bearer token

Description: Get user metadata for a particular user.

Form Data:

- *username*: Username for which you want user metadata.

Response Codes: 200, 401, 404, 422

Successful Response:

```
{
  "user_id": "string",
  "internal_name": "string",
  "username": "string",
  "tier": 0,
  "created_at": "string",
  "client_api_key": "string",
  "parent_id": "string"
}
```

risk

Notes concerning risk -

risk is a value used in calculating future events. A risk is calculated using algorithms based on sliding time frames and associated historical data that projects forward in time to predict the likelihood of the event. The outcome of the calculations is that the likelihood of an event occurring within a particular time frame becomes available for use. Note that risk values are dependent on the quality and extent of the historical data as well as the scope of the time frame used for evaluation.

Request Type: POST

URI: /risk/{failure_data}/{timeseries_data}

Headers:

- Authorization: Bearer token

Description: Create risk information for a dataset.

Parameter Descriptions:

- *failure_data*: Name of the failure data file.
- *timeseries_data*: Name of the timeseries data file.
- *job_name*: The job name.
- *artifact_name*: The artifact name.
- *risk_columns*: A list of column names in the index.
- *shutdown_column*: Name of the column in the risk data that denotes the beginning of the predicted event of interest.
- *return_column*: Name of the column in the risk data that denotes the end of the predicted event *and* when all data can again be considered “normal”.
- *asset_column*: Name of the asset column in the risk data. This parameter is used when the datasets consist of multiple different assets.
- *lead_time*: Lead time in seconds. This value is half width of the risk function - this means. the risk index is 0 prior to $2 * lead_time$ and increases to 1 at a failure time.
Note: The *lead_time* value must be greater than zero.
- *Functional_form*: Shape of a risk function, includes:
 - step: Step function
 - linear: Linear function
 - sigmoid: Sigmoid function
 - exponential: Exponential function

Payload:

```
{
  "target": "string",
  "job_name": "string",
  "risk_columns": [
    "risk"
  ],
  "shutdown_column": "Shutdown Time",
  "return_column": "Return Time",
  "asset_column": "Asset",
  "lead_time": 1,
  "functional_form": "linear"
}
```

Response Code: 201, 400, 401, 403, 404, 422**Successful Response:**

```
{
  "job_name": "nameofjob",
  "artifact_name": "name_of_artifact",
}
```

run

Request Type: POST

URI: /v1/run/model/{model_name}/{dataset_name}

Headers:

- Authorization: Bearer token

Form Data:

- *job_name*: The name of the job.
- *artifact_name*: The name of the artifact.
- *supervised*: **(Deprecated.** This argument exists only for backward compatibility.) A boolean (true/false) indicating whether the model is supervised or not, for example, set this to *false* for *unsupervised*.

Description: Run a model on a dataset and return the predictions/classifications/clusters found by the model.

Response Codes: 201, 400, 401, 403, 404, 408, 422

Successful Response:

```
{
  "job_name": "nameofjob",
  "artifact_name": "name_of_artifact"
}
```

train

Request Type: POST

URI: /v1/train/model

Headers:

- Authorization: Bearer token

Description: Create a model trained on the dataset identified by *dataset_name*.

Parameter descriptions:

- *target*: (Mandatory) String denoting target prediction column in input data.
- *dataset_names*: A list of dataset names to use for training.
Note: Using only 1 dataset is currently supported.
- *job_name*: The job name.
- *model_name*: The string identifier of the model to be trained.

- *max_train_time* (supervised only): Sets the training time for the model in 'HH:MM' format. Default value is 00:01.
- *max_epochs* (unsupervised only): Expected input/type: *numeric*. Sets the training time for the model in epochs. Default value is 10.
- *recurrent*: Expected input/type: *true/false*. Enables recurrent connections to be evolved in the model. This option can be useful for timeseries or sequential data.
Note: This option is automatically enabled if a *datetime* column is detected in the input data. This can result in slower model evolution.
- *impute*: String alias that indicates how to fill in missing values in input data.

ALIAS	DESCRIPTION	COMPLEXITY
'genetic'	Genetic Fill: Automatically determines the most appropriate fast imputation method using evolutionary methods.	Linear Fast
'ffill'	(Default) Forward Fill: Propagate values forward from one example into the missing cell of the next example. Might be useful for timeseries data, but also applicable for both numerical and categorical data.	Linear Fast
'bfill'	Backward Fill: Propagate values backward from one example into the missing cell of the previous example. Might be useful for timeseries data, but also applicable for both numerical and categorical data.	Linear Fast
'mean'	Mean Fill: Computes the mean value of all non-missing examples in a column to fill in missing examples. The result may or might not be interpretable in terms of the input space for categorical variables.	Linear Fast
'median'	Median Fill: Computes the median value of all non-missing examples in a column to fill in missing examples. While the result is interpretable in terms of the input space for categorical variables, the approach might not be appropriate for non-ordinal data.	Linear Fast
'mode'	Mode Fill: Uses the most common value on a column-by-column basis to fill in missing examples. The result is interpretable for both numerical and categorical variables.	Linear Fast
'spline'	Spline Fill: Interpolation using a spline (piecewise function). Might be useful for timeseries or sequential data.	Linear Fast
'linear'	Linear Interpolation Fill: Interpolation using a Linear function. Might be useful for timeseries or sequential data.	Linear Fast

- *drop*: Enables automatic pruning of input columns based on different criteria such as amount of missing data, number of unique values, and standard deviation. Possible values are: *'hard'*, *'soft'*, or *'no'*.
Note: This automatically drops identifier columns (unique value for each sample) and columns that do not contain sufficient data to aid prediction.

- *max_int_uniques*: Expected input/type: *integer*. Threshold for automatic encoding of categorical variables. If a column contains at least *max_int_uniques* unique values, it is treated as categorical and one hot encoded during preprocessing.
- *max_unique_values*: Expected input/type: *integer*. Threshold for automatic pruning of categorical columns prior to one hot encoding based on the number of unique values.
Note: If a categorical column contains at least *max_unique_values*, it is dropped during preprocessing prior to one hot encoding.
- *feature_eng*: Enables automatic feature generation. Identifies an appropriate time window and augments input with new features derived in the frequency and time domains.
Note: Can only be applied to timeseries data. String aliases specify methods for window computation.

ALIAS	DESCRIPTION
'mi'	Uses mutual information to estimate the window length.
'auc'	(Default) Uses autocorrelation to estimate the window length.
'user'	User specified window length: see <i>window_len</i> below.

- *window_len*: Expected input/type: *integer*. User specified window length for feature generation.
Note: This parameter is used only in the case that *user* is provided for the *feature_eng* parameter.
- *feature_select*: A number in [0,1] specifying the percentage of numerical features to maintain based on their dependency to the target. Ranks all features using mutual information and drops (1 - *feature_select*)% of the lowest-ranking features. **Default is 1** (keep all features).
- *outlier*: A string alias that indicates the outlier detection to apply during preprocessing.
Note: Outliers are removed and later filled using imputation.

ALIAS	DESCRIPTION
'mad'	Uses Median Absolute Deviation to detect outliers.
'perc'	Uses Percentile-based outlier detection.
'isol'	Uses an Isolation Forest to detect outliers.

- *imbalance* (*supervised* only): Expected input/type: *true/false*. Enables automatic imbalance correction that selectively applies *random oversampling*, *random undersampling*, *synthetic minority oversampling* (SMOTE), or *adaptive synthetic sampling* (ADASYN) to the input data depending on problem characteristics.
- *n_clusters* (*unsupervised* only): Specifies the number of clusters to be used.
Note: If this value is not provided, the number of clusters will be heuristically determined.
- *anomaly_prior* (*supervised* only): Expected input/type: *between [0,1]*. Significance level at which a point is defined as anomalous.

Payload:


```
{
  "target": "string",
  "dataset_names": ["dataset_name1"],
  "job_name": "my_job",
  "model_name": "string",
  "max_train_time": "00:01",
  "max_epochs": 0,
  "recurrent": true,
  "impute": "mean",
  "drop": "no",
  "max_int_uniques": 15,
  "max_unique_values": 50,
  "feature_eng": "mi",
  "feature_select": 1,
  "outlier": "mad",
  "imbalance": true,
  "n_clusters": 5,
  "anomaly_prior": 0.01
}
```

Response Codes: 201, 401, 403, 404, 408, 422

Successful Response:

```
{
  "job_name": "nameofjob",
  "model_name": "nameofmodel",
}
```

Request Type: PATCH

URI: /v1/train/model/{*model_name*}

Headers:

- Authorization: Bearer token

Description: Resume training for a model on the dataset identified by *dataset_name*.

Parameter Descriptions:

- *target*: String denoting target prediction column in input data.
- *dataset_names*: A list of dataset names to use for training.
Note: Using only 1 dataset is currently supported.
- *job_name*: The job name
- *max_train_time* (supervised only): Sets the training time for the model in 'HH:MM' format. Default value is 00:01.
- *max_epochs* (unsupervised only): Sets the training time for the model in epochs. Default value is 10.

Payload:

```
{
  "target": "string",
  "dataset_names": ["dataset_name1"],
  "job_name": "my_job",
  "max_train_time": "00:01",
  "max_epochs": 0
}
```

Response Codes: 201, 401, 403, 404, 408, 422**Successful Response:**

```
{
  "job_name": "nameofjob",
  "model_name": "nameofmodel",
}
```

Request Type: DELETE**URI:** /v1/train/model/{*model_name*}**Headers:**

- Authorization: Bearer token

Description: Delete a model.**Form Data:**

- *model_name*: - Name of the model to delete.

Response Codes: 204, 400, 401, 403, 404, 408, 422**Successful Response:** None

upload**Request Type:** POST**URI:** /v1/upload**Headers:**

- Authorization: Bearer token

Description: Upload a dataset, model, or a figure.**Form Data:**

- *dataset*: a dataset file in a supported format (csv, xls, h5)

- *dataset_name*: the name for the uploaded dataset

Note: If not set, a guid will be provided

Response Codes: 201, 400, 401, 403, 408, 413, 422

Successful Response:

```
{
  "dataset_name": "name_of_dataset "
}
```

Request Type: DELETE

URI: /v1/upload/{*dataset_name*}

Headers:

- Authorization: Bearer token

Description: Delete a dataset, model, or a figure.

Form Data:

- *dataset_name*: Name or identifier of dataset to delete.

Response Codes: 204, 401, 404, 422

Successful Response: None

Examples

The following sections provide examples of how to use the Darwin API.

Login

1. Login using the /v1/auth routes. It is possible to login as either a *service* or a *user*.

Login	Request
Login as service:	Request Type: POST URI: /v1/auth/login Form Data: <i>api_key</i> : The api key of the service <i>pass1</i> : The service level password

Login	Request
Login as an end user:	Request Type: POST URI: /v1/auth/login/user Form Data: <i>api_key</i> : The api key of the service <i>username</i> : The end user name <i>pass1</i> : The end user level password

2. Receive token. If login is successful, a response arrives with an access token. This token is used in the *authorization header* for other requests:

```
{
  'access_token': 'token_string'
}
```

Note: The token (in this example “some string”) must be prepended with the string *Bearer*. For example the token becomes:

Bearer MyNewTokenString - (that is: **Bearer(space)MyNewTokenString**).

Train a model - supervised

1. Upload a dataset using the following:

Request Type: POST

URI: /v1/upload

Headers:

- Authorization: Bearer token

Form Data:

- *dataset*: a dataset file
- *dataset_name*

Notes:

- Assign a name to the dataset. If no name is assigned, a random string is assigned in its place. It is necessary to keep track of lookup current datasets with the /v1/lookup/dataset route.
- Ensure not to exceed upload limits. If the limits are exceeded, a *403 forbidden error* is generated. To fix the exceeded limit, delete a dataset that is older or no longer required.

2. Set target parameter.

Use the uploaded dataset to train a model. Specify the dataset name in the URI of the train route. Note that training a supervised model requires the *target* parameter is set:

Request Type: POST

URI: /v1/train/model/{dataset_name}

Headers:

- Authorization: Bearer token

Payload:

```
{
  "target": "string",
  "dataset_names": ["dataset_name1"],
  "job_name": "nameofjob",
  "artifact_name": "string",
  "model_name": "string",
  "max_train_time": "00:01",
  "max_epochs": 0,
  "recurrent": true,
  "impute": "mean",
  "drop": "no",
  "max_int_uniques": 15,
  "max_unique_values": 50,
  "feature_eng": "mi",
  "feature_select": 1,
  "outlier": "mad",
  "imbalance": true,
  "n_clusters": 5,
  "anomaly_prior": 0.01
}
```

Note: Because many of the payload parameters are optional, depending on your use case, it is possible to use a simple payload, for example:

```
{
  "target": "string",
  "dataset_names": ["dataset_name1"]
}
```

3. Consult return.

In response to the payload, a job name and model name are returned. Note that if the dataset was not named, a random string is returned as its name. For example:

```
{
  "job_name": "nameofjob",
  "model_name": "nameofmodel",
}
```

4. Check job status.

When the job name is returned, use the `/v1/job/status` or `/v1/job/status/{job_name}` route together with the job name to check the job status. For example:

Request Type: GET

URI: `/v1/job/status`

Headers:

- Authorization: Bearer token

Query Parameters:

- *age*: List jobs that are less than *X* units old, for example, *3 weeks, 2 days*.
- *status*: List job of a particular status, for example *Running*.

The query return contains information about how far the job has progressed, as a `percent_complete` and `status`, the number of generations run (so far), and the model loss. For example:

```
{
  "status": "Requested",
  "percent_complete": 0,
  "loss": 0,
  "generations": 0,
  "dataset_names": [
    "phone_data"
  ]
  "model_name": "nameofmodel",
}
```

When the job completes, the `percent_complete` shows 100 and `status` is set to `Complete`. The generated model can be used for additional tasks, described below.

Train a model - unsupervised

The process to train an unsupervised model follows the same procedure as the supervised model training procedure. The difference is the target parameter in the `/v1/train/model/{dataset_name}` route is left unspecified. Depending on the use case, it is possible to simplify the payload to a set of empty braces:

```
{ }
```

Create risk data

The following example shows how to generate risk data.

1. Upload a failure dataset and time-series dataset through the `/v1/upload` route and follow the instructions above to create risk data. For example:

Request Type: POST

URI: `/v1/risk/{failure_data}/{timeseries_data}`

Headers:

- Authorization: Bearer token

Payload:

```
{
  "risk_columns": [
    "risk"
  ],
  "shutdown_column": "Shutdown Time",
  "return_column": "Return Time",
  "asset_column": "Asset",
  "lead_time": 1,
  "functional_form": "linear"
}
```

2. Consult the return.

The post action returns job and artifact names. The job name enables monitoring the job status.

3. Download the risk data.

When the job completes, download the risk data via the `/v1/download/artifacts/{artifact_name}` route.

Analyze a dataset

1. If necessary, upload a dataset using the instructions and the `/v1/upload` route.
2. Analyze the dataset through the `/v1/analyze/data/{dataset_name}` route:

Request Type: POST

URI: `/v1/analyze/data/{dataset_name}`

Headers:

- Authorization: Bearer token

Payload:

```
{
  "target": "string",
  "impute": "mean",
  "drop": "no",
  "max_int_uniques": 15,
  "max_unique_values": 50,
  "feature_eng": "mi",
  "feature_select": 1,
  "outlier": "mad"
}
```

3. Consult the return.

The post action returns job and artifact names. The job name enables monitoring the job status.

4. Download the analysis.

When the job completes, download the data analysis with the `/v1/download/artifacts/{artifact_name}` route.

Analyze a model

Analyze the trained model.

1. Use the `/v1/analyze/model/{model_name}` route:

Request Type: POST

URI: `v1/analyze/model/{model_name}`

Headers:

- Authorization: Bearer token

Form Data:

- *job_name*: The name of the job
- *artifact_name*: The name of the artifact

2. Consult the return.

The post action returns job and artifact names. The job name enables monitoring the job status.

3. Download the analysis.

When the job completes, download the model analysis with the `/v1/download/artifacts/{artifact_name}` route.

Note: The model analysis takes the form of a decoded PNG. You must encode this yourself ("latin-1" encoding) or you can use the provided Python SDK to retrieve the results automatically.

Model uses

A trained model and dataset can be used for prediction, classification, or for detecting data clusters and/or anomalies.

After a model is trained, additional datasets can be uploaded and the model applied against those additional datasets. To perform these tasks:

1. Use the `/v1/run/model/{model_name}/{dataset_name}` route:

Request Type: POST

URI: `/v1/run/model/{model_name}/{dataset_name}`

Headers:

- Authorization: Bearer token

Form Data:

- *model_name*: The name or identifier of the model.
- *dataset_name*: The name or identifier of the dataset.

2. Consult the return.

The post action returns job and artifact names. The job name enables monitoring the job status.

3. Download the results.

When the job completes, download the results with the `/v1/download/artifacts/{artifact_name}` route.

Revision Table

Version	Date	Notes
v 1.0	02-Feb-2018	First Release
v 1.1	15-Feb-2018	added types: supervised and ensembled
v 1.2(pre)	16-Mar-2018	added Status: Type= PATCH
v 1.2	27-Mar-2018	Added or changed: <ul style="list-style-type: none"> • /v1/job/status/{job_name} • /v1/lookup/user • /v1/lookup/username/{username} • /v1/train/model • /v1/run/model/{model_name}/{dataset_name} Name change: /v1/lookup/client to /v1/lookup/limits
v 1.3	23-May-2018	Added or changed: <ul style="list-style-type: none"> • /v1/analyze/model/{model_name} • /v1/analyze/model/predictions/{model_name}/{dataset_name} • /v1/auth/email • /v1/auth/password/reset • /v1/auth/register • /v1/train/model • /v1/train/model/{model_name} Name change: /v1/lookup/client to /v1/lookup/limits
v 1.3.1	14-Jun-2018	Edits to: <ul style="list-style-type: none"> /v1/job/status/ /v1/download/artifacts Model uses example