



# Darwin™ Python SDK Guide

---

**A SparkCognition™ Education Document**

***v. 1.44.0 - July 2019***

---

This document contains copyrighted and proprietary information of SparkCognition and is protected by United States copyright laws and international treaty provisions. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning or otherwise, except as permitted under such laws or with the prior written permission of SparkCognition Inc.

SparkCognition™, the sparkcognition logo, Darwin™, DeepArmor®, DeepNLP™, MindFabric®, SparkSecure® and SparkPredict™, are trademarks of SparkCognition, Inc. and/or its affiliates and may not be used without written permission. All other trademarks are the property of their respective owners.

©SparkCognition, Inc. 2017-2019. All rights reserved.

# SparkCognition Darwin Python SDK Guide

## Contents

<b>About this guide</b>	<b>3</b>
Expectation . . . . .	3
<b>Darwin overview</b>	<b>3</b>
Accessing the API . . . . .	4
<b>Darwin SDK interface</b>	<b>4</b>
Setup Darwin SDK . . . . .	4
Set up Users . . . . .	5
Set up Admin account . . . . .	5
Set up User accounts . . . . .	5
<b>Darwin SDK methods</b>	<b>6</b>
URL Get/Set methods . . . . .	6
DarwinSdk. <b>get_info</b> () . . . . .	6
DarwinSdk. <b>get_sdk_version</b> () . . . . .	7
DarwinSdk. <b>get_url</b> () . . . . .	7
DarwinSdk. <b>set_url</b> (url, version='v1') . . . . .	8
Authentication methods . . . . .	8
DarwinSdk. <b>auth_register</b> (password, api_key, email) . . . . .	8
DarwinSdk. <b>auth_login</b> (password, api_key) . . . . .	9
DarwinSdk. <b>auth_register_user</b> (username, password, email) . . . . .	9
DarwinSdk. <b>auth_set_email</b> (username, email) . . . . .	10
DarwinSdk. <b>auth_login_user</b> (username, password) . . . . .	10
DarwinSdk. <b>auth_change_password</b> (curpass, newpass) . . . . .	11
DarwinSdk. <b>auth_reset_password</b> (username) . . . . .	11
DarwinSdk. <b>auth_delete_user</b> (username) . . . . .	12
DarwinSdk. <b>disable_ssl_cert_check</b> () . . . . .	13
DarwinSdk. <b>enable_ssl_cert_check</b> () . . . . .	13
Job status methods . . . . .	13
DarwinSdk. <b>lookup_job_status</b> (age=None, status=None) . . . . .	13
DarwinSdk. <b>lookup_job_status_name</b> (job_name) . . . . .	14
DarwinSdk. <b>delete_job</b> (job_name) . . . . .	15
DarwinSdk. <b>stop_job</b> (job_name) . . . . .	15
Lookup methods . . . . .	16

DarwinSdk. <b>lookup_artifact</b> ( <i>type=None</i> )	16
DarwinSdk. <b>lookup_artifact_name</b> ( <i>artifact_name</i> )	16
DarwinSdk. <b>lookup_limits</b> ()	17
DarwinSdk. <b>lookup_dataset</b> ()	17
DarwinSdk. <b>lookup_dataset_name</b> ( <i>dataset_name</i> )	18
DarwinSdk. <b>lookup_model</b> ()	19
DarwinSdk. <b>lookup_model_name</b> ( <i>model_name</i> )	19
DarwinSdk. <b>lookup_tier</b> ()	20
DarwinSdk. <b>lookup_tier_num</b> ( <i>tier_num</i> )	20
DarwinSdk. <b>lookup_user</b> ()	21
DarwinSdk. <b>lookup_username</b> ( <i>username</i> )	22
DarwinSdk. <b>display_population</b> ( <i>model_name</i> )	22
Datasets and artifact methods	23
DarwinSdk. <b>upload_dataset</b> ( <i>dataset, dataset_name=None</i> )	23
DarwinSdk. <b>download_dataset</b> ( <i>dataset_name</i> )	24
DarwinSdk. <b>delete_dataset</b> ( <i>dataset_name</i> )	25
DarwinSdk. <b>download_model</b> ( <i>model_name</i> )	25
DarwinSdk. <b>download_artifact</b> ( <i>artifact_name, artifact_path=None</i> )	26
DarwinSdk. <b>delete_artifact</b> ( <i>artifact_name</i> )	30
Data Analysis and Data Cleaning methods	30
DarwinSdk. <b>analyze_data</b> ( <i>dataset_name, **kwargs</i> )	30
DarwinSdk. <b>clean_data</b> ( <i>dataset_name, **kwargs</i> )	34
Modeling and analysis methods	35
DarwinSdk. <b>create_model</b> ( <i>dataset_names, **kwargs</i> )	35
DarwinSdk. <b>delete_model</b> ( <i>model_name</i> )	37
DarwinSdk. <b>resume_training_model</b> ( <i>model_name, dataset_names, **kwargs</i> )	37
DarwinSdk. <b>analyze_model</b> ( <i>model_name, job_name=None, artifact_name=None</i> )	38
DarwinSdk. <b>analyze_predictions</b> ( <i>model_name, dataset_name, job_name=None, artifact_name=None</i> )	38
DarwinSdk. <b>run_model</b> ( <i>dataset_name, model_name, job_name=None, artifact_name=None</i> )	39
Convenience methods	40
DarwinSdk. <b>delete_all_datasets</b> ()	40
DarwinSdk. <b>delete_all_models</b> ()	40
DarwinSdk. <b>delete_all_artifacts</b> ()	40
DarwinSdk. <b>wait_for_job</b> ( <i>job_name, time_limit=600</i> )	41
DarwinSdk. <b>help</b> ()	41
<b>Reference</b>	<b>42</b>
SDK modeling examples	42
Supervised modeling example	43
Unsupervised modeling example	48
NBM modeling example	52
Contact Support	60
Revision Table	60

## About this guide

This guide describes using the Darwin™ SDK to access and use the Darwin API in automated model building. It is intended for data scientists, software engineers and analysts who want to use the Darwin API to interact with Darwin to create and train models, test the generated models, monitor jobs and perform analysis. The SDK also provides some convenience functions. Note that throughout this document, long key and token values are truncated, indicated by ellipses (...).

The Darwin SDK has an independent version number to allow for release outside of the normal Darwin product release window. As of this printing, the Darwin SDK is at version 1.44.0.

## Expectation

This document assumes experience of the data scientist or software engineer that is commensurate with data science techniques and associated programming tasks.

## Darwin overview

Darwin is a SparkCognition™ tool that automates model building processes to solve specific problems. This tool enhances data scientist potential because it automates various tasks that are often manually performed. These tasks include data cleaning, latent relationship extraction, and optimal model determination. Darwin promotes rapid and accurate feature generation through both automated windowing and risk generation. Darwin quickly creates highly-accurate, dynamic models using both supervised and unsupervised learning methods.

The general workflow for simple modeling includes:

- Upload training data
- Analyze training data
- Clean training data
- Create model
- Wait for job to complete
- Upload test data
- Clean test data
- Run the model
- Wait for job to complete
- Download the result artifact

**Note:** Darwin expects all uploaded ingestion files to be in a *rectangular* format. This means a flat file with features that span columns and data samples that span rows. Plan your data file so it fits this expectation to help prevent errors.

See the [SDK examples](#) for modeling examples of supervised, unsupervised, and normal behavior modeling (NBM) problems.

For additional information on Darwin, contact your local SparkCognition partner for access to the white paper titled: *Darwin - A Neurogenesis Platform*.

## Accessing the API

This document describes the python SDK and explains how to access the Darwin API and its functionality. Additional methods to access the Darwin API include:

- through the `https://darwin-api.sparkcognition.com/v1/` end point
- optionally, through user created `curl` commands

For additional information on the Darwin API, contact your local SparkCognition partner for access to see the *SparkCognition Darwin API User Guide*.

### Notes:

- An *api key* is necessary to use the Darwin SDK.  
Contact SparkCognition or your IT manager for an appropriate key.
- All methods return a 2-tuple, for example:

```
(True, <context-dependent-return-object> )  
(False, <some-helpful-message> )
```

## Darwin SDK interface

### Setup Darwin SDK

Perform the following to download and setup the Darwin SDK:

1. Install Python 3.5 or greater. Alternatively, install *Miniconda*, from <https://conda.io/miniconda.html>.
2. Create a directory to receive the git repository clone.
3. Change (*cd*) into the new directory.
4. Clone the *darwin-sdk* repository:

```
git clone https://github.com/sparkcognition/darwin-sdk
```

5. Change into the new root directory of the *darwin-sdk* cloned darwin-sdk project:

```
cd darwin-sdk
```

**Note:** By default this is the *master* trunk.

6. Ensure code is from master trunk:

```
git pull
```

7. Setup the SDK:

```
python setup.py install
```

The SDK defaults to using the production URL: <https://darwin-api.sparkcognition.com/v1/>

**Note:** Ensure you have a trailing slash (/) on the production URL.

**ON-PREM ONLY:** For on-prem installations, the product URL will be in the form:

```
https://customerdomainname.customerdomain.com:8000/v1/
```

**Note:** On-prem installation must add port 8000 to the product URL.

#### 8. Verify the connection.

Use `get_url()` and `set_url()` to verify connection to the correct Darwin service. See the [URL Get/Set methods](#) below for more information.

## Set up Users

Before you can set up any user accounts, you need to know your api key, also known as an admin key. This key can be obtained from SparkCognition support or your IT manager. The api key is a long string, for example:

```
'RsJ74ZS5AvwznbHh0AfVSgrchhS9KxACDy3jefaQnxb9f6QTSDBFmhnGa0cOIWtNAIFRAG9ToOTpi0mn'
```

### Set up Admin account

Register the api key using the `auth_register()` method.

The purpose of this method is to create a password and an email address for the Darwin admin account. This method must be invoked once for each api key to establish an admin account for that key.

#### Example

```
>>> from amb_sdk.sdk import DarwinSdk
>>> s = DarwinSdk()
>>> s.auth_register('adminpassword', 'iRgwut4kGs0ymULiuKtMd0WFvBYLMWSj16q2uysQeteq\
UvcysnPojRpfycLVHa2IlN1IlrfEk1YMA', 'admin@company.com')
(True, 'Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJleHAiOiE1MTU1MzM4NjEsImh\
dCI6MTUxNTUzMDI2MS...F56xZQiT-89nrRzlnIXD5LfawHIj_MlUHQQm36vU')
```

### Set up User accounts

While you can use the SDK as an admin, it is more convenient to create additional user accounts so that you can have certain datasets/models be owned by specific users. Perform the following to create additional user accounts:

Log in to the *service* as an admin. In the following example, you need to enter your admin password and the api key.

#### Example

```
>>> s.auth_login('adminpassword', 'iRgwut4kGs0ymULiuKtMd0WFvBYLMWSj16q2uysQeteq\
UvcysnPojRpfycLVHa2IlN1IlrfEk1YMA')
(True, 'Bearer iLCJhbGciOiJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJleHAiOiE1MTU1MzQxNzIsImh\
dUxNTUCI6MTzMD...UQQfoXqYFKJSorXXDNPE985-a08cE6_o')
```

#### Notes:

- Although Bearer <auth-token>, returned by `auth_login()`, is used in subsequent calls to validate authenticity, it is not required for each method.
- The SDK remembers the auth token for the `DarwinSdk` object. Although an auth token is currently valid for 2 hours, if the `DarwinSdk` object session life time exceeds 2 hours, the SDK will request another auth token until the session ends.

Register a new user by calling the `auth_register_user()` method. You need to input the username, password, and email address for the new user.

#### Example

```
>>> s.auth_register_user('user1', 'user1-password', 'user1@company.com')
(True,
 'Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJqdGkiOiJkNjY0MmJjOC1iMmU5LTQxO\
DctODFlNS00YjI2MD ... 5zMp_1FfxU')
```

You can repeat this procedure for additional users.

The user can now log in by using the `auth_login_user()` method. The user needs to input the username and password.

#### Example

```
>>> s.auth_login_user('user1', 'user1-password')
(True,
 'Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJqdGkiOiI3NGYzYmUxZS0yOTlmLTRhN\
zMtODU5ZC01NGRmM2F ... ulzGCeCONA')
```

The user is now logged in and can perform other functions. See the following sections for other SDK methods.

## Darwin SDK methods

### URL Get/Set methods

#### `DarwinSdk.get_info()`

Get info on the routes available and the API version. The `local` flag will return `True` for an on-prem installation.

**Parameters:** None

**Returns:**

```
(True, {available_routes: {}, local: False})
```

#### Example

```
In [29]: s.get_info()
```

```
Out[29]: (True,
```



```
{'available_routes': {'Info': True,
'Auth': True,
'Job': True,
'Metadata': True,
'Train': True,
'Risk': True,
'Upload': True,
'Download': True,
'Analyze': True,
'Run': True,
'Admin': True,
'Clean': True,
'Model': True},
'local': False, 'api_version': '1.34.0'}}
```

---

### **DarwinSdk.get\_sdk\_version()**

Get the version of the SDK.

**Parameters:** None

**Returns:**

```
(True, '1.44.0')
```

### **Example**

```
In [8]: s.get_sdk_version()
```

```
Out[8]: (True, '1.44.0')
```

---

### **DarwinSdk.get\_url()**

Get Darwin service url.

**Parameters:** None

**Returns:**

```
(True, <url-string>)
```

### **Example**

```
In [10]: s.get_url()
```

```
Out[10]: (True, 'https://darwin-api.sparkcognition.com/v1/')
```

**DarwinSdk.set\_url(url, version='v1')**

Set Darwin service url and version.

**Parameters:**

- **url** - URL to the Darwin service
- **version** - Set to 'v1'

**Returns:**

(True, <url>) or (False, 'invalid url')

**Example for SaaS**

```
In [9]: s.set_url('https://darwin-api.sparkcognition.com/v1/')
```

```
Out[9]: (True, 'https://darwin-api.sparkcognition.com/v1/')
```

**Example for On-prem**

```
In [9]: s.set_url('https://customerdomainname.customerdomain.com:8000/v1/')
```

```
Out[9]: (True, 'https://customerdomainname.customerdomain.com:8000/v1/')
```

---

**Authentication methods****DarwinSdk.auth\_register(password, api\_key, email)**

Register the api key, also known as an admin key, as a service and establish an admin account. The purpose of this method is to set a password and an email address for the Darwin Admin account. This method is invoked only once for each api key to establish a password and Admin account. After registration, the admin can log in to the service using the *auth\_login()* method.

**Parameters:**

- *password* - The service level password for the admin
- *api\_key* - The api key for the service
- *email* - Email address

**Returns:**

(True, 'Bearer <auth-token>') or (False, <error-message>)

Bearer <auth-token> is used in subsequent calls to validate authenticity.

The SDK remembers the auth token for the DarwinSdk object.

**Note:** Although an auth token is currently valid for 2 hours, if the DarwinSdk object session life time exceeds 2 hours, the SDK will request another auth token until the session ends.

**Example**

```
In [4]: s.auth_register('adminpassword', 'RsJ74ZS5AvwznbHh0AfVSgrchhS9KxACDy\
3jefaQnxb9f6QTSDBFmhnGa0cOIWtNAIFRAG9ToOTpi0mnEo3zFA', 'admin@company.com')

Out[4]:
(True,
'Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHAiO...iSdU8xlF4yJk')
```

---

### **DarwinSdk.auth\_login(password, api\_key)**

Log in to the *service* as an admin.

**Note:** A service must have a password set using `auth_register()` to login successfully.

#### **Parameters:**

- *password* - The service level password for the admin
- *api\_key* - The api key for the service

#### **Returns:**

(True, 'Bearer <auth-token>') or (False, <error-message>)

Bearer <auth-token> is used in subsequent calls to validate authenticity. The SDK remembers the auth token for the DarwinSdk object.

**Note:** Although an auth token is currently valid for 2 hours, if the DarwinSdk object session life time exceeds the 2 hour limit, the SDK will acquire another auth token until the session ends.

#### **Example**

```
In [5]: s.auth_login('adminpassword',
'iRgwut4kGs0ymULiuKtMd0WFvBYLMWSj16q2uysQeteqH9ssc+EETUvcysnPojRpfyc\
LVHa2I1N1I1rfEk1YMA')

Out[5]:
(True,
'Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJleHAiOjE1MTU1MzQxN....')
```

---

### **DarwinSdk.auth\_register\_user(username, password, email)**

Register a user. This method registers a new user.

**Note:** You must be logged in as a service to create a user.

#### **Parameters:**

- *username* - The new end user's username
- *password* - The new end user's password
- *email* - The new end user's email address

**Returns:**

(True, 'Bearer <auth-token>') or (False, <error-message>)

Bearer <auth-token> is used in subsequent calls to validate authenticity. The SDK remembers the auth token for the DarwinSdk object.

**Note:** Although an auth token is currently valid for 2 hours, if the DarwinSdk object session life time exceeds the 2 hour limit, the SDK will acquire another auth token until the session ends.

**Example**

```
In [8]: s.auth_register_user('user1', 'user1-password', 'user1@company.com')

Out[8]:
(True,
 'Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJleHAiOjE1MTU1MzQyN....')
```

**DarwinSdk.auth\_set\_email(username, email)**

Add or change a user's email address.

**Parameter:**

- *username* - The end user's username
- *email* - The end user's email address

**Returns:**

(True, None) or (False, <error-message>)

User must be logged in to add or change an email address. For cloud installations, this email address will be used for password resets and other notifications. For on-prem installations, password resets are executed using a new default password, there is no email sent. If you do not know the default password, contact Darwin support.

**Example**

```
In [9]: s.auth_set_email('user1', 'user1@company.com')

Out [9]: (True, None)
```

**DarwinSdk.auth\_login\_user(username, password)**

Login as a user.

**Note:** A user must have a username and password set using **auth\_register\_user()** to successfully login.

**Parameters:**

- *username* - The end user's username

- *password* - The end user's password

**Returns:**

(True, 'Bearer <auth-token>') or (False, <error-message>)

Bearer <auth-token> is used in subsequent calls to validate authenticity. The SDK remembers the auth token for the DarwinSdk object.

**Note:** Although an auth token is currently valid for 2 hours, if the DarwinSdk object session life time exceeds the 2 hour limit, the SDK will acquire another auth token until the session ends.

**Example**

```
In [9]: s.auth_login_user('user1', 'user1-password')

Out[9]:
(True,
 'Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJleHAiOiE1MTU1MzQzM....')
```

---

**DarwinSdk.auth\_change\_password(*curpass*, *newpass*)**

Change the current user's password.

**Parameters::**

- *curpass* - User's current password
- *newpass* - User's new password

**Returns:**

(True, None) or (False, <error-message>)

User must be logged in to change password. If the current password is forgotten, use the following **DarwinSdk.auth\_reset\_password(*username*)** method to reset it. For cloud installations, an email will be generated with a temporary password. For on-prem installations, password resets are executed using a new default password, there is no email sent. If you do not know the default password, contact Darwin support.

**Example**

```
In [10]: s.auth_change_password('user1-password', 'user1-newpassword')

Out[10]: (True, None)
```

---

**DarwinSdk.auth\_reset\_password(*username*)**

Reset a user's password. Any user can reset another user's password. You do not have to be an admin to execute this function. For cloud installation, a temporary password will be sent to the user's email

address. For on-prem installations, password resets are executed using a new default password, there is no email sent. If you do not know the default password, contact Darwin support.

**Parameter:**

- *username* - Username to reset password for.

**Returns:**

(True, None) or (False, <error-message>)

**Example**

```
In [8]: s.auth_reset_password('user1')
```

```
Out[8]: (True, None)
```

---

**DarwinSdk.auth\_delete\_user(username)**

Remove/Unregister a user. This can only be performed by an admin account.

**Parameter:**

- *username* - Username of the user to be deleted.

**Returns:**

(True, <deleted-user-id>) or (False, <error-message>)

**Example**

```
In [8]: s.lookup_username('testuser2')
```

```
Out[8]:
```

```
(True,  
[{'client_api_key': 'RsJ74ZS5AvwznbHh0AfVSgrch...Eo3zFA',  
  'created_at': '2018-01-03T12:54:30.653478',  
  'parent_id': '2516b462-df85-11e7-bdd1-e37424c63ea4',  
  'tier': 0,  
  'username': 'testuser2'}])
```

```
In [9]: s.auth_delete_user('testuser2')
```

```
Out[9]: (True, '87d721fc-f0b7-11e7-b58d-a3441423b160')
```

```
In [10]: s.auth_delete_user('testuser2')
```

```
Out[10]:
```

```
(False,  
'404: NOT FOUND - {\n    "message": "Username not found. \\  
You have requested this URI [/v1/auth/register/user/testuser2] \\'
```

```
but did you mean /v1/auth/register/user/ <username> or /v1/auth/register/user \
or /v1/auth/register ?"\n}\n')
```

---

### **DarwinSdk.disable\_ssl\_cert\_check()**

For on-prem customers, this disables the SSL certificate check when calling `auth_login_user(<username>, <password>)`

If you want to re-enable the SSL certificate check, call the `enable_ssl_cert_check()` method.

**Parameters:** None

---

### **DarwinSdk.enable\_ssl\_cert\_check()**

For on-prem customers, this enables the SSL certificate check when calling `auth_login_user(<username>, <password>)`

If you want to disable the SSL certificate check, call the `disable_ssl_cert_check()` method.

**Parameters:** None

---

## **Job status methods**

### **DarwinSdk.lookup\_job\_status(*age=None, status=None*)**

Get status information for all jobs belonging to the current user or service.

**Parameters:**

- *age* - (optional) Filter jobs that are less than X units old, for example 3w, 2d, or 1h.
- Optional parameters:
  - *status* - If not specified, returns all jobs.
  - *running* (Note that only 2 jobs can be running concurrently.)
  - *requested*
  - *complete*
  - *failed*

**Returns:**

(True, <list-of-jobs>) or (False, <error-message>)

### **Example**

```
In [6]: s.lookup_job_status(status='Complete')
```

```
Out[6]:
```

```
(True,
 [{'artifact_names': None,
   'dataset_names': ['cancer-train'],
   'endtime': '2018-02-01T10:53:50.451598',
   'generations': 0,
   'job_name': 'eeef500d629e4a2185eb8af6e18a83b4',
   'job_type': 'TrainModel',
   'loss': 2.0,
   'model_name': 'cancer-model',
   'percent_complete': 100,
   'starttime': '2018-02-01T10:52:42.280929',
   'status': 'Complete'}])
```

---

### **DarwinSdk.lookup\_job\_status\_name(job\_name)**

Get job status information for a job by its name.

#### **Parameters:**

- *job\_name* - The name of the job you want status on

#### **Returns:**

(True, <job-info>) or (False, <error-message>)

#### **Example**

```
In [19]: s.lookup_job_status_name('eeef500d629e4a2185eb8af6e18a83b4')
```

```
Out[19]:
```

```
(True,
 {'artifact_names': None,
   'dataset_names': ['cancer-train'],
   'endtime': None,
   'generations': 0,
   'job_error': "MultipleDateColumns: multiple date columns \
- ['Date' 'PeakMonth' 'PeakQuarter']",
   'job_type': 'TrainModel',
   'loss': None,
   'model_name': 'cancer-model',
   'percent_complete': 0,
   'starttime': '2018-02-01T10:52:42.280929',
   'status': 'Running'})
```

```
In [20]: s.lookup_job_status('Running')
```



**DarwinSdk.delete\_job(job\_name)**

Delete a job.

**Parameter:**

- *job\_name* - The name of the job you want to delete

**Returns:**

(True, None) or (False, <error-message>)

**Example**

```
In [17]: s.lookup_job_status_name('7df54dfddfa046d581522f7540e3256c')
```

```
Out[17]:
```

```
(True,
{'artifact_names': ['7a245119ca3b42efadc27006e75a225d'],
 'dataset_names': ['market-train'],
 'endtime': '2018-03-06T14:23:59.975793',
 'generations': None,
 'job_error': '',
 'job_type': 'AnalyzeData',
 'loss': None,
 'model_name': None,
 'percent_complete': 100,
 'starttime': '2018-03-06T14:23:57.18095',
 'status': 'Complete'})
```

```
In [18]: s.delete_job('7df54dfddfa046d581522f7540e3256c')
```

```
Out[18]: (True, None)
```

```
In [19]: s.lookup_job_status_name('7df54dfddfa046d581522f7540e3256c')
```

```
Out[19]: (False, '404: NOT FOUND - {\n      "message": "Job name not found"\n}\n')
```

**DarwinSdk.stop\_job(job\_name)**

Stop a running job. The job will not stop right away, but it will stop when the current generation is complete.

**Parameter:**

- *job\_name* - The name of the job you want to stop.

**Returns:**

(True, 'Job is scheduled to stop') or (False, <error-message>)

### Example

```
In [21]: s.stop_job('34787793a48b42b48a319bbbf68f13ea')

Out[21]: (True, 'Job is scheduled to stop')
```

---

## Lookup methods

### DarwinSdk.lookup\_artifact(*type=None*)

Get a list of artifacts belonging to the current user or service.

#### Parameter:

- *type* - (optional) specifies the type of artifact. Values can be 'Model', 'Dataset', 'Run'.

#### Returns:

(True, <artifact-list>) or (False, <error-message>)

#### Example:

```
In [30]: s.lookup_artifact('Run')
http://localhost:5000/v1/lookup/artifact

Out[30]:
(True,
 [{ 'created_at': '2018-02-01T11:09:55.731040',
    'id': 'b9a9205a-0772-11e8-a003-3b1c8766dad0',
    'mbytes': 0.0,
    'name': '8a63e21030d1483abb0f892963c1728f',
    'type': 'Run' },
  { 'created_at': '2018-02-01T11:11:17.560360',
    'id': 'ea6f3f80-0772-11e8-9abe-77bc32e350c5',
    'mbytes': 0.0,
    'name': 'artifact-1',
    'type': 'Run' } ])
```

---

### DarwinSdk.lookup\_artifact\_name(*artifact\_name*)

Get information for an artifact specified by its name.

#### Parameter:

- *artifact* - specifies an artifact by its name

#### Returns:

---

(True, <job-info>) or (False, <error-message>)

**Example:**

```
In [31]: s.lookup_artifact_name('artifact-1')

Out[31]:
(True,
 {'created_at': '2018-02-01T11:11:17.560360',
  'mbytes': 0.0,
  'name': 'artifact-1',
  'type': 'Run'})
```

---

**DarwinSdk.lookup\_limits()**

Get a client's metadata. A client is the current user or service in context.

**Parameters:** None

**Returns:**

(True, <client-info>) or (False, <error-message>)

**Example**

```
In [21]: s.lookup_limits()

Out[21]:
(True,
 {'job_limit': None,
  'model_limit': None,
  'tier': 0,
  'upload_limit': None,
  'user_limit': None,
  'username': None})
```

---

**DarwinSdk.lookup\_dataset()**

Get the dataset(s) metadata for a user. The user is the current user or service in the current context. This is useful for listing all created datasets.

**Parameters:** None

**Returns:**

(True, <list-of-dataset-info>) or (False, <error-message>)

### Example

```
In [4]: s.lookup_dataset()

Out[4]:
(True,
 [{'categorical': None,
   'imbalanced': None,
   'mbytes': 0.02019977569580078,
   'minimum_recommended_train_time': "string",
   'name': 'unittest-cancer-dataset2',
   'sequential': None,
   'updated_at': '2018-01-31T15:37:28.310994'},
 {'categorical': None,
   'imbalanced': None,
   'mbytes': 0.02019977569580078,
   'minimum_recommended_train_time': "string",
   'name': 'cancer-train',
   'sequential': None,
   'updated_at': '2018-02-01T10:52:06.076279'}])
```

---

### DarwinSdk.lookup\_dataset\_name(*dataset\_name*)

Get a specific dataset's metadata.

#### Parameters:

- *dataset\_name* - The dataset name. The dataset name is established in the **upload\_dataset()** method.

#### Returns:

(True, <dataset-info>) or (False, <error-message>)

### Example

```
In [36]: s.lookup_dataset_name('cancer-train')

Out[36]:
(True,
 {'categorical': None,
   'imbalanced': None,
   'mbytes': 0.02019977569580078,
   'minimum_recommended_train_time': "string",
   'sequential': None,
   'updated_at': '2018-02-01T10:52:06.076279'})
```

### DarwinSdk.lookup\_model()

Get the model(s) metadata for a user. The user is the current user or service in the current context. This is useful for listing all models.

**Parameters:** None

**Returns:**

(True, <list-of-model-info>) or (False, <error-message>)

#### Example

```
In [37]: s.lookup_model()
```

```
Out[37]:
```

```
(True,
 [{ 'generations': 0,
     'loss': 2.0,
     'name': 'cancer-model',
     'parameters': { 'target': 'Diagnosis' },
     'trained_on': ['cancer-train'],
     'updated_at': '2018-02-01T10:53:50.443166',
     'description': { "best_genome": "DeepNet(\n  (l0): LSTM(20, 18, num_layers=2)\n  (l1): Linear(in_features=18, out_features=1, bias=True)\n)", "recurrent": True }
   }
 ]
)
```

---

### DarwinSdk.lookup\_model\_name(model\_name)

Get a specific model's metadata. The name of a model is established in the *create\_model()* method.

**Parameters:**

- *model\_name* - The name of the model

**Returns:**

(True, <model-info>) or (False, <error-message>)

#### Example

```
In [40]: s.lookup_model_name('cancer-model')
```

```
Out[40]:
```

```
(True,
 [{ 'generations': 0,
     'loss': 2.0,
     'parameters': { 'target': 'Diagnosis' },
     'trained_on': ['cancer-train'],
```

```
'updated_at': '2018-02-01T10:53:50.443166',
'description': {"best_genome": "DeepNet(\n  (l0): LSTM(20, 18, num_layers=2)\n  (l1): Linear(in_features=18, out_features=1, bias=True)\n)", "recurrent": True}
}]
)
```

---

### DarwinSdk.lookup\_tier()

Get metadata for all tiers. A tier specifies certain usage limits such as *number of models* and *datasets*.

**Parameters:** None

**Returns:**

(True, <list-of-tier-info>) or (False, <error-message>)

### Example

```
In [41]: s.lookup_tier()
```

```
Out[41]:
```

```
(True,
[{'job_limit': None,
  'model_limit': None,
  'tier': 0,
  'upload_limit': None,
  'user_limit': None},
 {'job_limit': 10000,
  'model_limit': 10000,
  'tier': 1,
  'upload_limit': 10000,
  'user_limit': 1000}])
```

---

### DarwinSdk.lookup\_tier\_num(tier\_num)

Get a specific tier's metadata. A tier specifies certain usage limits such as the *number of models* or *datasets*.

**Parameters:**

- *tier\_num* - The number of the tier

**Returns:**

(True, <tier-info>) or (False, <error-message>)

### Example

```
In [44]: s.lookup_tier_num(1)
```

```
Out[44]:
```

```
(True,  
 {'job_limit': 10000,  
  'model_limit': 10000,  
  'tier': 1,  
  'upload_limit': 10000,  
  'user_limit': 1000})
```

---

### **DarwinSdk.lookup\_user()**

Returns information for users that were created with the current `api_key`.

**Note:** Each customer site is assigned a *unique api\_key*. All users from that site have the same `api_key`.

**Parameters:** None

**Returns:**

(True, <list-of-user-info>) or (False, <error-message>)

### **Example**

```
In [25]: s.lookup_user()
```

```
Out[25]:
```

```
(True,  
 [[{'client_api_key': 'RsJ74ZS5AvwznbHh0AfVSgrchhS9...3zFA',  
     'created_at': '2018-01-03T12:54:30.653478',  
     'parent_id': '2516b462-df85-11e7-bdd1-e37424c63ea4',  
     'tier': 0,  
     'username': 'testuser2'},  
    {'client_api_key': 'RsJ74ZS5AvwznbHh0AfVSgrchhS9...3zFA',  
     'created_at': '2018-01-03T13:14:36.188371',  
     'parent_id': '2516b462-df85-11e7-bdd1-e37424c63ea4',  
     'tier': 0,  
     'username': 'testuser5'},  
    {'client_api_key': 'RsJ74ZS5AvwznbHh0AfVSgrchhS9...3zFA',  
     'created_at': '2018-01-03T13:21:21.099148',  
     'parent_id': '2516b462-df85-11e7-bdd1-e37424c63ea4',  
     'tier': 0,  
     'username': 'testuser6'}]])
```

---

**DarwinSdk.lookup\_username(username)**

Returns information for a user.

**Notes:**

- The user in question should have been created using the current `api_key`.
- Each customer site is assigned a *unique api\_key*. All users from that site have the same `api_key`.

**Parameters:** None

**Returns:**

(True, <user-info>) or (False, <error-message>)

**Example**

```
In [26]: s.lookup_username('testuser2')

Out[26]:
(True,
 [{'client_api_key': 'RsJ74ZS5AvwznbHh0AfVSgrchhS9...3zFA',
   'created_at': '2018-01-03T12:54:30.653478',
   'parent_id': '2516b462-df85-11e7-bdd1-e37424c63ea4',
   'tier': 0,
   'username': 'testuser2'}])
```

**DarwinSdk.display\_population(model\_name)**

Get a specific model's population data. The name of the model is established in the **create\_model()** method.

**Parameters:**

- *model\_name* - The name of the model

**Returns:**

(True, <population-info>) or (False, <error-message>)

**Example**

```
In [40]: s.display_population('cancer-model')

Out[40]:
(True,
 {
   "population": {
     "model_types": {
       "DeepNeuralNetwork": {
         "model_description": [
           {
             "layer 1": {
```



```

        "type": "LinearLayer",
        "parameters": {
            "activation": "leakyrelu",
            "numunits": 221
        }
    },
    {
        "layer 2": {
            "type": "LinearLayer",
            "parameters": {
                "activation": "relu",
                "numunits": 2
            }
        }
    },
    "loss_function": "CrossEntropy",
    "fitness": 1.9667300770467946
},
"RandomForest": {
    "model_description": {
        "type": "RandomForestClassifier",
        "parameters": {
            "bootstrap": true,
            ....
        }
    },
    "loss_function": "CrossEntropy",
    "fitness": 1.9321841524601422
}
}
})

```

## Datasets and artifact methods

### **DarwinSdk.upload\_dataset(dataset, dataset\_name=None)**

Upload a dataset.

**Note:** Supported file formats are .csv and .h5.

**Note:** For .csv files, ensure they are encoded to one of the following standards:

- utf-8
- us-ascii
- iso-8859-1
- iso-8859-2
- ascii

**Note:** The maximum size that can be uploaded is 10GB due to only supporting uploading data via http. Files larger than ~2GB can be processed by `analyze_data()` only. Model creation might not be successful for files larger than ~2GB until Big Data is fully supported. `Analyze_data()` is the only method that supports Big Data.

**Parameters:**

- *dataset*- Path to dataset
- *dataset\_name* - Name to be given to dataset, or defaults to filename

**Returns:**

(True, {dataset\_name: <name-given-to-dataset>}) or (False, <error-message>)

**Example**

```
In [5]: s.upload_dataset('sets/cancer_train.csv', 'unittest-cancer-dataset')

Out[5]:
(True,
 {'dataset_name': 'unittest-cancer-dataset'})
```

---

**DarwinSdk.download\_dataset(*dataset\_name*)**

Download a dataset artifact given its name.

**Parameters:**

- *dataset\_name* - Name of the dataset to be downloaded.

**Returns:**

(True, <path-to-file>) or (True, <python-list>) or (False, <error-message>)

**Example**

```
In [5]: s.download_dataset('cancer-cleandata3', \
    artifact_path='/Users/username/Downloads/artifacts')

Out[5]:
(True,
 {'filename': \
 '/Users/username/Downloads/artifacts/cancer-cleandata3-cleaned-8m38g07j.csv'})
```

**DarwinSdk.delete\_dataset(*dataset\_name*)**

Delete the named dataset.

**Parameters:**

- *dataset\_name* - Name of the dataset to be deleted.

**Returns:**

(True, None) or (False, <error-message>)

**Example**

```
In [6]: s.delete_dataset('unittest-cancer-dataset')
```

```
Out[6]:
```

```
(True, None)
```

**DarwinSdk.download\_model(*model\_name*)**

Download a supervised model given its name.

**Parameters:**

- *model\_name* - Name of the model to be downloaded.
- *path* - (optional) Relative or absolute path of the directory to download the model to. This directory must already exist prior to model download. If the path is not specified, the current directory is used. There are two files associated with a model: *'model'* and *'data\_profiler'*.
- *model\_type* - (optional) Model type of the model to be downloaded. Possible values include the following: *DeepNeuralNetwork*, *RandomForest*, *GradientBoosted*.
- *model\_format* - (optional) Format in which the model is to be downloaded. Possible values include: *json*, *onnx*. The ONNX format is only available for neural network models.

**Returns:**

(True, None) or (False, <error-message>)

**Example**

```
In [6]: s.download_model('my-model-name', path='Users/auser/Downloads/mymodel')
```

```
Out[6]:
```

```
(True, None)
```

```
% ls -l ~/Downloads/mymodel
```

```
total 272
```

```
-rw-r--r-- 1 auser staff 58609 Oct 10 15:55 data_profiler
```

```
-rw-r--r-- 1 auser staff 75507 Oct 10 15:55 model
```

## DarwinSdk.download\_artifact(*artifact\_name*, *artifact\_path*=None)

Download artifact given its name. The methods that return artifacts are:

- *analyze\_data()*
- *analyze\_model()*
- *analyze\_predictions()*
- *run\_model()*

**Note:** The artifact for *analyze\_model()* is a pandas Series. The artifact displays a two-column series where the name of the feature is in the first column and the second column is a number between 0 and 1 indicating how much that feature influenced the model's predictions over the entire dataset that the model was trained on.

**Note:** The artifact for *analyze\_predictions* is a pandas DataFrame. The artifact has one column for each feature that indicates how much that feature influenced the model's prediction, plus additional columns for the average model prediction ("base\_value"), and the model prediction for each row ("predicted\_value" for regression or "predicted-class" and "predicted\_probability" for classification).

### Parameters:

- *artifact\_name* - Name of the artifact to download.
- *artifact\_path*: (optional) Relative path of the directory to download the artifact to (only applicable for the artifacts where a temporary file is created). This directory must already exist prior to artifact download.

### Returns:

(True, <path-to-file>) or (True, <python-list>) or (False, <error-message>)

### Example *run\_model()* or prediction artifact

```
In [16]: s.download_artifact('5da17d64be9c4441899316edb9afd403')
```

```
Out[16]:
```

	Diagnosis	prob_BENIGN	prob_MALIGNANT
0	BENIGN	0.999400	6.002134e-04
1	BENIGN	1.000000	3.600000e-09
2	BENIGN	0.999999	8.689000e-07
3	BENIGN	1.000000	2.500000e-09
4	MALIGNANT	0.004159	9.958413e-01
5	MALIGNANT	0.002674	9.973264e-01
..	...	...	...
92	MALIGNANT	0.002499	9.975013e-01
93	BENIGN	1.000000	5.250000e-08
94	BENIGN	1.000000	3.100000e-08
95	BENIGN	0.999901	9.866350e-05
96	BENIGN	1.000000	9.230000e-08
97	MALIGNANT	0.003884	9.961160e-01
98	MALIGNANT	0.002777	9.972232e-01

```
99 MALIGNANT      0.003686      9.963139e-01
```

```
[100 rows x 3 columns])
```

### Example `analyze_data()` artifact

```
In [97]: s.download_artifact('1a38f1af934c4cbabb9136ee94f72718')
```

```
Out[97]:
```

```
(True,
```

	count	drop	is_date	low_samples	max	\
name						
Code	599	False	False	[]	8233704.0	
Clump Thickness	599	False	False	[]	10.0	
Uniformity of Cell Size	599	False	False	[]	10.0	
Uniformity of Cell Shape	599	False	False	[]	10.0	
Marginal Adhesion	599	False	False	[]	10.0	
Single Epithelial Cell Size	599	False	False	[]	10.0	
Bare Nuclei	599	False	False	[]	10.0	
Bland Chromatin	599	False	False	[]	10.0	
Normal Nucleoli	599	False	False	[]	10.0	
Mitoses	599	False	False	[]	10.0	
Diagnosis	599	False	False	[]	NaN	

  

mean	min	missing	num_uniques	stddev	\
1.044171e+06	6.163400e+04	0.0	557	4.140964e+05	
4.555927e+00	1.000000e+00	0.0	10	2.887488e+00	
3.215359e+00	1.000000e+00	0.0	10	3.044601e+00	
3.287145e+00	1.000000e+00	0.0	10	2.971045e+00	
2.859766e+00	1.000000e+00	0.0	10	2.873655e+00	
3.290484e+00	1.000000e+00	0.0	10	2.275159e+00	
-2.309692e+17	-9.223372e+18	0.0	11	1.442374e+18	
3.520868e+00	1.000000e+00	0.0	10	2.369500e+00	
2.966611e+00	1.000000e+00	0.0	10	3.084466e+00	
1.607679e+00	1.000000e+00	0.0	9	1.734369e+00	
NaN	NaN	0.0	2	NaN	

  

top_unique_values	treatment	type	type_note	\
[]	numeric	int64		
[]	numeric	int64		
[]	numeric	int64		
[]	numeric	int64		
[]	numeric	int64		
[]	numeric	int64		
[]	numeric	int64		

```

[]                numeric    int64
[]                numeric    int64
[]                numeric    int64
[[BENIGN, 379], [MALIGNANT, 220]] categorical object

uniques
[61634, 63375, 76389, 95719, 128059, 142932, 1...
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[-9223372036854775808, 1, 2, 3, 4, 5, 6, 7, 8,...
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 10]
[BENIGN, MALIGNANT])

```

### Example `analyze_model()` or prediction artifact

```
In [5]: s.download_artifact('6e4861de29424cb7ad09e467d1869c17',\
    'path_to_download_dir/')
```

Out[5]:

```

True RM          0.216088
CRIM             0.141956
LSTAT            0.134069
DIS              0.104101
PTRATIO          0.089905
AGE              0.078864
NOX              0.074132
B                0.067823
TAX              0.045741
INDUS            0.023659
ZN               0.011041
RAD = 4.0        0.009464
RAD = 5.0        0.001577
RAD = 6.0        0.001577
RAD = 24.0       0.000000
RAD = 3.0        0.000000
RAD = 7.0        0.000000
CHAS = 1.0       0.000000
RAD = 8.0        0.000000
RAD = 2.0        0.000000
dtype: float64

```

### Example `analyze_predictions()` artifact

```
In [8]: (code, fis) = s.download_artifact('34b461c7a52a48318e982068f87e6562',\
'path_to_download_dir/')
```

```
In [9]: fis.head()
```

```
Out[9]: ##Sample return for regression, has predicted_value column
```

	AGE	B	CHAS = 1.0	CRIM	DIS	INDUS	LSTAT \
0	0.000000	0.000000	0.000000	-0.664664	-0.923219	-0.720941	2.328635
1	-1.220243	-0.648893	0.000000	0.000000	1.187539	-0.630767	3.506132
2	-0.456561	-0.226880	-0.424802	0.000000	-0.077616	-0.333270	-0.292705
3	-0.195096	0.352712	0.000000	-1.867664	-0.152037	0.273082	-3.583178
4	0.632119	0.079678	0.000000	0.076080	-0.488128	-0.016690	-0.102031

  

	NOX	PTRATIO	RAD = 2.0	...	RAD = 4.0	RAD = 5.0 \
0	-0.342404	0.224360	0.0	...	-0.641678	-0.570788
1	-0.556636	-2.168356	0.0	...	0.000000	-0.741561
2	0.000000	1.458677	0.0	...	0.000000	-0.340486
3	-0.945060	-1.068743	0.0	...	0.000000	0.217991
4	0.309544	0.298940	0.0	...	0.000000	-0.047708

  

	RAD = 6.0	RAD = 7.0	RAD = 8.0	RM	TAX	ZN	base_value \
0	0.0	0.0	0.0	-1.835851	-0.563795	-0.600155	21.63455
1	0.0	0.0	0.0	-1.016655	-0.699813	-0.727181	21.63455
2	0.0	0.0	0.0	-1.137559	0.000000	-0.310209	21.63455
3	0.0	0.0	0.0	-1.220045	0.156790	0.256763	21.63455
4	0.0	0.0	0.0	-0.999328	-0.149627	-0.045493	21.63455

  

	predicted_value
0	24.620939
1	26.128595
2	24.200972
3	11.255393
4	21.982929

```
[5 rows x 22 columns]
```

```
Out[9]: ##Sample return for classification, returns predicted_class as well
```

	petal length (cm)	petal width (cm)	sepal length (cm)	sepal width (cm) \
0	0.217699	0.424209	0.026237	0.005834
1	0.292612	0.315358	0.019236	-0.014442
2	0.325615	0.329229	0.003208	0.016954
3	0.232265	0.410938	0.043014	0.004154
4	0.317190	0.339065	0.015227	0.003523

  

	base_value	predicted_value	predicted_class
--	------------	-----------------	-----------------

---

0	0.309628	0.983607	virginica
1	0.365378	0.978142	versicolor
2	0.324994	1.000000	setosa
3	0.309628	1.000000	virginica
4	0.324994	1.000000	setosa

---

### **DarwinSdk.delete\_artifact(*artifact\_name*)**

Delete the artifact given its name.

#### **Parameters:**

- *artifact\_name* - Name of the artifact to be deleted.

#### **Returns:**

(True, None) or (False, <error-message>)

#### **Example**

```
In [8]: s.delete_artifact('6c482eac9f894cdb9b0ele487e41730a')
```

```
Out[8]:
```

```
(True, None)
```

## **Data Analysis and Data Cleaning methods**

### **DarwinSdk.analyze\_data(*dataset\_name*, **\*\*kwargs**)**

Analyze the dataset given its *name*. Basic statistics about the data are returned. This method supports Big Data (greater than 2GB) although *upload\_dataset()* is currently artificially limited to 10GB due to only supporting uploading data via http.

**Note:** Please contact us if you have data greater than 10GB. We would like to see a sampling of the large datasets that you'd like to see supported.

**Note:** You can only analyze a dataset once. If you try to analyze the dataset a second time, you will get a 400: BAD REQUEST error.

#### **Parameters:**

*dataset\_name* - (required) The name of the dataset to be analyzed.

**\*\*kwargs** - variable number of keyword arguments, described below:

- *job\_name* - (optional) If not specified, a uuid will be created as the *job\_name*.
- *artifact\_name*: (optional) If not specified, a uuid will be created as the *artifact\_name*.
- *max\_unique\_values*: Expected input/type: *integer*. Default value of 15. Threshold for automatic pruning of categorical columns prior to one hot encoding based on the number of unique values.



**Note:** If a categorical column contains at least *max\_unique\_values*, it is dropped during preprocessing prior to one hot encoding.

### Returns:

(True, {"job\_name": <string>, "artifact\_name": <string>}) or (False, <error-message>)

Statistics included in the artifact:

- *col\_name* - name of the column (any periods ('.') in the column name will be replaced by underscores ('\_'))
- *col\_type* - type of column
- *drop* - returns True if column is dropped for modeling. Also returns True if the number of unique values is greater than the number defined in *max\_unique\_values* (default of 15) or if it has more than 80% missing values or has a standard deviation of 0.
- *is\_cat* - returns True for categorical otherwise returns False
- *max* - column maximum
- *mean* - column mean
- *min* - column minimum
- *missing* - percentage of missing values
- *num\_uniques* - number of unique values if the distinct count is less than the number defined in *max\_unique\_values* (default of 15), otherwise the value is the approximate number of unique values.
- *scalable* - returns True if column is scalable
- *stddev* - column standard deviation
- *uniques* - actual unique values if there are less than the number defined in *max\_unique\_values* (default of 15). Otherwise, nothing is returned, see *num\_uniques* for the approximate number of unique values.

### Example

```
In [6]: s.analyze_data('boston')
```

```
Out[6]:
```

```
(True,
 {'artifact_name': 'db968d77d2c4444ab731777d01e5e0c0',
  'job_name': '8c12f0df4c39485f9a488fa63196e00c'})
```

```
In [8]: s.download_artifact('db968d77d2c4444ab731777d01e5e0c0')
```

```
Out[8]:
```

```
(True,
      col_name      col_type  drop  is_cat      max  \
0          PID  StringType  True  False  2205663001_
1        ST_NUM  StringType  True  False      999
2        ST_NAME  StringType  True  False    ZELLER
3    ST_NAME_SUF  StringType  True  False      XT
4        ZIPCODE  StringType  True  False    02467_
5  Assessed_Value    int64  True  False  23095700
6        Lot_Area    int64  True  False    107158
7      Gross_Area    int64  True  False    23335
8    Living_Area    int64  True  False    21711
```

9	Owner_Occupied	categorical	False	True	None
10	Year_Built	int64	True	False	2016
11	Number_of_Floors	float64	False	False	5.0
12	Total_Number_of_Rooms	int64	True	False	27
13	Number_of_Bedrooms	categorical	False	True	None
14	Number_of_Full_Baths	categorical	False	True	None
15	Number_of_Half_Baths	categorical	False	True	None
16	Number_of_Kitchens	categorical	False	True	None
17	Has_AC	categorical	False	True	None
18	Number_of_Fireplaces	categorical	False	True	None
19	Year_Since_Remodel_or_Build	int64	True	False	307
20	Year_Remodeled	StringType	True	False	Unremodeled
21	Structure_Type	categorical	False	True	None
22	Building_Style	StringType	True	False	Victorian
23	Roof_Type	categorical	False	True	None
24	Exterior_Finish	categorical	False	True	None
25	Main_Bathroom_Style	categorical	False	True	None
26	Main_Kitchen_Style	categorical	False	True	None
27	Heating_type	categorical	False	True	None
28	Exterior_Condition	categorical	False	True	None
29	Overall_Condition	categorical	False	True	None
30	Interior_Condition	categorical	False	True	None
31	Interior_Finish	categorical	False	True	None
32	View	categorical	False	True	None

	mean	min	missing	num_uniques	scalable	\
0	None	0100021000_	0.000000	28578	True	
1	122.09705524787249	1005R	0.010223	1922	True	
2	None	ABBOTSFORD	0.000000	2246	True	
3	None	ST	0.003015	21	True	
4	None	02108_	0.000000	28	True	
5	534716.6815977456	101300	0.000000	7737	True	
6	5116.273150271971	375	0.000000	8342	True	
7	2931.1126220591127	510	0.000000	4472	True	
8	1752.7717084999017	332	0.000000	3169	True	
9	0.8408480241169146	None	0.000000	2	False	
10	1926.970935185792	1710	0.000000	225	True	
11	1.8748115866046269	1.0	0.000000	9	True	
12	7.233632610262796	2	0.000000	26	True	
13	3.3851169801428664	None	0.000000	12	False	
14	1.4273543482534898	None	0.000000	10	False	
15	0.5716953928828888	None	0.000000	7	False	
16	1.0287043711907726	None	0.000000	4	False	
17	0.18733206632151517	None	0.000000	2	False	
18	0.590995478078511	None	0.000000	13	False	

19	60.88419948882627	1	0.000000	190	True
20	2000.3376960831488	1890	0.000000	82	True
21	None	None	0.000000	5	False
22	None	Bi-Level	0.000000	17	True
23	None	None	0.000000	7	False
24	None	None	0.000000	13	False
25	None	None	0.000000	4	False
26	None	None	0.000000	4	False
27	None	None	0.000000	6	False
28	None	None	0.000000	5	False
29	None	None	0.000000	5	False
30	None	None	0.000000	5	False
31	None	None	0.000000	3	False
32	None	None	0.000000	5	False

	stddev	uniques
0	None	None
1	294.1511958893473	None
2	None	None
3	None	None
4	None	None
5	634750.7826113638	None
6	3218.286557124007	None
7	1069.3847598444354	None
8	758.9874732061347	None
9	0.3658237412175791	[0, 1]
10	34.9170355483078	None
11	0.5737101635770085	None
12	1.8082562295656077	None
13	1.0095185504254367	[12, 9, 1, 5, 2, 6, 3, 10, 7, 4, 11, 8]
14	0.6850264359951297	[12, 9, 1, 5, 2, 6, 3, 7, 4, 8]
15	0.5645602408681473	[0, 1, 5, 2, 6, 3, 4]
16	0.17162236936210065	[0, 1, 2, 3]
17	0.3901842537872663	[0, 1]
18	0.8584446055814273	[0, 12, 9, 1, 5, 2, 6, 3, 10, 7, 4, 11, 8]
19	43.323487380439225	None
20	13.578956800881818	None
21	None	['Residential', 'Wood/Frame', 'Unknown', 'Bric...
22	None	None
23	None	['Shed', 'Gambrel', 'Flat', 'Other', 'Mansard'...
24	None	['Cement Board', 'Frame/Clapboard', 'Wood Shak...
25	None	['Semi-Modern', 'Luxury', 'No Remodeling', 'Mo...
26	None	['Semi-Modern', 'Luxury', 'No Remodeling', 'Mo...
27	None	['Electric', 'Other', 'None', 'Hot Water', 'Sp...
28	None	['Poor', 'Good', 'Excellent', 'Average', 'Fair']

29	None	['Poor', 'Good', 'Excellent', 'Average', 'Fair']
30	None	['Poor', 'Good', 'Excellent', 'Average', 'Fair']
31	None	['Elaborate', 'Normal', 'Substandard']
32	None	['Poor', 'Good', 'Excellent', 'Average', 'Fair'] )

### DarwinSdk.clean\_data(dataset\_name, \*\*kwargs)

Clean the dataset given its name. The output is the cleaned dataset which is scaled and one-hot-encoded based on parameters in *analyze\_data()*. Use *download\_dataset()* to retrieve the cleaned dataset. *clean\_data()* needs to be performed prior to creating a model and again before running a model. When you run *clean\_data()* before creating a model, you must specify a *dataset\_name* and a *target*. When you run *clean\_data()* before running a model, you must specify a *dataset\_name* and a *model\_name*. *clean\_data()* can also be used for visualizing what Darwin would do with the dataset or for when you want to use the cleaned data outside of Darwin.

#### Parameters:

- *dataset\_name* - (required) The name of the dataset to be analyzed.
- *\*\*kwargs* - variable number of keyword arguments, described below:
  - *job\_name* : (optional) If not specified, a uuid will be created as the *job\_name*.
  - *artifact\_name*: (optional) If not specified, a uuid will be created as the *artifact\_name*.
  - *model\_name*: (Mandatory for running a model) Specify the model name when you clean data before running a model.
  - *target*: (Mandatory for Supervised Model Building) String denoting target prediction column in input data.
  - *index*: String denoting the date/time column name to use as an index.
  - *impute*: String alias that indicates how to fill in missing values in input data.

ALIAS	DESCRIPTION	COMPLEXITY
'ffill'	<b>(Default)</b> Forward Fill: Propagate values forward from one example into the missing cell of the next example. Might be useful for timeseries data, but also applicable for both numerical and categorical data.	Linear Fast
'bfill'	Backward Fill: Propagate values backward from one example into the missing cell of the previous example. Might be useful for timeseries data, but also applicable for both numerical and categorical data.	Linear Fast
'mean'	Mean Fill: Computes the mean value of all non-missing examples in a column to fill in missing examples. The result may or might not be interpretable in terms of the input space for categorical variables.	Linear Fast

- *max\_int\_uniques*: Expected input/type: *integer*. Threshold for automatic encoding of categorical variables. If a column contains less than *max\_int\_uniques* unique values, it is treated as

categorical and one hot encoded during preprocessing. **Note:** If the target has more numeric values than the *max\_int\_uniques* set point, the problem is treated as a regression and will use MSE.

- *max\_unique\_values*: Expected input/type: *integer*. Threshold for automatic pruning of categorical columns prior to one hot encoding based on the number of unique values.

**Note:** If a categorical column contains at least *max\_unique\_values*, it is dropped during preprocessing prior to one hot encoding.

### Example

```
In [16]: s.clean_data('pacman-cancer', target='Diagnosis')
Out[16]:
(True,
 {'job_name': '77b47b391b0d483699fe0741cc52e6ad',
  'job_id': '72756658-a63b-11e9-824c-c75a5cadd55f',
  'profile_name': '60f9429a0a2141d9ad98c3d073b8425f',
  'profile_id': '7276d1d2-a63b-11e9-824c-6be79b2f3967'})
```

## Modeling and analysis methods

### DarwinSdk.create\_model(*dataset\_names*, **\*\*kwargs**)

Create a model trained on the dataset identified by *dataset\_names*. You must clean the data using *clean\_data()*. The name of a model is specified in a parameter in *kwargs*.

**Note:** If no name is specified, the model is named with a *uuid-like* name.

#### Parameters:

*dataset\_names* - (required) A single dataset name as a string or a list of dataset string names to be used for training. The maximum file size is 500 MB for unsupervised and NBM and 10 GB for supervised.

*fit\_profile\_name*: (required) This is the *profile\_name* that is generated from the *clean\_data* call.

**\*\*kwargs** - variable number of keyword arguments, described in *parameters*.

*parameters* -

- *val\_size*: Portion of the dataset to be used as a validation set during training, expressed as a decimal that is greater than 0 and less than 1. Default value is 0.2 (i.e., 20%).
- *cv\_kfold*: k-fold cross-validation, where k is the number of groups that a given data sample is to be split into for training/validation. Default is 1 for non-timeseries data or 3 for timeseries data. Maximum value allowed is 10.
- *model\_name*: The string identifier of the model to be trained. If no name is specified, the model is named with a *uuid-like* name.
- *job\_name*: If no name is specified, the job is named with a *uuid-like* name.
- *max\_train\_time* (supervised only): Sets the training time for the model in 'HH:MM' format. Default value is 00:01.

- *max\_epochs*: Expected input/type: *numeric*. Sets the training time for the model in epochs. Default value is 10.
- *recurrent*: Expected input/type: *True/False*. Enables recurrent connections to be evolved in the model. This can result in slower model evolution.
- *anomaly*: Setting this parameter to **True** indicates that an isolation forest should be built for anomaly detection. If set to **True**, clustering will automatically be interpreted as **False**.
- *clustering* (unsupervised only): Enables clustering for unsupervised problems. If *False*, detects outliers.
- *n\_clusters* (unsupervised only): Expected input/type: *integer*. Specifies the number of clusters.  
**Note:** If this value is not provided, the number of clusters will be heuristically determined.
- *forecast\_horizon* (forecasting only): Integer indicating how long in the future you want to forecast predictions. For example, if you have 6 months of time-series data and each row represents a 1 day interval and you want to predict the next week of data, you should set `forecast_horizon=7`. If each row is a 1 hour interval, then you should set `forecast_horizon=168`. ( $168 = 7 \times 24$ )

**Note:** For best results, be sure that the minimum length to run the model is 5 times of the *forecast\_horizon* specified.

- *anomaly\_prior* (unsupervised only): Expected input/type: *between [0,1]*. Significance level at which a point is defined as anomalous. This is only used for unsupervised problems if *clustering* is disabled.
- *class\_weights*: A string to indicate how relatively important each class is for predictive correctness. This is done by providing a numeric value to each class. Note that the class name is case-sensitive. The following is an example *class\_weights* setting:

```
class_weights = '{"BENIGN': 4, 'MALIGNANT': 6}"
```

- *loss\_fn\_name*: Specify the loss function. Possible values include: *"CrossEntropy"*, *"MSE"*, *"BCE"*, *"L1"*, *"NLL"*, *"BCEWithLogits"*, *"SmoothL1"*.  
*"CrossEntropy"*, *"BCE"*, and *"BCEWithLogits"* can be used for classification data, while all others can be used for regression data. The default value is *CrossEntropy* if this field is left empty.
- *fitness\_fn\_name*: Specify the fitness function. This represents the name of the fitness function used for evolution of the model population during training. Possible values include: *"Accuracy"*, *"F1"*, *"R2"*, *"MSE"*. "F1" is the default for classification and "R2" is the default for regression problems. "Accuracy" and "F1" are for classification only. "R2" and "MSE" are for regression only.
- *lead\_time\_days* (*nbm* only): Expected input/type: *integer*. Default value is 60. The number of days prior to failure when the behavior starts trending toward either abnormal behavior or failure.
- *nbm\_window\_size* (*nbm* only): Expected input/type: *integer*. Default value is 256. The number of sample points to consider for each failure detection.
- *nbm* (*nbm* only): Expected input/type: *True/False*. Default value is *False*. Set value to *True* for a normal behavioral model (NBM).
- *failure\_dates* (*nbm* only): Expected input/type: *string*. List of failure dates to use for the calculation. Currently, only a list of one date can be used in the query. Example date format: *"07/01/2015"*

- *recovery\_dates* (*nbm* only): Expected input/type: *string*. List of recovery dates to use for the calculation. Currently, only a list of one date can be used in the query. Example date format: "11/01/2015"

**Returns:**

(True, {'job\_id': <uuid1>, model\_name: <model\_name>}) or (False, <error-message>)

**Example**

```
In [18]: s.create_model('pacman-cancer', \
    fit_profile_name='60f9429a0a2141d9ad98c3d073b8425f', max_train_time='00:02')
Out[18]:
(True,
 {'job_name': 'b29d680547f94d1e87bf0e6ae6913ae0',
  'job_id': '81a68bde-a63b-11e9-aa27-2ba9c50e485f',
  'model_name': '1f871bd9b0b3405680a2bce0c3b2b226'})
```

---

**DarwinSdk.delete\_model(model\_name)**

Delete a model named by *model\_name*.

**Parameters:**

- *model\_name* - Name of the model to be deleted.

**Returns:**

(True, None) or (False, <error-message>)

**Example**

```
In [5]: s.delete_model('unittest-cancer-model')
Out[5]: (True, None)
```

---

**DarwinSdk.resume\_training\_model(model\_name, dataset\_names, \*\*kwargs)**

Resume training for a model on the dataset(s) identified by *dataset\_names*.

**Parameters:**

- *model\_name* - Name of the model to be trained.
- *dataset\_name*- Name of dataset(s) used for training.
- *\*\*kwargs* - variable number of keyword arguments, described below:
  - *job\_name* - If not specified, a uuid is created as the *job\_name*.
  - *max\_train\_time* - If not specified, the *default* is used.

**Returns:**

```
(True, {"job_id": "<uuid>", "model_name": "<model_name>"}) or (False, <error-message>)
```

### Example

```
In [39]: s.resume_training_model('1f871bd9b0b3405680a2bce0c3b2b226', \
    'pacman-cancer', max_train_time='00:01')
Out[39]:
(True,
 {'job_name': '30ba83c61814459f95b668a8316e647f',
  'job_id': '66e3ef92-a63d-11e9-9792-a38b3282194d',
  'model_name': '1f871bd9b0b3405680a2bce0c3b2b226'})
```

### DarwinSdk.analyze\_model(model\_name, job\_name=None, artifact\_name=None)

Analyze the universal feature importances for a particular model given the model name.

**Note:** This method is not supported in forecasting models.

#### Parameters:

- *model\_name* - (required) The name of the model to be analyzed.
- *job\_name* - (optional) If not specified, a uuid is created as the *job\_name*.
- *artifact\_name* - (optional) If not specified, a uuid is created as the *artifact\_name*.
- *category\_name* - (optional) The name of the class for supervised or cluster for unsupervised to get feature importance for. If this is not specified, the feature importance will be over all classes/clusters.
- *model\_type*: (optional) Model type from the population. Possible values include: *DeepNeuralNetwork*, *RandomForest*, *GradientBoosted*.

#### Returns:

```
(True, {"job_name": <string>, "artifact_name": <string>}) or (False, <error-message>)
```

### Example

```
In [5]: s.analyze_model('unittest-cancer-model')
Out [5]:
(True, {'artifact_id': '71a8ae55f2934014b45c13a3975f419c', 'job_id': \
'4e59ffc425e047e1a3b872f1e7396976'})
```

### DarwinSdk.analyze\_predictions(model\_name, dataset\_name, job\_name=None, artifact\_name=None)

Analyze specific feature importances for a particular sample or samples given the model name and sample data. Analyze predictions cannot be used if you trained your model with a dataset that is larger than 500 MB.

**Note:** This method is not supported in forecasting models.



**Parameters:**

- *dataset\_name* - (required) The name of the dataset containing the data to analyze predictions for. This is a new dataset that was not used during training for which you want feature importance scores for each row of this dataset. This dataset has a limit of 500 rows. There is no limit for columns.
- *model\_name* - (required) The name of the model to be analyzed.
- *job\_name* - (optional) If not specified, a uuid is created as the *job\_name*.
- *artifact\_name* - (optional) If not specified, a uuid is created as the *artifact\_name*.
- *start\_index* - (optional) Index to start at in the dataset when analyzing model predictions. All numeric and datetime data types can be indexes. When specifying an index as a datetime, the preferred timestamp format is 2019-02-15 19:46:48.
- *end\_index* - (optional) Index to stop at in the dataset when analyzing model predictions. All numeric and datetime data types can be indexes. When specifying an index as a datetime, the preferred timestamp format is 2019-02-15 19:46:48.
- *model\_type*: (optional) Model type from the population. Possible values include: *DeepNeuralNetwork*, *RandomForest*, *GradientBoosted*.

**Returns:**

(True, {"job\_name": <string>, "artifact\_name": <string>}) or (False, <error-message>)

**Example**

```
In [5]: s.analyze_predictions('model_name', 'dataset_name')
Out [5]:
(True, {'artifact_name': '71a8ae55f2934014b45c13a3975f419c', 'job_name': \
'4e59ffc425e047e1a3b872f1e7396976'})
```

**DarwinSdk.run\_model(dataset\_name, model\_name, job\_name=None, artifact\_name=None)**

Run the model given its name and a dataset to use. Use **upload\_dataset()** to upload a data set.

**Parameters:**

- *dataset\_name* - The name of a dataset to use for running the model.
- *model\_name* - The name of the model to run.
- *anomaly*: Setting this parameter to **True** indicates that an isolation forest should be built for anomaly detection. If set to **True**, clustering will automatically be interpreted as **False**.
- *supervised* - (**Deprecated**: This argument exists only for backward compatibility.) (optional) A boolean (True/False) indicating whether the model is supervised or not, for example, set this to *False* for *unsupervised*.
- *job\_name* - (optional) If not specified, a uuid is created as the *job\_name*.
- *artifact\_name* - (optional) If not specified, a uuid is created as the *artifact\_name*.

- *model\_type* - (optional) Model type of the model to be downloaded. Possible values include the following: *DeepNeuralNetwork*, *RandomForest*, *GradientBoosted*.

**Returns:**

(True, {"job\_name": <string>, "artifact\_name": <string>}) or (False, <error-message>)

**Example**

```
In [21]: s.run_model('pacman-cancer', '1f871bd9b0b3405680a2bce0c3b2b226')
Out[21]:
(True,
 {'job_name': 'dfd758d43bda429cb19b4d9460db689d',
  'job_id': '612b7b2a-a63c-11e9-acd6-7b9b48091c5f',
  'artifact_name': '2f8502b4e3494ba3b5ce2133e066ec1a'})
```

---

## Convenience methods

**DarwinSdk.delete\_all\_datasets()**

Deletes user datasets. This method deletes all datasets in the current user or service context.

**Note:** Use *lookup\_dataset()* to view/verify the datasets for deletion.

**Parameters:** None

**Returns:**

(True, None) or (False, <error-message>)

---

**DarwinSdk.delete\_all\_models()**

Delete all models for a user. This method will delete all models in the current user's or service's context.

**Note:** Use *lookup\_model()* to review and verify that you want to delete all listed models.

**Parameters:** None

**Returns:**

(True, None) or (False, <error-message>)

---

**DarwinSdk.delete\_all\_artifacts()**

Delete all artifacts for a user. This method will delete all artifacts in the current user's or service's context.

**Note:** Use *lookup\_artifact()* to review and verify that you want to delete all listed artifacts.

**Parameters:** None

**Returns:**

(True, None) or (False, <error-message>)

---

### **DarwinSdk.wait\_for\_job(job\_name, time\_limit=600)**

Synchronously wait for a job to complete, limited by *time\_limit* that defaults to 600 seconds. If the *time\_limit* is reached, your job will continue to run but **wait\_for\_job** will discontinue monitoring it. You can re-run **wait\_for\_job** or modify the *time\_limit* parameter.

#### **Parameters:**

- *job\_name* - The id for the job
- *time\_limit* - (optional) defaults to 600 seconds

#### **Returns:**

(True, None) or (False, <error-message>)

---

### **DarwinSdk.help()**

Shows all the methods available.

**Parameters:** None

#### **Example**

```
In [5]: s.help()
Out [5]:
analyze_data (self, dataset_name, **kwargs)
analyze_model (self, model_name, job_name=None, artifact_name=None, \
    category_name=None, model_type=None)
analyze_predictions (self, model_name, dataset_name, job_name=None, \
    artifact_name=None, model_type=None)
auth_change_password (self, curpass, newpass)
auth_delete_user (self, username)
auth_login (self, password, api_key)
auth_login_user (self, username, password)
auth_register (self, password, api_key, email)
auth_register_user (self, username, password, email)
auth_reset_password (self, username)
auth_set_email (self, username, email)
clean_data (self, dataset_name, **kwargs)
create_model (self, dataset_names, **kwargs)
delete_all_artifacts (self)
delete_all_datasets (self)
delete_all_models (self)
```

```
delete_artifact (self, artifact_name)
delete_dataset (self, dataset_name)
delete_job (self, job_name)
delete_model (self, model_name)
disable_ssl_cert_check (self)
display_population (self, model_name)
download_artifact (self, artifact_name, artifact_path=None)
download_dataset (self, dataset_name, file_part=None, artifact_path=None)
download_model (self, model_name, path=None, model_type=None, model_format=None)
enable_ssl_cert_check (self)
get_info (self)
get_url (self)
lookup_artifact (self, type=None)
lookup_artifact_name (self, artifact_name)
lookup_dataset (self)
lookup_dataset_name (self, dataset_name)
lookup_job_status (self, age=None, status=None)
lookup_job_status_name (self, job_name)
lookup_limits (self)
lookup_model (self)
lookup_model_name (self, model_name)
lookup_tier (self)
lookup_tier_num (self, tier_num)
lookup_user (self)
lookup_username (self, username)
resume_training_model (self, model_name, dataset_names, **kwargs)
run_model (self, dataset_name, model_name, **kwargs)
set_url (self, url, version='v1')
stop_job (self, job_name)
upload_dataset (self, dataset_path, dataset_name=None, has_header=True)
wait_for_job (self, job_name, time_limit=600)
```

## Reference

- [SDK modeling example](#)
- [Revision table](#)

## SDK modeling examples

The following section details modeling examples for the following types of problems:

- [Supervised](#)
- [Unsupervised](#)
- [NBM](#)

## Supervised modeling example

```
---
In [1]: from amb_sdk.sdk import DarwinSdk

In [2]: s = DarwinSdk()

In [3]: s.auth_login_user('your-username', 'your-password')
Out[3]:
(True,
 'Bearer eyJ0eXAiOiJK...A8sj4pAzX1FpMMscwY_rMJbnGo0YQ_4')

In [14]: s.upload_dataset('sets/cancer_train.csv', 'pacman-cancer')
Out[14]: (True, {'dataset_name': 'pacman-cancer'})

In [15]: s.analyze_data('pacman-cancer')
Out[15]:
(True,
 {'job_name': '3b3a54324a68427583ccae1194822fdd',
  'job_id': '688d5aba-a63b-11e9-b969-d3fc6b14b182',
  'artifact_name': '5b38f0d797cd45c5a7081a0c1b02ccad'})

In [16]: s.clean_data('pacman-cancer', target='Diagnosis')
Out[16]:
(True,
 {'job_name': '77b47b391b0d483699fe0741cc52e6ad',
  'job_id': '72756658-a63b-11e9-824c-c75a5cadd55f',
  'profile_name': '60f9429a0a2141d9ad98c3d073b8425f',
  'profile_id': '7276d1d2-a63b-11e9-824c-6be79b2f3967'})

In [18]: s.create_model('pacman-cancer', \
    fit_profile_name='60f9429a0a2141d9ad98c3d073b8425f', max_train_time='00:02')
Out[18]:
(True,
 {'job_name': 'b29d680547f94d1e87bf0e6ae6913ae0',
  'job_id': '81a68bde-a63b-11e9-aa27-2ba9c50e485f',
  'model_name': '1f871bd9b0b3405680a2bce0c3b2b226'})

In [19]: s.wait_for_job('b29d680547f94d1e87bf0e6ae6913ae0')
{'status': 'Running', 'starttime': '2019-07-14T08:30:11.995459', \
 'endtime': None, 'percent_complete': 0, 'job_type': 'TrainModel', \
 'loss': None, 'generations': 0, 'dataset_names': ['pacman-cancer'], \
 'artifact_names': None, 'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', \
 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:30:11.995459', \
 'endtime': None, 'percent_complete': 50, 'job_type': 'TrainModel', \
```

```
'loss': 0.20505395531654358, 'generations': 1, 'dataset_names': ['pacman-cancer'], \
'artifact_names': None, 'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', \
'job_error': ''}
...
'generations': 29, 'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
{'status': 'Complete', 'starttime': '2019-07-14T08:30:11.995459', \
'endtime': '2019-07-14T08:34:40.40471', 'percent_complete': 100, \
'job_type': 'TrainModel', 'loss': 0.20505395531654358, 'generations': 31, \
'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
Out[19]: (True, 'Job completed')

In [21]: s.run_model('pacman-cancer', '1f871bd9b0b3405680a2bce0c3b2b226')
Out[21]:
(True,
{'job_name': 'dfd758d43bda429cb19b4d9460db689d',
'job_id': '612b7b2a-a63c-11e9-acd6-7b9b48091c5f',
'artifact_name': '2f8502b4e3494ba3b5ce2133e066ec1a'})

In [22]: s.wait_for_job('dfd758d43bda429cb19b4d9460db689d')
{'status': 'Complete', 'starttime': '2019-07-14T08:36:26.997233', \
'endtime': '2019-07-14T08:36:40.418987', 'percent_complete': 100, \
'job_type': 'RunModel', 'loss': 0.20505395531654358, 'generations': 31, \
'dataset_names': ['pacman-cancer'], \
'artifact_names': ['2f8502b4e3494ba3b5ce2133e066ec1a'], \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
Out[22]: (True, 'Job completed')

In [23]: s.download_artifact('2f8502b4e3494ba3b5ce2133e066ec1a')
Out[23]:
(True,
      Diagnosis  prob_BENIGN  prob_MALIGNANT
0      BENIGN      0.896724      0.103276
1    MALIGNANT      0.313960      0.686040
...
597    BENIGN      0.886773      0.113227
598    BENIGN      0.931960      0.068040

[599 rows x 3 columns])

In [26]: s.upload_dataset('sets/cancer_test.csv', 'pacman-cancertest')
Out[26]: (True, {'dataset_name': 'pacman-cancertest'})

In [27]: s.clean_data('pacman-cancertest', \
model_name='1f871bd9b0b3405680a2bce0c3b2b226')
```

```

Out[27]:
(True,
{'job_name': '462ade77431d4fde92b780ddc00573d9',
 'job_id': 'a868dd5c-a63c-11e9-94d1-8b9399879e43',
 'artifact_name': 'd8d4e61a4c624e70abb8bf66fde42e45',
 'artifact_id': 'a86a8a30-a63c-11e9-94d1-93c25fc085f5'})

In [28]: s.run_model('pacman-cancertest', \
'1f871bd9b0b3405680a2bce0c3b2b226')
Out[28]:
(True,
 {'job_name': '015bc7fa826c4f36b5ca2b4e8b27dba0',
  'job_id': 'b3eff6c4-a63c-11e9-bfd4-2387a41a7f36',
  'artifact_name': 'f5e5de3ac8bc413385d94ff9203ed919'})

In [29]: s.wait_for_job('015bc7fa826c4f36b5ca2b4e8b27dba0')
{'status': 'Complete', 'starttime': '2019-07-15T12:53:34.483154', \
'endtime': '2019-07-15T12:53:42.266985', 'percent_complete': 100, \
'job_type': 'RunModel', 'loss': 0.4324471354484558, 'generations': 21, \
'dataset_names': ['pacman-cancer'], \
'artifact_names': ['f5e5de3ac8bc413385d94ff9203ed919'], \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
Out[29]: (True, 'Job completed')

In [30]: s.download_artifact('f5e5de3ac8bc413385d94ff9203ed919')
Out[30]:
(True,
      Diagnosis  prob_BENIGN  prob_MALIGNANT
0      BENIGN      0.816393      0.183607
1      BENIGN      0.947398      0.052602
2      BENIGN      0.947646      0.052354
3      BENIGN      0.947398      0.052602
4     MALIGNANT      0.189687      0.810313
5     MALIGNANT      0.256924      0.743076
...
98     MALIGNANT      0.225788      0.774212
99     MALIGNANT      0.202293      0.797707
100     BENIGN      0.816393      0.183607
101     BENIGN      0.816393      0.183607

[102 rows x 3 columns])

In [31]: s.analyze_model('1f871bd9b0b3405680a2bce0c3b2b226')
Out[31]:
(True,

```

```
{'job_name': '173bc091175c41c3a03d2cef9b4344fb',
 'job_id': 'eef624aa-a63c-11e9-94d1-2bccd93a7796',
 'artifact_name': '4d4684c1956844df8b412119637e890b'})
```

```
In [32]: s.wait_for_job('173bc091175c41c3a03d2cef9b4344fb')
{'status': 'Complete', 'starttime': '2019-07-14T08:40:24.885663', \
 'endtime': '2019-07-14T08:40:26.360908', 'percent_complete': 100, \
 'job_type': 'AnalyzeModel', 'loss': 0.20505395531654358, 'generations': 31, \
 'dataset_names': None, 'artifact_names': ['4d4684c1956844df8b412119637e890b'], \
 'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
Out[32]: (True, 'Job completed')
```

```
In [33]: s.download_artifact('4d4684c1956844df8b412119637e890b')
Out[33]:
```

```
(True, Diagnosis = BENIGN                0.143460
      Single Epithelial Cell Size        0.141226
      Bland Chromatin                    0.114085
      Normal Nucleoli                    0.112659
      Mitoses                            0.100054
      Marginal Adhesion                   0.091280
      Uniformity of Cell Size             0.070170
      Uniformity of Cell Shape            0.066997
      Code                                0.058587
      Clump Thickness                     0.053780
      Diagnosis = MALIGNANT               0.046033
      Bare Nuclei                         0.001669
      dtype: float64)
```

```
In [34]: s.analyze_predictions('1f871bd9b0b3405680a2bce0c3b2b226', \
                                'pacman-cancertest')
```

```
Out[34]:
(True,
 {'job_name': 'b8e93f64e00f41819886cccbd2cad488',
  'job_id': 'f9f081a0-a729-11e9-8035-c3c7e048165a',
  'artifact_name': 'cbb36947ba5e4511846a80668207c77c'})
```

```
In [35]: s.wait_for_job('b8e93f64e00f41819886cccbd2cad488')
{'status': 'Running', 'starttime': '2019-07-15T12:57:14.029058', \
 'endtime': None, 'percent_complete': 0, 'job_type': 'AnalyzePredictions', \
 'loss': 0.4324471354484558, 'generations': 21, 'dataset_names': None, \
 'artifact_names': ['cbb36947ba5e4511846a80668207c77c'], \
 'model_name': '9f3ffa24162448158bdb1c0f3fe8c21e', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-15T12:57:14.029058', \
 'endtime': None, 'percent_complete': 0, 'job_type': 'AnalyzePredictions', \
 'loss': 0.4324471354484558, 'generations': 21, 'dataset_names': None, \
```



```
'artifact_names': ['cbb36947ba5e4511846a80668207c77c'], \
'model_name': '9f3ffa24162448158bdb1c0f3fe8c21e', 'job_error': ''}
{'status': 'Complete', 'starttime': '2019-07-15T12:57:14.029058', \
'endtime': '2019-07-15T13:05:26.715496', 'percent_complete': 100, \
'job_type': 'AnalyzePredictions', 'loss': 0.4324471354484558, 'generations': 21, \
'dataset_names': None, 'artifact_names': ['cbb36947ba5e4511846a80668207c77c'], \
'model_name': '9f3ffa24162448158bdb1c0f3fe8c21e', 'job_error': ''}
Out[35]: (True, 'Job completed')
```

```
In [36]: s.download_artifact('cbb36947ba5e4511846a80668207c77c')
```

```
Out[36]:
```

```
(True,
Code_shap  Clump Thickness_shap  Uniformity of Cell Size_shap  Uniformity of ... \
0         0.001568                0.029792                0.068253
1         0.000836                0.039068                0.052454
2         0.000584                0.039056                0.052201
3         0.002181                0.037539                0.052797
4        -0.001198                0.012781                0.124094
...
98        -0.001878                0.000495                0.131678
99        -0.000813                0.000495                0.141285
100        0.001568                0.029792                0.068253
101        0.001568                0.029792                0.068253

[102 rows x 13 columns])
```

```
In [39]: s.resume_training_model('1f871bd9b0b3405680a2bce0c3b2b226', \
'pacman-cancer', max_train_time='00:01')
```

```
Out[39]:
```

```
(True,
{'job_name': '30ba83c61814459f95b668a8316e647f',
'job_id': '66e3ef92-a63d-11e9-9792-a38b3282194d',
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226'})
```

```
In [40]: s.wait_for_job('30ba83c61814459f95b668a8316e647f')
```

```
{'status': 'Running', 'starttime': '2019-07-14T08:43:46.090825', 'endtime': None, \
'percent_complete': 0, 'job_type': 'UpdateModel', 'loss': 0.20505395531654358, \
'generations': 31, 'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:43:46.090825', 'endtime': None, \
'percent_complete': 13, 'job_type': 'UpdateModel', 'loss': 0.20505395531654358, \
'generations': 40, 'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:43:46.090825', 'endtime': None, \
```

```
'percent_complete': 35, 'job_type': 'UpdateModel', 'loss': 0.20505395531654358, \
'generations': 43, 'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:43:46.090825', 'endtime': None, \
'percent_complete': 61, 'job_type': 'UpdateModel', 'loss': 0.20505395531654358, \
'generations': 47, 'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:43:46.090825', 'endtime': None, \
'percent_complete': 95, 'job_type': 'UpdateModel', 'loss': 0.20505395531654358, \
'generations': 52, 'dataset_names': ['pacman-cancer'], 'artifact_names': None, \
'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', 'job_error': ''}
{'status': 'Complete', 'starttime': '2019-07-14T08:43:46.090825', 'endtime': \
'2019-07-14T08:46:07.389587', 'percent_complete': 100, 'job_type': 'UpdateModel', \
'loss': 0.20505395531654358, 'generations': 52, 'dataset_names': ['pacman-cancer'], \
'artifact_names': None, 'model_name': '1f871bd9b0b3405680a2bce0c3b2b226', \
'job_error': ''}
Out[40]: (True, 'Job completed')

In [41]: s.run_model('pacman-cancer', '1f871bd9b0b3405680a2bce0c3b2b226')
Out[41]:
(True,
 {'job_name': 'cc623240c5b1453eb73cdcdc93777f55',
  'job_id': 'c4380d18-a63d-11e9-85df-2337b425c294',
  'artifact_name': '48d74e4277944412ac032879fc23c5ba'})

In [45]: s.download_artifact('48d74e4277944412ac032879fc23c5ba')
Out[45]:
(True,
  Diagnosis  prob_BENIGN  prob_MALIGNANT
0      BENIGN      0.920420      0.079580
1  MALIGNANT      0.461758      0.538242
...
597     BENIGN      0.834559      0.165441
598     BENIGN      0.949016      0.050984

[599 rows x 3 columns])
```

## Unsupervised modeling example

```
---
In [47]: s.upload_dataset('sets/pulsars.csv', 'pacman-pulsars')
Out[47]: (True, {'dataset_name': 'pacman-pulsars'})
```

```
In [48]: s.analyze_data('pacman-pulsars')
Out[48]:
(True,
 {'job_name': '294ed354f3484b2ebebe658033284128',
  'job_id': '80193b9c-a63e-11e9-85df-fba3623db3bc',
  'artifact_name': 'b3d8dacf77fc409b9dd48030b2dda07b'})

In [49]: s.clean_data('pacman-pulsars')
Out[49]:
(True,
 {'job_name': '454f781b2a02403ea74d915a4b6b530c',
  'job_id': '8763baf8-a63e-11e9-900b-4335c8f0f324',
  'artifact_name': 'b9820a205bf140blae24bc6b1b133d2d',
  'artifact_id': '876560d8-a63e-11e9-900b-7f0b539a80a9'})

In [50]: s.create_model('pacman-pulsars', \
    fit_profile_name='b9820a205bf140blae24bc6b1b133d2d')
Out[50]:
(True,
 {'job_name': '2a9a1e55f8e34ddd828326ecee2b42f4',
  'job_id': '97a92592-a63e-11e9-a08f-cf415e11311a',
  'model_name': 'falb82cab28c46cdac3b44c8e8bc1265'})

In [51]: s.wait_for_job('2a9a1e55f8e34ddd828326ecee2b42f4')
{'status': 'Running', 'starttime': '2019-07-14T08:52:17.412985', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
 'dataset_names': ['pacman-pulsars'], 'artifact_names': None, \
 'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:52:17.412985', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
 'dataset_names': ['pacman-pulsars'], 'artifact_names': None, \
 'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
...
{'status': 'Complete', 'starttime': '2019-07-14T08:52:17.412985', \
 'endtime': '2019-07-14T08:53:53.736499', 'percent_complete': 100, \
 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
 'dataset_names': ['pacman-pulsars'], 'artifact_names': None, \
 'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
Out[51]: (True, 'Job completed')

In [53]: s.run_model('pacman-pulsars', 'falb82cab28c46cdac3b44c8e8bc1265')
Out[53]:
(True,
 {'job_name': 'c72ef79400014a3fb9e0a5821adf0826',
  'job_id': '0b58fb52-a63f-11e9-9f7b-53a24e4e1e2a',
```

```
'artifact_name': '05380df9e93c4650ab6f7e5e67e23f72'})

In [54]: s.wait_for_job('c72ef79400014a3fb9e0a5821adf0826')
{'status': 'Complete', 'starttime': '2019-07-14T08:55:31.501449', \
 'endtime': '2019-07-14T08:55:34.679054', 'percent_complete': 100, \
 'job_type': 'RunModel', 'loss': None, 'generations': 0, \
 'dataset_names': ['pacman-pulsars'], \
 'artifact_names': ['05380df9e93c4650ab6f7e5e67e23f72'], \
 'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
Out[54]: (True, 'Job completed')

In [55]: s.download_artifact('05380df9e93c4650ab6f7e5e67e23f72')
Out[55]:
(True,
 {'filename': '/var/folders/wc/w7ktf3392_s7c6t2djlhyb9/T/artifact-6ac2m9yp.csv'})

n [17]: s.analyze_model('b7d28ee423d4430fafa51a017be827ac')
Out[17]:
(True,
 {'job_name': 'b36800c1a47f4c559c231d155a12fd85',
  'job_id': '8c5dfd70-a8f5-11e9-88ca-173db83c1239',
  'artifact_name': 'a417260dfabc409a8204falceeae112f'})

In [18]: s.wait_for_job('b36800c1a47f4c559c231d155a12fd85')
{'status': 'Complete', 'starttime': '2019-07-17T19:46:58.691115', \
 'endtime': '2019-07-17T19:47:02.152927', 'percent_complete': 100, \
 'job_type': 'AnalyzeModel', 'loss': None, 'generations': 0, \
 'dataset_names': None, 'artifact_names': ['a417260dfabc409a8204falceeae112f'], \
 'model_name': 'b7d28ee423d4430fafa51a017be827ac', 'job_error': ''}
Out[18]: (True, 'Job completed')

In [19]: s.download_artifact('a417260dfabc409a8204falceeae112f')
Out[19]:
(True, kurt_dmsnr      0.0
      skew_dmsnr      0.0
      skew_profile    0.0
      kurt_profile    0.0
      class           0.0
      std_profile     0.0
      mean_dmsnr      0.0
      mean_profile    0.0
      std_dmsnr       0.0
      dtype: float64)

In [22]: s.upload_dataset('sets/pulsars_predict.csv', 'pulsars-test')\
```

```
# Need to trim original dataset to have fewer than 500 rows.
Out[22]: (True, {'dataset_name': 'pulsars-test'})

In [23]: s.clean_data('pulsars-test', model_name='b7d28ee423d4430fafa51a017be827ac')
Out[23]:
(True,
 {'job_name': '8324da8dea734455a73daeddd3e0b5f',
  'job_id': 'fc2a4974-a8f5-11e9-9074-7fa762e40db7',
  'profile_name': 'bccde471e8514ef59b0b106fa7af6be9',
  'profile_id': 'fc2c0e76-a8f5-11e9-9074-13d39d00d68d'})

In [24]: s.analyze_predictions ('b7d28ee423d4430fafa51a017be827ac', 'pulsars-test')
Out[24]:
(True,
 {'job_name': 'def26ef5be3a4d5b822542fd125c8600',
  'job_id': '12995024-a8f6-11e9-89b8-cf7654542d20',
  'artifact_name': 'd726a45761a1431d8bbe381c4f4f2782'})

In [25]: s.wait_for_job('def26ef5be3a4d5b822542fd125c8600')
{'status': 'Complete', 'starttime': '2019-07-17T19:50:43.895873', \
 'endtime': '2019-07-17T19:50:49.098101', 'percent_complete': 100, \
 'job_type': 'AnalyzePredictions', 'loss': None, 'generations': 0, \
 'dataset_names': None, 'artifact_names': ['d726a45761a1431d8bbe381c4f4f2782'], \
 'model_name': 'b7d28ee423d4430fafa51a017be827ac', 'job_error': ''}
Out[25]: (True, 'Job completed')

In [26]: s.download_artifact('d726a45761a1431d8bbe381c4f4f2782')
Out[26]:
(True,
  std_dmsnr_shap  mean_dmsnr_shap  kurt_dmsnr_shap  mean_profile_shap  ... \
0                0.0              0.0              0.0              0.0
1                0.0              0.0              0.0              0.0
2                0.0              0.0              0.0              0.0
3                0.0              0.0              0.0              0.0
4                0.0              0.0              0.0              0.0
5                0.0              0.0              0.0              0.0
6                0.0              0.0              0.0              0.0
7                0.0              0.0              0.0              0.0
8                0.0              0.0              0.0              0.0
[9 rows x 12 columns])
```

## NBM modeling example

```
---
In [13]: s.upload_dataset('sets/SmokyT025_full_raw.csv', 'pacman-smoky')
Out[13]: (True, {'dataset_name': 'pacman-smoky'})

In [14]: s.analyze_data('pacman-smoky')
Out[14]:
(True,
 {'job_name': 'af7d01c94e774b3aa5648bf675cf990f',
  'job_id': 'fc4e1f30-a895-11e9-be40-8b36979e9d84',
  'artifact_name': 'c267aa0daa43407fbb59f44c3644d2b8'})

In [15]: s.clean_data('pacman-smoky', index='timestamp')
Out[15]:
(True,
 {'job_name': '1950b29aef9a42afb1eb17125cea38a5',
  'job_id': '567ddbe4-a896-11e9-b2c6-c3499b5ebff0',
  'profile_name': '1700ee4ecb854ba8977a06f85efd1644',
  'profile_id': '567f38e0-a896-11e9-b2c6-770cfb81b384'})

In [18]: s.create_model('pacman-smoky', \
    fit_profile_name='1700ee4ecb854ba8977a06f85efd1644', \
    max_train_time='00:02', recurrent=False, failure_dates=['08/23/2015'], nbm=True)
Out[18]:
(True,
 {'job_name': '23ce4b284df14f0ca14c0a49f63806fc',
  'job_id': '8b91e172-a896-11e9-be40-df999689405b',
  'model_name': '7e080e51cc15408492d6136e07df2a63'})

In [19]: s.wait_for_job('23ce4b284df14f0ca14c0a49f63806fc')
{'status': 'Running', 'starttime': '2019-07-17T08:26:55.165137', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
 'dataset_names': ['pacman-smoky'], 'artifact_names': None, \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-17T08:26:55.165137', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
 'dataset_names': ['pacman-smoky'], 'artifact_names': None, \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
...
{'status': 'Complete', 'starttime': '2019-07-17T08:26:55.165137', \
 'endtime': '2019-07-17T08:29:11.943704', 'percent_complete': 100, \
 'job_type': 'TrainModel', 'loss': 0.054839795631057814, 'generations': 1, \
 'dataset_names': ['pacman-smoky'], 'artifact_names': None, \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
Out[19]: (True, 'Job completed')
```

```
In [21]: s.run_model('pacman-smoky', '7e080e51cc15408492d6136e07df2a63')
Out[21]:
(True,
 {'job_name': '268b0fb872054ec58c0344053625e69c',
  'job_id': '1351b15a-a897-11e9-a06a-2b396d284046',
  'artifact_name': '4fd95f6ec4c442e586b941f7e2656dbf'})
```

```
In [24]: s.wait_for_job('268b0fb872054ec58c0344053625e69c')
{'status': 'Complete', 'starttime': '2019-07-17T08:30:42.913437', \
 'endtime': '2019-07-17T08:31:08.226901', 'percent_complete': 100, \
 'job_type': 'RunModel', 'loss': 0.054839795631057814, 'generations': 1, \
 'dataset_names': ['pacman-smoky'], \
 'artifact_names': ['4fd95f6ec4c442e586b941f7e2656dbf'], \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
Out[24]: (True, 'Job completed')
```

```
In [25]: s.download_artifact('4fd95f6ec4c442e586b941f7e2656dbf')
Out[25]:
```

```
(True,
      Risk
0      0.000000
1      0.000000
2      0.000000
3      0.000000
4      0.000000
...
51401  3.175640
51402  3.153954
51403  3.131895
51404  3.109017
51405  3.087970

[51406 rows x 1 columns])
```

```
In [27]: s.upload_dataset('sets/SmokyT025_test_raw.csv', 'pacman-smokytest')
Out[27]: (True, {'dataset_name': 'pacman-smokytest'})
```

```
In [28]: s.clean_data('pacman-smokytest', \
  model_name='7e080e51cc15408492d6136e07df2a63')
Out[28]:
(True,
 {'job_name': '229b24bfc46d4601aef1ce8b017e4ff7',
  'job_id': 'bd369cca-a898-11e9-8ea7-2bc9c8ab84c4',
  'profile_name': 'b4f5cc08f980442f983a8137a756dc79',
  'profile_id': 'bd38ac40-a898-11e9-8ea7-9fb23d6a2658'})
```

```
In [29]: s.run_model('pacman-smokytest', '7e080e51cc15408492d6136e07df2a63')
```

```
Out[29]:
```

```
(True,
 {'job_name': '35d9cd3b4a3b45a99eb8dc089ef9b152',
  'job_id': 'c7d0d5ce-a898-11e9-bfef-379c562f822e',
  'artifact_name': 'f750090766f14e82b3713e3f3ef9bcb5'})
```

```
In [30]: s.wait_for_job('35d9cd3b4a3b45a99eb8dc089ef9b152')
```

```
{'status': 'Complete', 'starttime': '2019-07-17T08:42:55.232948', \
 'endtime': '2019-07-17T08:43:01.540698', 'percent_complete': 100, \
 'job_type': 'RunModel', 'loss': 0.054839795631057814, 'generations': 1, \
 'dataset_names': ['pacman-smokytest'], \
 'artifact_names': ['f750090766f14e82b3713e3f3ef9bcb5'], \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
```

```
Out[30]: (True, 'Job completed')
```

```
In [31]: s.download_artifact('f750090766f14e82b3713e3f3ef9bcb5')
```

```
Out[31]:
```

```
(True,
      Risk
0      0.000000
1      0.000000
2      0.000000
3      0.000000
```

```
...
```

```
17276  3.121538
17277  3.098760
17278  3.077858
```

```
[17279 rows x 1 columns])
```

```
In [32]: s.analyze_model('7e080e51cc15408492d6136e07df2a63')
```

```
Out[32]:
```

```
(True,
 {'job_name': 'e54bfd3d620d44b083f5ea65dda12aec',
  'job_id': '605a6300-a899-11e9-bfef-6fedf02afe89',
  'artifact_name': 'd8ea781de54c4303ad49e17f0d208db3'})
```

```
In [33]: s.wait_for_job('e54bfd3d620d44b083f5ea65dda12aec')
```

```
{'status': 'Running', 'starttime': '2019-07-17T08:47:11.149655', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'AnalyzeModel', 'loss': 0.054839795631057814, \
 'generations': 1, 'dataset_names': None, \
 'artifact_names': ['d8ea781de54c4303ad49e17f0d208db3'], \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
{'status': 'Complete', 'starttime': '2019-07-17T08:47:11.149655', \
 'endtime': '2019-07-17T08:47:27.795439', 'percent_complete': 100, \
```



```
'job_type': 'AnalyzeModel', 'loss': 0.054839795631057814, 'generations': 1,\n  'dataset_names': None, 'artifact_names': ['d8ea781de54c4303ad49e17f0d208db3'],\n  'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}\nOut[33]: (True, 'Job completed')
```

```
In [34]: s.download_artifact('d8ea781de54c4303ad49e17f0d208db3')
```

```
Out[34]:
```

```
(True, ICA                                0.290290\n  PSETKW                                0.095161\n  GENTMPSLIPDEGC                        0.075301\n  AMBTMPDEGC                           0.062500\n  NACTMPDEGC                           0.040816\n  XFMRTMPPHCDEGC                       0.034540\n  GENTMPPHADEGC                        0.032311\n  YAWDIRDEG                           0.031473\n  GENTMPPHCDEGC                       0.027232\n  WDRELDEG                             0.026735\n  HYDRPRESBAR                          0.026336\n  FREQHZ                               0.022709\n  XFMRTMPPHADEGC                      0.020440\n  GENTMPPHBDEGC                       0.018139\n  BRGTMPGENNDEDEGC                    0.017267\n  WD10MDEG                             0.016984\n  VANV                                 0.015967\n  PF                                   0.012871\n  TMPCTRLTOPDEGC                      0.012038\n  IBA                                  0.011195\n  TMPSPINNERDEGC                     0.011191\n  BLDANGDEG                           0.010891\n  WS10MMPS                             0.010032\n  VBNV                                 0.009880\n  VCNV                                 0.008443\n  XFMRTMPPHBDEGC                     0.007716\n  OILTMPGBXDEGC                       0.007068\n  GENSPDRPM                           0.006877\n  TMPCTRLHUBDEGC                     0.006240\n  PEXPKW                              0.005889\n  WSMPS                               0.005433\n  BRGTMPGBXADEGC                     0.004322\n  QKVAR                               0.004213\n  HYDRTMPDEGC                         0.003860\n  P10MACTKW                           0.003125\n  RTRSPDRPM                           0.002313\n  IAA                                 0.002204\n  dtype: float64)
```

```
In [39]: s.upload_dataset('sets/SmokyT025_test_small.csv', 'pacman-smokytestsmall')
Out[39]: (True, {'dataset_name': 'pacman-smokytestsmall'})
```

```
In [40]: s.clean_data('pacman-smokytestsmall', \
    model_name='7e080e51cc15408492d6136e07df2a63')
Out[40]:
(True,
 {'job_name': 'a9a68568b4f44fe19661f0b5d4e8822d',
  'job_id': 'f68898c4-a899-11e9-9e51-2b93b6669bbd',
  'profile_name': '5c90c01159684d6491d956f035651c6f',
  'profile_id': 'f68a2a5e-a899-11e9-9e51-5bba6c3dc2d1'})
```

```
In [41]: s.analyze_predictions ('7e080e51cc15408492d6136e07df2a63', \
    'pacman-smokytestsmall')
Out[41]:
(True,
 {'job_name': '04e5d614672a4e598276bd19a06f7df9',
  'job_id': 'felc8906-a899-11e9-8ea7-cfc85b8e9384',
  'artifact_name': '96fd4aa1b57043d69b658e72071c35c9'})
```

```
In [42]: s.wait_for_job('04e5d614672a4e598276bd19a06f7df9')
{'status': 'Running', 'starttime': '2019-07-17T08:51:35.824573', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'AnalyzePredictions', \
 'loss': 0.054839795631057814, 'generations': 1, 'dataset_names': None, \
 'artifact_names': ['96fd4aa1b57043d69b658e72071c35c9'], \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-17T08:51:35.824573', 'endtime': None, \
 'percent_complete': 0, 'job_type': 'AnalyzePredictions', \
 'loss': 0.054839795631057814, 'generations': 1, 'dataset_names': None, \
 'artifact_names': ['96fd4aa1b57043d69b658e72071c35c9'], \
 'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
...In [47]: s.upload_dataset('sets/pulsars.csv', 'pacman-pulsars')
Out[47]: (True, {'dataset_name': 'pacman-pulsars'})
```

```
In [48]: s.analyze_data('pacman-pulsars')
Out[48]:
(True,
 {'job_name': '294ed354f3484b2ebebe658033284128',
  'job_id': '80193b9c-a63e-11e9-85df-fba3623db3bc',
  'artifact_name': 'b3d8dacf77fc409b9dd48030b2dda07b'})
```

```
In [49]: s.clean_data('pacman-pulsars')
Out[49]:
(True,
 {'job_name': '454f781b2a02403ea74d915a4b6b530c',
```

```
'job_id': '8763baf8-a63e-11e9-900b-4335c8f0f324',
'artifact_name': 'b9820a205bf140b1ae24bc6b1b133d2d',
'artifact_id': '876560d8-a63e-11e9-900b-7f0b539a80a9'})

In [50]: s.create_model('pacman-pulsars', \
    fit_profile_name='b9820a205bf140b1ae24bc6b1b133d2d')
Out[50]:
(True,
 {'job_name': '2a9ale55f8e34ddd828326ecee2b42f4',
  'job_id': '97a92592-a63e-11e9-a08f-cf415e11311a',
  'model_name': 'falb82cab28c46cdac3b44c8e8bc1265'})

In [51]: s.wait_for_job('2a9ale55f8e34ddd828326ecee2b42f4')
{'status': 'Running', 'starttime': '2019-07-14T08:52:17.412985', 'endtime': None, \
'percent_complete': 0, 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
'dataset_names': ['pacman-pulsars'], 'artifact_names': None, \
'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
{'status': 'Running', 'starttime': '2019-07-14T08:52:17.412985', 'endtime': None, \
'percent_complete': 0, 'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
'dataset_names': ['pacman-pulsars'], 'artifact_names': None, \
'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
....
{'status': 'Complete', 'starttime': '2019-07-14T08:52:17.412985', \
'endtime': '2019-07-14T08:53:53.736499', 'percent_complete': 100, \
'job_type': 'TrainModel', 'loss': None, 'generations': 0, \
'dataset_names': ['pacman-pulsars'], 'artifact_names': None, \
'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
Out[51]: (True, 'Job completed')

In [53]: s.run_model('pacman-pulsars', 'falb82cab28c46cdac3b44c8e8bc1265')
Out[53]:
(True,
 {'job_name': 'c72ef79400014a3fb9e0a5821adf0826',
  'job_id': '0b58fb52-a63f-11e9-9f7b-53a24e4e1e2a',
  'artifact_name': '05380df9e93c4650ab6f7e5e67e23f72'})

In [54]: s.wait_for_job('c72ef79400014a3fb9e0a5821adf0826')
{'status': 'Complete', 'starttime': '2019-07-14T08:55:31.501449', \
'endtime': '2019-07-14T08:55:34.679054', 'percent_complete': 100, \
'job_type': 'RunModel', 'loss': None, 'generations': 0, \
'dataset_names': ['pacman-pulsars'], \
'artifact_names': ['05380df9e93c4650ab6f7e5e67e23f72'], \
'model_name': 'falb82cab28c46cdac3b44c8e8bc1265', 'job_error': ''}
Out[54]: (True, 'Job completed')
```

```
In [55]: s.download_artifact('05380df9e93c4650ab6f7e5e67e23f72')
Out[55]:
(True,
 {'filename': '/var/folders/wc/w7ktf3_h8br6t2djlhyb9/T/artifact-6ac2m9yp.csv'})

In [17]: s.analyze_model('b7d28ee423d4430fafa51a017be827ac')
Out[17]:
(True,
 {'job_name': 'b36800c1a47f4c559c231d155a12fd85',
  'job_id': '8c5dfd70-a8f5-11e9-88ca-173db83c1239',
  'artifact_name': 'a417260dfabc409a8204falceeae112f'})

In [18]: s.wait_for_job('b36800c1a47f4c559c231d155a12fd85')
{'status': 'Complete', 'starttime': '2019-07-17T19:46:58.691115', \
 'endtime': '2019-07-17T19:47:02.152927', 'percent_complete': 100, \
 'job_type': 'AnalyzeModel', 'loss': None, 'generations': 0, \
 'dataset_names': None, 'artifact_names': ['a417260dfabc409a8204falceeae112f'], \
 'model_name': 'b7d28ee423d4430fafa51a017be827ac', 'job_error': ''}
Out[18]: (True, 'Job completed')

In [19]: s.download_artifact('a417260dfabc409a8204falceeae112f')
Out[19]:
(True, kurt_dmsnr      0.0
      skew_dmsnr      0.0
      skew_profile     0.0
      kurt_profile     0.0
      class           0.0
      std_profile     0.0
      mean_dmsnr      0.0
      mean_profile     0.0
      std_dmsnr       0.0
      dtype: float64)

In [22]: s.upload_dataset('sets/pulsars_predict.csv', 'pulsars-test') \
# Need to trim original dataset to have fewer than 500 rows.
Out[22]: (True, {'dataset_name': 'pulsars-test'})

In [23]: s.clean_data('pulsars-test', model_name='b7d28ee423d4430fafa51a017be827ac')
Out[23]:
(True,
 {'job_name': '8324da8dea734455a73daeeddd3e0b5f',
  'job_id': 'fc2a4974-a8f5-11e9-9074-7fa762e40db7',
  'profile_name': 'bccde471e8514ef59b0b106fa7af6be9',
  'profile_id': 'fc2c0e76-a8f5-11e9-9074-13d39d00d68d'})
```

```
In [24]: s.analyze_predictions ('b7d28ee423d4430fafa51a017be827ac', \
'pulsars-test')
Out[24]:
(True,
 {'job_name': 'def26ef5be3a4d5b822542fd125c8600',
  'job_id': '12995024-a8f6-11e9-89b8-cf7654542d20',
  'artifact_name': 'd726a45761a1431d8bbe381c4f4f2782'})

In [25]: s.wait_for_job('def26ef5be3a4d5b822542fd125c8600')
{'status': 'Complete', 'starttime': '2019-07-17T19:50:43.895873', \
'endtime': '2019-07-17T19:50:49.098101', 'percent_complete': 100, \
'job_type': 'AnalyzePredictions', 'loss': None, 'generations': 0, \
'dataset_names': None, 'artifact_names': ['d726a45761a1431d8bbe381c4f4f2782'], \
'model_name': 'b7d28ee423d4430fafa51a017be827ac', 'job_error': ''}
Out[25]: (True, 'Job completed')
In [26]: s.download_artifact('d726a45761a1431d8bbe381c4f4f2782')
Out[26]:
(True,
      std_dmsnr_shap  mean_dmsnr_shap  kurt_dmsnr_shap  mean_profile_shap  ... \
0                0.0                0.0                0.0                0.0
1                0.0                0.0                0.0                0.0
2                0.0                0.0                0.0                0.0
3                0.0                0.0                0.0                0.0
4                0.0                0.0                0.0                0.0
5                0.0                0.0                0.0                0.0
6                0.0                0.0                0.0                0.0
7                0.0                0.0                0.0                0.0
8                0.0                0.0                0.0                0.0
[9 rows x 12 columns])

In [27]:
{'status': 'Complete', 'starttime': '2019-07-17T08:51:35.824573', \
'endtime': '2019-07-17T08:55:05.619098', 'percent_complete': 100, \
'job_type': 'AnalyzePredictions', 'loss': 0.054839795631057814, \
'generations': 1, 'dataset_names': None, \
'artifact_names': ['96fd4a1b57043d69b658e72071c35c9'], \
'model_name': '7e080e51cc15408492d6136e07df2a63', 'job_error': ''}
Out[42]: (True, 'Job completed')

In [43]: s.download_artifact('96fd4a1b57043d69b658e72071c35c9')
Out[43]:
(True,
      GENSPDRPM_shap  VANV_shap  PSETKW_shap  P10MACTKW_shap  ... \
0          20.060011    5.785717    0.000000    -1.762059
1          -1.002102   -4.857683   -1.833142    0.000000
```

```

2          0.641536    0.015167    0.000000    0.000000
3          0.000000   -1.827971    0.000000    0.000000
4         -5.824179    6.567310   10.847957   -5.231445
5        -16.634360    0.000000   -8.437045   -9.929700
..          ...          ...          ...          ...

396        -1.932885   -1.780289   -1.361495    0.000000
397         5.469176   -8.030168   38.908720   -1.336821
398        -0.598940   -8.100026   57.731217   17.159244

[399 rows x 39 columns])

```

## Contact Support

The following methods enable you to research issues, create a support ticket, or contact SparkCognition:

- Use the [Darwin support portal](#) - Read Frequently Asked Questions (FAQ), download documentation, or log your issue.
- **Email Support** - Send email to [darwin\\_support@sparkcognition.com](mailto:darwin_support@sparkcognition.com).
- **Phone Support** - The SparkCognition support line is +1-512-400-2001.

## Revision Table

Version	Date	Notes
v 1.6	16-Jan-2019	<p>New endpoints:</p> <ul style="list-style-type: none"> <li>• DarwinSdk.display_population</li> <li>• DarwinSdk.delete_all_artifacts</li> </ul> <p>Updated endpoints:</p> <ul style="list-style-type: none"> <li>• DarwinSdk.analyze_data</li> <li>• DarwinSdk.download_artifact</li> <li>• DarwinSdk.create_model</li> <li>• DarwinSdk.clean_data</li> </ul>
v 1.6.1	06-Feb-2019	Fixed issues only. See Release Notes. Added on-prem installation notes.
v 1.6.2	22-Mar-2019	<p>New endpoints:</p> <ul style="list-style-type: none"> <li>• DarwinSdk.get_info</li> <li>• DarwinSdk.help</li> </ul> <p>Added Setup Users section.</p> <p>On-prem SDK users need to add port 8000 to the URL.</p>

---

Version	Date	Notes
v 1.43.0	16-May-2019	<p>Major change to version number to facilitate independent releases of the API</p> <p>New endpoints:</p> <ul style="list-style-type: none"><li>• DarwinSdk.disable_ssl_cert_check</li><li>• DarwinSdk.enable_ssl_cert_check</li><li>• DarwinSdk.get_sdk_version</li></ul> <p>Updated endpoints:</p> <ul style="list-style-type: none"><li>• DarwinSdk.create_model</li></ul>
v 1.44.0	22-Jul-2019	<p>Updated modeling examples for Supervised, Unsupervised, and NBM</p> <p>Added Analyze Training Data step to basic workflow</p> <p>Updated endpoints:</p> <ul style="list-style-type: none"><li>• DarwinSdk.create_model: Added forecast_horizon, class_weights, cv_kfold, fit_profile_name</li></ul>

---