



SparkCognition[™] Darwin[™] Release Notes

v 1.3 - 05.23.2018

This document contains copyrighted and proprietary information of SparkCognition and is protected by United States copyright laws and international treaty provisions. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning or otherwise, except as permitted under such laws or with the prior written permission of SparkCognition Inc.

SparkCognition^{$^{\text{IM}}$}, the sparkcognition logo, Darwin^{$^{\text{IM}}$}, DeepArmor^{$^{\text{IM}}$}, DeepNLP^{$^{\text{IM}}$}, MindFabric^{$^{\text{IM}}$}, SparkSecure^{$^{\text{IM}}$} and SparkPredict^{$^{\text{IM}}$}, are trademarks of SparkCognition, Inc. and/or its affiliates and may not be used without written permission. All other trademarks are the property of their respective owners.

©SparkCognition, Inc. 2017-2018. All rights reserved.

Darwin Release Notes v 1.3

Darwin release 1.3 has incorporated customer feedback to introduce new approaches to both supervised and unsupervised model generation as well as better explainable AI through the introduction of an *analyze_predictions* endpoint and modification of the *analyze_model* endpoint. The following changes are completed and rolled into the Darwin release 1.3 for immediate use:

New Features

New supervised approach

- · Grammar-based approach for building deeper neural networks
- Genetic optimized DNNs with other tree-based models

New unsupervised approach

- Leverage a neural-network-based clustering mechanism that can scale to significantly larger data
- Automated cluster number detection

Change to analyze_model

• *analyze_model* now outputs a generalized feature importance for the model.



• If the model is a multi-class model or a clustering model, *analyze_model* can also output a feature importance for each independent cluster or class.

New route: analyze_predictions

• Users can now get individualized feature importance per data sample to better explain why certain predictions were made.

Ability to reset password

- Email address is required for user registration
- Existing users can add an email address via the auth_set_email route.

Fixed Issues

- You can no longer create a new model with the same name as an existing model. Model names are also now case-sensitive.
- Fixed issue where Target Columns containing non-alphabetic characters can cause problems in API calls.
- Added error message for testing files that do not have header information.

Known Issues

- Darwin will split the training set into a train and validation set using an 80/20 split:
 - For classification problems, the split will be created using stratified shuffling.
 - For regression problems, the split will be created using random shuffling.
 - For problems with a timestamp (regression or classification problems), no reordering will be done and the last 20% of the input data will be used as validation data. So if sparse time-series data is used for modeling and the important points for predictions are clustered densely together, there is the potential that the resulting model may only train on non-useful data. If this issue is occurring, try removing the time stamp from the data set.
- Models created from earlier versions of Darwin are incompatible with version 1.3. These models need to be re-created.
- If a user does not specify a number of clusters for unsupervised, Darwin is likely to select a smaller number to minimize separation space. User should set *n_clusters* to specify a specific number of clusters.
- Data submitted to *run_model* must have the same number of columns and column headers as data submitted to *create_model*, otherwise an error message is returned.

Note: Affects create_model, run_model.

• Setting *recurrent=true* does not work for unsupervised.

Note: Affects create_model.

- Any created models can only specify either zero or a single Target column.
- Because Darwin cannot one hot encode categorical columns with more than *max_unique_values* in training and test sets, these columns are dropped in test and training sets.



- Darwin only drops duplicated columns in data sets with less than 5000 rows.
- When using *feature_eng*, the percent complete reads 0% until the automated windowing, preprocessing, and feature engineering is complete.

Notes:

- Depending on data set size, this process can require substantial time to complete.
- Affects create_model.
- Any dataset can only have a single (one) date time column or be indexed by date/time, otherwise an error message is returned.

Note: Affects create_model, analyze_data.

• max_int_uniques keyword parameter must be a natural number, otherwise an error message is returned.

Note: Affects create_model, analyze_data.

• max_unique_values keyword parameter must be a natural number, otherwise an error message is returned.

Note: Affects create_model, analyze_data.

- window_len parameter (optional) to create_model must:
 - 1. be a natural number,
 - 2. be smaller than the size of any training set, and
 - 3. be smaller than the size of any test set, otherwise an error message is returned.

Note: Affects create_model, analyze_data.

• *feature_select* parameter must be a real number in [0,1], otherwise an error message is returned. **Note**: Affects *create_model*, *analyze_data*.

Contact Support

The following methods enable you to research issues, create a support ticket, or contact SparkCognition:

- Use the Darwin support portal Read Frequently Asked Questions (FAQ), download documentation, or log your issue.
- **Email Support** Send email to support@darwinamb.zendesk.com.
- **Phone Support** The SparkCognition support line is +1-512-956-5576.

Revision Table

Version	Date
v 1.0	02.05.2018
v 1.1	02.22.2018
v 1.2	03.29.2018
v 1.3	05.23.2018