YETI PAW v1.2 — Lateral Raise Handle — Bill of Materials

Designed by **Schnibbz** · YETI STRENGTH

What it costs

	One Yeti Paw	A pair (both arms)
Parts cost, pro-rated — what the parts in one unit cost; packs split across the units they build; no tax; raw handles	**≈ $72**	**≈ $144**
Cash to buy everything for a pair — whole packs, no tax, plenty of hardware and filament left over	—	**≈ $217**
What my first batch actually cost — 4 units, real receipts, incl. tax and anodized handles	**$86.22**	**$172.44**

How the first batch got from ≈ $72 of parts per unit to $86.22: sales tax, anodized handles instead of raw ($58 vs $48 a pair), and the spare bearings, nuts, sleeves and ~600 g of filament left over from whole packs. Prices are approximate, checked 2026-10-13, and will drift.

Assumes free Rogue shipping: Rogue ships free once your cart has 3 ship-free items, so add the handles to a bigger Rogue order (or a friend's). Other shipping is included in the parts cost: Bolt Depot economy $12.12 and aluminumspacers.com $10 flat, both split across a pair. Amazon is free over $35.

Quantities below are **per Yeti Paw** (one handle). Double them for a pair.

Amazon

Amazon links are affiliate links (I earn a small commission at no extra cost to you). Prices change, so they aren't listed.

Part	Qty	Pack	Link
Handle bearing FR8-2RS flanged ball bearing, 1/2" bore × 1-1/8" OD × 5/16"	2	10	B0FKH4Z7K2
Yoke bearing 6000-2RS ball bearing, 10 × 26 × 8 mm	2	10	B0DTKDKSTF
Yoke compression sleeve SF-1 1020 bushing, 10 × 12 × 20 mm	2	10	B07FPH25F3
Carabiner eye sleeve uxcell flanged bronze sleeve, ID 20 × OD 23 × 10 long, Ø30 flange (size **20x23x10x30mm**; 12 mm long also fits)	1	20	B0GWDG85L3
Yoke lock nut M8 × 1.25 nylon-insert, DIN 985, black oxide	2	25	B083Z2GCRR
Yoke washer M8 flat washer, 8 × 12 × 0.8 mm, 304 stainless	2	20	B0DP6Y9MQP
Wrist pad CONCAVE foam roller pad, 2.95" OD × 5.71", 0.87" bore — trim evenly from both ends to 132 mm	1	2	B094D5ZJXK

Threadlocker Loctite 243 blue, 6 mL — handle screws only	a drop	1	B004L439FE
Body filament ELEGOO PETG-CF, black, 1.75 mm	≈ 350 g	1 kg	B0F37YCK6K
Logo filament SUNLU PETG, white, 1.75 mm	≈ 18 g	1 kg	B085TH48N6

Bolt Depot

Screws and bolts are black oxide; the pad washer is black-oxide stainless. Economy shipping was **$12.12** on a real order.

Part	Qty	Unit price	Link
Handle screw Socket button head 1/2"-13 × 1-1/4", alloy steel	2	$0.87	#13198
Pad screw Socket button head 1/2"-13 × 2", FULL THREAD, alloy steel	2	$1.38	#13201
Pad washer Flat washer 1/2", 18-8 stainless, black oxide, 1-1/4" OD	2	$0.43	#22033
Yoke pivot Shoulder bolt ISO 7379, Ø10 × 25 mm shoulder, M8 × 1.25, class 12.9	2	$2.34	#14248

Parts **$10.04** per Yeti Paw; a pair is $20.08 + $12.12 shipping = **$32.20**.

aluminumspacers.com

$10 flat shipping. Order by phone; their web checkout was broken as of Oct 2026.

Part	Qty	Unit price	Link
Handle spacer Round spacer, 6061-T6, 0.509" ID × 0.625" OD × 0.188"	4	$1.31 (25+ @ $0.82)	AS62-22-12

A pair is 8 × $1.31 + $10 = **$20.48**.

Rogue Fitness

Part	Qty	Unit price	Link
Handle Rogue H-5, 45 mm straight × 5", 1/2"-13 both ends — sold as a pair	1	$24 ($48 / pair, raw)	Rogue H-5

One pair of handles builds a pair of Yeti Paws. **Shipping is free once the cart has 3 ship-free items**; the prices here assume you get that.

Printed parts

Bambu Studio projects, one per print: side plates (both on one bed), yoke and pad dowel. STL files and settings for any other printer: `stl/` and `PRINT-SETTINGS.md`.

Part	Qty	Material	Print time

Side plates, left + right (PAW logo), one bed	1 pair	PETG-CF + white PETG logo · 6 walls, 40 % gyroid	≈ 7.7 h
Carabiner yoke (YETI STRENGTH)	1	PETG-CF + white PETG lettering · 100 % infill	≈ 2.8 h
Pad dowel	1	PETG-CF · 100 % infill · PLA for the support interface only (about 1 g)	≈ 3.9 h

Not included

A steel screw-gate carabiner, rated 25 kN or more. Its bar must pass through a 20 mm hole.

Tools

- Hex keys: 5 mm and 5/16".
- 13 mm wrench.
- Inch-pound torque driver: 35 in-lb for the yoke nylocks.
- Foot-pound torque wrench: about 10 ft-lb, never more than 15, for the handle screws.
- Ø12 mm drill bit, turned by hand, to clean the yoke pivot bores.
- Bench vise or clamp, to press in the bearings and sleeves.
- Fine sandpaper, a deburring tool (for the spacer chamfer) and a little wax (for the dowel threads).
- Sharp knife or fine saw, to trim the pad to 132 mm.
- Light oil for the black-oxide hardware.

Not professionally engineered. The Yeti Paw was designed by a hobbyist, not by a licensed or qualified engineer. Any strength or safety-factor figures are amateur estimates from a simplified computer model. They are not a certified load rating and come with no guarantee.

Build and use at your own risk. You are responsible for printing, assembling, inspecting and using this device. Print quality, materials, settings and assembly vary, so your parts may be weaker than described. Inspect every part before each use, and stop using it at the first sign of cracking, play or damage. The designer accepts no liability for injury or damage arising from building or using it.

Disclosure: The Amazon links on this page are affiliate links. If you buy through them, I earn a small commission on the sale, at no extra cost to you. As an Amazon Associate I earn from qualifying purchases.