

ACT 02 - Permisos de usuarios

1. Comprobar permisos de ac901local

```
SHOW GRANTS FOR 'ac901local'@'localhost';
```

2. Operaciones sobre ac901local

2.1 Comprobar sus permisos

```
SHOW GRANTS FOR 'ac901local'@'localhost';
```

2.2 Asignar permisos sobre ayuntamiento.usuario

```
GRANT SELECT, INSERT, DELETE ON ayuntamiento.usuario TO 'ac901local'@'localhost';
```

2.3 Comprobar de nuevo los permisos

```
SHOW GRANTS FOR 'ac901local'@'localhost';
```

2.4 Insertar un nuevo usuario

```
INSERT INTO ayuntamiento.usuario (nombre) VALUES ('Test');
```

2.5 Intentar modificar el nuevo usuario

```
UPDATE ayuntamiento.usuario SET nombre='Modificado' WHERE nombre='Test';
```

2.6 Eliminar el usuario insertado

```
DELETE FROM ayuntamiento.usuario WHERE nombre='Test';
```

3. Crear usuario ac902lectura

```
CREATE USER 'ac902lectura'@'%' IDENTIFIED BY 's8a';  
GRANT SELECT ON ayuntamiento.* TO 'ac902lectura'@'%';  
FLUSH PRIVILEGES;
```

4. Crear usuario ac903todo (administrador)

```
CREATE USER 'ac903todo'@'%' IDENTIFIED BY 's8a';  
GRANT ALL PRIVILEGES ON *.* TO 'ac903todo'@'%' WITH GRANT OPTION;  
FLUSH PRIVILEGES;
```

5. Eliminar ac901local y ac902lectura como ac903todo

```
DROP USER 'ac901local'@'localhost';  
DROP USER 'ac902lectura'@'%';  
FLUSH PRIVILEGES;
```

6. Usuarios existentes en el sistema

```
SELECT user, host FROM mysql.user;
```

```
XAMPP for Windows - mysql
+-----+
| root   | 127.0.0.1 |
| root   | ::1       |
| ac901local | localhost |
| pma    | localhost |
| root   | localhost |
+-----+
5 rows in set (0.001 sec)

MariaDB [(none)]> SHOW GRANTS FOR 'ac901local'@'localhost';
+-----+
| Grants for ac901local@localhost |
+-----+
| GRANT USAGE ON *.* TO 'ac901local'@'localhost' IDENTIFIED BY PASSWORD '*3D3F19386045EE9D580D9527B41DF893A95325B7' |
+-----+
1 row in set (0.000 sec)

MariaDB [(none)]> GRANT SELECT, INSERT, DELETE ON ayuntamiento.usuario TO 'ac901local'@'localhost';
Query OK, 0 rows affected (0.002 sec)

MariaDB [(none)]> SHOW GRANTS FOR 'ac901local'@'localhost';
+-----+
| Grants for ac901local@localhost |
+-----+
| GRANT USAGE ON *.* TO 'ac901local'@'localhost' IDENTIFIED BY PASSWORD '*3D3F19386045EE9D580D9527B41DF893A95325B7' |
| GRANT SELECT, INSERT, DELETE ON `ayuntamiento`.`usuario` TO 'ac901local'@'localhost' |
+-----+
2 rows in set (0.000 sec)

MariaDB [(none)]>

MariaDB [ayuntamiento]> INSERT INTO ayuntamiento.usuario (nombre) VALUES ('Test');
Query OK, 1 row affected (0.003 sec)

MariaDB [ayuntamiento]> UPDATE ayuntamiento.usuario SET nombre='Modificado' WHERE nombre='Test';
Query OK, 1 row affected (0.002 sec)
Rows matched: 1 Changed: 1 Warnings: 0

MariaDB [ayuntamiento]> DELETE FROM ayuntamiento.usuario WHERE nombre='Test';
Query OK, 0 rows affected (0.000 sec)

MariaDB [ayuntamiento]> CREATE USER 'ac902lectura'@'%' IDENTIFIED BY 's8a';
Query OK, 0 rows affected (0.002 sec)

MariaDB [ayuntamiento]> GRANT SELECT ON ayuntamiento.* TO 'ac902lectura'@'%';
Query OK, 0 rows affected (0.002 sec)

MariaDB [ayuntamiento]> CREATE USER 'ac903todo'@'%' IDENTIFIED BY 's8a';

MariaDB [ayuntamiento]> DROP USER 'ac901local'@'localhost';
Query OK, 0 rows affected (0.002 sec)

MariaDB [ayuntamiento]> DROP USER 'ac902lectura'@'%';
Query OK, 0 rows affected (0.003 sec)

MariaDB [ayuntamiento]> FLUSH PRIVILEGES;
Query OK, 0 rows affected (0.000 sec)

MariaDB [ayuntamiento]> SELECT user, host FROM mysql.user;
+-----+
| User      | Host      |
+-----+
| ac903todo | %         |
| root      | 127.0.0.1 |
| root      | ::1       |
| pma       | localhost |
| root      | localhost |
+-----+
5 rows in set (0.001 sec)

MariaDB [ayuntamiento]> |
```