

MIT WORLD PEACE UNIVERSITY

Vulnerability Identification and Penetration Testing  
Third Year B. Tech, Semester 6

---

---

SCANNING WITH NMAP

---

---

ASSIGNMENT 2

Prepared By

Krishnaraj Thadesar  
Cyber Security and Forensics  
Batch A1, PA 10

April 15, 2024

# Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Aim</b>   | <b>1</b>  |
| <b>2</b> | <b>Objectives</b>  | <b>1</b>  |
| <b>3</b> | <b>Theory</b>  | <b>1</b>  |
| <b>4</b> | <b>Introduction to Nmap</b>                                | <b>1</b>  |
| 4.1      | Need/Purpose of Nmap . . . . .                             | 1         |
| 4.2      | Advantages of Nmap . . . . .                               | 1         |
| 4.3      | Disadvantages of Nmap . . . . .                            | 2         |
| <b>5</b> | <b>Implementation</b>                                      | <b>2</b>  |
| 5.1      | Get ip Address . . . . .                                   | 2         |
| 5.2      | Scan 1 port, current IP . . . . .                          | 2         |
| 5.2.1    | Syntax . . . . .   | 2         |
| 5.3      | Scan any IP . . . . .                                      | 3         |
| 5.3.1    | Syntax . . . . .   | 3         |
| 5.4      | Scan a range of IPs . . . . .                              | 3         |
| 5.4.1    | Syntax . . . . .   | 3         |
| 5.5      | Scan 1 Port . . . . .                                      | 3         |
| 5.5.1    | Syntax . . . . .   | 3         |
| 5.6      | Scan a range of ports . . . . .                            | 4         |
| 5.6.1    | Syntax . . . . .   | 4         |
| 5.7      | Fragmented Scan . . . . .                                  | 4         |
| 5.7.1    | Syntax . . . . .   | 4         |
| 5.8      | TCP SYN Scan . . . . .                                     | 5         |
| 5.8.1    | Syntax . . . . .   | 5         |
| 5.9      | OS Detection . . . . .                                     | 5         |
| 5.9.1    | Syntax . . . . .   | 5         |
| 5.10     | Syn Scan for specific ports with ping . . . . .            | 5         |
| 5.10.1   | Syntax . . . . .   | 5         |
| 5.11     | Syn Scan for specific ports without ping . . . . .         | 6         |
| 5.11.1   | Syntax . . . . .   | 6         |
| 5.12     | Nmap Timing Templates . . . . .                            | 7         |
| 5.12.1   | Syntax . . . . .   | 7         |
| 5.13     | Scannig Vulnerabilities . . . . .                          | 8         |
| 5.13.1   | Syntax . . . . .   | 8         |
| 5.14     | Sweeping IP Ranges for Live host using ARP Scan . . . . .  | 9         |
| 5.14.1   | Syntax . . . . .   | 9         |
| 5.15     | Sweeping IP Ranges for Live host using ICMP Scan . . . . . | 9         |
| 5.15.1   | Syntax . . . . .   | 9         |
| 5.16     | Sweeping IP Ranges for Live host using TCP Scan . . . . .  | 10        |
| 5.16.1   | Syntax . . . . .   | 10        |
| 5.17     | Sweeping IP Ranges for Live host using UDP Scan . . . . .  | 10        |
| 5.17.1   | Syntax . . . . .   | 10        |
| <b>6</b> | <b>Platform</b>  | <b>11</b> |

**7 Conclusion**

**11**

## 1 Aim

To perform scanning with nmap.

## 2 Objectives

1. To learn about nmap.
2. To perform live host scanning.

## 3 Theory

### 4 Introduction to Nmap

Nmap, short for Network Mapper, is a widely-used open-source tool designed for network exploration and security auditing. It provides a comprehensive view of a network by discovering hosts and services running on them.

#### 4.1 Need/Purpose of Nmap

Nmap serves various purposes in the field of cybersecurity and network management. Its primary objectives include:

- **Host Discovery:** Identifying active hosts on a network, aiding in network mapping.
- **Port Scanning:** Determining open ports on a system, crucial for understanding potential vulnerabilities.
- **Service Version Detection:** Identifying the version and type of services running on open ports.
- **OS Fingerprinting:** Attempting to determine the operating system of target hosts.
- **Vulnerability Assessment:** Assessing potential security risks and vulnerabilities within a network.

#### 4.2 Advantages of Nmap

Nmap offers several advantages that make it a preferred choice in the cybersecurity community:

- **Versatility:** Nmap can be used for a wide range of network exploration and security auditing tasks.
- **Accuracy:** It provides accurate information about hosts, open ports, and services.
- **Scripting Engine:** Nmap's scripting engine allows users to create custom scripts for specific tasks.
- **Community Support:** Being open-source, Nmap benefits from a large and active user community, ensuring continuous improvement.
- **Platform Independence:** Nmap is available on multiple platforms, making it accessible to a diverse range of users.

### 4.3 Disadvantages of Nmap

Despite its many strengths, Nmap has some limitations and potential drawbacks:

- **Firewall Interference:** Firewalls may block Nmap scans, limiting the tool's effectiveness.
- **Legal and Ethical Concerns:** Improper use of Nmap for unauthorized scanning may lead to legal and ethical issues.
- **False Positives:** In certain scenarios, Nmap might produce false positives, leading to inaccurate assessments.
- **Resource Intensive:** Intensive scanning can consume significant network resources and slow down target systems.
- **Limited Stealth:** While Nmap offers stealthy scanning options, complete stealth is challenging to achieve in some situations.

## 5 Implementation

### 5.1 Get ip Address

#### Syntax

```
$ifconfig
```

#### Command

```
$ifconfig
```

#### Purpose

To get the IP Address of the machine.

#### Output

Figure 1: Get IP Address

### 5.2 Scan 1 port, current IP

#### 5.2.1 Syntax

```
$ nmap -p <port> <ip>
```

#### Command

```
$ nmap -p 80 192.168.1.38
```

#### Purpose

To get the IP Address of the machine.

**Output**

Figure 2: Get IP Address

**5.3 Scan any IP****5.3.1 Syntax**

```
$ nmap <ip>
```

**Command**

```
$ nmap 192.168.1.38
```

**Purpose**

Scan a single ip

**Output**

Figure 3: Scan google.com

**5.4 Scan a range of IPs****5.4.1 Syntax**

```
$ nmap <ip range>
```

**Command**

```
$ nmap 192.168.1.38-40
```

**Purpose**

To Scan a range of IPs.

**Output**

Figure 4: scan range of ips.

Figure 5: scan range of ips.

**5.5 Scan 1 Port****5.5.1 Syntax**

```
$ nmap -p <port> <ip>
```

**Command**

```
$ nmap -p 80 www.example.com
```

**Purpose**

To perform a scan on a single port.

**Output**

Figure 6: Scan a single port

**5.6 Scan a range of ports****5.6.1 Syntax**

```
$ nmap -p <port range> <ip>
```

**Command**

```
$ nmap -p 1-100 www.example.com
```

**Purpose**

To perform a scan on a range of ports.

**Output**

Figure 7: Scan a range of ports

**5.7 Fragmented Scan****5.7.1 Syntax**

```
$ nmap -F <ip>
```

**Command**

```
$ nmap -F www.example.com
```

**Purpose**

Fragmented Scan is used to evade firewalls.

## **Output**

Figure 8: Perform a fragmented scan.

## **5.8 TCP SYN Scan**

### **5.8.1 Syntax**

```
$ nmap -sS <ip>
```

### **Command**

```
$ nmap -sS www.example.com
```

### **Purpose**

To scan a host for open ports using TCP SYN scan.

## **Output**

Figure 9: Check if tcp syn scan is possible on a host.

## **5.9 OS Detection**

### **5.9.1 Syntax**

```
$ nmap -O <ip>
```

### **Command**

```
$ nmap -O www.example.com
```

### **Purpose**

To scan operating system of a host.

## **Output**

Figure 10: Scan Operating System of example.com

Figure 11: Scan Operating System of host

## **5.10 Syn Scan for specific ports with ping**

### **5.10.1 Syntax**

```
$ sudo nmap -sS -p< <ip>
```



**Command**

```
$ sudo nmap -sS -p80-90 172.16.182.162
```

**Purpose**

To perform a syn scan on specific ports with ping.

**Output**

Figure 12: scan with ping

**5.11 Syn Scan for specific ports without ping****5.11.1 Syntax**

```
$ sudo nmap -sS -Pn -p<port or range> <ip>
```

**Command**

```
$ sudo nmap -sS -Pn -p40-6000 172.16.182.162
```

**Purpose**

To scan the open ports of a host without ping to reduce time.

What is the use of ports from 80 to 90?

1. **Port 80:** HTTP (Hypertext Transfer Protocol): Standard port used for serving web pages over the internet.
2. **Port 81:** Alternative HTTP: Sometimes used as an alternative to port 80 for serving HTTP traffic.
3. **Port 82:** Reserved: Not assigned for any specific use by the IANA.
4. **Port 83:** Reserved: Not officially assigned for any specific use.
5. **Port 84:** Commonly Unassigned: Doesn't have a well-known or standardized use.
6. **Port 85:** Commonly Unassigned: No specific use assigned.
7. **Port 86:** Commonly Unassigned: Typically not assigned.
8. **Port 87:** Commonly Unassigned: Not typically used for any specific purpose.
9. **Port 88:** Kerberos: Used by the Kerberos authentication system.
10. **Port 89:** Commonly Unassigned: No well-known or standardized use.

**Output**

Figure 13: scan without ping

**5.12 Nmap Timing Templates**

Figure 14:

The use of these timing templates is to control the speed of the scan.  
From the nmap documentation:

While the fine-grained timing controls discussed in the previous section are powerful and effective, some people find them confusing. Moreover, choosing the appropriate values can sometimes take more time than the scan you are trying to optimize. So Nmap offers a simpler approach, with six timing templates. You can specify them with the -T option and their number (0–5) or their name. The template names are paranoid (0), sneaky (1), polite (2), normal (3), aggressive (4), and insane (5). The first two are for IDS evasion. Polite mode slows down the scan to use less bandwidth and target machine resources. Normal mode is the default and so -T3 does nothing. Aggressive mode speeds scans up by making the assumption that you are on a reasonably fast and reliable network. Finally insane mode assumes that you are on an extraordinarily fast network or are willing to sacrifice some accuracy for speed.

**5.12.1 Syntax**

```
$ sudo nmap --packet-trace <ip> -T<0-6>
```

**Command**

```
$ sudo nmap --packet-trace antibrutus.surge.sh -T5
```

**Purpose**

To perform packet tracing with timing templates.

**Output**

Figure 15: With T5

Figure 16: With T4

Figure 17: With T3

Figure 18: With T2

As we can see, the time taken per scan increases as we go from T5 to T2.

## 5.13 Scanning Vulnerabilities

### 5.13.1 Syntax

```
$ sudo nmap -Pn --script vuln <ip> -v
```

#### Command

```
$ sudo nmap -Pn --script vuln www.antibrutus.surge.sh -v
```

#### Purpose

To scan for vulnerabilities in a host.

#### Output

Figure 19: Scan for vulnerabilities

Figure 20: Scan for vulnerabilities

## Meaning of Scanned Vulnerabilities and Output

### Host Status

- **Host is up (0.011s latency):** Indicates that the host (www.simpli.com in this case) is up and responsive with a latency of 0.011 seconds.

### Scanned Ports

- **80/tcp open http:** Port 80 is open and running an HTTP service, typically used for serving web pages.
- **443/tcp open https:** Port 443 is open and running an HTTPS service, which is a secure version of HTTP.

## Vulnerability Detection

### DOM-based XSS: DOM-based Cross-Site Scripting

**Description:** DOM-based Cross-Site Scripting (XSS) is a type of XSS attack that occurs when an attacker injects malicious code into a web application, which is then executed by the victim's browser. The attack exploits vulnerabilities in the Document Object Model (DOM) of the web page to manipulate its content.

### Stored XSS: Stored Cross-Site Scripting

**Description:** Stored Cross-Site Scripting (XSS), also known as persistent XSS, occurs when an attacker injects malicious code into a web application, which is then stored and displayed to other users. The injected code is executed when other users visit the affected page, making it a serious security vulnerability.

### CSRF: Cross-Site Request Forgery

**Description:** Cross-Site Request Forgery (CSRF) is an attack that tricks a user into unknowingly executing unwanted actions on a web application in which they are authenticated. The attack occurs when an attacker exploits the user's active session to execute malicious requests without their consent. CSRF attacks can lead to unauthorized actions such as changing account settings or making financial transactions.

### NSE Scripts

- NSE scripts were initiated and completed successfully, but no vulnerabilities were detected.

### Scan Summary

- Nmap completed scanning 1 IP address with 1 host up in 615.48 seconds.
- 998 TCP ports were filtered (no response), and 2 ports were open (HTTP and HTTPS).

## 5.14 Sweeping IP Ranges for Live host using ARP Scan

### 5.14.1 Syntax

```
$ nmap -PR -sn <ip range>
```

### Command

```
$ nmap -PR -sn 172.16.182.224/24
```

### Purpose

To scan live hosts using ARP scan.

### Output

Figure 21: To scan live hosts using arp scan.

## 5.15 Sweeping IP Ranges for Live host using ICMP Scan

### 5.15.1 Syntax

```
$ nmap -PP -sn <ip range>
```

### Command

```
$ nmap -PP -sn 172.16.182.224
```

**Purpose**

To scan live hosts using ICMP scan.

**Output**

Figure 22: To scan live hosts using ICMP scan.

**5.16 Sweeping IP Ranges for Live host using TCP Scan****5.16.1 Syntax**

```
$ nmap -PA -sn <ip range>
```

**Command**

```
$ nmap -PA -sn 172.16.182.224
```

**Purpose**

To scan live hosts using TCP scan. This performs 3 way handshaking as opposed to the -sS syn scan option which does not perform 3 way handshaking.

**Output**

Figure 23: To scan live hosts using TCP scan.

**5.17 Sweeping IP Ranges for Live host using UDP Scan****5.17.1 Syntax**

```
$ nmap -PU -sn <ip range>
```

**Command**

```
$ nmap -PU -sn 172.16.182.224
```

**Purpose**

To scan live hosts using UDP scan.

**Output**

Figure 24: To scan live hosts using UDP scan.

## **6 Platform**

**Operating System:** Arch Linux X8664

**IDEs or Text Editors Used:** Visual Studio Code

## **7 Conclusion**

Thus, we have successfully performed scanning with nmap, and learnt about the various options available with nmap.