

cap-able

Make it more able to caption — now that is cap-able

v0.0.1

2026-04-12

MIT

A comprehensive Typst package for creating professional three-line tables and figures with bilingual caption support, continued tables/figures, subfigures, and flexible customization options for academic documents.

SCHRÖDINGER BLUME

cap-able is a powerful Typst package designed for academic documents, providing:

- **Three-line tables** — Academic-standard tables (top, middle, bottom rules)
- **Bilingual captions** — Auto-formatted bilingual captions (Chinese/English, German/English, etc.)
- **Continued tables/figures** — Multi-page tables and figures with automatic numbering
- **Subfigures** — Flexible multi-image grid layouts with overlay labels and subcaptions
- **Notes** — Auto-width-matched notes for tables and figures
- **Multilingual support** — 25+ languages including RTL languages
- **Unified configuration** — Configure both via `cap-style`, or override per-type with `cap-tab-style` / `cap-fig-style`

The package is particularly suited for academic papers, theses, and technical documents requiring professional typography and multi-language support.

Table of Contents

Introduction	4	III.3 Bilingual Captions	7
I.1 Design Philosophy	4	Tables in Detail	8
I.2 Dependencies	4	IV.1 Table Syntax	8
Installation	5	IV.1.1 Basic Syntax	8
II.1 From Typst Universe	5	IV.1.2 Alignment	8
II.2 Manual Installation	5	IV.1.3 Cell Merging	9
Quick Start	6	IV.2 Column Configuration	9
III.1 Basic Three-Line Table	6	IV.2.1 Auto mode cols: ()	9
III.2 Basic Figure	6		

IV.2.2 Absolute units cols: (8cm, 3cm, 2cm)	10	VIII.8 capfig Complete Parameters	29
IV.2.3 fr units cols: (3fr, 1fr, 1fr) — First column third as wide ..	10	VIII.9 capsubfig Complete Parameters .	29
IV.2.4 Mixed cols: (5fr, 3cm, 1fr) — Value column fixed at 3cm; Description and Unit columns share remaining width at 5:1 ..	10	VIII.9.1 Subfigure Dict Structure	29
IV.3 Additional Lines	10	VIII.9.2 label-style-override dict keys	29
IV.4 Table Notes	11	VIII.9.3 Function Parameters	29
IV.5 Continued Tables	11	VIII.9.4 Label Style Parse Rules	30
IV.5.1 Continuation Mode	11	VIII.9.5 Overlay with Circle Background	30
Figures in Detail	13	VIII.9.6 Multi-row Subfigures	30
V.1 Single Figures	13	VIII.10 captnote Complete Parameters .	31
V.2 Subfigures	13	VIII.11 capfnote Complete Parameters .	31
V.3 Overlay Labels	14	VIII.12 Full Multilingual Rules	31
V.3.1 Label Style Reference	14	API Reference	33
V.4 Subfigure Cross-References	15	IX.1 Configuration Module (config.typ)	33
Configuration	16	IX.1.1 cap-style	33
VI.1 Unified Configuration	16	IX.1.2 capfig-style	34
VI.2 Table Configuration	16	IX.1.3 captab-style	36
VI.3 Figure Configuration	17	IX.1.4 resolve-lang-indent	37
VI.4 Table Width	17	IX.1.5 set-figure-width	37
VI.5 Bilingual Outline	17	IX.1.6 set-table-width	37
Multilingual Support	19	IX.2 Caption Module (bicap.typ)	37
VII.1 Supported Languages	19	IX.2.1 bicap	37
VII.2 Simplified vs Traditional Chinese .	20	IX.3 Table Module (table.typ)	39
VII.3 RTL Language Support	20	IX.3.1 captab	39
VII.4 Language-Specific Formatting	21	IX.4 Note Module (note.typ)	40
Complete Usage Reference	22	IX.4.1 capfnote	40
VIII.1 Public API Overview	22	IX.4.2 captnote	40
VIII.2 set-table-width Complete Parameters	22	IX.5 Figure Module (figure.typ)	41
VIII.3 cap-style Complete Parameters .	22	IX.5.1 capfig	41
VIII.4 captab-style Complete Parameters	23	IX.5.2 capsubfig	42
VIII.5 capfig-style Complete Parameters	25	Frequently Asked Questions	44
VIII.6 captab Complete Parameters	26	X.1 Why Markdown syntax for tables? .	44
VIII.6.1 Continuation Mode Examples	27	X.2 How do I create tables without captions?	44
VIII.7 bicap Standalone Caption Function	28	X.3 Can I use regular Typst table syntax?	44
		X.4 How do I reference tables and figures?	45
		X.5 Why doesn't my continued table show the caption?	45
		X.6 How do I fix missing indentation after tables in Chinese?	45

X.7 How do I show bilingual captions in the table of contents?	45
Changelog	46
XI.1 Version 0.0.1	46
Index	47

Part I

Introduction

cap-able brings professional table and figure capabilities to Typst, following academic publishing standards and best practices.

The name “cap-able” is a wordplay on “caption” and “able” — making your documents more **able** to handle complex **captions**, very capable, huh!

I.1 Design Philosophy

The package follows these design principles:

1. **Declarative Configuration:** Configure once at the document start, use everywhere
2. **Sensible Defaults:** Works out of the box with minimal configuration
3. **Language Awareness:** Automatic formatting based on document language
4. **Academic Standards:** Follows established conventions for scholarly publishing

I.2 Dependencies

This package depends on:

- `@preview/tablem:0.3.0` — Markdown-style table syntax support

For documentation generation only:

- `@preview/tidy:0.4.3` — Auto-generate API reference from docstrings
- `@preview/mantys:1.0.2` — Documentation template

Part II

Installation

II.1 From Typst Universe

Once published to Typst Universe, import directly:

```
1 #import "@preview/cap-able:0.0.1": *
```

II.2 Manual Installation

After downloading from the repository:

1. Place the `cap-able` folder in your project directory
2. Import with a relative path:

```
1 #import "cap-able/0.0.1/lib.typ": *
```

Part III

Quick Start

This chapter provides a quick overview of the most common use cases.

III.1 Basic Three-Line Table

The simplest way to create a table uses Markdown-like syntax:

```
1 #captab(  
2   caption: [Sample Data],  
3 ) [  
4   | Name   | Age | Score |  
5   | ----- | --- | ----- |  
6   | Alice  | 25  | 95    |  
7   | Bob    | 30  | 87    |  
8 ]
```

Table 1: Sample Data

Name	Age	Score
Alice	25	95
Bob	30	87

The table automatically gets:

- Full text width
- 1.5pt top rule
- 0.5pt rule below the header
- 1.5pt bottom rule
- Centered content with proper spacing

III.2 Basic Figure

Creating figures is equally straightforward:

```
1 #capfig(  
2   rect(width: 15%, height: 1.15cm, fill: blue.lighten(80%)),  
3   caption: [A Simple Rectangle],  
4 )
```




Figure 1: A Simple Rectangle

III.3 Bilingual Captions

For documents requiring bilingual captions, simply add the `caption-en` parameter:

```
1 #set text(lang: "es") // Set the document language to non-English
2
3 #captab(
4   caption: [Parámetros experimentales],
5   caption-en: [Experimental Parameters],
6 ) [
7   | Parámetro | Valor | Unidad |
8   | ----- | ---- | ----- |
9   | Temperatura | 25 | °C |
10  | Presión | 1 | atm |
11 ]
```

Tabla 2. Parámetros experimentales
Table 2. Experimental Parameters

Parámetro	Valor	Unidad
Temperatura	25	°C
Presión	1	atm

The package automatically:

- Detects the document language
- Formats the primary caption in that language
- Adds an English caption below when `enable-english-caption: true`

Note: When the document language is English (`#set text(lang: "en")`), if both `caption` and `caption-en` are provided, only `caption-en` is displayed as a single-language caption — `caption` is ignored, since the document is already in English and bilingual output is unnecessary.

Part IV

Tables in Detail

IV.1 Table Syntax

captab uses the `tablem` package to parse Markdown-style table syntax, avoiding verbose Typst table syntax.

IV.1.1 Basic Syntax

```
1 | Header1 | Header2 | Header3 |
2 | ----- | ----- | ----- | <- Separator
3 | Cell 1 | Cell 2 | Cell 3 |
4 | Cell 4 | Cell 5 | Cell 6 |
```

Table 3: Basic Syntax Example

Header1	Header2	Header3
Cell 1	Cell 2	Cell 3
Cell 4	Cell 5	Cell 6

Note: The separator row (| --- |) marks the boundary between header and body rows.

IV.1.2 Alignment

Control alignment using colons in the separator:

```
1 | Left      | Center   | Right    |
2 | :-----: | :-----: | :-----: |
3 | L         | C         | R         |
```

Table 4: Column Alignment Example

Left	Center	Right
L	C	R

IV.1.3 Cell Merging

tablem supports cell merging:

- Use < to merge with cell to the left (horizontal)
- Use ^ to merge with cell above (vertical)

```
1 | A   | B   |
2 | ----| ----|
3 | Span| <   |
4 | C   | Span|
5 | D   | ^   |
```

Table 5: Cell Merging Example

A		B	
Span			
C		Span	
D			

IV.2 Column Configuration

Customize column widths using the cols parameter.

Column width rules:

- Without cols (auto mode): columns fit content; may overflow with long text.
- Only absolute units (e.g., cm, pt): table width = sum of columns; may be narrower or overflow.
- With fr units: table expands proportionally to text width. fr and absolute units can be mixed — absolute columns take fixed widths first, and the remaining space is distributed by fr ratio.

The cols parameter accepts an array of lengths, for example:

```
1 cols: (8cm, 2cm, 2cm)    // Absolute units
2 cols: (3fr, 1fr, 1fr)    // fr units
3 cols: (3fr, 2cm, 1fr)    // Mixed
```

IV.2.1 Auto mode cols: ()

Table 6: Auto Columns

Description	Value	Unit
This is a very very, really really, truly truly long text	42	m/s

IV.2.2 Absolute units cols: (8cm, 3cm, 2cm)

Table 7: Absolute Columns

Description	Value	Unit
This is a very very, really really, truly truly long text	42	m/s

IV.2.3 fr units cols: (3fr, 1fr, 1fr) — **First column third as wide**

Table 8: Proportional Columns

Description	Value	Unit
This is a very very, really really, truly truly long text	42	m/s

IV.2.4 Mixed cols: (5fr, 3cm, 1fr) — **Value column fixed at 3cm; Description and Unit columns share remaining width at 5:1**

Table 9: Mixed Columns

Description	Value	Unit
This is a very very, really really, truly truly long text	42	m/s

IV.3 Additional Lines

Add extra horizontal or vertical lines for complex layouts:

```
1 #captab(  
2   hlines: ((row: 3, stroke: 1pt),), // Add 1pt horizontal line after row 3  
3   vlines: ((col: 1, start: 1),), // Add vertical line at column 1 (from row 1)  
4   caption: [Table with Extra Lines],  
5 ) [...]
```

Table 10: Table with Extra Lines

A	B	C
1	2	3
4	5	6
7	8	9

IV.4 Table Notes

Add explanatory notes below tables:

```
1 #captab(caption: [Statistical Results])[
2   | Variable | Mean | SD |
3   | ----- | ---- | --- |
4   | X         | 3.2* | 0.5 |
5   | Y         | 4.1  | 0.8 |
6 ]
7 #captnote[
8   Note:  $p < 0.05$ . SD = Standard Deviation.
9 ]
```

Table 11: Statistical Results

Variable	Mean	SD
X	3.2*	0.5
Y	4.1	0.8

Note: $p < 0.05$. SD = Standard Deviation.

IV.5 Continued Tables

For tables spanning multiple pages, use the `refer-to` parameter:

```
1 // First part (original table)
2 #captab(
3   caption: [Long Data Table],
4   label: <tab:long>,          // Set label for continuation reference
5 )[...]
6
7 // Continuation (header shows "Continued Table X")
8 #captab(
9   caption: [Long Data Table],
10  refer-to: <tab:long>,        // Reference original for numbering
11 )[...]
```

The continuation automatically:

- Uses the same number as the original table
- Adds continuation prefix/suffix
- Does not create a new entry in the table of contents

IV.5.1 Continuation Mode

Control the continuation style via `continued-mode`:

- "prefix" (default): Prefix mode, e.g. "Continuation of Table 1"
- "suffix": Suffix mode, e.g. "Table 1 (continued)"

Part V

Figures in Detail

V.1 Single Figures

Create single figures with bilingual captions using `capfig`:

```
1 #capfig(  
2   image("example.png", width: 30%),  
3   caption: [Typst Logo],  
4   label: <fig:typst-logo>,  
5 )
```

V.2 Subfigures

`capsubfig` creates multi-image parallel layouts:


```
1 #capsubfig(  
2   (  
3     (content: rect(width: 3cm, height: 2cm, fill: red.lighten(70%)),  
4       subcaption: [Red]),  
5     (content: rect(width: 3cm, height: 2cm, fill: green.lighten(70%)),  
6       subcaption: [Green]),  
7     (content: rect(width: 3cm, height: 2cm, fill: blue.lighten(70%)),  
8       subcaption: [Blue]),  
9   ),  
10  columns: 3,  
11  show-subcaption: true,      // Show subcaptions  
12  caption: [Color Comparison],  
13 )
```



(a) Red



(b) Green



(c) Blue

Figure 2: Color Comparison

V.3 Overlay Labels

Use overlay label mode to place (a), (b) labels directly on images for a cleaner look:

```
1 #capsubfig(
2   (
3     (content: rect(width: 4cm, height: 3cm, fill: orange.lighten(70%))),
4     (content: rect(width: 4cm, height: 3cm, fill: purple.lighten(70%))),
5   ),
6   columns: 2,
7   caption: [Overlay Labels Demo],
8   label-mode: "overlay",      // Enable overlay mode
9   label-style: "(a)",        // Label style
10  label-bg: white.transparentize(20%), // Semi-transparent white bg
11  label-offset: (5pt, 5pt),   // Offset from top-left
12 )
```



Figure 3: Overlay Labels Demo

V.3.1 Label Style Reference

The `label-style` parameter supports various formats:

Style	Example	Description
"(a)"	(a), (b), (c)	Parenthesized lowercase
"(A)"	(A), (B), (C)	Parenthesized uppercase
"(1)"	(1), (2), (3)	Parenthesized numbers
"(i)"	(i), (ii), (iii)	Parenthesized roman lowercase
"(I)"	(I), (II), (III)	Parenthesized roman uppercase
"a)"	a), b), c)	Trailing parenthesis only
"Fig. A"	Fig. A, Fig. B	English prefix

V.4 Subfigure Cross-References

After setting a `label` for each subfigure, reference them with `@`:

```
1 #capsubfig(  
2   (  
3     (content: rect(fill: gray), label: <fig:sub-a>),  
4     (content: rect(fill: gray), label: <fig:sub-b>),  
5   ),  
6   label-mode: "overlay",  
7   caption: [Referenced Subfigures],  
8   label: <fig:main>,  
9 )  
10  
11 See @fig:sub-a and @fig:sub-b for details.
```

Live demonstration:



Figure 4: Referenced Subfigures

See [Figure 4a](#) and [Figure 4b](#) (overall [Figure 4](#)).

Part VI

Configuration

VI.1 Unified Configuration

`cap-style` configures shared styles (numbering, caption, language, notes, ...) for both tables and figures at once. A subsequent `captab-style` / `capfig-style` call can override per-type.

```
1  #show: cap-style.with(  
2    numbering-format: "1.1",  
3    use-chapter: true,  
4    caption-weight: "regular",  
5    enable-english-caption: true,  
6  )  
7  
8  // Per-type override still works afterwards:  
9  #show: capfig-style.with(  
10   label-mode: "overlay",  
11   label-style: "(a)",  
12 )
```

VI.2 Table Configuration

Use `captab-style` to configure all table-related settings. Typically called via `#show:` at the document start:

```
1  #show: captab-style.with(  
2    // Numbering  
3    numbering-format: "1.1",      // Chapter.Number format  
4    use-chapter: true,           // Include chapter number  
5  
6    // Caption style  
7    caption-size: 10.5pt,  
8    caption-weight: "regular",    // or "bold"  
9  
10   // Spacing  
11   caption-above: 1em,           // Above caption  
12   caption-below: 0.95em,       // Between caption and table  
13  
14   // Language  
15   lang: auto,                  // Auto-detect  
16   enable-english-caption: true, // Enable English sub-caption
```



```

17
18 // Table content
19 body-size: 10.5pt,
20 cell-inset: (x: 3pt, y: 6.5pt),
21
22 // Continuation
23 continued-mode: "prefix", // "prefix" or "suffix"
24 )

```

VI.3 Figure Configuration

Use `capfig-style` for figure and subfigure settings:

```

1 #show: capfig-style.with(
2 // Numbering
3 numbering-format: "1.1",
4
5 // Subfigure defaults
6 label-mode: "overlay", // Default overlay mode
7 label-style: "(a)",
8 gutter: 1em,
9 subcaption-pos: "bottom",
10
11 // Caption
12 enable-english-caption: true,
13 )

```

VI.4 Table Width

Adjust table width as a percentage of text width:

```

1 #set-table-width(percentage: 80) // 80% of text width
2
3 #captab(caption: [Narrow Table])[...]
4
5 #set-table-width(percentage: 100) // Reset to full width

```

VI.5 Bilingual Outline

By default, only the primary language caption appears in the outline (table of contents). Enable `outline-bilingual` to show both languages in the outline.

```

1 #show: captab-style.with(
2 outline-bilingual: true, // Enable bilingual outline
3 outline-separator: " / ", // Separator between primary and English

```

```
4  outline-newline: false,          // false: same line; true: English on new line
5  )
```

Three related parameters:

- `outline-bilingual`: Show bilingual captions in outline (default `false`)
- `outline-separator`: Separator between primary and English captions (default `" / "`)
- `outline-newline`: Put English caption on a new line (default `false`)

All three configuration functions (`captab-style`, `capfig-style`, `cap-style`) support these parameters. Use `cap-style` to enable bilingual outline for both tables and figures at once.

Part VII

Multilingual Support

The package supports 25+ languages with automatic localization. Just set the document language and the package automatically uses the correct text.

```
1 #set text(lang: "de") // Switch to German
2
3 #captab(
4   caption: [Experimentelle Ergebnisse],
5   caption-en: [Experimental Results],
6 )[...]
7 // Caption shows: Tabelle 1 Experimentelle Ergebnisse
8 //                Table 1 Experimental Results
```

VII.1 Supported Languages

Code	Language	Code	Language
en	English	zh	Chinese
de	German	fr	French
es	Spanish	it	Italian
pt	Portuguese	ru	Russian
ja	Japanese	ko	Korean
ar	Arabic ↵	he	Hebrew ↵
fa	Persian ↵	ur	Urdu ↵
nl	Dutch	pl	Polish
cs	Czech	sv	Swedish
da	Danish	no	Norwegian
fi	Finnish	tr	Turkish
el	Greek	hi	Hindi
th	Thai	vi	Vietnamese

↵ = Right-to-left language; Traditional Chinese is distinguished via the `region` parameter.

VII.2 Simplified vs Traditional Chinese

The package distinguishes Simplified Chinese (zh) from Traditional Chinese (zh-TW) using Typst's `text.region` parameter:

```
1 // Simplified Chinese (default)
2 #set text(lang: "zh")
3
4 // Traditional Chinese
5 #set text(lang: "zh", region: "TW")
```

Key differences:

Item	Simplified	Traditional
Table prefix	表	表
Figure prefix	图	圖
Continued table	续表	續表
Continued figure	续图	續圖
Continued suffix	(续)	(續)

表 12 繁體中文測試表格
Table 12 Traditional Chinese Test Table

項目	數值
測試	100

續表 12 繁體中文測試表格
Continuation of Table 12 Traditional Chinese Test Table

項目	數值
測試	100



圖 5 繁體中文測試圖片
Figure 5 Traditional Chinese Test Figure

VII.3 RTL Language Support

For RTL languages (Arabic, Hebrew, Persian, Urdu), the package automatically:

- Reverses bilingual caption line order (RTL first, then English)
- Uses `box[]` wrapping to prevent direction confusion in RTL content

- Forces dir: rtl for the English line

جدول 13: أهم المدن في العالم العربي
Table 13: Major Cities in the Arab World

عدد السكان (مليون)	الدولة	المدينة
20.9	مصر	القاهرة
7.5	العراق	بغداد
7.2	المملكة العربية السعودية	الرياض
5.8	السودان	الخرطوم
3.7	المغرب	الدار البيضاء
3.5	الجزائر	الجزائر
2.5	سوريا	دمشق
4.0	الأردن	عمّان
2.4	لبنان	بيروت
2.3	تونس	تونس

VII.4 Language-Specific Formatting

Each language has customized separators and spacing:

- **Chinese/Japanese:** No space between prefix and number, em-space before title
- **French:** Space before colon (“Tableau 1 : Title”)
- **Spanish/Italian:** Dot separator (“Table 1. Title”)
- **English/German:** Colon+space (“Table 1: Title”)

Part VIII

Complete Usage Reference

This chapter is the authoritative reference listing every public function, every parameter, every accepted value, every alias, and every behavioral detail of capable.

VIII.1 Public API Overview

Function	Category	Purpose
<code>cap-style</code>	Config	Shared style for tables & figures
<code>captab-style</code>	Config	Global table style
<code>capfig-style</code>	Config	Global figure style
<code>set-table-width</code>	Config	Global table width %
<code>captab</code>	Table	Three-line table
<code>capfig</code>	Figure	Single bilingual figure
<code>capsubfig</code>	Figure	Subfigure layout
<code>captnote</code>	Note	Table note
<code>capfnote</code>	Note	Figure note
<code>bicap</code>	Caption	Standalone bilingual caption

VIII.2 `set-table-width` Complete Parameters

Param	Type	Description
<code>percentage</code>	<code>int</code> (1–100)	Table width as % of text area (asserted 1–100)

```
1 #set-table-width(percentage: 80) // 80% wide
2 #set-table-width(percentage: 100) // Reset to full
```

VIII.3 `cap-style` Complete Parameters

`cap-style` is the unified entry point: it writes all shared parameters into both the table and figure config states (equivalent to calling `captab-style.with(...)` and `capfig-style.with(...)` in sequence). A subsequent `captab-style` / `capfig-style` call can still override per-type.

Param	Default	Description
<code>numbering-format</code>	<code>"1"</code>	Numbering format string
<code>use-chapter</code>	<code>false</code>	Include chapter number

Param	Default	Description
supplement	auto	Main language prefix
supplement-en	auto	English prefix
continued-prefix	auto	Continued prefix (main lang)
continued-prefix-en	auto	Continued prefix (English)
continued-suffix	auto	Continued suffix (main lang)
continued-suffix-en	auto	Continued suffix (English)
continued-mode	"prefix"	Continuation mode "prefix" / "suffix"
continued-show-caption	auto	Show caption text in continuation
caption-size	10.5pt	Caption size
caption-weight	"regular"	Caption weight
caption-leading	0.5em	Caption line spacing
caption-above	0.5em	Space above caption
pre-supplement-number-spacing	auto	Prefix-number spacing
post-supplement-number-spacing	auto	Number-suffix spacing
number-title-spacing	auto	Number-title separator
number-title-spacing-en	auto	Number-English-title separator
lang	auto	Language code override
enable-english-caption	true	Enable English sub-caption
outline-bilingual	false	Bilingual outline
outline-separator	" / "	Outline separator
outline-newline	false	Newline in outline
after-indent	auto	Post-block indent fix
note-above	0.7em	Above note
note-below	1em	Below note
note-size	10.5pt	Note size
note-leading	6.5pt	Note leading
note-justify	true	Justify note

Parameters not exposed by *cap-style* — *table-body* (*body-size* / *body-leading* / *cell-inset* / *table-below*) and *figure-only* fields (*figure-above* / *figure-below* / *subcaption-** / *gutter* / *subfigure label-**) — must still be configured via *captab-style* / *capfig-style* directly.

VIII.4 *captab-style* Complete Parameters

All parameters of *captab-style* with defaults. *auto* means auto-select based on document language.

Param	Default	Description
caption-above	1.5em	Space above caption block
caption-below	0.5em	Between caption and body

Param	Default	Description
table-below	0.5em	Below whole table
caption-leading	0.5em	Caption line spacing
numbering-format	"1"	Numbering format
use-chapter	true	Include chapter number
supplement	auto	Main language prefix
supplement-en	auto	English prefix
continued-prefix	auto	Continued prefix
continued-prefix-en	auto	English continued prefix
continued-suffix	auto	Continued suffix
continued-suffix-en	auto	English continued suffix
continued-mode	"prefix"	Continuation mode "prefix" / "suffix"
continued-show-caption	auto	Show caption text in continuation
caption-size	10.5pt	Caption size
caption-weight	"regular"	Caption weight
pre-supplement-number-spacing	auto	Prefix-number spacing
post-supplement-number-spacing	auto	Number-suffix spacing
number-title-spacing	auto	Number-title separator
number-title-spacing-en	auto	Number-English-title separator
lang	auto	Language override
enable-english-caption	true	Enable English sub-caption
body-size	10.5pt	Body font size
body-leading	0.45em	Body line spacing
cell-inset	(x: 5pt, y: 5pt)	Cell padding (dict or scalar)
note-above	0.5em	Above note
note-below	1em	Below note
note-size	10.5pt	Note size
note-leading	6.5pt	Note leading
note-justify	true	Justify note
outline-bilingual	false	Bilingual outline
outline-separator	" / "	Outline separator
outline-newline	false	Newline in outline
after-indent	auto	Post-table indent fix

Spacing parameters may be length or content: any *-spacing OR pre/post-supplement-number-spacing accepts a length (e.g. 0.5em) or content directly (e.g. [\u{3000}] em-space).

VIII.5 capfig-style Complete Parameters

capfig-style merges figure style + figure spacing + subfigure defaults, updating all three states at once.

Caption/numbering/language section

Param	Default	Description
numbering-format	"1"	Numbering format string
use-chapter	false	Include chapter number
supplement	auto	Main language prefix
supplement-en	auto	English prefix
continued-prefix	auto	Continued prefix (main lang)
continued-prefix-en	auto	Continued prefix (English)
continued-suffix	auto	Continued suffix (main lang)
continued-suffix-en	auto	Continued suffix (English)
continued-mode	"prefix"	Continuation mode "prefix" / "suffix"
continued-show-caption	auto	Show caption text in continuation
caption-size	10.5pt	Caption size
caption-weight	"regular"	Caption weight
caption-leading	0.5em	Caption line spacing
pre-supplement-number-spacing	auto	Prefix-number spacing
post-supplement-number-spacing	auto	Number-suffix spacing
number-title-spacing	auto	Number-title separator
number-title-spacing-en	auto	Number-English-title separator
lang	auto	Language code override
enable-english-caption	true	Enable English sub-caption
outline-bilingual	false	Bilingual outline
outline-separator	" / "	Outline separator
outline-newline	false	Newline in outline
after-indent	auto	Post-block indent fix
note-above	0.7em	Above note
note-below	1em + 1.5pt	Below note
note-size	10.5pt	Note size
note-leading	6.5pt	Note leading
note-justify	true	Justify note

Figure spacing section

Param	Default	Description
figure-above	1em	Space above figure
figure-below	1em	Space below figure
caption-above	0.5em	Image-caption gap
caption-leading	0.5em	Caption leading
subcaption-above	0.3em	Subfig-subcaption gap
subcaption-below	0.5em	Below subcaption

Subfigure defaults section

Param	Default	Description
gutter	1em	Horizontal gap
subcaption-pos	"bottom"	Subcaption position
show-subcaption	false	Show subcaptions
show-subcaption-label	true	Subcaption includes label
align	"horizon"	Vertical alignment
label-mode	none	Label mode (<i>none</i> / "overlay")
label-style	"(a)"	Label style string
label-font	("Arial",)	Label font list
label-size	12pt	Label size
label-offset	(4pt, 4pt)	Offset
label-text-color	black	Text color
label-stroke	none	Stroke
label-bg	none	Background
label-bg-shape	"rect"	Background shape
label-bg-radius	2pt	Rect radius
label-bg-inset	3pt	Background padding
label-sep	auto	Subref separator (<i>auto</i> : number -> ".", letter -> "")

VIII.6 captab Complete Parameters

Param	Type	Description
cols	auto / int / array	Column config (<i>auto</i> or length array, supports fr/abs units)
size	auto / length	Body font size
leading	auto / length	Body line spacing
inset	auto / length / dictionary	Cell padding (dict (x:, y:) or scalar)
caption	none / content	Main language caption

Param	Type	Description
<code>caption-en</code>	<code>none</code> / <code>content</code>	English caption
<code>refer-to</code>	<code>none</code> / <code>label</code>	Label ref for continuation
<code>show-caption</code>	<code>auto</code> / <code>bool</code>	Show caption in continuation
<code>hlines</code>	array of dictionary	Extra horizontal rules (see below)
<code>vlines</code>	array of dictionary	Extra vertical rules (see below)
<code>label</code>	<code>none</code> / <code>label</code>	Cross-reference label
<code>content</code>	<code>content</code> (positional)	Markdown-style body

`hlines` / `vlines` **dict structure:**

Key	<code>hlines</code> fault	de- <code>vlines</code> fault	de- Description
<code>row</code> / <code>col</code>	2	1	Row above (h) or col right (v)
<code>start</code>	0	0	Start col/row index
<code>end</code>	<code>none</code>	<code>none</code>	End index (<code>none</code> = to end)
<code>stroke</code>	0.5pt	0.5pt	Rule stroke

```
1  #captab(  
2    hlines: (  
3      (row: 2, stroke: 1pt),  
4      (row: 4, start: 1, end: 3, stroke: 0.3pt + red),  
5    ),  
6    vlines: (  
7      (col: 1, start: 1, stroke: 0.5pt),  
8    ),  
9    caption: [Complex Rules],  
10 ) [...]
```

Table 14: Complex Rules

A	B	C	D
1	2	3	4
5	6	7	8
9	0	1	2

VIII.6.1 Continuation Mode Examples

Prefix mode (default): shows "Continuation of Table 1.1"

Suffix mode: shows "Table 1.1 (continued)"

```
1  #show: captab-style.with(continued-mode: "suffix")
```

```

2 #captab(caption: [Long Table], label: <tab:long2>)[...]
3 #captab(refer-to: <tab:long2>)[...] // Shows "Table 1.1 (continued)"

```

Force show / hide caption text:

```

1 // Force show
2 #captab(
3   refer-to: <tab:original>,
4   caption: [Original Caption],
5   show-caption: true,
6 )[...]
7
8 // Force hide (even when caption is provided)
9 #captab(
10  refer-to: <tab:original>,
11  show-caption: false,
12 )[...]

```

VIII.7 `bicap` Standalone Caption Function

`bicap` is the standalone caption generator; usable independently of `captab`/`capfig` for custom layouts or embedding bilingual captions in plain Typst tables/figures.

Param	Type	Description
<code>caption</code>	<code>none</code> / <code>content</code>	Main caption
<code>caption-en</code>	<code>none</code> / <code>content</code>	English caption
<code>refer-to</code>	<code>none</code> / <code>label</code>	Continuation ref label
<code>label</code>	<code>none</code> / <code>label</code>	Label for cross-ref
<code>kind</code>	<code>"table"</code> / <code>"figure"</code>	Kind (selects counter and config source)
<code>show-caption</code>	<code>auto</code> / <code>bool</code>	Show caption in continuation
<code>config</code>	<code>auto</code> / <code>dictionary</code>	<code>auto</code> reads the global config matching kind; otherwise uses the dict

```

1 // Standalone bilingual caption for a figure
2 #align(center)[
3   #rect(width: 6cm, height: 3cm, fill: gray.lighten(70%))
4   #bicap(
5     caption: [Custom Figure],
6     caption-en: [Custom Figure],
7     kind: "figure",
8     label: <fig:custom>,
9   )
10 ]

```

VIII.8 capfig Complete Parameters

Param	Type	Description
content	content (positional)	Figure body
caption	none / content	Main language caption
caption-en	none / content	English caption
label	none / label	Cross-reference label
refer-to	none / label	Continuation ref label
show-caption	auto / bool	Show caption in continuation
figure-above	auto / length	Space above figure (auto = global)
figure-below	auto / length	Space below figure (auto = global)
caption-above	auto / length	Image-caption gap (auto = global)
caption-leading	auto / length	Caption leading (auto = global)

The figure body and caption are always wrapped in a non-breakable block; the caption is always placed below the image; if `capfig-style.lang` is `auto` while `captab-style.lang` is not, the figure inherits the table's language setting.

VIII.9 capsubfig Complete Parameters

VIII.9.1 Subfigure Dict Structure

`subfigs` is an array of dicts; each supports:

Key	Required	Description
content	Yes	Subfigure body
subcaption	Cond.	Subcaption (used when <code>show-subcaption: true</code>)
label	Opt.	Cross-ref label, e.g. Figure 1.1a
label-style-override	Opt.	Per-item style override (overlay), see below

VIII.9.2 label-style-override dict keys

Key	Overrides
text-color	label text color
stroke	label stroke
bg	label background
bg-shape	background shape
bg-radius	rect radius
bg-inset	background padding

VIII.9.3 Function Parameters

All params besides `subfigs` accept `auto` (inherit global `capfig-style`):

- `columns` (auto / int): Columns per row; auto = single row.
- `caption` / `caption-en` / `label` / `refer-to` / `show-caption`: Same as `capfig`.
- `gutter`, `subcaption-pos`, `show-subcaption`, `show-subcaption-label`, `align`, `label-mode`, `label-style`, `label-font`, `label-size`, `label-offset`, `label-text-color`, `label-stroke`, `label-bg`, `label-bg-shape`, `label-bg-radius`, `label-bg-inset`, `label-sep`: Override the subfigure defaults from `capfig-style`.
- `figure-above`, `figure-below`, `caption-above`, `subcaption-above`, `subcaption-below`: Spacing overrides.

VIII.9.4 Label Style Parse Rules

The parser scans `label-style` left-to-right, locates the **first** format char (`a/A/1/i/I`); everything before is prefix, everything after is suffix. If no format char exists, the whole string becomes prefix with default format `"a"`.

- Roman numerals support 1–20; fallback to Arabic.
- `label-sep` auto rule: number format `-> "."` (e.g. "Figure 1.1.2"), letter/roman format `-> ""` (e.g. "Figure 1.1a").

VIII.9.5 Overlay with Circle Background

```

1  #capsubfig(
2    (
3      (content: rect(width: 4cm, height: 2.5cm, fill: yellow.lighten(70%))),
4      (content: rect(width: 4cm, height: 2.5cm, fill: red.lighten(70%)),
5        label-style-override: (bg: green, text-color: white)),
6    ),
7    columns: 2,
8    label-mode: "overlay",
9    label-style: "(1)",
10   label-bg: blue.lighten(60%),
11   label-bg-shape: "circle",
12   label-size: 10pt,
13   caption: [Circle bg + per-item override],
14 )

```

VIII.9.6 Multi-row Subfigures

Set `columns`: N; overflow auto-wraps, the last row shrinks to the actual count.

```

1  #capsubfig(
2    (
3      (content: rect(width: 2cm, height: 2cm, fill: red)),
4      (content: rect(width: 2cm, height: 2cm, fill: green)),
5      (content: rect(width: 2cm, height: 2cm, fill: blue)),
6      (content: rect(width: 2cm, height: 2cm, fill: orange)),

```

```
7      (content: rect(width: 2cm, height: 2cm, fill: purple)),
8    ),
9    columns: 3,                // 3 per row: 3+2
10   label-mode: "overlaid",
11   caption: [Five Subfigures],
12 )
```

VIII.10 captnote Complete Parameters

Param	Type	Description
width	auto / ratio / length	Width (three modes below)
justify	auto / bool	Justify (auto = global note-justify)
content	content positional	Table note body

Three width modes:

- width: auto (default): Match current captab width via table-width-config.
- width: 80% etc. ratio: Narrow to percentage, centered.
- width: 10cm etc. length: Fixed width, centered.

```
1 #captnote[Auto match table width]
2 #captnote(width: 70%)[70% width centered]
3 #captnote(width: 8cm)[Fixed 8cm]
4 #captnote(justify: false)[No justification]
```

VIII.11 capfnote Complete Parameters

Param	Type	Description
width	ratio / length	Default 100%; auto not supported
justify	auto / bool	Justify (auto = global capfig-style.note-justify)
content	content	Figure note body

```
1 #capfig(image("chart.png"), caption: [Results])
2 #capfnote(width: 90%)[
3   Source: 2024 Survey.
4 ]
```

VIII.12 Full Multilingual Rules

The following table lists prefix words and spacing rules for each language (pre = pre-supplement-number-spacing, sep = number-title-spacing):

lang	table	figure	pre	sep	continued-suffix
en	Table	Figure	" "	": "	(continued)
zh	表	图	0em	U+3000	(续)
zh-TW	表	圖	0em	U+3000	(續)
de	Tabelle	Abbildung	" "	": "	(Fortsetzung)
fr	Tableau	Figure	" "	" : "	(suite)
es	Tabla	Figura	" "	". "	(continuación)
it	Tabella	Figura	" "	". "	(continua)
pt	Tabela	Figura	" "	": "	(continuação)
ru	Таблица	Рисунок	" "	". "	(продолжение)
ja	表	図	0em	U+3000	(続き)
ko	표	그림	" "	". "	(계속)
ar	جدول	شكل	" "	": "	(تابع)
nl	Tabel	Figuur	" "	": "	(vervolg)
pl	Tabela	Rysunek	" "	". "	(cd.)
cs	Tabulka	Obrázek	" "	": "	(pokračování)
sv	Tabell	Figur	" "	". "	(forts.)
da	Tabel	Figur	" "	": "	(fortsat)
no	Tabell	Figur	" "	": "	(forts.)
fi	Taulukko	Kuva	" "	". "	(jatkoa)
tr	Tablo	şekil	" "	". "	(devam)
el	Πίνακας	Σχήμα	" "	". "	(συνέχεια)
he	טבלה	תמונה	" "	": "	(המשך)
hi	तालिका	चित्र	" "	": "	(जारी)
th	ตาราง	รูป	" "	" "	(ต่อ)
vi	Bảng	Hình	" "	". "	(tiếp theo)
fa	جدول	شكل	" "	": "	(ادامه)
ur	جدول	شكل	" "	": "	(جاری)

↔ = Right-to-left language

Auto-triggers post-table indent fix (after-indent: auto) **for:** zh, ja, ko, fr, vi, th. Any language can override via explicit after-indent: true/false.

RTL bilingual layout: for ar/he/fa/ur, the main-language and English lines are auto-swapped, the English line is wrapped in #text(dir: ltr)[...] to prevent direction confusion, and in monolingual mode the main-language body is wrapped in box[.].

Part IX

API Reference

This chapter provides auto-generated documentation from source code docstrings via tidy.

IX.1 Configuration Module (config.typ)

The configuration module provides global state management, multilingual text, utility functions, and the two main configuration functions.

- `cap-style()`
- `capfig-style()`
- `captab-style()`
- `resolve-lang-indent()`
- `set-figure-width()`
- `set-table-width()`

IX.1.1 cap-style

同时为表格和图片设置全局样式。共享参数会同时作用于两者；之后再调用 `captab-style` 或 `capfig-style` 可对某一类进行覆盖。Configure both table and figure global styles at once. Shared params are applied to both; a subsequent `captab-style` / `capfig-style` call can override for one type only.

Parameters

```
cap-style(  
  numbering-format,  
  use-chapter,  
  supplement,  
  supplement-en,  
  continued-prefix,  
  continued-prefix-en,  
  continued-suffix,  
  continued-suffix-en,  
  continued-mode,  
  continued-show-caption,  
  caption-size,  
  caption-weight,  
  caption-leading,  
  caption-above,  
  pre-supplement-number-spacing,  
  post-supplement-number-spacing,  
  number-title-spacing,  
  number-title-spacing-en,  
  lang,  
  enable-english-caption,  
  outline-bilingual,  
  outline-separator,  
  outline-newline,  
  after-indent,  
  note-above,  
  note-below,  
  note-size,  
  note-leading,  
  note-justify,  
  it  
) -> content
```

IX.1.2 capfig-style

Configure global figure and subfigure style within the body.

Parameters

```

capfig-style(
  numbering-format,
  use-chapter,
  supplement,
  supplement-en,
  continued-prefix,
  continued-prefix-en,
  continued-suffix,
  continued-suffix-en,
  continued-mode,
  continued-show-caption,
  caption-size,
  caption-weight,
  pre-supplement-number-spacing,
  post-supplement-number-spacing,
  number-title-spacing,
  number-title-spacing-en,
  lang,
  enable-english-caption,
  outline-bilingual,
  outline-separator,
  outline-newline,
  after-indent,
  figure-above,
  figure-below,
  caption-above,
  caption-leading,
  subcaption-above,
  subcaption-below,
  gutter,
  subcaption-pos,
  show-subcaption,
  show-subcaption-label,
  align,
  label-mode,
  label-style,
  label-font,
  label-size,
  label-offset,
  label-text-color,
  label-stroke,
  label-bg,
  label-bg-shape,
  label-bg-radius,
  label-bg-inset,
  label-sep,
  note-above,
  note-below,
  note-size,
  note-leading,
  note-justify,
  it
) -> content

```

IX.1.3 captab-style

Configure global table style for all cap-table, bicap and table-note calls within the body.

Parameters

```
captab-style(  
  caption-above,  
  caption-below,  
  table-below,  
  caption-leading,  
  numbering-format,  
  use-chapter,  
  supplement,  
  supplement-en,  
  continued-prefix,  
  continued-prefix-en,  
  continued-suffix,  
  continued-suffix-en,  
  continued-mode,  
  continued-show-caption,  
  caption-size,  
  caption-weight,  
  pre-supplement-number-spacing,  
  post-supplement-number-spacing,  
  number-title-spacing,  
  number-title-spacing-en,  
  lang,  
  enable-english-caption,  
  body-size,  
  body-leading,  
  cell-inset,  
  note-above,  
  note-below,  
  note-size,  
  note-leading,  
  note-justify,  
  outline-bilingual,  
  outline-separator,  
  outline-newline,  
  after-indent,  
  it  
) -> content
```

IX.1.4 resolve-lang-indent

共享语言与缩进修复解析函数。给定含 lang/after-indent 字段的配置， 返回 (lang, should-indent)。供 captab/capfig/captnote/capfnote 复用。 Shared language/indent resolution. Given a config dict with lang/after-indent fields, returns (lang, should-indent). Used by captab/capfig/captnote/capfnote.

Parameters

`resolve-lang-indent`(config)

IX.1.5 set-figure-width

Set figure width percentage (1-100) for capfnote auto-width matching.

Parameters

`set-figure-width`(percentage) -> `content`

IX.1.6 set-table-width

Set table width percentage (1-100) for all subsequent captab calls.

Parameters

```
set-table-width(  
  ,  
  percentage  
) -> content
```

IX.2 Caption Module (bicap.typ)

The caption module provides the core bilingual caption generation engine, supporting both main and continuation (continued table/figure) modes.

· `bicap()`

IX.2.1 bicap

独立双语标题函数，可用于表格 (kind: "table") 或图片 (kind: "figure")。 Standalone bilingual caption for tables (kind: "table") or figures (kind: "figure").

Parameters

```
bicap(  
  caption: none content ,  
  caption-en: none content ,  
  refer-to: none label ,  
  label: none label ,  
  kind: str ,  
  show-caption: auto bool ,  
  config: auto dictionary  
) -> content
```

caption none or content

主语言标题文本 Main language caption text

Default: none

caption-en none or content

英文标题文本（双语模式） English caption text (bilingual mode)

Default: none

refer-to none or label

引用原始表/图的标签（提供此参数则进入续表模式） Reference to the original table/figure label (enables continuation mode)

Default: none

label none or label

此标题的标签（用于交叉引用） Label for this caption (for cross-references)

Default: none

kind str

内容类型：“table” 或 “figure” Content type: “table” or “figure”

Default: "table"

show-caption `auto` or `bool`

续表/图是否显示标题文本（auto=自动根据 caption 是否提供决定） Whether to show caption text in continuation (auto = based on whether caption is provided)

Default: `auto`

config `auto` or `dictionary`

样式配置，auto 则从全局 table-style-config 获取 Style config, auto = use global table-style-config

Default: `auto`

IX.3 Table Module (table.typ)

The table module provides academic-standard three-line table creation and its aliases.

· `captab()`

IX.3.1 captab

创建三线表，支持 Markdown 语法、双语标题、续表和自定义线条。Create a three-line table with Markdown syntax, bilingual captions, continuation, and custom lines.

- `cols` (auto | int | array): 列配置 (auto=自动检测, int=等宽列数, array=列宽数组) / Column config
- `size` (auto | length): 表格内容字号 / Table content font size
- `leading` (auto | length): 表格内容行距 / Table content line spacing
- `inset` (auto | length | dictionary): 单元格内边距 / Cell padding
- `caption` (none | content): 主语言标题 / Main language caption
- `caption-en` (none | content): 英文标题 / English caption
- `refer-to` (none | label): 续表引用的原表标签 / Original label for continuation
- `show-caption` (auto | bool): 续表是否显示标题文本 / Show caption in continuation
- `hlines` (array): 额外横线，每项为 (row: int, start: int, end: none|int, stroke: stroke) / Extra h-rules
- `vlines` (array): 额外竖线，每项为 (col: int, start: int, end: none|int, stroke: stroke) / Extra v-rules
- `label` (none | label): 表格标签，用于交叉引用 / Label for cross-reference
- `content` (content): Markdown 风格的表格内容 / Markdown-style table content

Parameters

```
captab(  
  cols,  
  size,  
  leading,  
  inset,  
  caption,  
  caption-en,  
  refer-to,  
  show-caption,  
  hlines,  
  vlines,  
  label,  
  content  
)
```

IX.4 Note Module (note.typ)

The note module provides table and figure notes with auto-width matching and multiple width modes.

- `capfnote()`
- `captnote()`

IX.4.1 capfnote

创建图片注释(图注), 从 `figure-style-config` 读取样式, 默认宽度自动匹配。Create a figure note; reads style from `figure-style-config`, auto-matches figure width.

- `width` (auto | ratio | length): 图注宽度 / Note width
- `justify` (auto | bool): 是否两端对齐 / Text justification
- `content` (content): 图注内容 / Note content

Parameters

```
capfnote(  
  width,  
  justify,  
  content  
)
```

IX.4.2 captnote

创建表格注释(表注), 默认宽度自动匹配 `captab` 表格宽度。Create a table note; default width auto-matches `captab` width.

- `width` (auto | ratio | length): 表注宽度 / Note width
- `justify` (auto | bool): 是否两端对齐 (auto=使用全局配置) / Text justification

- `content (content)`: 表注内容 / Note content

Parameters

```
captnote(
  width,
  justify,
  content
)
```

IX.5 Figure Module (figure.typ)

The figure module provides single figure and multi-subfigure layout functions, supporting bilingual captions, overlay labels, and subcaptions.

- `capfig()`
- `capsubfig()`

IX.5.1 capfig

创建带双语标题的单个图片，标题始终在图片下方。 Create a single figure with bilingual caption; caption always below image.

- `content (content)`: 图片内容 (通常为 `image()` 调用) / Figure content (usually `image()`)
- `caption (none | content)`: 主语言标题 / Main language caption
- `caption-en (none | content)`: 英文标题 / English caption
- `label (none | label)`: 图片标签，用于交叉引用 / Figure label for cross-references
- `refer-to (none | label)`: 续图引用的原图标签 / Original label for continued figure
- `show-caption (auto | bool)`: 续图是否显示标题文本 / Show caption in continued figure
- `figure-above (auto | length)`: 图片上方间距 / Space above figure
- `figure-below (auto | length)`: 图片下方间距 / Space below figure
- `caption-above (auto | length)`: 标题与图片间距 / Space between image and caption
- `caption-leading (auto | length)`: 标题行距 / Caption line spacing

Parameters

```
capfig(
  content,
  caption,
  caption-en,
  label,
  refer-to,
  show-caption,
  figure-above,
  figure-below,
  caption-above,
  caption-leading
)
```

IX.5.2 capsubfig

创建多子图网格布局，支持子标题、覆盖标签和主双语标题。Create a multi-subfigure grid layout with subcaptions, overlay labels, and bilingual main caption.

每个子图为字典: (content: ..., subcaption: ..., label: ..., label-style-override: (...))。Each subfigure is a dict: (content: ..., subcaption: ..., label: ..., label-style-override: (...)).

- subfigs (array): 子图字典数组 / Array of subfigure dicts
- columns (auto | int): 每行列数, auto=所有子图在一行 / Columns per row
- caption (none | content): 主标题 (主语言) / Main caption (main language)
- caption-en (none | content): 主标题 (英文) / Main caption (English)
- label (none | label): 主图标签 / Main figure label
- refer-to (none | label): 续图引用的原图标签 / Original label for continuation
- show-caption (auto | bool): 续图是否显示标题 / Show caption in continuation
- gutter (auto | length): 子图水平间距 / Horizontal gap between subfigures
- subcaption-pos (auto | str): 子标题位置 “top” / “bottom”
- show-subcaption (auto | bool): 是否显示子标题 / Show subcaptions
- show-subcaption-label (auto | bool): 子标题是否含标签 / Subcaption includes label
- align (auto | str): 垂直对齐 “top” / “horizon” / “bottom”
- label-mode (auto | none | str): 标签模式 / Label mode (none or “overlay”)
- label-style (auto | str): 标签样式, 如 “(a)” / “图 a” / Label style
- label-font (auto | array): 标签字体 / Label font
- label-size (auto | length): 标签大小 / Label size
- label-offset (auto | tuple): 标签偏移 (dx, dy) / Label offset
- label-text-color (auto | color): 标签颜色 / Label text color
- label-stroke (auto | none | stroke): 标签描边 / Label stroke
- label-bg (auto | none | color): 标签背景 / Label background
- label-bg-shape (auto | str): 背景形状 / Background shape
- label-bg-radius (auto | length): 背景圆角 / Background radius
- label-bg-inset (auto | length): 背景内边距 / Background padding
- label-sep (auto | str): 子图引用分隔符 / Subfigure reference separator
- figure-above (auto | length): 图片上方间距 / Space above figure
- figure-below (auto | length): 图片下方间距 / Space below figure
- caption-above (auto | length): 主标题上方间距 / Space above main caption
- subcaption-above (auto | length): 子标题上方间距 / Space above subcaption
- subcaption-below (auto | length): 子标题下方间距 / Space below subcaption

Parameters

```
capsubfig(  
  subfigs,  
  columns,  
  caption,  
  caption-en,  
  label,  
  refer-to,  
  show-caption,  
  gutter,  
  subcaption-pos,  
  show-subcaption,  
  show-subcaption-label,  
  align,  
  label-mode,  
  label-style,  
  label-font,  
  label-size,  
  label-offset,  
  label-text-color,  
  label-stroke,  
  label-bg,  
  label-bg-shape,  
  label-bg-radius,  
  label-bg-inset,  
  label-sep,  
  figure-above,  
  figure-below,  
  caption-above,  
  subcaption-above,  
  subcaption-below  
)
```

Part X

Frequently Asked Questions

X.1 Why Markdown syntax for tables?

The Markdown table syntax (via `tablem`) is:

- Familiar to most users
- Easy to read and edit
- Quick to type
- Compatible with many editors

X.2 How do I create tables without captions?

Simply omit the `caption` parameter:

```
1 #captab()[  
2   | A | B |  
3   | - | - |  
4   | 1 | 2 |  
5 ]
```

X.3 Can I use regular Typst table syntax?

Yes! Use `bicap` to add a caption to any native Typst table:

```
1 #align(center)[  
2   #bicap(  
3     caption: [Regular Typst Table],  
4     caption-en: [Regular Typst Table],  
5     kind: "table",  
6   )  
7   #table(  
8     columns: 3,  
9     [A], [B], [C],  
10    [1], [2], [3],  
11  )  
12 ]
```

Table 15: Regular Typst Table

A	B	C
1	2	3

X.4 How do I reference tables and figures?

Use Typst's standard label and reference system:

```
1 #captab(caption: [...], label: <tab:example>)[...]  
2  
3 See @tab:example for details.
```

X.5 Why doesn't my continued table show the caption?

By default, continued tables only show the number when `caption` is not provided. To force showing the caption text:

```
1 #captab(  
2   refer-to: <tab:original>,  
3   caption: [Original Caption], // Provide caption text  
4   show-caption: true,          // Or force it  
5 ) [...]
```

X.6 How do I fix missing indentation after tables in Chinese?

The package automatically detects the language and fixes indentation (for Chinese, Japanese, etc.).

For manual control:

```
1 #show: captab-style.with(  
2   after-indent: true, // Force fix  
3   // or  
4   after-indent: false, // Disable fix  
5 )
```

X.7 How do I show bilingual captions in the table of contents?

```
1 #show: captab-style.with(  
2   outline-bilingual: true, // Enable bilingual outline  
3   outline-separator: " / ", // Separator  
4   outline-newline: false, // true=newline, false=same line  
5 )
```

Part XI

Changelog

XI.1 Version 0.0.1

Initial release with:

- `captab` three-line table support
- Bilingual caption support
- Continued tables and figures
- `capsubfig` subfigure layouts
- Table and figure notes
- 25+ language localization
- RTL language support (Arabic, Hebrew, Persian, Urdu)
- Comprehensive configuration system
- Configuration functions: `cap-style` (unified), `captab-style`, `capfig-style`, `set-table-width`

Part XII

Index