

jurlstify

Manual

URL typesetting with line-break opportunities
— the url package port for Typst.

typst

jurlstify

0.3.0

MIT

SchrodingerBlume^{*}

Contents

Overview	2
Quick Start	2
Reference	3
jurlstify	3
jurl	4
jurlstify-links	4
Examples	5
Migration (0.2.x → 0.3.0)	6

^{*}<https://github.com/SchrodingerBlume>

Overview

This package ports the line-breaking logic of L^AT_EX's *url package*¹ to Typst. Typst breaks bare URLs only at a fixed, non-configurable set of characters. A URL that contains none of them overflows the margin, and the available break points can produce uneven word spacing in justified paragraphs. This package inserts break opportunities at a configurable set of characters, and can add further breaks at a fixed interval inside long runs.

The options fall into two groups:

Where a line may break: `break-chars`, `big-break-chars`, `no-break-chars`, `break-at-literal-hyphens`, `extra-break-every`.

Whether to show a visible hyphen at a break: `show-hyphens-after-delimiters` (for delimiter breaks) and `show-hyphens-at-extra-breaks` (for extra breaks).

① By default, the package breaks only at delimiter characters and shows no hyphen, matching the `url` package. The hyphen is omitted because it could be mistaken for part of the URL itself.

Quick Start

```
#import "@preview/jurlstify:0.3.0": jurlstify, jurl, jurlstify-links

// Render a URL string with break opportunities
#jurlstify("https://example.com/very/long/path?query=value&more=stuff")

// Clickable link – same breaking, wrapped in link()
#jurl("https://example.com/very/long/path?query=value")

// Apply automatically to every link() in the document
#show: jurlstify-links.with()
#link("https://example.com/automatically/handled")
```

¹<https://ctan.org/pkg/url>

Reference

The three default character sets are exported as `break-chars-default`, `big-break-chars-default`, and `no-break-chars-default`, so you can extend them — e.g. `break-chars: break-chars-default + ("~",)`.

jurlstify

Render a URL string as inline content, with line-break opportunities at positions compatible with L^AT_EX's `url` package. Automatic hyphenation and ligatures are disabled inside the URL, matching that package's behaviour.

With no options set, only the delimiter breaks are active and no hyphen is shown — the copy-safe default. Opt into extra breaks and visible hyphens with the options below.

url `str` *(required)*

The URL string to render.

break-chars `array`

Characters after which a normal break may occur. Defaults to `. @ \ / ! _ | ; > ] ) , ? & ' + = #`.

big-break-chars `array`

Higher-priority break characters. Defaults to `(":",)`.

no-break-chars `array`

Characters that drop a break landing immediately before them. Defaults to `("(", "[", "{", "<")`.

break-at-literal-hyphens `bool`

Allow a break after a literal - already present in the URL. Defaults to `false`, so `my-domain.com` never breaks mid-word.

extra-break-every `none` `int`

Insert one extra break opportunity every N consecutive non-break characters, for long unbroken runs. Defaults to `none` (disabled).

show-hyphens-after-delimiters `bool`

Show a - at a delimiter break when the line breaks there. Defaults to `false`. Also places a - after punctuation, e.g. a line ending in `com/-`.

show-hyphens-at-extra-breaks `bool`

Show a - at an **extra-break-every** break when the line breaks there. Defaults to **false**.

show-spaces-as `str` `none`

How to render a literal space in the URL: **"nbsp"** (non-breaking space), **"normal"** (ordinary breakable space), or **none** (remove it). Defaults to **"nbsp"**.

stretch `bool`

Make break points stretchable so URL-internal lines reach the right margin in justified paragraphs, at the cost of small gaps at breaks. Defaults to **false**.

font `auto` `str` `array`

URL font; **auto** inherits the body font. Defaults to **auto**.

size `auto` `length`

Font size; **auto** inherits from context. Defaults to **auto**.

fill `auto` `color`

Text colour; **auto** inherits from context. Defaults to **auto**.

jurl

A clickable hyperlink whose visible text is formatted by **jurlstify**. Accepts every **jurlstify** option as a trailing keyword argument.

dest `str`

(required)

Link destination (the URL).

display `none` `str` `content`

Visible content. **none** shows **dest** itself (formatted by **jurlstify**); a string is likewise formatted; **content** is used verbatim. Defaults to **none**.

jurlstify-links

A document-level show rule that routes every **link("http://...")** whose body equals its destination through **jurlstify**. Links with explicit display content are left untouched. All **jurlstify** options are forwarded.

body `content`

(required)

The content the rule applies to.

Examples

Break at delimiters only (default) versus showing a hyphen at each delimiter break — shown in a narrow column so the wrapping is visible:

```
#jurlstify("https://example.com/very/long/path/to/resource")
#jurlstify("https://example.com/very/long/path/to/resource",
  show-hyphens-after-delimiters: true)
```

default

```
https://example.com/very/
long/path/to/resource
```

show-hyphens-after-delimiters

```
https://example.com/-
very/long/path/to/-
resource
```

A long run with no delimiter, broken every 1 chars with a hyphen shown:

```
#jurlstify("https://example.com/averylongpathsegmentwithnobreaks",
  extra-break-every: 1)
#jurlstify("https://example.com/averylongpathsegmentwithnobreaks",
  extra-break-every: 1, show-hyphens-at-extra-breaks: true)
```

default

```
https://example.com/avery
longpathsegmentwithnobrea
ks
```

show-hyphens-at-extra-breaks

```
https://example.com/aver-
ylongpathsegmentwithnob-
reaks
```

Applying the show rule to a whole document:

```
#show: jurlstify-links.with(show-hyphens-after-delimiters: true)
```

```
The homepage is #link("https://example.com/very/long/path").
// auto-formatted
```

```
See #link("https://example.com", "the docs").
// untouched
```

```
The homepage is https://example.-
com/very/long/path/to/resource.

See the docs.
```

Migration (0.2.x → 0.3.0)

0.2.x	0.3.0
hyphens	break-at-literal-hyphens
every	extra-break-every
breaks	break-chars
big-breaks	big-break-chars
no-breaks	no-break-chars
show-hyphen	show-hyphens-after-delimiters + show-hyphens-at-extra-breaks
spaces: "nobreak"	show-spaces-as: "nbsp"
spaces: "break"	show-spaces-as: "normal"
spaces: "strip"	show-spaces-as: none

① Compatibility

0.3.0 is a clean rename with no old-name aliases. Code written for older versions keeps working by pinning `@preview/jurlstify:0.2.x`.