

*Elements of Photonics, Volume II: For Fiber and Integrated Optics.* Keigo Iizuka  
Copyright © 2002 John Wiley & Sons, Inc.  
ISBNs: 0-471-40815-8 (Hardback); 0-471-22137-6 (Electronic)

# ELEMENTS OF PHOTONICS

## Volume II

## WILEY SERIES IN PURE AND APPLIED OPTICS

Founded by Stanley S. Ballard, University of Florida

EDITOR: Bahaa E.A. Saleh, Boston University

BEISER. *Holographic Scanning*

BERGER. SCHUNN. *Practical Color Measurement*

BOYD. *Radiometry and The Detection of Optical Radiation*

BUCK. *Fundamentals of Optical Fibers*

CATHEY. *Optical Information Processing and Holography*

CHUANG. *Physics of Optoelectronic Devices*

DELONE AND KRAINOV. *Fundamentals of Nonlinear Optics of Atomic Gases*

DERENIAK AND BOREMAN. *Infrared Detectors and Systems*

DERENIAK AND CROWE. *Optical Radiation Detectors*

DE VANY. *Master Optical Techniques*

GASKILL. *Linear Systems, Fourier Transform, and Optics*

GOODMAN. *Statistical Optics*

HOBBS. *Building Electro-Optical Systems: Making It All Work*

HUDSON. *Infrared System Engineering*

JUDD AND WYSZECKI. *Color in Business, Science, and Industry*. Third Edition

KAFRI AND GLATT. *The Physics of Moire Metrology*

KAROW. *Fabrication Methods for Precision Optics*

KLEIN AND FURTAK. *Optics*, Second Edition

MALACARA. *Optical Shop Testing*, Second Edition

MILONNI AND EBERLY. *Lasers*

NASSAU. *The Physics and Chemistry of Color*

NIETO-VESPERINAS. *Scattering and Diffraction in Physical Optics*

O'SHEA. *Elements of Modern Optical Design*

SALEH AND TEICH. *Fundamentals of Photonics*

SCHUBERT AND WILHELMI. *Nonlinear Optics and Quantum Electronics*

SHEN. *The Principles of Nonlinear Optics*

UDD. *Fiber Optic Sensors: An Introduction for Engineers and Scientists*

UDD. *Fiber Optic Smart Structures*

VANDERLUGT. *Optical Signal Processing*

VEST. *Holographic Interferometry*

VINCENT. *Fundamentals of Infrared Detector Operation and Testing*

WILLIAMS AND BECKLUND. *Introduction to the Optical Transfer Function*

WYSZECKI AND STILES. *Color Science: Concepts and Methods, Quantitative Data and Formulae*, Second Edition

XU AND STROUD. *Acousto-Optic Devices*

YAMAMOTO. *Coherence, Amplification, and Quantum Effects in Semiconductor Lasers*

YARIV AND YEH. *Optical Waves in Crystals*

YEH. *Optical Waves in Layered Media*

YEH. *Introduction to Photorefractive Nonlinear Optics*

YEH AND GU. *Optics of Liquid Crystal Displays*

IIZUKA. *Elements of Photonics Volume I: In Free Space and Special Media*

IIZUKA. *Elements of Photonics Volume II: For Fiber and Integrated Optics*

---

# ELEMENTS OF PHOTONICS

## Volume II For Fiber and Integrated Optics

---

Keigo Iizuka

University of Toronto



**WILEY-INTERSCIENCE**  
A JOHN WILEY & SONS, INC., PUBLICATION

Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where John Wiley & Sons, Inc., is aware of a claim, the product names appear in initial capital or ALL CAPITAL LETTERS. Readers, however, should contact the appropriate companies for more complete information regarding trademarks and registration.

Copyright © 2002 by John Wiley & Sons, Inc., New York. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic or mechanical, including uploading, downloading, printing, decompiling, recording or otherwise, except as permitted under Sections 107 or 108 of the 1976 United States Copyright Act, without the prior written permission of the Publisher. Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 605 Third Avenue, New York, NY 10158-0012, (212) 850-6011, fax (212) 850-6008, E-Mail: PERMREQ@WILEY.COM.

This publication is designed to provide accurate and authoritative information in regard to the subject matter covered. It is sold with the understanding that the publisher is not engaged in rendering professional services. If professional advice or other expert assistance is required, the services of a competent professional person should be sought.

**ISBN 0-471-22137-6**

This title is also available in print as ISBN 0-471-40815-8.

For more information about Wiley products, visit our web site at [www.Wiley.com](http://www.Wiley.com).

Kuro, starling dear,  
nature's gentle companion  
from start to finish

---

# CONTENTS

## Volume I

---

### Preface

xxv

### 1 Fourier Optics: Concepts and Applications

1

- 1.1 Plane Waves and Spatial Frequency / 1
  - 1.1.1 Plane Waves / 1
  - 1.1.2 Spatial Frequency / 4
- 1.2 Fourier Transform and Diffraction Patterns in Rectangular Coordinates / 9
- 1.3 Fourier Transform in Cylindrical Coordinates / 16
- 1.4 Special Functions in Photonics and Their Fourier Transforms / 20
  - 1.4.1 Rectangle Function / 20
  - 1.4.2 Triangle Function / 21
  - 1.4.3 Sign and Step Functions / 25
  - 1.4.4 Circle Function / 25
  - 1.4.5 Delta Function / 28
  - 1.4.6 Shah Function (Impulse Train Function) / 30
  - 1.4.7 Diffraction from an Infinite Array of Similar Apertures with Regular Spacing / 32
  - 1.4.8 Diffraction from an Infinite Array of Similar Apertures with Irregular Spacing / 36
  - 1.4.9 Diffraction from a Finite Array / 37
- 1.5 The Convex Lens and Its Functions / 40
  - 1.5.1 Phase Distribution After a Plano-Convex Lens / 41
  - 1.5.2 Collimating Property of a Convex Lens / 42
  - 1.5.3 Imaging Property of a Convex Lens / 43
  - 1.5.4 Fourier Transformable Property of a Convex Lens / 46
  - 1.5.5 How Can a Convex Lens Perform the Fourier Transform? / 50
  - 1.5.6 Invariance of the Location of the Input Pattern to the Fourier Transform / 50
- 1.6 Spatial Frequency Approaches in Fourier Optics / 52
  - 1.6.1 Solution of the Wave Equation by Means of the Fourier Transform / 52
  - 1.6.2 Rayleigh–Sommerfeld Integral / 58
  - 1.6.3 Identifying the Spatial Frequency Components / 60

1.7	Spatial Filters	/	61
1.7.1	Image Processing Filters	/	61
1.7.2	Optical Correlators	/	64
1.7.2.1	<i>Vander Lugt Correlator</i>	/	64
1.7.2.2	<i>Detailed Analysis of the Vander Lugt Correlator</i>	/	66
1.7.2.3	<i>Joint Transform Correlator</i>	/	70
1.7.2.4	<i>Comparison Between VLC and JTC</i>	/	72
1.7.3	Rotation and Scaling	/	73
1.7.4	Real-Time Correlation	/	77
1.7.5	Cryptograph	/	78
1.8	Holography	/	81
1.8.1	Gabor-Type Hologram	/	82
1.8.2	Off-Axis Hologram	/	85
1.8.3	Pseudoscopic Image	/	87
1.8.4	Volume Hologram	/	87
1.8.5	Applications of Holography	/	92
1.8.5.1	<i>Three-Dimensional Displays</i>	/	92
1.8.5.2	<i>Microfiche Recording</i>	/	93
1.8.5.3	<i>Measurement of Displacement</i>	/	93
1.8.5.4	<i>Measurement of Vibration</i>	/	95
1.8.5.5	<i>Nonoptical Holographies</i>	/	95
1.8.5.6	<i>Computer-Generated Holograms</i>	/	97
1.8.5.7	<i>Holographic Video Display</i>	/	99
	Problems	/	101
	References	/	108
<b>2</b>	<b>Boundaries, Near-Field Optics, and Near-Field Imaging</b>		<b>110</b>
2.1	Boundary Conditions	/	110
2.2	Snell's Law	/	112
2.3	Transmission and Reflection Coefficients	/	113
2.3.1	Transmission and Reflection Coefficients (at Normal Incidence)	/	114
2.3.2	Transmission and Reflection Coefficients (at an Arbitrary Incident Angle)	/	118
2.3.3	Impedance Approach to Calculating Transmission and Reflection Coefficients	/	124
2.4	Transmittance and Reflectance (at an Arbitrary Incident Angle)	/	124
2.5	Brewster's Angle	/	127
2.6	Total Internal Reflection	/	130
2.6.1	Bends in a Guide	/	131
2.7	Wave Expressions of Light	/	132
2.7.1	Fields Near the Boundary	/	133
2.8	The Evanescent Wave	/	134
2.8.1	Transmission and Reflection Coefficients for Total Internal Reflection	/	135

2.8.2	Goos-Hänchen Shift /	141
2.8.3	Evanescent Field and Its Adjacent Fields /	142
2.8.4	$k$ Diagrams for the Graphical Solution of the Evanescent Wave /	145
2.9	What Generates the Evanescent Waves? /	147
2.9.1	Structures for Generating Evanescent Waves /	147
2.10	Diffraction-Unlimited Images out of the Evanescent Wave /	150
2.10.1	Resolution of a Lens-Type Microscope /	150
2.10.2	Near-Field Optical Microscopes /	152
2.10.2.1	<i>Photon Tunneling Microscope</i> /	152
2.10.2.2	<i>Scanning Near-Field Optical Microscope (SNOM)</i> /	154
2.10.3	Probes to Detect the Evanescent Field /	154
2.10.4	Apertures of the SNOM Probes /	158
2.10.5	Modes of Excitation of the SNOM Probes /	158
2.10.6	SNOM Combined with AFM /	160
2.10.7	Concluding Remarks /	161
	Problems /	163
	References /	164

### 3 Fabry–Pérot Resonators, Beams, and Radiation Pressure 166

3.1	Fabry–Pérot Resonators /	166
3.1.1	Operating Principle of the Fabry–Pérot Resonator /	167
3.1.2	Transmittance and Reflectance of the Fabry–Pérot Resonator with an Arbitrary Angle of Incidence /	170
3.2	The Scanning Fabry–Pérot Spectrometer /	176
3.2.1	Scanning by the Reflector Spacing /	177
3.2.1.1	<i>Fabry–Pérot Resonator with a Fixed Resonator Spacing (Etalon)</i> /	179
3.2.1.2	<i>Monochromatic Incident Light with Scanned Reflector Spacing</i> /	179
3.2.1.3	<i>Free Spectral Range (FSR)</i> /	179
3.2.2	Scanning by the Angle of Incidence /	184
3.2.3	Scanning by the Index of Refraction /	187
3.2.4	Scanning by the Frequency of Incident Light /	190
3.3	Resolving Power of the Fabry–Pérot Resonator /	192
3.4	Practical Aspects of Operating the Fabry–Pérot Interferometer /	199
3.4.1	Methods for Parallel Alignment of the Reflectors /	199
3.4.2	Method for Determining the Spacing Between the Reflectors /	202
3.4.3	Spectral Measurements Without Absolute Measurement of $d$ /	203
3.5	The Gaussian Beam as a Solution of the Wave Equation /	205
3.5.1	Fundamental Mode /	206



3.5.2	Properties of the $q$ Parameter	/	208
3.5.2.1	Beam Waist	/	208
3.5.2.2	Location of the Waist	/	208
3.5.2.3	Radius of Curvature of the Wavefront	/	208
3.5.3	With the Origin at the Waist	/	209
3.5.3.1	Focal Parameters	/	209
3.5.3.2	Correction Factor	/	210
3.5.4	Gaussian Beam Expressions	/	211
3.5.4.1	Amplitude Distribution	/	211
3.5.4.2	Intensity Distribution	/	211
3.5.4.3	Angle of the Far-Field Divergence	/	212
3.5.4.4	Depth of Focus	/	213
3.6	Transformation of a Gaussian Beam by a Lens	/	214
3.6.1	Transformation of the $q$ Parameter by a Lens	/	215
3.6.2	Size of the Waist of the Emergent Beam	/	216
3.6.3	Location of the Waist of the Emergent Beam	/	217
3.6.4	Rayleigh Range of the Emergent Beam	/	218
3.6.5	Angle of the Far-Field Divergence of the Emergent Beam	/	218
3.6.6	Comparison with Ray Optics	/	218
3.6.7	Summary of the Equations of the Transformation by a Lens	/	219
3.6.8	Beam Propagation Factor $m^2$	/	220
3.7	Hermite Gaussian Beam (Higher Order Modes)	/	223
3.8	The Gaussian Beam in a Spherical Mirror Cavity	/	227
3.9	Resonance Frequencies of the Cavity	/	232
3.10	Practical Aspects of the Fabry–Pérot Interferometer	/	234
3.10.1	Plane Mirror Cavity	/	234
3.10.2	General Spherical Mirror Cavity	/	235
3.10.3	Focal Cavity	/	235
3.10.4	Confocal Cavity	/	236
3.11	Bessel Beams	/	237
3.11.1	Features of the Bessel Beam	/	237
3.11.2	Practical Applications of the Bessel Beam	/	239
3.11.2.1	Precision Optical Measurement	/	239
3.11.2.2	Power Transport	/	239
3.11.2.3	Nonlinear Optics	/	239
3.11.3	One-Dimensional Model	/	239
3.11.4	Mathematical Expressions for the Bessel Beam	/	242
3.11.5	Methods of Generating Bessel Beams	/	245
3.12	Manipulation with Light Beams	/	249
3.12.1	Radiation Pressure of Laser Light	/	249
3.12.2	Optical Tweezers	/	251
3.13	Laser Cooling of Atoms	/	254
	Problems	/	255
	References	/	260

**4 Propagation of Light in Anisotropic Crystals 263**

- 4.1 Polarization in Crystals / 264
- 4.2 Susceptibility of an Anisotropic Crystal / 266
- 4.3 The Wave Equation in an Anisotropic Medium / 268
- 4.4 Solving the Generalized Wave Equation in Uniaxial Crystals / 269
  - 4.4.1 Graphical Derivation of the Condition of Propagation in a Uniaxial Crystal / 270
  - 4.4.2 Analytical Representation of the Conditions of Propagation in a Uniaxial Crystal / 273
  - 4.4.3 Wavenormal and Ray Direction / 275
  - 4.4.4 Derivation of the Effective Index of Refraction / 280
- 4.5 Graphical Methods / 282
  - 4.5.1 Wavevector Method / 282
  - 4.5.2 Indicatrix Method / 285
- 4.6 Treatment of Boundary Problems Between Anisotropic Media by the Indicatrix Method / 292
  - 4.6.1 Refraction of the e-Wave at the Boundary of Anisotropic Media / 292
  - 4.6.2 Reflection of the e-Wave at the Boundary of Anisotropic Media / 294
  - 4.6.3 Total Internal Reflection of the e-Wave at the Boundary of Anisotropic Media / 296
- Problems / 298
- References / 301

**5 Optical Properties of Crystals Under Various External Fields 302**

- 5.1 Expressing the Distortion of the Indicatrix / 302
- 5.2 Electrooptic Effects / 304
  - 5.2.1 Pockels Electrooptic Effect / 304
  - 5.2.2 Kerr Electrooptic Effect / 316
- 5.3 Elastooptic Effect / 317
- 5.4 Magneto optic Effect / 326
  - 5.4.1 Faraday Effect / 326
  - 5.4.2 Cotton-Mouton Effect / 327
- 5.5 Optical Isolator / 327
  - 5.5.1 Polarization-Dependent Optical Isolator / 328
  - 5.5.2 Polarization-Independent Optical Isolator / 330
- 5.6 Photorefractive Effect / 331
- 5.7 Optical Amplifier Based on the Photorefractive Effect / 334
  - 5.7.1 Enhanced Photorefractive Effect by an External Electric Field / 334
  - 5.7.2 Energy Transfer in the Crystal / 335
  - 5.7.3 Optical Amplifier Structure / 338
- 5.8 Photorefractive Beam Combiner for Coherent Homodyne Detection / 339
- 5.9 Optically Tunable Optical Filter / 341

5.10	Liquid Crystals	/	341
5.10.1	Types of Liquid Crystals	/	341
5.10.1.1	<i>Cholesteric</i>	/	342
5.10.1.2	<i>Smectic</i>	/	343
5.10.1.3	<i>Nematic</i>	/	343
5.10.1.4	<i>Discotic</i>	/	344
5.10.2	Molecular Orientations of the Nematic Liquid Crystal Without an External Field	/	344
5.10.3	Molecular Reorientation of the Nematic Liquid Crystal with an External Electric Field	/	345
5.10.4	Liquid Crystal Devices	/	346
5.10.4.1	<i>Liquid Crystal Fabry–Pérot Resonator</i>	/	346
5.10.4.2	<i>Liquid Crystal Rotatable Waveplate</i>	/	346
5.10.4.3	<i>Liquid Crystal Microlens</i>	/	347
5.10.4.4	<i>Twisted Nematic (TN) Liquid Crystal Spatial Light Modulator (TNSLM)</i>	/	349
5.10.4.5	<i>Electrically Addressed Spatial Light Modulator (EASLM)</i>	/	350
5.10.4.6	<i>Optically Addressed Spatial Light Modulator (OASLM)</i>	/	351
5.10.4.7	<i>Polymer-Dispersed Liquid Crystal (PDLC)-Type Spatial Light Modulator (SLM)</i>	/	352
5.10.5	Guest–Host Liquid Crystal Cell	/	353
5.10.6	Ferroelectric Liquid Crystal	/	354
5.11	Dye-Doped Liquid Crystal	/	357
	Problems	/	358
	References	/	359

## **6 Polarization of Light**

**362**

6.1	Introduction	/	363
6.2	Circle Diagrams for Graphical Solutions	/	365
6.2.1	Linearly Polarized Light Through a Retarder	/	365
6.2.2	Sign Conventions	/	368
6.2.3	Handedness	/	374
6.2.4	Decomposition of Elliptically Polarized Light	/	375
6.2.5	Transmission of an Elliptically Polarized Wave Through a $\lambda/4$ Plate	/	377
6.3	Various Types of Retarders	/	378
6.3.1	Waveplates	/	379
6.3.2	Compensator	/	380
6.3.3	Fiber-Loop Retarder	/	382
6.4	How to Use Waveplates	/	385
6.4.1	How to Use a Full-Waveplate	/	385
6.4.2	How to Use a Half-Waveplate	/	385
6.4.3	How to Use a Quarter-Waveplate	/	386
6.4.3.1	<i>Conversion from Linear to Circular Polarization by Means of a <math>\lambda/4</math> Plate</i>	/	386

6.4.3.2	<i>Converting Light with an Unknown State of Polarization into Linearly Polarized Light by Means of a <math>\lambda/4</math> Plate</i>	/ 389
6.4.3.3	<i>Measuring the Retardance of a Sample</i>	/ 392
6.4.3.4	<i>Measurement of Retardance of an Incident Field</i>	/ 393
6.5	Linear Polarizers	/ 394
6.5.1	Dichroic Polarizer	/ 394
6.5.2	Birefringence Polarizer or Polarizing Prism	/ 402
6.5.3	Birefringence Fiber Polarizer	/ 404
6.5.4	Polarizers Based on Brewster's Angle and Scattering	/ 407
6.5.5	Polarization Based on Scattering	/ 408
6.6	Circularly Polarizing Sheets	/ 409
6.6.1	Antiglare Sheet	/ 409
6.6.2	Monitoring the Reflected Light with Minimum Loss	/ 411
6.7	Rotators	/ 412
6.7.1	Saccharimeter	/ 417
6.7.2	Antiglare TV Camera	/ 419
6.8	The Jones Vector and the Jones Matrix	/ 421
6.8.1	The Jones Matrix of a Polarizer	/ 422
6.8.2	The Jones Matrix of a Retarder	/ 424
6.8.3	The Jones Matrix of a Rotator	/ 425
6.8.4	Eigenvectors of an Optical System	/ 428
6.9	States of Polarization and Their Component Waves	/ 431
6.9.1	Major and Minor Axes of an Elliptically Polarized Wave	/ 431
6.9.2	Azimuth of the Principal Axes of an Elliptically Polarized Wave	/ 434
6.9.3	Ellipticity of an Elliptically Polarized Wave	/ 438
6.9.4	Conservation of Energy	/ 437
6.9.5	Relating the Parameters of an Elliptically Polarized Wave to Those of Component Waves	/ 439
6.9.6	Summary of Essential Formulas	/ 439
	Problems	/ 446
	References	/ 449

## **7 How to Construct and Use the Poincaré Sphere**

**451**

7.1	Component Field Ratio in the Complex Plane	/ 452
7.2	Constant Azimuth $\theta$ and Ellipticity $\epsilon$ Lines in the Component Field Ratio Complex Plane	/ 455
7.2.1	Lines of Constant Azimuth $\theta$	/ 455
7.2.2	Lines of Constant Ellipticity $\epsilon$	/ 458
7.3	Argand Diagram	/ 459
7.3.1	Solution Using a Ready-Made Argand Diagram	/ 460
7.3.2	Orthogonality Between Constant $\theta$ and $\epsilon$ Lines	/ 465
7.3.3	Solution Using a Custom-Made Argand Diagram	/ 468

7.4	From Argand Diagram to Poincaré Sphere /	469
7.4.1	Analytic Geometry of Back-Projection /	469
7.4.2	Poincaré Sphere /	474
7.5	Poincaré Sphere Solutions for Retarders /	479
7.6	Poincaré Sphere Solutions for Polarizers /	485
7.7	Poincaré Sphere Traces /	490
7.8	Movement of a Point on the Poincaré Sphere /	494
7.8.1	Movement Along a Line of Constant Longitude (or Constant $\theta$ Line) /	494
7.8.2	Movement Along a Line of Constant Latitude (or Constant $\beta$ Line) /	497
	Problems /	501
	References /	503
<b>8</b>	<b>Phase Conjugate Optics</b>	<b>504</b>
8.1	The Phase Conjugate Mirror /	504
8.2	Generation of a Phase Conjugate Wave Using a Hologram /	504
8.3	Expressions for Phase Conjugate Waves /	507
8.4	Phase Conjugate Mirror for Recovering Phasefront Distortion /	508
8.5	Phase Conjugation in Real Time /	511
8.6	Picture Processing by Means of a Phase Conjugate Mirror /	512
8.7	Distortion-Free Amplification of Laser Light by Means of a Phase Conjugate Mirror /	513
8.8	Self-Tracking of a Laser Beam /	514
8.9	Picture Processing /	519
8.10	Theory of Phase Conjugate Optics /	521
8.10.1	Maxwell's Equations in a Nonlinear Medium /	521
8.10.2	Nonlinear Optical Susceptibilities $\chi^{(2)}$ and $\chi^{(3)}$ /	523
8.10.3	Coupled Wave Equations /	526
8.10.4	Solutions with Bohr's Approximation /	529
8.11	The Gain of Forward Four-Wave Mixing /	533
8.12	Pulse Broadening Compensation by Forward Four-Wave Mixing /	537
	Problems /	541
	References /	543
<b>Appendix A</b>	<b>Derivation of the Fresnel–Kirchhoff Diffraction Formula from the Rayleigh–Sommerfeld Diffraction Formula</b>	<b>545</b>
<b>Appendix B</b>	<b>Why the Analytic Signal Method is Not Applicable to the Nonlinear System</b>	<b>547</b>
<b>Appendix C</b>	<b>Derivation of <math>P_{NL}</math></b>	<b>551</b>
	<b>Answers to Problems</b>	<b>554</b>
	<b>Index</b>	<b>I-1</b>

---

# CONTENTS

## Volume II

---

<b>Preface</b>	<b>xxv</b>
<b>9 Planar Optical Guides for Integrated Optics</b>	<b>605</b>
9.1 Classification of the Mathematical Approaches to the Slab Optical Guide /	606
9.2 Wave Optics Approach /	607
9.3 Characteristic Equations of the TM Modes /	610
9.3.1 Solutions for $K$ and $\gamma$ /	610
9.3.2 Examples Involving TM Modes /	612
9.4 Cross-Sectional Distribution of Light and its Decomposition into Component Plane Waves /	615
9.5 Effective Index of Refraction /	619
9.6 TE Modes /	620
9.7 Other Methods for Obtaining the Characteristic Equations /	622
9.7.1 Coefficient Matrix Method /	623
9.7.2 Transmission Matrix Method (General Guides) /	625
9.7.3 Transmission Matrix Method (Symmetric Guide) /	630
9.7.4 Modified Ray Model Method /	636
9.8 Asymmetric Optical Guide /	638
9.9 Coupled Guides /	643
9.9.1 Characteristic Equations of the Coupled Slab Guide /	643
9.9.2 Amplitude Distribution in the Coupled Slab Guide /	646
9.9.3 Coupling Mechanism of the Slab Guide Coupler /	651
Problems /	652
References /	654
<b>10 Optical Waveguides and Devices for Integrated Optics</b>	<b>655</b>
10.1 Rectangular Optical Waveguide /	655
10.1.1 Assumptions /	655

10.1.2	Characteristic Equation for the Rectangular Guide /	657
10.1.3	A Practical Example /	659
10.2	Effective Index Method for Rectangular Optical Guides /	661
10.3	Coupling Between Rectangular Guides /	664
10.4	Conflexion /	666
10.4.1	Conflexion Lens /	667
10.5	Various Kinds of Rectangular Optical Waveguides for Integrated Optics /	670
10.5.1	Ridge Guide /	670
10.5.2	Rib Guide /	670
10.5.3	Strip-Loaded Guide /	671
10.5.4	Embedded Guide /	671
10.5.5	Immersed Guide /	672
10.5.6	Bulge Guide /	672
10.5.7	Metal Guide /	672
10.5.8	Buffered Metal Guide /	672
10.5.9	Photochromic Flexible Guide /	672
10.6	Power Dividers /	673
10.6.1	The Y Junction and Arrayed-Waveguide Grating /	673
10.6.2	Power Scrambler /	677
10.7	Optical Magic T /	678
10.8	Electrode Structures /	680
10.8.1	Laminated Electrodes /	680
10.8.2	Electrode Configurations /	681
	10.8.2.1 <i>Applying a Longitudinal Field to Bulk Waves</i> /	681
	10.8.2.2 <i>Applying a Transverse Field to Bulk Waves</i> /	681
	10.8.2.3 <i>Vertical Field in an Embedded Guide</i> /	683
	10.8.2.4 <i>Vertical Field in Adjacent Embedded Guides</i> /	683
	10.8.2.5 <i>Velocity Matched Mach–Zehnder Interferometer</i> /	683
	10.8.2.6 <i>Horizontal Field in an Embedded Guide</i> /	683
	10.8.2.7 <i>Horizontal Field in a Rib Guide</i> /	684
	10.8.2.8 <i>Horizontal and Vertical Fields</i> /	684
	10.8.2.9 <i>Periodic Vertical Field</i> /	684
	10.8.2.10 <i>Periodic Horizontal Field</i> /	684
	10.8.2.11 <i>Trimming Electrodes</i> /	684
	10.8.2.12 <i>Switching Electrodes</i> /	685
10.9	Mode Converter /	685
	Problems /	688
	References /	690

**11 Modes and Dispersion in Optical Fibers****692**

- 11.1 Practical Aspects of Optical Fibers / 693
  - 11.1.1 Numerical Aperture of a Fiber / 693
  - 11.1.2 Transmission Loss of Fibers / 694
  - 11.1.3 Loss Increase Due to Hydrogen and Gamma-Ray Irradiation / 695
  - 11.1.4 Dispersion / 699
  - 11.1.5 Mode Dispersion / 699
  - 11.1.6 Material and Waveguide Dispersions / 701
  - 11.1.7 Various Kinds of Optical Fibers / 703
    - 11.1.7.1 *Multimode Step-Index Fiber* / 703
    - 11.1.7.2 *Multimode Graded-Index Fiber* / 705
    - 11.1.7.3 *Single-Mode Fiber* / 705
    - 11.1.7.4 *Dispersion-Shifted Fiber* / 705
    - 11.1.7.5 *Silica Core Fluorine-Added Cladding Fiber* / 705
    - 11.1.7.6 *Plastic Fiber* / 706
    - 11.1.7.7 *Multi-Ingredient Fiber* / 706
    - 11.1.7.8 *Holey Optical Fiber (HF)* / 706
    - 11.1.7.9 *Polarization-Preserving Fiber* / 707
  - 11.1.8 Optical Fibers Other Than Silica Based Fibers / 708
- 11.2 Theory of Step-Index Fibers / 709
  - 11.2.1 Solutions of the Wave Equations in Cylindrical Coordinates / 709
  - 11.2.2 Expressions for the  $E_z$  and  $H_z$  Components / 711
    - 11.2.2.1 *Solutions in the Core Region* / 713
    - 11.2.2.2 *Solutions in the Cladding Region* / 714
  - 11.2.3 Expressions for the  $E_r$ ,  $E_\phi$ ,  $H_r$ , and  $H_\phi$  Components / 715
  - 11.2.4 Characteristic Equation of an Optical Fiber / 717
  - 11.2.5 Modes in Optical Fibers / 718
    - 11.2.5.1 *Meridional Modes:  $v = 0$*  / 718
    - 11.2.5.2 *Skew Modes:  $v \neq 0$*  / 721
- 11.3 Field Distributions Inside Optical Fibers / 730
  - 11.3.1 Sketching Hybrid Mode Patterns / 732
  - 11.3.2 Sketching Linearly Polarized Mode Patterns / 735
- 11.4 Dual-Mode Fiber / 739
- 11.5 Photoimprinted Bragg Grating Fiber / 741
  - 11.5.1 Methods of Writing Photoinduced Bragg Gratings in an Optical Fiber / 742
    - 11.5.1.1 *Internal Writing* / 743
    - 11.5.1.2 *Holographic Writing* / 743
    - 11.5.1.3 *Point-by-Point Writing* / 744
    - 11.5.1.4 *Writing by a Phase Mask* / 744
  - 11.5.2 Applications of the Photoinduced Bragg Gratings in an Optical Fiber / 744



11.6	Definitions Associated with Dispersion	/	748
11.6.1	Definitions of Group Velocity and Group Delay	/	748
11.6.2	Definition of the Dispersion Parameter	/	749
11.7	Dispersion-Shifted Fiber	/	749
11.7.1	Group Delay in an Optical Fiber	/	749
11.7.2	Dispersion Parameter of an Optical Fiber	/	751
11.8	Dispersion Compensator	/	755
11.8.1	Phase Conjugation Method	/	755
11.8.2	Bragg Grating Method	/	755
11.8.3	Dual-Mode Fiber Method	/	757
11.9	Ray Theory for Graded-Index Fibers	/	759
11.9.1	Eikonal Equation	/	759
11.9.2	Path of Light in a Graded-Index Fiber	/	762
11.9.3	Quantization of the Propagation Constant in a Graded-Index Fiber	/	766
11.9.4	Dispersion of Graded-Index Fibers	/	768
11.9.5	Mode Patterns in a Graded-Index Fiber	/	770
11.10	Fabrication of Optical Fibers	/	775
11.10.1	Fabrication of a Fiber by the One-Stage Process	/	775
11.10.2	Fabrication of a Fiber by the Two-Stage Process	/	777
	11.10.2.1 <i>Fabrication of Preforms</i>	/	777
	11.10.2.2 <i>Drawing into an Optical Fiber</i>	/	782
11.11	Cabling of Optical Fibers	/	783
11.12	Joining Fibers	/	786
	11.12.1 Splicing Fibers	/	786
	11.12.2 Optical Fiber Connector	/	790
	Problems	/	790
	References	/	793

## **12 Detecting Light**

**796**

12.1	Photomultiplier Tube	/	796
12.2	Streak Camera	/	798
12.3	Miscellaneous Types of Light Detectors	/	800
12.4	PIN Photodiode and APD	/	801
12.4.1	Physical Structures of PIN and APD Photodetectors	/	801
12.4.2	Responsivity of the PIN Photodiode and APD	/	803
12.5	Direct Detection Systems	/	805
12.6	Coherent Detection Systems	/	807
12.6.1	Heterodyne Detection	/	807
12.6.2	Homodyne Detection	/	809
12.6.3	Intradyne System	/	812

12.7	Balanced Mixer /	814
12.8	Detection by Stimulated Effects /	815
12.8.1	Stimulated Effects /	816
12.8.2	Homodyne Detection by Stimulated Brillouin Scattering /	817
12.9	Jitter in Coherent Communication Systems /	819
12.9.1	Polarization Jitter Controls /	819
12.9.1.1	<i>Computer-Controlled Method of Jitter Control</i> /	820
12.9.1.2	<i>Polarization Diversity Method</i> /	822
12.9.2	Phase Jitter /	823
12.10	Coherent Detection Immune to Both Polarization and Phase Jitter /	826
12.11	Concluding Remarks /	830
	Problems /	830
	References /	831

### **13 Optical Amplifiers**

**833**

13.1	Introduction /	833
13.2	Basics of Optical Amplifiers /	834
13.3	Types of Optical Amplifiers /	836
13.4	Gain of Optical Fiber Amplifiers /	838
13.4.1	Spectral Lineshape /	839
13.5	Rate Equations for the Three-Level Model Of $\text{Er}^{3+}$ /	848
13.5.1	Normalized Steady-State Population Difference /	849
13.5.2	Gain of the Amplifier /	852
13.6	Pros and Cons of 1.48- $\mu\text{m}$ and 0.98- $\mu\text{m}$ Pump Light /	853
13.7	Approximate Solutions of the Time-Dependent Rate Equations /	857
13.8	Pumping Configuration /	864
13.8.1	Forward Pumping Versus Backward Pumping /	864
13.8.2	Double-Clad Fiber Pumping /	866
13.9	Optimum Length of the Fiber /	867
13.10	Electric Noise Power When the EDFA is Used as a Preamplifier /	868
13.11	Noise Figure of the Receiver Using the Optical Amplifier as a Preamplifier /	880
13.12	A Chain of Optical Amplifiers /	882
13.13	Upconversion Fiber Amplifier /	889
	Problems /	889
	References /	892

### **14 Transmitters**

**893**

14.1	Types of Lasers /	893
14.1.1	Gas Lasers /	893

14.1.2	Solid-State Lasers	/	894
14.1.3	Dye Lasers	/	894
14.1.4	Chemical Lasers	/	895
14.2	Semiconductor Lasers	/	895
14.2.1	Gain of a Semiconductor Laser Amplifier	/	895
14.2.2	Laser Cavity	/	903
14.2.3	Conditions for Laser Oscillation	/	904
	14.2.3.1 Amplitude Condition for Laser Oscillation	/	905
	14.2.3.2 Phase Condition for Laser Oscillation	/	907
14.2.4	Qualitative Explanation of Laser Oscillation	/	908
14.3	Rate Equations of Semiconductor Lasers	/	909
14.3.1	Steady-State Solutions of the Rate Equations	/	911
14.3.2	Threshold Electron Density and Current	/	911
14.3.3	Output Power from the Laser	/	913
14.3.4	Time-Dependent Solutions of the Rate Equations	/	914
	14.3.4.1 Turn-On Delay	/	914
	14.3.4.2 Relaxation Oscillation	/	916
14.3.5	Small Signal Amplitude Modulation	/	916
	14.3.5.1 Time Constant of the Relaxation Oscillation	/	917
	14.3.5.2 Amplitude Modulation Characteristics	/	919
	14.3.5.3 Comparisons Between Theoretical and Experimental Results	/	920
14.4	Confinement	/	930
14.4.1	Carrier Confinement	/	930
14.4.2	Confinement of the Injection Current	/	933
	14.4.2.1 Narrow Stripe Electrode	/	934
	14.4.2.2 Raised Resistivity by Proton Bombardment	/	934
	14.4.2.3 Barricade by a Back-Biased p-n Junction Layer	/	935
	14.4.2.4 Dopant-Diffused Channel	/	936
	14.4.2.5 Modulation of the Layer Thickness	/	937
14.4.3	Light Confinement	/	937
	14.4.3.1 Gain Guiding	/	937
	14.4.3.2 Plasma-Induced Carrier Effect	/	939
	14.4.3.3 Kink in the Characteristic Curve	/	941
	14.4.3.4 Stabilization of the Lateral Modes	/	942
14.5	Wavelength Shift of the Radiation	/	943

14.5.1	Continuous Wavelength Shift with Respect to Injection Current	/ 944
14.5.2	Mode Hopping	/ 945
14.6	Beam Pattern of a Laser	/ 946
14.7	Temperature Dependence of $L-I$ Curves	/ 951
14.8	Semiconductor Laser Noise	/ 952
14.8.1	Noise Due to External Optical Feedback	/ 953
14.8.2	Noise Associated with Relaxation Oscillation	/ 955
14.8.3	Noise Due to Mode Hopping	/ 955
14.8.4	Partition Noise	/ 955
14.8.5	Noise Due to Spontaneous Emission	/ 955
14.8.6	Noise Due to Fluctuations in Temperature and Injection Current	/ 955
14.9	Single-Frequency Lasers	/ 956
14.9.1	Surface Emitting Laser	/ 956
14.9.2	Laser Diodes with Bragg Reflectors	/ 957
14.9.3	$\lambda/4$ Shift DFB Lasers	/ 961
14.9.4	Diode Pumped Solid-State Laser	/ 967
14.10	Wavelength Tunable Laser Diode	/ 970
14.10.1	Principle of Frequency Tuning of the DFB Laser	/ 970
14.10.1.1	<i>Tuning of Wavelength by the Phase Controller Tuning Current <math>I_p</math> Alone</i>	/ 973
14.10.1.2	<i>Tuning of Wavelength by the Bragg Reflector Tuning Current <math>I_b</math> Alone</i>	/ 973
14.10.1.3	<i>Continuous Wavelength Tuning by Combining <math>I_p</math> and <math>I_b</math></i>	/ 975
14.10.2	Superstructure Grating Laser Diode (SSG-LD)	/ 977
14.11	Laser Diode Array	/ 980
14.12	Multi-Quantum-Well Lasers	/ 984
14.12.1	Energy States in a Bulk Semiconductor	/ 985
14.12.2	Energy States in a Quantum Well	/ 988
14.12.3	Gain Curves of the MQW Laser	/ 992
14.12.4	Structure and Characteristics of a MQW Laser	/ 994
14.12.5	Density of States of a Quantum Wire and Quantum Dot	/ 999
14.13	Erbium-Doped Fiber Laser	/ 1004
14.14	Light-Emitting Diode (LED)	/ 1007
14.14.1	LED Characteristics	/ 1007
14.14.2	LED Structure	/ 1008
14.15	Fiber Raman Lasers	/ 1009
14.16	Selection of Light Sources	/ 1011
	Problems	/ 1013
	References	/ 1014

<b>15</b>	<b>Stationary and Solitary Solutions in a Nonlinear Medium</b>	<b>1017</b>
15.1	Nonlinear (Kerr) Medium /	1017
15.2	Solutions in the Unbounded Kerr Nonlinear Medium /	1021
15.2.1	Method by a Trial Solution /	1024
15.2.2	Method by Integration /	1026
15.2.3	Method Using Jacobi's Elliptic Functions /	1027
15.3	Guided Nonlinear Boundary Wave /	1030
15.4	Linear Core Layer Sandwiched by Nonlinear Cladding Layers /	1037
15.4.1	General Solutions /	1038
15.4.2	Characteristic Equations from the Boundary Conditions /	1039
15.4.3	Normalized Thickness of the Nonlinear Guides /	1041
15.4.4	Fields at the Top and Bottom Boundaries /	1042
15.4.5	Modes Associated with Equal Boundary Field Intensities ( $a_0 = a_2$ ) /	1043
15.4.6	Modes Associated with $a_0 + a_2 = \epsilon_1 - \epsilon_0$ /	1048
15.5	How the Soliton Came About /	1049
15.6	How a Soliton is Generated /	1050
15.7	Self-Phase Modulation (SPM) /	1053
15.8	Group Velocity Dispersion /	1055
15.9	Differential Equation of the Envelope Function of the Solitons in the Optical Fiber /	1059
15.10	Solving the Nonlinear Schrödinger Equation /	1067
15.11	Fundamental Soliton /	1068
15.12	Pulsewidth and Power to Generate a Fundamental Soliton /	1071
15.13	Ever-Expanding Soliton Theories /	1074
	Problems /	1077
	References /	1079
<b>16</b>	<b>Communicating by Fiber Optics</b>	<b>1081</b>
16.1	Overview of Fiber-Optic Communication Systems /	1082
16.1.1	Transmitters /	1082
16.1.2	Modulation of Light /	1082
16.1.3	Transmission Through the Optical Fiber /	1084
16.1.4	Received Signal /	1085
16.1.5	Multiplexing Hierarchies /	1085
16.2	Modulation /	1085
16.2.1	Amplitude Modulation /	1086
16.2.2	Variations of Amplitude Modulation /	1086
16.2.3	Angle Modulation /	1092

16.2.4	Pulse Modulation	/	1094
16.2.5	Pulse Code Modulation	/	1094
16.2.6	Binary Modulation (Two-State Modulation)	/	1095
16.2.7	Amplitude Shift Keying (ASK)	/	1095
16.2.8	Frequency Shift Keying (FSK) and Phase Shift Keying (PSK)	/	1095
16.2.9	Representation of Bits	/	1096
16.3	Multiplexing	/	1097
16.3.1	Wavelength Division Multiplexing (WDM)	/	1098
16.3.2	Frequency Division Multiplexing (FDM)	/	1099
16.3.3	Time Division Multiplexing (TDM)	/	1100
16.4	Light Detection Systems	/	1102
16.4.1	Equivalent Circuit of the PIN Photodiode	/	1102
16.4.2	Frequency Response of the PIN Diode	/	1104
16.4.3	Coupling Circuits to a Preamplifier	/	1106
	16.4.3.1	<i>Coupling Circuits to a Preamplifier at Subgahertz</i>	/ 1106
	16.4.3.2	<i>Coupling Circuits to a Preamplifier Above a Gigahertz</i>	/ 1110
16.5	Noise in the Detector System	/	1113
16.5.1	Shot Noise	/	1113
16.5.2	Thermal Noise	/	1114
16.5.3	Signal to Noise Ratio	/	1115
16.5.4	Excess Noise in the APD	/	1117
16.5.5	Noise Equivalent Power (NEP)	/	1117
16.5.6	Signal to Noise Ratio for ASK Modulation	/	1121
16.5.7	Signal to Noise Ratio of Homodyne Detection	/	1122
16.5.8	Borderline Between the Quantum-Limited and Thermal-Noise-Limited S/N	/	1123
16.5.9	Relationship Between Bit Error Rate (BER) and Signal to Noise Ratio	/	1123
16.6	Designing Fiber-Optic Communication Systems	/	1129
16.6.1	System Loss	/	1130
16.6.2	Power Requirement for Analog Modulation	/	1130
16.6.3	Rise-Time Requirement for Analog Modulation	/	1132
16.6.4	Example of an Analog System Design	/	1134
16.6.5	Required Frequency Bandwidth for Amplifying Digital Signals	/	1139
16.6.6	Digital System Design	/	1141
16.6.7	Example of Digital System Design	/	1144
	16.6.7.1	<i>Power Requirement</i>	/ 1144
	16.6.7.2	<i>Rise-Time Requirement</i>	/ 1145
	Problems	/	1147
	References	/	1149

<b>Appendix A</b>	<b>PIN Photodiode on an Atomic Scale</b>	<b>1151</b>
A.1	PIN Photodiode    /    1151	
A.2	I–V Characteristics    /    1156	
<b>Appendix B</b>	<b>Mode Density</b>	<b>1160</b>
<b>Appendix C</b>	<b>Perturbation Theory</b>	<b>1164</b>
<b>Answers to Problems</b>		<b>1167</b>
<b>Index</b>		<b>I-1</b>

---

# PREFACE

---

After visiting leading optics laboratories for the purpose of producing the educational video *Fiber Optic Labs from Around the World* for the Institute of Electrical and Electronics Engineers (IEEE), I soon realized there was a short supply of photonics textbooks to accommodate the growing demand for photonics engineers and evolving fiber-optic products. This textbook was written to help fill this need.

From my teaching experiences at Harvard University and the University of Toronto, I learned a great deal about what students want in a textbook. For instance, students hate messy mathematical expressions that hide the physical meaning. They want explanations that start from the very basics, yet maintain simplicity and succinctness. Most students do not have a lot of time to spend reading and looking up references, so they value a well-organized text with everything at their fingertips. Furthermore, a textbook with a generous allotment of numerical examples helps them better understand the material and gives them greater confidence in tackling challenging problem sets. This book was written with the student in mind.

The book amalgamates fundamentals with applications and is appropriate as a text for a fourth year undergraduate course or first year graduate course. Students need not have a previous knowledge of optics, but college physics and mathematics are prerequisites.

*Elements of Photonics* is comprised of two volumes. Even though cohesiveness between the two volumes is maintained, each volume can be used as a stand-alone textbook.

Volume I is devoted to topics that apply to propagation in free space and special media such as anisotropic crystals. Chapter 1 begins with a description of Fourier optics, which is used throughout the book, followed by applications of Fourier optics such as the properties of lenses, optical image processing, and holography.

Chapter 2 deals with evanescent waves, which are the basis of diffraction unlimited optical microscopes whose power of resolution is far shorter than a wavelength of light.

Chapter 3 covers the Gaussian beam, which is the mode of propagation in free-space optical communication. Topics include Bessel beams characterized by an unusually long focal length, optical tweezers useful for manipulating microbiological objects like DNA, and laser cooling leading to noise-free spectroscopy.

Chapter 4 explains how light propagates in anisotropic media. Such a study is important because many electrooptic and acoustooptic crystals used for integrated optics are anisotropic. Only through this knowledge can one properly design integrated optics devices.



Chapter 5 comprehensively treats external field effects, such as the electrooptic effect, elasto-optic effect, magneto-optic effect, and photorefractive effect. The treatment includes solid as well as liquid crystals and explains how these effects are applied to such integrated optics devices as switches, modulators, deflectors, tunable filters, tunable resonators, optical amplifiers, spatial light modulators, and liquid crystal television.

Chapter 6 deals with the state of polarization of light. Basic optical phenomena such as reflection, refraction, and deflection all depend on the state of polarization of the light. Ways of converting light to the desired state of polarization from an arbitrary state of polarization are explained.

Chapter 7 explains methods of constructing and using the Poincaré sphere. The Poincaré sphere is an elegant tool for describing and solving polarization problems in the optics laboratory.

Chapter 8 covers the phase conjugate wave. The major application is for optical image processing. For example, the phase conjugate wave can correct the phasefront distorted during propagation through a disturbing medium such as the atmosphere. It can also be used for reshaping the light pulse distorted due to a long transmission distance inside the optical fiber.

Volume II is devoted to topics that apply to fiber and integrated optics.

Chapter 9 explains how a lightwave propagates through a planar optical guide, which is the foundation of integrated optics. The concept of propagation modes is fully explored. Cases for multilayer optical guides are also included.

Chapter 10 is an extension of Chapter 9 and describes how to design a rectangular optical guide that confines the light two dimensionally in the  $x$  and  $y$  directions. Various types of rectangular optical guides used for integrated optics are compared. Electrode configurations needed for applying the electric field in the desired direction are also summarized.

Chapter 11 presents optical fibers, which are the key components in optical communication systems. Important considerations in the choice of optical fibers are attenuation during transmission and dispersion causing distortion of the light pulse. Such special-purpose optical fibers as the dispersion-shifted fiber, polarization-preserving fiber, diffraction grating imprinted fiber, and dual-mode fiber are described. Methods of cabling, splicing, and connecting multifiber cables are also touched on.

Chapter 12 contains a description of light detectors for laboratory as well as communication uses. Mechanisms for converting the information conveyed by photons into their electronic counterparts are introduced. Various detectors, such as the photomultiplier tube, the photodiode, and the avalanche photodiode, and various detection methods, such as direct detection, coherent detection, homodyne detection, and detection by stimulated Brillouin scattering, are described and their performance is compared for the proper choice in a given situation.

Chapter 13 begins with a brief review of relevant topics in quantum electronics, followed by an in-depth look at optical amplifiers. The optical amplifier has revolutionized the process of pulse regeneration in fiber-optic communication systems. The chapter compares two types of optical amplifier: the semiconductor optical amplifier and the erbium-doped fiber amplifier. Knowledge gained from the operation of a single fiber amplifier is applied to the analysis of concatenated fiber amplifiers.

Chapter 14 is devoted to lasers, which is a natural extension of the preceding chapter on optical amplifiers. The chapter begins with an overview of different types of lasers,

followed by an in-depth treatment of semiconductor lasers, which are the preferred light sources for most fiber-optic communication systems. The basic relationship among the laser structure, materials, and operational characteristics are clarified. The ability to tune the laser wavelength, which is indispensable to the wavelength division multiplexing of the communication system, is addressed. The quantum well, quantum wire, and quantum dot laser diodes that have low threshold current and hence a high upper limit on the modulation frequency are also included. The erbium-doped or Raman fiber lasers that are simple in structure and easy to install in an optical fiber system are also explained.

In Chapter 15, an introduction to the nonlinear (Kerr) effect is presented. Optical devices based on the Kerr effect are controlled by photons and can respond much faster than those controlled by electrons. The chapter also provides the mechanism of formation of a soliton wave. A light pulse that propagates in an optical fiber spreads due to the dispersion effect of the fiber, but as the intensity of the pulse is increased, the nonlinear effect of the fiber starts to generate a movement directed toward the center of the light pulse. When these two counteracting movements are balanced, a soliton wave pulse that can propagate distortion-free over thousands of kilometers is formed. The attraction of distortion-free pulse propagation is that it can greatly reduce, or even eliminate, the need for pulse regenerators (repeaters) in long-haul fiber-optic communication systems.

Chapter 16 interweaves the design skills developed throughout the book with realistic problems in fiber-optic communication systems.

The problems at the end of each chapter are an integral part of the book and supplement the explanations in the text.

As a photonics textbook, each volume would be sufficient for a two-semester course. If time is really limited, Chapter 16 alone can serve as a crash course in fiber-optic communication systems and will give the student a good initiation to the subject.

For those who would like to specialize in optics, I highly recommend reading through each volume, carefully and repeatedly. Each chapter will widen your horizon of optics that much more. You will be amazed to discover how many new applications are born by adding a touch of imagination to a fundamental concept.

This two-volume work has been a long time in the making. I applaud Beatrice Shube, and George Telecki and Rosalyn Farkas of John Wiley & Sons for their superhuman patience. Sections of the manuscript went through several iterations of being written, erased, and then rewritten. As painstaking as this process was, the quality of the manuscript steadily improved with each rewrite.

I am very grateful to Professor Joseph W. Goodman of Stanford University who first suggested I publish my rough lecture notes in book form.

I am indebted especially to Mary Jean Giliberto, who spent countless hours proof-reading the text, smoothing the grammatical glitches, and checking equations and numerical examples for completeness and accuracy. I greatly valued her comments and perspective during our many marathon discussions. This book was very much a partnership, in which she played a key role.

I would like to express my gratitude to Dr. Yi Fan Li, who provided much input to Chapter 15 on nonlinear optics, and Professor Subbarayan Pasupathy of the University of Toronto and Professor Alfred Wong of the University of California, Los Angeles, who critically read one of the appendixes. Frankie Wing Kei Cheng has double-checked the equations and calculations of the entire book.

I would also like to acknowledge the following students, who went through the manuscript very critically and helped to refine it: Claudio Aversa, Hany H. Loka, Benjamin Wai Chan, Soo Guan Teh, Rob James, Christopher K. L. Wah, and Megumi Iizuka.

Lena Wong's part in typing the entire manuscript should not be underestimated. I also owe my gratitude to Linda Espeut for retyping the original one-volume manuscript into the current two-volume manuscript. I wish to express my heartfelt thanks to my wife, Yoko, and children, Nozomi, Izumi, Megumi, and Ayumi, for their kind sacrifices. Ayumi Iizuka assisted in designing the cover of the book.

KEIGO IIZUKA

*University of Toronto*

# ELEMENTS OF PHOTONICS

Volume II

# INDEX

---

- A (Einstein's  $A$  coefficient), 842, 900
- A mode in a nonlinear layer, 1048
- Absorption indicatrix, 400
- Acceptor
  - action in semiconductors, 1153–1155
  - atoms, 1153
  - energy level, 1153
- Accommodation in eye vision, 93
- Acetone ( $\text{CH}_3)_2\text{CO}$ , 239
- Acoustic wave
  - imaging, 95
  - surface, 324
- Acoustooptic modulator (AOM), 100, 324
  - surface acoustic wave (SAW), 324
  - used for holographic video displays, 100
- Active layer of laser diodes, 904
  - gain of, 905
  - plasma effect of, 944
- Adaptive fiber coupler, 517
- ADP, *see* Ammonium dihydrogen phosphate
- AFM (atomic force microscope), 160, 161
- Ahrens polarizing prisms, 404, 405
- Airy pattern, 28
  - calculation of, 1172
- Alcohol  $\text{C}_2\text{H}_5\text{OOH}$ , stimulated Brillouin scattering of, 512
- $\text{Al}_2\text{O}_3$  (aluminum oxide), 681, 894
- $\text{Al}_x\text{Ga}_{1-x}\text{As}$  (gallium arsenide doped with aluminum) laser, 895, 949
- Alkali metals as cathode materials, 796
- Aluminum oxide ( $\text{Al}_2\text{O}_3$ ), 687, 894
- AM (amplitude modulation), 919, 1086, 1087
- Amino acids, optical activity of, 412
- Ammonium dihydrogen phosphate (ADP)
  - elastooptic properties of, 322
  - electrooptic properties of, 305, 316, 1018
- Ammonium fluoride ( $\text{NH}_4\text{F}$ ), 158
- Amplified signal power, 847
- Amplified spontaneous emission (ASE) noise, 838, 847, 856, 864, 866, 868, 870
- Amplitude distribution
  - in coupled slab guides, 646
  - in slab optical guides, 615, 616
- Amplitude modulation (AM), 919, 1086, 1087
- Amplitude modulators, 312, 679, 1018
- Amplitude shift keying (ASK), 812, 818, 831, 832, 1089, 1095
- Analog modulation, 1083, 1134, 1137
- Analytic signal, 526, 547, 1022
  - proof of not being applicable to nonlinear cases, 547, 1022
- Angle modulation, 1088, 1092
- Angular frequency, 1
  - convention of, 3, 368
- Anisotropic media, 263
- Annihilation of negative carriers, 898, 1155
- Anomalous dispersion region, 1056, 1066
- Antenna radiation pattern, 13, 95
  - calculated by Fourier optics, 103, 556
  - visualized by microwave holography, 96
- Antiglare sheet, 409
  - analyzed using Poincaré sphere, 502
- Antiglare TV camera, 419
- Antireflection (AR) coating, 803, 838, 954
- Anti-Stokes radiation, 816
- AOM, *see* Acoustooptic modulator
- APC (automatic power control), 952
- APD detectors, *see* Avalanche photodiode
- Aperture functions
  - of rectangles, 20
  - of triangles, 21
  - of circles, 25
  - of delta functions, 28
  - of shah functions, 30
  - of SNOM probes, 114, 158
  - numerical (NA), 151, 693, 694, 701, 703, 706, 770
- Apodization of radiation patterns, 22
- AR (antireflection) coating, 803, 838, 954
- $\text{Ar}_2$  (argon) for excimer lasers, 894

## I.2 INDEX

- Argand diagram, 459
  - converted into Poincaré sphere, 469
  - custom made, 466
  - how to use, 459, 460
  - orthogonality between  $\theta$  and  $\epsilon$  lines, 465
  - ready made, 460
- Argon ( $\text{Ar}_2$ ) for excimer lasers, 894
- Argon ion ( $\text{Ar}^+$ ) for gas lasers, 894
- Array diffraction patterns, 32
  - array pattern, 40, 88
  - element pattern, 38, 40, 88
  - in thin emulsion, 88
  - of finite size, 37
  - of infinite size, 32
  - of irregular spacing, 36
  - of regular spacing, 32
- Arrayed-waveguide grating (AWG), 673, 674, 1099
- Arsenic trisulfide ( $\text{AsS}_3$ ), 330
- Artificial ruby for solid state lasers, 894
- ASE (amplified spontaneous emission) noise, 838, 847, 856, 864, 866, 868, 870
- ASK (amplitude shift keying), 812, 818, 831, 832, 1089, 1095
- $\text{AsS}_3$  (arsenic trisulfide), 330
- Asymmetric optical guide, 606, 638
- Atomic clock, 255
- Atomic force microscope (AFM), 160, 161
- Atomic polarization, 265
- Autocorrelation, 67, 69
  - Fourier transform of, 69
- Automatic power control (APC), 952
- Avalanche effect of APD, 803, 1103, 1159
  - multiplication factor, 804
- Avalanche photodiode (APD), 796, 801, 803, 1085, 1159
  - excess noise of, 1117
  - multiplication factor  $M$  of, 1118
  - noise equivalent power (NEP) of, 1117
  - optimizing gain of, 1148
  - structure of, 802
- AWG (arrayed-waveguide grating), 673, 674, 1099
- Axicon, 245
- Axis image, 245
- $b$  (normalized propagation parameter), 728
- $B$  (Einstein's  $B$  coefficient), 843, 899
- $B$  mode in nonlinear guides, 1048
- $\beta$  matching, 113
- Babinet compensator, 380
- Back focal plane, 62, 66, 80
- Back projection, 469
- Backward pumping of EDFA, 864
- Balanced mixer, 814, 1122
- $\text{Ba}_2\text{NaNb}_5\text{O}_{15}$  (BNN), 1018
- Bandgap energy (energy gap), 804, 901, 925, 945, 996, 998
- Band-pass optical filter, 747
- Band-stop optical filter, 745
- Barium titanate ( $\text{BaTiO}_3$ )
  - photorefractive effect, 332, 337, 511, 517, 521
  - electrooptic properties, 306, 316
- Barricade of current by means of a back-biased p-n junction layer, 935
- Baseband signal, 1085, 1086
- Baseline wander of receivers, 1096
- $\text{BaTiO}_3$ , *see* Barium titanate
- BC (buried crescent) laser, 934, 936, 942
- $\text{BCl}_3$  (boron chloride), 777
- Beam pattern of laser diodes, 946
- Beam propagation factor  $m^2$  of Gaussian beam, 220
- Beam radius of Gaussian beams, 209
- Beam splitter
  - nonpolarizing, 411
  - polarizing, 402, 412
- Beam waist of Gaussian beams, 208
- Beamwidth of laser beams, 948
- Beat noise
  - signal-spontaneous, 870, 871
  - spontaneous-spontaneous, 870, 871
- $\text{BeF}_2$ , 708
- Bend-induced birefringence in optical fibers, 382
  - used for polarizer, 404
  - used for retarder, 382
- Bends in an optical guide for integrated optics, 131
- Benzene ( $\text{C}_6\text{H}_6$ ), Kerr constant of, 316, 317, 1017
- BER (bit error rate), 1123, 1124, 1134, 1148
- Bessel beams, 237, 242, 245, 259
  - one dimensional model of, 239
- Bessel function
  - modified, 714
  - of approximate form, 723
  - of the first kind of  $n$ th order, 17, 27, 243, 713
  - of the second kind of  $n$ th order, 713
  - recurrence formula of, 723
  - relationship of, 719
- BGO ( $\text{Bi}_{12}\text{GeO}_{20}$ ) (bismuth germanium oxide),
  - photorefractive effect of, 332
- Bias voltage, 899
- Biaxial crystal, 267, 300
- Bidirectional pumping of EDFA, 864
- $\text{Bi}_{12}\text{GeO}_{20}$  (bismuth germanium oxide) (BGO), 332
- $\text{Bi}_{12}\text{SiO}_{20}$  (bismuth silicon oxide) (BSO), 332
- Binary coding, 1095, 1096
- Binocular parallax, 92
- Binomial expansion, 11, 729
- Biometric indicators for identification, 77
- Birefringence, 95, 263, 821
  - bent-induced in fibers, 382, 404
  - circular, 413
  - Jones matrix of, 424
  - linear, 413
  - materials, 365, 412
  - of nematic liquid crystals, 822
  - of polarization-maintaining fibers, 707, 821

- Birefringence fiber polarizer, 404
- Birefringence polarizer or polarizing prism, 396, 402
- Bismuth germanium oxide (BGO) ( $\text{Bi}_{12}\text{GeO}_{20}$ ), photorefractive effect of, 332
- Bismuth silicon oxide (BSO) ( $\text{Bi}_{12}\text{SiO}_{20}$ ), photorefractive effect of, 332, 511
- Bit error rate (BER), 1123, 1124, 1134, 1148
  - versus signal to noise ratio, 1123
- Bit rate, 1073, 1081, 1097, 1102, 1139
- Blackbody radiation, 843
- BNN ( $\text{Ba}_2\text{NaNb}_5\text{O}_{15}$ ), 1018
- $\text{B}_2\text{O}_3$  (boric oxide) to lower the melting point of glass, 706
- Bolometer, 800
- Bohr's approximation, 529
- Boltzman constant, 816, 876, 926, 1114
- Boltzman distribution function, 816, 1157
- Boltzman population ratio, 849
- Borderline between the quantum-limited and thermal-noise-limited S/N, 1123
- Boric oxide ( $\text{B}_2\text{O}_3$ ) to lower the melting point of glass, 706
- Boron chloride ( $\text{BCl}_3$ ), 777
- Boundary, 110
  - of anisotropic media, 292
  - of isotropic media, 110
  - of nonlinear media, 1030
- Boundary conditions, 110
  - Maxwell's, 112
  - periodic, 1161, 1163
  - standing-wave, 1161, 1163
  - wavelength matching, 113
- Bow-tie fiber, 707
- Bragg condition, 959
- Bragg frequency, 961, 963
- Bragg grating method of dispersion compensation, 755
- Bragg grating sensor of photoinprinted fibers, 742, 745, 747
- Bragg reflection, 89
- Bragg reflector, 962, 970, 971, 973
- Breakdown voltage of air, 803
- Brewster angle, 127, 407, 566
- Brewster window, 129, 408
- Brillouin scattering, 512, 602, 816, 817
- BSO ( $\text{Bi}_{12}\text{SiO}_{20}$ ) (bismuth silicon oxide), photorefractive effect of, 332, 511
- Buffer-covered fiber, 784
- Buffered metal guide, 672
- Bulge guide, 672
- Bulge of field, 1044
- Bulk waves, 144, 681
- Buried crescent (BC) laser, 934, 936, 942
- Burrus-type LED, 1008
- Cabling of optical fibers, 783
- $\text{CaCO}_3$  (calcite), 277, 290, 402
- Cadmium (Cd), 936
- Cadmium selenide (CdSe), of photocell, 800
- Cadmium sulfide (CdS), electrooptic properties of, 306, 800
- Cadmium telluride (CdTe), electrooptic properties of, 306
- Calcite crystal (Iceland spar) ( $\text{CaCO}_3$ ), 277, 290, 402
  - physical constants of, 290
- Calcium oxide (CaO) to lower the melting point of glass, 706
- Calorimetric methods of detecting light, 800
- Canada balsam cement, 402, 404
- CaO (calcium oxide) to lower melting point of glass, 706
- Capacity for information transmission through optical fibers, 703
- Capping layer, 803
- Carbon dioxide ( $\text{CO}_2$ ) laser, 512, 894
- Carbon disulfide ( $\text{CS}_2$ )
  - Kerr constant of, 317
  - Kerr effect of, 1017
- Carbon dioxide ( $\text{CO}_2$ )
  - laser, 894
  - stimulated Brillouin scattering effect of, 512
- Carbon tetrachloride ( $\text{CCl}_4$ ), Kerr constant of, 316, 317
- Card for encryption, 80, 108, 560
- Carrier, 841
  - concentration of, 930
  - confinement of, 930
  - negative and positive, 898
  - number of, 841
  - population inversion of, 847
  - rate of transition of, 841
- Carrier electrons, 1151
- Carrier frequency, 1085
- Cassegrain telescope, 107, 108
- Cavity resonance frequencies of laser diodes, 960
- Cavity, *see* Fabry-Pérot cavity
- c* axis of crystals, 267
- $\text{C}_{60}$  (fullerene) doped liquid crystal, 357
- $\text{CCl}_4$  (carbon tetrachloride), 317
- Cd (cadmium), 936
- CDH (constricted double heterojunction) laser, 937
- CDM (code division multiplexing), 1085, 1094
- CdS (cadmium sulfide), 306, 800
- CdSe (cadmium selenide), 800
- CdTe (cadmium telluride), 306
- $\text{CH}_4$  (gaseous methane), 512
- $\text{C}_6\text{H}_6$  (benzene), 316, 317, 1017
- $\text{C}_{10}\text{H}_{16}$  (turpentine), optically active, 412
- $(\text{CH}_3)_2\text{CO}$  (acetone), 239
- $\text{C}_6\text{H}_4$  ( $\text{CH}_3$ ) $\text{NO}_2$  (nitrotoluene), 1017
- $\text{C}_6\text{H}_5\text{NO}_2$  (nitrobenzene), 316, 317, 1017, 1035
- $\text{C}_{12}\text{H}_{22}\text{O}_{11}$  (natural sugar), 414
- $\text{C}_2\text{H}_5\text{OOH}$  (alcohol), 512
- Chain of optical amplifiers, 882

- Channeled substrate planar (CSP) laser, 936, 943
- Characteristic equations, 605
  - for *EH* modes of optical fibers, 723
  - for *HE* modes of optical fibers, 723
  - for even TE modes, 622
  - for even TM modes, 610, 628, 632, 634
  - for odd TE modes, 622
  - for odd TM modes, 610, 612, 628, 633, 636
  - for TE modes of optical fibers, 719
  - for TM modes of optical fibers, 719
  - of coupled slab guides, 643
  - of optical fibers, 717, 718
  - of rectangular guides, 657
- Characteristic temperatures
  - of the external quantum efficiency, 951
  - of the threshold current, 951
- Characteristic wave impedance, 124
- Chemical lasers, 893, 895
- Chemical vapor deposition (CVD), 777
- $\chi^{(1)}$ , 1018
- $\chi^{(2)}$ , 523, 525, 1018
- $\chi^{(3)}$ , 523, 527, 1018
- Chiral, 355
  - smectic *C* liquid crystal, 354, 356
- Chirp noise, 955
- Chirped aperiodic Bragg grating, 748
  - photoimprinted in fiber cores, 755
- Cholesteric type liquid crystal, 341, 342
  - as an optically active substance, 412
- Chromium doped gallium arsenide (GaAs:Cr),
  - photorefractive effect of, 512
- Chromium oxide (CrO<sub>3</sub>), 894
- Cinnabar (HgS)
  - as an optically active substance, 412
  - electrooptic properties of, 305
- Circle diagrams for polarization, 365
- Circle function, 25
  - Fourier transform of, 25
- Circular apertures in random spacing, 37
- Circular birefringence, 413
- Circularly polarized wave, 364
- Circularly polarizing sheets, 409
  - for antiglare, 409
- Cladding of fibers, 382, 694
- Cladding layer of optical slab guides, 606
- Clamped by the Boltzmann distribution, 855
- Cleaved surfaces, 1013
- CO<sub>2</sub> (carbon dioxide) laser, 512, 894
- Code division multiplexing (CDM), 1085, 1094
- Code format
  - Manchester, 1097
  - nonreturn to zero (NRZ), 774, 1096, 1140
  - return to zero (RZ), 774, 1096, 1141
- Coefficient matrix method, 606, 622, 623
- Coherent communication systems, 807
  - jitter in, 819
- Coherent detection, 807, 812, 970, 1094
  - immune to both polarization and phase jitter, 826
- Collision of solitons, 1070
- Color holograms, 87, 92
- Comets' tails, 249
- Comb function, 30
  - Fourier transform of, 31
- Commensurate, 528
- Compensator, 380, 494
  - Babinet compensator, 380
  - Soleil compensator, 382
- Complementary error function, 1126
  - approximate expression of, 1127
- Complementary mode patterns, 735
- Complex fields, 452
- Complex (phase) conjugate waves, 507
- Complex refractive index of silver, 672
- Component field ratio in the complex plane, 452
- Component waves, 431, 615
- Computer-controlled method of jitter control, 820
- Computer generated holograms, 97, 98
- Concave end mirrors of gas lasers, 893
- Conduction band, 898, 988, 998, 1151
- Confined light in the lateral (horizontal) direction,
  - in laser diodes, 937
- Confined light in the vertical (transverse) direction,
  - 937
- Confinement factor, 861, 866, 994
- Confinement of injection current, 933
- Conflexion, 666
- Conflexion lens, 667
- Confocal cavity, 236
- Confocal reflector UV light cavity, 775, 783
- Conjugate waves, 504, 507, 512, 521
- Conical lens (axicon), 245, 246
- Connectors
  - fiber, 790
  - loss, 790, 1130, 1131, 1138, 1144, 1146
- Conservation of energy in elliptical polarization,
  - 437
- Constant azimuth  $\theta$  and ellipticity  $\epsilon$  lines of
  - Argand diagrams, 455
- Constricted double heterojunction (CDH) laser, 937
- Contact layer in electrode lamination, 680
- Contact potential of a junction, 932, 1155
- Continuous wavelength tuning by combining  $I_p$ 
  - and  $I_b$ , 975
- Conventions for expressing time dependence, 3
- Conversion of joules into electron volts, 997
- Conversion retarder of TM–TE converters, 499
- Conversion of state of polarization
  - from circular to linear, 484
  - from elliptic to linear, 389
  - from linear to circular, 386
  - from unknown to linear, 389
- Convolution, 14, 68, 69
- Copper chloride (CuCl), electrooptic properties of,
  - 306
- Core-cladding interface of optical fibers, 694
- Core glass of optical fibers, 694



- Core layer of slab guides, 606
- Correction factor of Gaussian beams, 210
- Correlation operation
  - autocorrelation, 67, 69
  - countermeasures for differences in scale, 74
  - cross-correlation, 68, 69
- Corrugated reflectors, 957, 959, 964
- Costas PLL (phase locked loop), 809
- Cotton–Mouton effect, 327
- Cotton type prism, 404
- Coulomb field, 1152
- Coulombic force, 341
- Coupled guides, 643, 665
- Coupled wave equations, 526
- Coupler (tunable), 740
- Coupling between rectangular guides, 664
- Coupling circuits to preamplifiers, 1106, 1110
- Coupling length, 664, 666, 740
- Coupling loss, 1130, 1138, 1144, 1146
- Coupling mechanism of slab guide couplers, 651
- Critical angle
  - anisotropic media, 285, 296, 575, 576
  - isotropic media, 131, 142, 694
- CrO<sub>3</sub> (chromium oxide), 894
- Crooks, Sir William, 259
- Cross-correlation, 68, 69, 72
- Cross-sectional ellipse, 307, 313, 399, 580
- Crosstalk between channels, 859
- Cryptograph, 78
- Crystal(s)
  - with inversion symmetry, 523, 599
  - without second order nonlinearity, 523, 525
  - under various external fields, 302
- Crystal axis
  - c* axis, 267
  - crystallographic axis, 307
  - z* axis, 307
- Crystal cut, 307
- Crystallography, 13, 307
- CS<sub>2</sub> (carbon disulphide), 239, 316, 1017
- CSP (channeled substrate planer) laser diode, 934, 936, 943
- CuCl (copper chloride), 306
- Cutoff
  - condition in fibers, 719
    - EH* modes, 723, 724
    - HE* modes, 723, 724
    - TE mode, 719
    - TM mode, 720
  - condition in planar optical guides, 612
    - of TM modes, 612, 613
    - of buried optical guides, 661
- CVD (chemical vapor deposition), 777
- Cylindrical-coordinates Fourier transform, 16
- d*-rotary (right-handed) quartz, 412, 415
- Dark current of photodiodes, 1103
- Dark light soliton, 1077
- DBR (distributed Bragg reflection) laser, 957, 963
- DC-PBH (double-channel planar buried heterostructure) laser, 932, 934, 936, 942, 1134
- De Broglie, Louis, 985
- DE**ks plane, 278
- Decomposition of elliptically polarized light, 375
- Decrypting, 80, 108, 560
- Degenerate modes, 768
- Delay-and-detect circuit, 825, 826, 827
- $\delta(x)$  (delta function), 28
  - convolution of, 29
  - Fourier transform of, 29
  - train of, 30
- Demountable fiber connectors, 786
- Denisyuk hologram, 92. *See also* Lippman hologram
- Density  $m(\nu)$  of modes per unit frequency per unit volume of blackbody radiators, 843, 847, 1160
- Density of states, 898, 987, 988
- Depletion region, 1155
- Depolarized (unpolarized) wave, 364
- Depth of focus of Gaussian beams, 213, 218
- Designing fiber-optic communication systems, 1129
- Detection of light by stimulated Brillouin scattering effects, 815, 830
- Devices for integrated optics, 655
- Dextrorotary (*d*-rotary) optical activity, 412, 415
- D-fiber, 708, 744, 757, 866
- DFB (distributed feedback) grating, nonlinear, 1019
- DFB (distributed feedback) laser, 896, 958, 961, 963, 970, 977
- Di Francia, Toraldis, 666
- Dichoric mirror, 167, 197, 865
- Dichoric polarizer, 394
- Dielectric constant, 112
  - absolute, 112
  - nonlinear, 1022
  - relative, 112, 266
  - relationship with refractive index, 112, 266
- Differential phase shift keying (DPSK), 824, 825, 828
- Diffraction-free beams, 237
- Diffraction from array, 32
  - of finite dimension, 37
  - of infinite dimension, 32, 36
- Diffraction limited, 45
- Diffraction patterns, 9, 1162
  - far field, 11
  - near field, 13
- Diffraction unlimited images, 150
- Diffusion constant, 1158
- Diffusion equation, 1157
- Diffusion length
  - of electrons, 932
  - of holes, 932

- Diffusion potential, 932
- Digital modulation, 1083
- Digital system 1 (DS-1), 1101
- Digital system design, 1144
- Digital video disk (DVD), 161
- Diode laser, *see* Laser diodes
- Diode pumped solid-state laser, 967
- Dipole antenna, 102, 103, 556, 557
- Dipole–dipole interactions, 341
- Dipole moment, 265
  - permanent, 265, 266
- Dirac delta function ( $\delta(x)$ ), *see*  $\delta(x)$  (delta function)
- Direct detection, 796, 805, 806, 830, 1086
- Direction of the wavenormal, 761, 762
- Directional couplers, 605, 1018
- Discotic liquid crystals, 341, 344
- Dislocation spots caused by  $\gamma$  rays, 697
- Dispersion, 699, 1086
  - anomalous, 1056, 1066
  - material, 699, 701, 752, 1086
  - mode, 699, 696, 703, 769
  - normal, 1056
  - waveguide, 699, 701, 752, 1086
- Dispersion compensator, 741, 755, 759
- Dispersion countermeasures, 1051
- Dispersion equation, 637, 638
- Dispersion parameter, 749, 769, 1055, 1072
  - definition of, 749
  - of graded-index fibers, 768, 769
- Dispersion-shifted fibers, 703, 705, 748, 749, 755, 769, 1051
- Distortion of light pulses during transmission, 635, 709, 838
- Distributed amplifier approach, 1111
- Distributed Bragg reflection (DBR) laser, 957, 963
- Distributed element preamplifier, 1106
- Distributed feedback (DFB) grating, 1019
- Distributed feedback (DFB) laser, 896, 958, 961, 963, 970, 977
- Distributed FET amplifiers, 1111
- Divergence of Gaussian beams, 212, 218
- DMOAP (*N,N*-dimethyl-*N*-octadecyl-3-aminopropyltrimethoxysilyl chloride), 353
- DNA, 77, 160, 253
- Doppler cooling, 255
- Doppler shift, 254
- Dominant mode, 612, 724
- Donor atoms, 1152
- Dopant-diffused channel, 936
- Double balanced mixer, 814
- Double heterojunction, 930
- Double sideband (DSB) modulation, 1086, 1087
- Double sideband suppressed carrier (DSBC) modulation, 1087
- Double-channel planar buried heterostructure (DC-PBH) laser, 934, 936, 942, 1134
- Double-clad fiber, 866
- Double-crucible method, 775
- DPSK (differential phase shift keying), 824, 825, 828
- Drawing into optical fibers, 782
- Drift of the operating point, 1092
- Drift force, 334
- DS-1 (digital system 1), 1101
- DS-4 (digital system 4) PCM, 1145
- DSB (double sideband) modulation, 1086, 1087
- DSBC (double sideband suppressed carrier) modulation, 1087
- D-shaped inner cladding, 866
- Dual-mode fiber, 739, 758
  - dispersion compensator, 741, 757
  - tunable coupler, 740
- DVD (digital video disk), 161
- Dye-doped liquid crystals, 357
- Dye lasers, 893, 894
- Dynodes, 796, 797
- $E_{pq}^x$ , 656, 657
- $E_{pq}^y$ , 656
- EASLM (electrically addressed spatial light modulator), 350
- ECB (electrically controlled birefringence), 345, 357
- E* mode
  - in linear optical fibers, 722
  - in nonlinear optical guides, 1043, 1048
- EDFA, *see* Erbium-doped fiber amplitude
- Edge-emitting LED, *see* LED
- Edge enhancement of images, 63
- Edible laser, 896
- Effective core area, 1072
- Effective densities of states, 926
- Effective index method for rectangular optical guides, 661
- Effective index of refraction *N*, 619, 659
  - of e-waves, 279, 280, 282, 290, 294
- Effective masses, 925, 926
  - of electrons, 898
  - of holes, 899
- EH* modes, 722, 731, 732
- $EH_{\mu\nu}$ , 732
- Eigenvalue equation of *M*, 428, 433
  - eigenvalue of, 429, 433
  - eigenvector of, 429, 430
  - orthogonal eigenvectors of, 429, 430
- Eikonal, 760
- Eikonal equation, 759, 760
- Einstein's *A* coefficient, 842, 900
- Einstein's *B* coefficient, 843, 899
- Elasto-optic effect, 304, 317, 324
  - due to principal strain, 318
  - due to shearing strain, 318
  - table of elasto-optic constants, 320
- Electric flux density, 112
- Electric noise power of EDFA, 868

- Electrical S/N of output from PIN photodiodes, 876
- Electrically addressed spatial light modulator (EASLM), 350
- Electrically controlled birefringence (ECB) cell, 345, 357
- Electrode configurations of integrated optics, 680, 681
- Electron-beam lithography, 98
- Electron density, 898
- Electron mass, 924
- Electron microscope, 161
- Electrooptic effect, 304, 1017
  - Kerr, 316
  - material, 605
  - table of, 305
- Electrooptic material, 605
- Electrooptic modulator, 1086
  - of amplitude, 1086
  - of phase, 1096
- Electrooptic probe, 313
- Element fibers of fiber cables, 784
- Element patterns of diffraction, 40, 88
- Eliminating wave front distortion by phase conjugate waves, 508
- Ellipse or hyperbola, 434
- Ellipsoid, 286
- Elliptical core fiber, 707
- Elliptically polarized wave, 364, 819
  - azimuth of major axes, 431
  - converted from linearly polarized wave, 367
  - converted into linearly polarized wave, 389
- Ellipticity, 431, 436
- Embedded guide, 671
- Emission
  - spontaneous, 842
  - stimulated, 842
- Encryption scheme, 80, 108, 560
  - encrypted card, 80, 108, 560
- Energy gap, 804, 901, 925, 945, 996, 998
- Energy states, 985
  - in bulk semiconductors, 985
  - in quantum wells, 988
- Energy transfer in photorefractive crystals, 335
- Enhanced photorefractive effect by external electric fields, 334
- Envelope function of solitons, 1059
  - dynamics of, 1064
- Equivalent circuit of PIN photodiodes, 1102
- $\text{Er}^{+3}$  (erbium), 844, 845, 848, 853, 854, 858, 891
- Erbium chloride ( $\text{ErCl}_3$ ), 837
- Erbium-doped fiber amplifier (EDFA)
  - ASE (amplified spontaneous emission), noise of, 847
  - basics of, 834
  - chain of, 882
  - compared to SLA, 838
  - cross-talk of, 859
  - electric noise power of, 868
  - ESA (excited state absorption) of, 855
    - gain of, 838, 852, 901
    - noise figure of, 880
    - pump light of, 853, 864
    - rate equations of, 848
    - saturation of, 856
    - spectral line shape of, 196, 839
- $\text{ErCl}_3$  (erbium chloride), 837
- ESA (excited state absorption), 855, 889
- Etalon, 167, 179
- Evanescent field, 58, 134, 139, 142
  - due to total internal reflection, 135
  - effective depth of penetration, 135
  - generating, 147
  - graphical solution of, 145
  - microscope by, 150
  - probes to detect, 154
- Evanescent wave, *see* Evanescent field
- Even TM modes in planar optical guides, 608, 609, 610, 611
- e-wave (extraordinary wave), 269, 272, 273, 365
- Excess noise in an APD, 1117
- Excess noise index, 1117
- Excimer laser, 894, 893
- Excited dimer, 894
- Excited state absorption (ESA), 855, 889
- Exposure meter, 800
- External quantum efficiency, 951
- External terminal potential of laser diodes, 928
- Extinction ratio, 916
- Extraordinary wave (e-wave), 269, 272, 273, 365
- “eyes” of Panda fiber, 407
- F (fluorine), 895
- Fabrication of optical fibers, 775
  - by one-stage process, 775
  - by two-stage process, 777
- Fabrication of preform rods, 775, 777
- Fabry–Pérot cavity, 166, 568
  - antiresonance of, 174
  - arbitrary angle of incidence of light, 170
  - determining the spacing of reflectors, 202, 203
  - finesse of, 194, 195, 196, 197
  - free spectral range, 171
  - modes, 232, 233
  - resolving power, 192
  - resonance, 174
  - stability diagram, 231
  - superstructure grating, 978
  - tunable fiber, 195
- Fabry–Pérot dichroic filter, 197
- Fabry–Pérot (FP) type laser, 904
- Fabry–Pérot type fiber laser, 1005
- Far field region, 11
  - divergence of Gaussian beams, 212
  - divergence of a Gaussian beam after a lens, 218
- Fraunhofer region, 11
- Faraday effect, 326, 327, 329, 415

- Faraday rotator mirror (FRM), 1005, 1007
- Fast axis of anisotropic media, 367
- FDM (frequency division multiplexing), 1085, 1094, 1099
- $\text{FeCl}_3$  (ferric chloride), 777
- $\text{Fe:LiNbO}_3$  (Fe doped lithium niobate), 91
- Fermat's principle, 666
- Fermi–Dirac distribution function, 898, 899, 992, 1151, 1157
- Fermi–Dirac energy level, 898, 1151, 1152
- Fermi level gap, 925
- Ferric chloride ( $\text{FeCl}_3$ ), 777
- Ferroelectric liquid crystals, 354
- FETs (field effect transistors), 1111
- FIB (focused ion beam), 158
- Fibers. *See also* Optical fibers
  - side pit, 707
  - side tunnel, 707
  - with internal Bragg gratings, 744, 755
- Fiber amplifier, types of, 836
- Fiber Bragg gratings, 741, 1010
- Fiber connectors, 790
- Fiber coupler, adaptive, 517
- Fiber Fabry–Pérot filter, 195
- Fiber lasers, erbium-doped, 1004
- Fiber-loop polarization controller (FPC), 824
- Fiber-loop retarders, 382
  - design of, 383
  - how to use, 385
  - $\lambda/2$  and  $\lambda/4$  of, 385, 386
- Fiber optic communication, 1081–1150
  - amplifiers for, 1085
  - coherent detection system, 807
  - design of, 1129
  - homodyne detection, 1143
  - modulated light for, 1082, 1085
  - multiplexing, 1097
  - overview of, 1082
  - receivers, 1085
  - soliton, 1073
  - space optic, 105
- Fiber-optic gyros, 1012
- Fiber Raman lasers, 1009
- Fiber sensing, 747
- 50- $\Omega$  circuit with mismatch in coupling to a photodetector, 1106
- Field effect transistor (FET), 1111
- Film layer as core layer, 606
- Finesse, 194, 195, 197
  - effective, 194
  - flatness, 194
  - reflection, 194
- Fingerprint detection, 77, 103, 105, 521
- First-order Bessel functions of the second kind, 714
- FLAG (fiber-optic link around the globe), 693
- Flame brushing method to enhance photosensitivity, 743
- Flatness finesse, 194
- Fleming, Sir John A., 396
- Fluorescent glow, 834, 835
- Fluorinated alkyl methacrylate copolymer for plastic fibers, 706
- Fluorine (F), 895
- Fluorozirconate glass (ZBLAN) fiber for upconversion fiber amplifiers, 889
- FM noise, 955
- FM (frequency modulation) signal, 1088, 1092, 1094
- Focal beam parameter (Rayleigh range of a Gaussian beam), 209
- Focal cavity, 235, 236
- Focal length, 43
- Focal plane, 47
- Focused ion beam (FIB), 158
- Fold-unfold-fold (FUF) law, 667
- Forward four-wave mixing, 533, 534, 537
- Forward pumping of EDFA, 864
- Forward pumping versus backward pumping, 864
- Fourier–Bessel transform, 18, 27
- Fourier–Hankel transform, 18, 561
- Fourier optics, 1
- Fourier transformable property of convex lenses, 46
- Fourier transform in cylindrical coordinates, 16, 18, 243
  - Fourier–Bessel transform, 18, 27
  - Fourier–Hankel transform, 18, 561
- Fourier transform in rectangular coordinates, 16, 20
  - of  $\delta(x)$ , 28
  - of derivatives, 64
  - of Fourier transforms, 69
  - of logarithms, 76
  - of the point spread function, 14
  - of shah functions, 32
  - of sinusoidal functions, 71, 103, 556
- Fourier transform spectroscopy, 166
- Four-level model of fiber amplifiers, 836
- Fourth order nonlinearity, 541, 599
- Four-wave mixing (FWM), 506, 1051
  - forward, 533, 534, 537
  - in a general direction, 526
- FP (Fabry–Pérot) type laser, 904
- FPC (fiber-loop polarization controller), 824
- Fraunhofer diffraction pattern, 11
- Fraunhofer region, 11
- Free electrons, 1151
- Free space optical communication link, 258, 1085
  - immune to turbulence, 516
- Free spectral range (FSR), 179, 182
  - in terms of frequency, 181, 235
  - in terms of wavelength, 179, 181
- Frequency chirp, 254
- Frequency discriminator, 1094
- Frequency division multiplexing (FDM), 1085, 1094, 1099
- Frequency modulation (FM), 1088, 1092, 1094
- Frequency response of PIN diodes, 1104

- Frequency shift keying (FSK), 1089, 1095  
 Fresnel field, 13  
 Fresnel–Kirchhoff diffraction formula, 11, 58, 243, 545  
 Fresnel–Kirchhoff integral, 56, 544  
 Fresnel reflection equation, 121  
 Fresnel region, 13  
 Fresnel rhomb, 137  
 Fresnel's explanation of optical activity, 413  
 Front focal plane, 47, 71  
 FRM (Faraday rotator mirror), 1005, 1007  
 FSK (frequency shift keying), 1089, 1095  
 FSR, *see* Free spectral range  
 FUF (fold-unfold-fold) law, 667  
 Full width at half maximum (FWHM), 197, 1071  
 Fullerene (C<sub>60</sub>) doped liquid crystals, 357  
 Full waveplate, 385  
 Fundamental soliton, 1069, 1071  
 Fused silica (SiO<sub>2</sub>)  
   elasto-optic properties of, 320  
   Kerr effect of, 1017  
 Fusen, 485  
 FWHM (full width at half maximum), 197, 1071  
 FWM, *see* Four-wave mixing
- GaAs, *see* Gallium arsenide  
 GaAs:Cr (chromium doped gallium arsenide), 512  
 GaAs MESFET, 1111  
 Ga<sub>x</sub>In<sub>1-x</sub>As<sub>y</sub>P<sub>1-y</sub> laser, 945  
 Gabor-type hologram, 81  
 Gain compression, 838  
 Gain constant  
   with respect to distance, 910  
   with respect to time, 910  
 Gain guiding, 937, 939, 942  
 Gain of optical amplifiers, 838, 850, 852, 895  
 Gain spectrum  
   of laser diodes, 902, 904, 923, 928  
   of MQW lasers, 992, 995, 1004  
 Gallium arsenide (GaAs)  
   elasto-optic properties of, 320  
   electro-optic properties of, 306  
   photorefractive properties of, 332  
 Galvanometric scanner, 101  
 Gamma-ray ( $\gamma$ -ray) irradiation to increase fiber loss, 697, 698  
 Gaseous methane CH<sub>4</sub>, stimulated Brillouin scattering, 512  
 Gas lasers, 893  
 Gas pipes for keeping moisture off, 786  
 Gaussian beam, 205  
   amplitude distribution, 211  
   beam waist, 208, 216, 217  
   cross-sectional area of, 209  
   depth of focus, 213  
   in spherical mirror cavities, 227  
   intensity distribution, 211  
   location of waist, 208, 217  
    $q$  parameter of, 207, 209, 213, 214, 215, 216  
   Rayleigh range of, 209, 218  
   transformation, 214, 259  
   with higher order modes, 223, 233, 235  
   with the fundamental mode, 206  
 Gaussian distribution, 1124  
 Gaussian lens formula, 43, 44, 219  
 General guides, 625  
 Generalized wave equation, 269  
 GeO<sub>2</sub> (germanium dioxide), 697, 705, 706,  
 GeO<sub>2</sub> (germanium dioxide)-doped core, 694, 697  
 Geological surveys, 97  
 Geometrical optics theory, 605, 759  
 Germanium dioxide (GeO<sub>2</sub>), 694, 697, 705, 706  
 GH (guest-host) liquid crystal cell, 353  
 Glan–Air polarizing prism, 402, 404  
 Glan–Faucault prism, 402, 404  
 Glan–Thompson polarizing prism, 404  
 Glass, photorefractive media, 512  
 Goos–Hänchen shift, 141, 142  
 Graded-index fiber, 705, 759, 762, 768, 769, 770  
 Graded index (GRIN) lens, 330  
 Gradient, 288  
 Graphical solution  
   of evanescent waves, 145  
   of polarization states, 365  
   of propagation in an uniaxial crystals, 269, 270  
 Grating  
   arrayed waveguide, 673, 676, 1099  
   photoinduced Bragg, 741, 747, 755  
   reflection from Bragg, 957  
   scattering from Bragg, 963  
   transcendental equations, 611  
 Grating spectroscopy, 166  
 Gravitational acceleration, 572  
 Gravitational wave, 257  
 GRIN (graded index) lenses, 330  
 Group delay in optical fibers, 699, 749, 759, 1055  
 Group index, 750, 768  
 Group velocity, 748, 1055  
 Group velocity dispersion (GVD), 1053, 1055, 1057, 1058, 1069  
 Guard ring, 803  
 Guest-host (GH) liquid crystal cell, 353  
 Guide, slab optical, *see* Optical slab guides  
 Guided nonlinear boundary wave, 1030  
 Guided waves, 681, 1031  
 GVD (group velocity dispersion), 1053, 1055, 1057, 1058, 1069
- H* mode, 722  
 Half-mirror (HM), 65, 505, 1005  
 Half-wave fiber loop, 383  
 Half-waveplate ( $\lambda/2$  plate), 383, 385  
   how to use, 385  
   polyimide, 677  
 Handedness of circular polarization, 364, 374, 439

- HBT (heterojunction bipolar transistor), 1111  
*HE* modes, 722, 731, 735, 736  
     cutoffs, 723  
*HE*<sub>11</sub> mode, 732  
*HE*<sub>vμ</sub>, 731, 735, 736  
 Heavyside's step function, 25, 992  
 HeCd (helium-cadmium) laser for blue light, 101  
 Helium-neon (HeNe) laser for red light, 101, 893  
 HEMT (high electron mobility transistor), 1111  
 HeNe (helium-neon) laser for red light, 101, 893  
 Hermite Gaussian beam (higher order modes), 223, 226  
 Hermite polynomial of order *n*, 224  
 Heterodyne detection, 807, 830  
 Heterojunction, 930  
 Heterojunction bipolar transistor (HBT), 1111  
 HF (holey fiber), 706  
 HF (hydrofluoric acid), 158  
 HgS (cinnabar), optically active, 305, 412  
 High density data storage, 87, 161, 162, 163  
 High electron mobility transistor (HEMT), 1111  
 High impedance (HZ) with compensating circuit, 1107, 1110  
 High pass spatial filter, 63  
 High-powered fiber amplifier, 866  
 Higher order Gaussian beam, 226  
 Hilbert transform, 1090  
 H<sub>2</sub>O (water), *see* Water  
 HM (half-mirror), 505, 1005  
 Holes in semiconductors, 1153  
 Hole burning, 939, 941  
     spatial, 968, 969, 1004, 1007  
     spectral, 945  
 Hole density, 898  
 Holey optical fiber (HF), 706  
 Hologram, 81  
     Gabor-type, 81  
     off-axis type, 85  
 Holographic writing of photoinduced Bragg grating, 743  
 Holography, 81  
     acoustic, 95, 97  
     applications of, 92  
     color, 87, 92  
     computer-generated, 97  
     interference, 93  
     microwave, 96  
     nonoptical, 95  
     to explain phase conjugate, 504, 530  
     thin emulsion, 88  
     synthetic aperture, 97  
     vibration measurement, 45  
     video display, 99  
     volume, 87  
     white light, 87  
 Homeotropic orientation, 344, 345  
 Homodyne detection, 339, 340, 809, 812, 817, 830, 1096, 1143  
     by stimulated Brillouin scattering, 817  
 Homogeneous broadening, 841  
 Homogeneous orientation, 344, 345  
 Homojunction, 930  
 Horizontal and vertical external fields, 684  
 Horizontal external field  
     in rib guides, 684  
     in embedded guides, 683  
     periodic, 684  
 Horseshoe crab's eyes, 447, 585  
 How to use waveplates, 385  
     full-wave plate, 385  
     half-wave plate, 385  
     quarter-wave plate, 386  
 Huygens' principle, 15, 16  
 Huygens' wavelet, 299  
 Huygens' wavelet ellipsoid, 577  
 Hybrid modes, 709, 723  
     designation of, 729, 730  
 Hydrogen to create transmission loss, 695, 697  
 Hydroxyl (OH) formation, 695, 697  
 Hyperbola or ellipse, 433  
 Hysteresis curve, 1021  
 HZ (high impedance) circuit, 1107, 1110  
  
 Iceland spar (calcite crystal) (CaCO<sub>3</sub>), 277, 290, 402  
 IF (intermediate frequency) amplifier, 808, 1094  
 IM (intensity modulation), 313, 1086, 1087  
 Image intensifier, 352  
 Image processing, *see* Picture processing  
 Immersed guide, 672  
 Immobile charges, 332, 1154  
 Impedance  
     characteristic wave, 124  
     electric, 112  
     intrinsic, 111, 112, 869  
     of p-n junction, 1159  
 Impedance approach, referring to the normal direction, 124  
 Impulse response function of free space, 14  
 Impulse train function, 30  
 Incoherent-coherent converter, 352  
 Incremental impedance of a p-n junction, 1159  
 Index of refraction, 112, 266  
     relationship to the dielectric constant, 112, 266  
 Index-matching fluids, 954  
 In<sub>1-x</sub>GaAs<sub>y</sub>P<sub>1-y</sub> (gallium arsenide doped with indium and phosphorus) laser, 895  
 Indicatrix, 264, 285, 292  
     absorption indicatrix, 400  
     distortion of, 302  
 Indium tin oxide (ITO), 188  
 Infrared absorption associated with the vibration of Si—O network, 708  
 Inhomogeneous broadening, 841

- Injection current, density of, 910, 911
- InP:Fe (iron-doped indium phosphide), 512
- In-phase component, 810, 1090
- InP:Ti (titanium-doped indium phosphide), 512
- Insertion loss, 132
- Integrated optics, 605
  - arrayed-waveguide grating (AWG) for, 673
  - couplers, 678
  - electrodes, 681
  - modulators, 312, 1086
  - optical guides, 670
  - optical interconnects, 982
  - optical magic T, 678
- Intensity modulation (IM), 313, 1086, 1087
- Intensity pattern of diffraction, 22, 27
- Interdigital electrode, 324
- Interference filter, 167
- Interference holography, 93
- Interferometers, 167, 605
- Intermediate frequency (IF), 1094
- Internal writing of Bragg gratings, 743
- Internal reflection, total, 130, 145, 147, 296
- Interrogation of handwritten letters, 521
- Intradyn detection, 812, 830
- Intrinsic impedance, 111, 112, 869
- Intrinsic impedance  $\eta_0$  of a vacuum, 111
- Intrinsic impedance  $\eta_1$  of a medium, 111
- Intrinsic type semiconductors, 1151
- Invariance of the location of the input pattern, 50
- Invariance of the state of polarization, 362
- Inversion, population, 836, 847, 864
- Inversion symmetry of crystals, 541, 599
- Ionic dipole, 818
- Iron doped indium phosphide (InP:Fe),
  - photorefractive effect of, 512
- Isopachic fringe pattern, 95
- Isolator, optical, 328, 330, 838, 954, 1005
- ITO (indium tin oxide) electrodes, transparent
  - electrode of, 188
- I-type layer, 803
- I-V characteristics of p-n junctions, 1156
  
- Jacobian elliptic function with modulus  $m$ , 1027
- Jitter in coherent communication systems, 819
- Joining fibers, 786
- Joint transform correlator (JTC), 64, 70
- Jones matrix of, 421, 444
  - eigenvectors, 428
  - half-wave plates, 424
  - polarizers, 422
  - quarter-wave plates, 424
  - retarders, 424, 425
  - rotators, 425
- Jones vector, 421
- JTC (joint transform correlator), 64, 70
  - compared to VLC, 72
  
- $\kappa - \beta$  diagram, 617, 618
- $\kappa - \gamma$  diagram, 618
- $k$  coordinate expression of Snell's law, 145, 164
- KBr (potassium bromide), 708
- KCl (potassium chloride), 708
- KDP (potassium dihydrogen phosphate),
  - electrooptic properties of, 305, 316, 321, 1018
- KD<sub>2</sub>PO<sub>4</sub>(K-KDP), 305
- $k$ -matching, 113
- Kepler, Johannes, 131, 249
- Kerr, John, 304, 316
  - cells, 317
  - coefficients, 316
  - constants, 317
  - electrooptic effect, 304, 316, 1019, 1051
  - media, 512, 518, 527, 1017
- Keying device, 1095
- Kink in the emission characteristic curve of laser diodes, 941
- Kirchhoff, Gustav Robert, 12, 13, 56, 58, 545
- Korteweg–de Vries (KdV) differential equation, 1049
- Kr<sub>2</sub> (krypton) for excimer lasers, 894
  
- $l$ -rotary (left-handed) quartz, 412, 415
- $\lambda/4$  shift DFB lasers, 961
- Laminated aluminium polyethylene (LAP), 697
- Laminated electrodes, 680
- Laplacian operator, 711
- Laser cavity, 175
- Laser(s)
  - chemical, 895
  - definition of, 833
  - dye, 894
  - edible, 895
  - erbium-doped fiber, 1004
  - fiber Raman, 1009
  - gas, 893
  - ring, 904
  - semiconductor, 895
  - solid state, 894, 967
- Laser cooling of atoms, 254
  - Doppler cooling, 254
  - polarization gradient cooling, 254
- Laser diode(s) (LD)
  - amplitude modulation characteristics, 919
  - arrays of, 980
  - beam patterns, 946
  - conditions of laser oscillation, 905
  - confinement of carriers, 930
  - confinement of injection current, 933
  - confinement of light, 937
  - distributed Bragg reflector (DBR), 957
  - distributed feedback (DFB), 958
  - gain spectrum, 896, 902
  - laser noise, 952
  - light transmitter, 1082
  - modulation characteristics, 919

- Laser diode(s) (LD) (*Continued*)
  - multi-quantum well (MQW), 984
  - noise, 952
  - output power, 913, 926
  - quantum dot, 1002
  - quantum well, 984
  - quantum wire, 999
  - rate equations, 909
  - relaxation oscillation, 916, 917
  - selection of light sources, 1011
  - single frequency, 956
  - temperature dependence, 951
  - threshold current density, 912
  - tunable, 189, 970, 977
  - turn on delay, 914, 926
  - unwanted FM, 944, 1086, 1095
  - wavelength tuning, 970
- Laser frequency stabilizer, 176
- Laser oscillation
  - condition for, 905
  - explanation of, 908
- Latitude lines of  $\beta$  (or  $\epsilon$ ) of Poincaré sphere, 478
- Laurent type saccharimeter, 417
- Law of superposition, 548–550, 1070
- LD, *see* Laser diode
- Leaky wave, 150
- LED, *see* Light-emitting diode
- Leith–Upatnieks type hologram, 82
- Lengths of major and minor axes of elliptical
  - polarization, 316
- Lens (convex lens), 40
  - collimating property, 42
  - diffraction limited, 45
  - finite aperture, 102, 103
  - focal length, 43
  - Fourier transformable property, 46
  - imaging property, 43
  - radiation pressure, 260
- Levorotary (*l*-rotary) optical activity, 412
- LiF (lithium fluoride), 708
- Lifetime, 834
  - of electrons in the conduction band, 910
  - of photons inside a cavity, 910, 920
- Light computer, 1021
- Light confinement in laser diodes in the horizontal (lateral) direction, 937
- Light confinement in laser diodes in the vertical (transverse) direction, 937
- Light detectors used in optics laboratories, 796, 800
- Light-emitting diode (LED), 952, 1007, 1011, 1013, 1082, 1092
  - characteristics, 1007
  - structure, 1008
- Light path (optical path), expression of, 761, 762
- Light to pump EDFA, 837
- Light rays, direction of, 274, 275, 299
- Light transmitters, 893, 1082
- Light tweezers, 226, 249, 251, 253
- LiIO<sub>3</sub> (lithium iodate), 306
- LiNbO<sub>3</sub>, *see* Lithium niobate
- Linear core layer sandwiched by nonlinear
  - cladding layers, 1037
- Linear normalized thickness, 1047
- Linear polarization (LP) mode, 709, 726, 727, 736
- Linear polarizer, 365, 394, 587
- Linearly birefringent, 413
- Linearly polarized LP <sub>$m\mu$</sub>  mode, 726. *See also* LP <sub>$m\mu$</sub>  modes
- Linearly polarized wave, 363
- Lines of constant parameters on Argand diagram
  - azimuth  $\theta$ , 455
  - ellipticity  $\epsilon$ , 458
- Li<sub>2</sub>O (lithium oxide) to lower the melting point of
  - glass, 706
- Lippmann hologram, 92. *See also* Denisjuk hologram
- Liquid carbon disulphide CS<sub>2</sub>, stimulated Brillouin scattering (SBS) of, 512
- Liquid crystal(s), 341
  - cholesteric, 342
  - discotic, 344
  - nematic, 343
  - smectic, 343
- Liquid crystal devices, 346
  - Fabry–Pérot resonator, 346
  - fiber filter, 176, 188
  - microlens, 347
  - rotatable waveplate, 346
  - spatial light modulator (SLM), 349, 350, 351, 352
  - television, 350
- Lithium iodate (LiIO<sub>3</sub>), electrooptic properties of, 306
- Lithium fluoride (LiF), 708
- Lithium oxide (LiO<sub>2</sub>), 706
- Lithium niobate LiNbO<sub>3</sub>
  - deposited on lithium tantalate, 296–299, 575
  - elasto-optic effect of, 320
  - electro-optic effect of, 144, 305, 307, 312, 358, 579, 649, 821
  - photorefractive effect of, 332, 511
- LiTaO<sub>3</sub>, *see* Lithium tantalate
- Lithium tantalate (LiTaO<sub>3</sub>)
  - electro-optic properties of, 296, 298, 299, 305, 321
  - photorefractive effect of, 511
- LO (local oscillator) light, 192, 807
- Local oscillator (LO) light, 192, 807
- Local oscillator intensity noise power (LOIN), 1122
- Location of the Gaussian beam waist, 208, 217
- Longitudinal external field to bulk waves, 681
- Longitudinal lines of the Poincaré sphere, 479
- Longitudinal mode number, 972
- Longitudinal modes, 846, 909
- Long-line effect, 954
- Loose-tube covered fiber, 784



- Lorentz lineshape function, 840  
 Loss, fiber  
     bending, 407  
     cavity, 173  
     connector, 790, 1130, 1131, 1138, 1144, 1146  
     coupling, 1130, 1138, 1144  
     fiber transmission, 694, 1138, 1146  
     increase due to hydrogen and gamma-ray irradiation, 695  
     splicing, 790, 1130, 1131, 1138, 1146  
 Low pass spatial filter, 62  
 Low-work-function material, 796  
 LP (linear polarization) mode, 709, 727, 736  
 $LP_{m\mu}$  modes, 726, 728, 730, 735, 737  
     designation of, 729  
     field pattern of, 735  
 Lumped element approach, 1106  
 Lyot–Ohman filter, 363, 385  
  
 $m^2$  (beam propagation factor), 220  
 Mach–Zehnder fiber coupler, 745  
 Mach–Zehnder interferometer, 679, 683, 793, 1019  
 Mach–Zehnder light modulator, 685  
 Magnesium fluoride ( $MgF_2$ ), 681, 708  
 Magnesium oxide ( $MgO$ ) to lower melting point of glass, 706  
 Magnetic flux densities, 112  
 Magnetic flux leaking out of transformer, 145  
 Magnetic permeability, 111, 326  
 Magneto optic effect, 326  
 Magneto optic property of a Nd:YAG crystal, 968  
 Magnification of images, 219, 220  
 Major and minor axes of elliptically polarized waves, 372, 431, 433  
 Major principal transmittance  $k_1$  of polarizer sheets, 396  
 MAN (metropolitan area network), 866  
 Manchester Code, 1097  
 Manipulation of micron-sized spheres with light beams, 249  
 Mass fusion splicing machine of fibers, 786, 787  
 Material dispersion of optical fiber, 699, 701, 752  
 Matrix  
     coefficient, 623  
     Jones, 421  
     transmission, 625, 626, 630  
 Maximum available power from source, 1114  
 Maximum energy coupling in four-wave mixing, 528  
 Maximum modulation frequency, 920  
 Maxwell's equations, 268, 521, 607, 609, 610, 709, 715  
     boundary conditions of continuity, 112, 121  
 MCVD (modified chemical vapor deposition)  
     method, 778  
 Mellin transform, 76  
 Memory disks, high density, 161  
 Mercury flash lamp, 894  
  
 Meridional rays, 693, 718, 771  
 Mesa structure (steep hill structure) laser diodes, 995  
 MESFET (metal semiconductor field effect transistor), 1110  
 Metal field plate to prevent stray light into detector diodes, 803  
 Metal guide for integrated optics, 672  
 Metal semiconductor field effect transistor (MESFET), 1110  
 Metastable lifetime of  $Er^{3+}$ , 891  
 Methane ( $CH_4$ ), 512  
 Method by trial solution, 1024  
 Method of separation of variables, 1022, 1160  
 Metropolitan area network (MAN), 866  
 $MgF_2$  (magnesium fluoride), 681, 708  
 $MgO$  (magnesium oxide) to lower the melting point of glass, 706  
 Michelson interferometry, 166  
 Microbending loss of optical fibers, 783, 784  
 Microbes, 363  
 Microchannel plate to enhance electron density, 800  
 Microfiche recording, 93  
 Microscope, Schlieren, 63  
 Microwave hologram, 96  
 Minimum detectable power of receivers, 1113  
 Minor principal transmittance  $k_2$  of polarizer sheets, 396  
 Mirrors  
     dichroic, 167  
     half, 65, 505  
     phase conjugate, 504  
 MISER (monolithic isolated single-mode end-pumped ring) laser, 968, 1012  
 MMI (multimode interference) splitter, 674  
 MNA (2-methyl-4-nitroaniline) crystal for phase modulation, 182  
 Modal noise, laser diode, 955  
 Modal retarder of TM–TE converter, 499  
 Mode  
     density, 843, 847, 1160  
     dispersion of optical fiber, 612, 699, 703, 769  
     hopping of laser diodes, 945  
     in graded index fibers, 759, 767, 768, 772  
     in nonlinear guides, 1043, 1048  
     in step index fibers, 718  
     inside cavities, 223, 226, 235  
     of propagation, 605  
     number with the periodic boundary condition, 1163  
     number in slab guides, 612  
     patterns in graded-index fibers, 770  
     pattern in rectangular guides, 662  
     patterns in slab guides, 615  
 Mode converter, 497, 502, 684, 685  
 Mode hopping, 945  
 Mode-index lens, 620

- Mode locking, 945
- Mode number, *see* Mode
- Modified Bessel function, 714
  - of the first kind, 714
  - of the second kind, 714
- Modified chemical vapor deposition (MCVD)
  - method, 778
- Modified ray model method, 606, 622, 636
- Modulation format
  - amplitude (AM), 1086, 1087, 1083
  - amplitude shift keying (ASK), 812, 1089, 1095
  - double sideband (DSB), 1086, 1087
  - double sideband suppressed carrier (DSBC), 1087
  - frequency (FM), 1088, 1092
  - frequency shift keying (FSK), 1089, 1095
  - intensity (IM), 313, 1086, 1087
  - phase (PM), 1088, 1092, 1094
  - phase shift keying (PSK), 1089, 1095
  - pulse amplitude (PAM), 1088, 1094
  - pulse code (PCM), 1084, 1089, 1094
  - pulse duration modulation (PDM), 1088, 1094
  - pulse position (PPM), 1088, 1094
  - quadrature amplitude (QAM), 1087, 1090
  - single sideband (SSB), 1087, 1090
  - sinusoidal, 103
  - vestigial sideband (VSB), 1087, 1091
- Modulation index, 1086
- Modulators, 312, 605, 1018
- Mole fraction, 923
- Molecular reorientation of nematic liquid crystals, 345
- Momentum of photons, 250, 572
- Momentum-matching, 113
- Monochromator, 175
- Monocoated fiber, 784
- Monolithic isolated single-mode end-pumping ring (MISER) laser, 968, 1012
- Monomode fiber (single mode fiber), 700, 705, 728
- Monomode optical guide, 612
- Morse code, 1095
- Movement of a point on the Poincaré sphere, 494
  - along constant latitude ( $\beta$ ), 497
  - along constant longitude ( $\theta$ ), 494
- Movement parallax, 92
- MQW laser, *see* Multi-quantum-well laser
- MQW (multi-quantum-well) nonlinear layers, 1019
- Multiexposed hologram, 519
- Multi-ingredient fiber, 706
- Multimode graded-index fiber, 705, 769
- Multimode interference (MMI) splitter, 674
- Multimode step-index fiber, 703
- Multiple D fiber, 866, 867
- Multiplexer, 677
- Multiplexing (MX), 1085, 1097
  - code-division (CDM), 1085, 1094
  - frequency division (FDM), 1085, 1094, 1099
  - time division (TDM), 1085, 1094, 1100
  - wavelength division (WDM), 191, 674, 676, 1085, 1098
- Multiplexing fiber sensor, 747
- Multiplier layers of APD, 803
- Multi-quantum-well (MQW) laser, 984, 992, 994–999
  - energy states, 988
  - gain curve, 992
  - threshold current, 994
- Multi-quantum-well (MQW) nonlinear layer, 1019
- Multiunit fiber cable, 784
- MX, *see* Multiplexing
- $N \times N$  matrix connection by AWG, 676
- NA (numerical aperture), 151, 693, 694, 701, 703, 706, 770
- $N_\alpha$  (zero gain electron density of laser media), 902
- NaCl (sodium chloride), 341, 708
- $\text{NaClO}_3$  (sodium chlorate), optically active, 412
- $\text{Na}_2\text{O}$  (sodium oxide) to lower the melting point of glass, 706
- Narrow stripe electrodes of laser diodes, 934
- N,N*-dimethyl-*N*-octadecyl-3-amino-propyltrimethoxysilyl chloride (DMOAP), 353
- Natural sugar ( $\text{C}_{12}\text{H}_{22}\text{O}_{11}$ ), 414
- Nd:YAG (neodymium-doped yttrium-aluminum-garnet) laser
  - rod, 890, 1178
  - solid-state laser, 967, 1012
- Near field (Fresnel field), 13
  - imaging, 110
  - of optical microscopes, 150
  - optics, 110
- Nebulae, Faraday effect of, 363
- Negative birefringence, 267
- Negative feedback circuit, 1109
- Nematic liquid crystal, 341, 343, 347, 357
- NEP (noise equivalent power), 1117
- Neodymium (Nd)-doped fiber amplifier, 836, 837
- Neodymium YAG laser, *see* Nd:YAG laser
- Neodymium YAG rod, 889
- $\text{NH}_4\text{F}$  (ammonium fluoride), 158
- Nicol prism, 402
- Nitrobenzene ( $\text{C}_6\text{H}_5\text{NO}_2$ )
  - Kerr constant of, 316, 317
  - Kerr effect of, 1017, 1035
- Nitrotoluene ( $\text{C}_6\text{H}_4(\text{CH}_3)\text{NO}_2$ ), Kerr effect of, 1017
- NLC (nematic liquid crystal), 341, 343, 347, 357
- Nondeformed strain, 304
- Noise
  - associated with relaxation oscillation, 955
  - due to external optical feedback, 953
  - due to fluctuations in temperature and injection current, 955
  - due to mode hopping, 955

- due to spontaneous emission, 955
- excess index, 1117
- FM, 955
- in an APD, 1117
- in detector systems, 1113
- partition, 955
- quantum limited, 1116, 1131
- shot, 1113
- thermal, 1114
- thermal noise limited, 1116, 1131
- Noise equivalent power (NEP), 1117
- Noise figure, 880, 883
- Nonlinear
  - differential equations, 550, 1022, 1024
  - distributed feedback (DFB) gratings, 1019
  - Kerr media, 512, 518
  - normalized thicknesses, 1041, 1048
  - parameter, 1072, 1077
  - saturable absorbers, 945
  - Schrödinger equation, 1067
  - susceptibility of photorefractive crystals, 511
- Nonlinear-index coefficient  $n_2$ , 1023, 1066
- Nonoptical holographies, 95
- Nonpolarizing beam splitter (NPBS), 411, 822, 830
- Nonradiative transitions, 835
- Nonreciprocal effects, 713
- Nonreturn to zero (NRZ) code, 774, 1096, 1140
- Normal dispersion region, 1056
- Normal to ellipse, expression of, 432
- Normalized guide index  $b$ , 659
- Normalized propagation parameter, 728
- Normalized pumping rate of fiber amplifiers, 850
- Normalized steady-state population difference, 849
- Normalized thickness of optical guides, 611, 1041, 1047, 1048
- “nose” of Panda fibers, 407
- NPBS (nonpolarizing beam splitter), 411, 822, 830
- NRZ (nonreturn to zero) code, 774, 1096, 1140
- n-type semiconductors, 1151, 1152
- Numerical aperture (NA), 151, 693, 694, 701, 703, 706, 770
- $v$ th order Bessel function of the first kind, 713
- $O$  modes in nonlinear guides, 1043, 1048
- OASLM (optically addressed spatial light modulator), 351
- Odd TM modes of optical planar optical guides, 608, 609, 610
- Off-axis type hologram, 85
- Offset core fiber, 866
- OH (hydroxyl) ion impurities, 695, 697
- On-off modulation (ASK modulation), 812, 1095
- One-stage processes of fabrication of optical fibers, 775
- OPC (optical phase conjugate), 541
- Operational amplifier, 1107
- Optic axis of crystals, 267
- Optical activity, 412, 415, 586
- Optical amplifier
  - based on doped fiber, 833. *See also* Erbium doped fiber amplifier (EDFA)
  - based on photorefractive effect, 334, 338
- Optical communication, *see* Fiber optic communication
- Optical correlators, 64
- Optical directional coupler, 988
- Optical feedback, 903
- Optical fiber(s)
  - cabling of, 783
  - characteristic equation of, 717, 718
  - cross sectional field distribution, 730
  - dispersion shifted, 703, 705, 749, 755, 1051
  - dominant mode of, 724
  - dual mode, 739, 757, 758
  - fabrication of, 775
  - gamma ray exposure, 697
  - graded index, 759, 762, 768, 769, 770
  - holey, 706
  - hydrogen exposure, 695
  - joining, 786
  - kinds of, 703
  - modes, 718, 726, 729, 736
  - multimode, 703
  - numerical aperture of, 693
  - other than silica based, 708
  - photoimprinted Bragg grating, 741, 1010
  - polarization preserving, 707
  - solution in the cladding region, 714
  - solution in the core region, 713
  - splicing, 786
  - transmission loss of, 694
- Optical fiber communication, *see* Fiber optic communication
- Optical fiber connector, 790, 1130
- Optical fibers other than silica-based fibers, 708
- Optical guide, *see* Optical slab guide
- Optical guide coupler, 144
- Optical interconnect, 99, 982
- Optical isolator, 327, 1005
  - polarization dependent, 328
  - polarization independent, 330
- Optical magic T, 678
- Optical modulator, 312, 679, 1018
- Optical phase conjugate (OPC), 541
- Optical resonator, *see* Fabry–Pérot cavity
- Optical signal multiplexing, 1085
- Optical signal processing, *see* Spatial filters
- Optical slab guides, 605, 606
  - asymmetric, 606, 638
  - characteristic equation, 610, 633, 634, 643
  - coefficient matrix approach, 622, 623
  - component waves, 615
  - coupled slab guide, 643, 651
  - dispersion equation, 612, 637, 638
  - effective index of refraction, 619
  - even modes, 608, 628

- Optical slab guides (*Continued*)
  - field distribution, 615
  - mode cutoff, 612
  - mode number, 612
  - modified ray model, 636
  - normalized thickness, 611
  - odd modes, 608, 628
  - propagation constant, 612
  - symmetric, 606
  - transmission matrix method, 625, 630
  - TE modes, 607, 620
  - TM modes, 607
  - wave optics approach, 607
- Optical tweezer, 226, 249, 251, 253
- Optical waveguides
  - arrayed waveguide grating (AWG), 673
  - characteristic equation, 657
  - confection, 666
  - confection lens, 667
  - coupling between guides, 664
  - effective index method, 661
  - electrode configurations, 681
  - electrode structures, 680
  - magic T, optical, 678
  - mode converter, 685
  - mode patterns, 662
  - polyimide half-waveplate, 677
  - power divider, 673
  - practical example of designing, 659
  - rectangular, 655
  - types of waveguides for integrated optics, 670
  - Y junction, 673
- Optically addressed spatial light modulator (OASLM), 351
- Optically tunable optical filter, 341
- Optimum length of fiber amplifiers, 867
- Optimum number of EDFA repeater stations, 882
- Optimum value of the multiplication factor of an APD, 1148
- Optoelastic, *see* Elastooptic effects
- Optoelectronic, *see* Electrooptic effects
- Orbital electrons, 1151
- Order of mode (mode number), *see* Mode
- Ordinary wave (o-wave), 269, 272, 273, 365
- Organohydrogen polysiloxane monomer as hardener, 697
- Orientation polarization, 265
- Orthogonal eigenvectors, 429
- Orthogonality between constant  $\theta$  and  $\epsilon$  lines of the Poincaré sphere, 465
- Orthoscopic image, 85
- OVD (outside vapor deposition) method, 778, 780
- Outlining input image, 64
- Output power from laser diodes, 913, 926
- Outside vapor deposition (OVD) method, 778, 780
- Overdrive parameter of the injection current, 952
- Overview of fiber-optic communication systems, 1082
- o-wave (ordinary wave), 269, 272, 273, 365
- Oxazine for dye lasers, 894
- $p$  wave (parallel wave), 118, 157
- Pair production, 1155, 1159
- PAM (pulse amplitude modulation), 1088, 1094
- Panda fiber, 406, 707
  - “eyes” of, 407
  - “nose” of, 407
  - polarizer, 407
- Parallax
  - accommodation, 93
  - binocular, 92
  - movement, 92
- Parallel alignment of the reflectors of a Fabry–Pérot interferometer, 199
- Parallel switching, 1092
- Parallel wave ( $p$  wave), 118, 157
- Paraxial, 11
- Partition noise of laser diodes, 955
- Parts per billion (ppb) ( $10^{-9}$ ), 695
- Pattern recognition, *see* Optical correlator; Phase conjugate optics
- PBS (polarizing beam splitter), 412, 822, 830
- PCS (plastic-clad silica) fiber, 775
- PCM (pulse code modulation), 1084, 1089, 1094
- PCVD (plasma chemical vapor deposition) method, 778, 779
- PDFA (praseodymium-doped fiber amplifier), 836
- PDLC (polymer-dispersed liquid crystal) type spatial light modulator (SLM), 352
- PDM (pulse duration modulation), 1088, 1094
- Period of relaxation oscillation, 930
- Periodic boundary condition, 1161, 1163
- Periodic horizontal external field, 684
- Periodic vertical external field, 684
- Permanent dipole moment, 265, 266
- Permanent joint, 786
- Permeability, magnetic, 111, 326
- Perpendicular wave (s wave), 118, 157
- Perturbation theory, 1164
- Phase conjugate optics, 504
  - expressions of, 507
  - for distortion free amplification, 513
  - for eliminating wave front distortion, 508
  - for picture processing, 512, 519
  - for self-tracking, 514, 517
  - in real time, 511
  - mirror, 504, 508
- Phase conjugate wave, 504, 521, 537, 539
  - explained by holography, 504
  - generation of, 506

- Phase conjugation method used in dispersion compensators, 755
- Phase correction factor of Fabry–Pérot resonators, 232
- Phase discriminator, 1094
- Phase diversity technique, 812
- Phase grating, 334
- Phase jitter, 819, 823
- Phase-lock loop (PLL), 809
- Phase matching, 113, 284
- Phase modulation (PM), 1088, 1090, 1092, 1094
- Phase modulators, 1018
- Phase shifter, 310
- Phase shift keying (PSK), 1089, 1095
- Phase velocity, 3, 748
- Phonons, 817, 835
- Phosphorus oxychloride ( $\text{POCl}_3$ ), 777
- Phosphorus pentaoxide ( $\text{P}_2\text{O}_5$ ), 697
- Photocell, 800
- Photochromic flexible guide, 672
- Photoconductive effect, 800
- Photoconductor cell, 800
- Photocurrent, 1159
- Photodetector, 1159
- Photodiode, 800
- Photoelastic effect, *see* Elastooptic effect
- Photoelastic fringes, 95
- Photoelastic sheet, 95
- Photoelasticity, 94
- Photoelectric effect, *see* Electrooptic effect
- Photoinduced Bragg grating, 741, 747, 755
  - applications of, 744
  - methods of writing, 742
  - photograph of, 745
- Photolithography machine, 513
- Photomultiplier tube (PMT), 796, 798
- Photon
  - flux density, 843
  - lifetime, 920
  - momentum, 250, 572
  - punch press, 903
  - radiation pressure, 249
- Photon–electron converter, of a cathode, 796
- Photon-induced pair production, 1103, 1159
- Photon tunneling microscope, 152, 161
- Photorefractive beam combiner for coherent homodyne detection, 339
- Photorefractive effect, 331
  - adaptive fiber couplers, 517
  - cockroach theory, 333
  - crystals, 77, 511, 517
  - energy transfer, 335
  - enhanced by external electric fields, 334
  - fly-swatter theory, 332
  - joint transform correlator, 77
  - optical amplifiers, 334
  - optically tunable filters, 341
  - real time phase conjugate mirrors, 511
- Photosensitivity, 741
- Phototransistor, 800
- Photovoltaic effect, 800
- $P$ – $I$  curve (light power vs. injection current) of laser diodes, 927
- Picture processing, 512, 519
  - by phase conjugate mirrors, 519
  - by spatial filters, 61
- Piezoelectric effect, 100
- Piezo transducer (PZT), 176
- Pigtailed laser diode, 1130
- PIN and PN photodetectors, 796, 801, 1085, 1104, 1151
  - equivalent circuit of, 1102
- Pinhole camera, 103, 558
- Planar optical guides, *see* Optical slab guide
- Planar-type W guide, 633
- Planck's constant, 250, 797
- Planck's factor of the radiation law, 1114
- Plane mirror cavity, 234
- Plane waves, 1, 268
- Plano-convex lens, 41
- Plasma chemical vapor deposition (PCVD)
  - method, 778, 779
- Plasma effect, 939, 944, 963
- Plasma-enhanced modified chemical vapor deposition (PMCD) method, 779
- Plastic-clad silica (PCS) fiber, 775
- Plastic fiber, 706
- PLL (phase locked loop), 809
- PM (phase modulation), 1088, 1092, 1094
- PM (pulse modulation), 1094
- PMCD (plasma-enhanced modified chemical vapor deposition) method, 779
- PMMA (polymethyl methacrylate), 706
- PMT (photomultiplier tube), 796, 798
- PN diode, 801
- p-n junction, 1154
- $\text{P}_2\text{O}_5$  (phosphorus pentaoxide), 697
- Pockels effect, 1018
- Pockels electrooptic effect, 304
  - electrooptic properties, 305, 307
  - for amplitude modulators, 312
  - for phase shifters, 310
  - for retarders, 311
- $\text{POCl}_3$  (phosphorus oxychloride), 777
- Poincaré, Henrie, 451
- Poincaré sphere, 451
  - constant  $\theta$  and  $\varepsilon$  lines, 465
  - converted from Argand diagram, 469
  - fabrication of a Poincaré sphere, 483
  - for solving polarizer problems, 485
  - for solving retarder problems, 479
  - how to construct, 451
  - how to use, 451
  - lines of constant  $\varepsilon$ , 458, 478
  - lines of constant  $\theta$ , 455, 479
  - traces of, 490

- Point-by-point writing of photoinduced Bragg grating, 744
- Point spread function, 14
  - in cylindrical coordinates, 243
  - in rectangular coordinates, 14
- Polariscope, 95, 363, 415
- Polarizers, 362
  - based on bending optical fibers, 404
  - based on scattering, 408
  - dichroic, 394
  - pile-of-plates, 407
  - polarizing beam splitter (PBS), 412
  - polaroid sheets, 399
- Polarization
  - azimuth of, 366
  - circular, 364
  - elliptical, 364
  - linear, 363
- Polarization dependent optical isolator, 328
- Polarization, electrical, 264, 266
- Polarization diversity method of detection, 822
- Polarization gradient laser cooling, 255
- Polarization independent optical isolator, 330
- Polarization jitter, 363, 819
- Polarization jitter controls, 819
- Polarization-maintaining fibers (or preserving), 404, 707, 819
- Polarization microscopes, 363
- Polarizing beamsplitter (PBS), 412, 822, 830
- Polaroid polarizer, 399
- Polygonal mirror, 101
- Polyimide half-wave-plate ( $\lambda/2$  plate), 677
- Polymer-dispersed liquid crystal (PDLC) type spatial light modulator (SLM), 352
- Polymethyl methacrylate (PMMA) for plastic fibers, 706
- Population difference of carriers, 860
- Population inversion of carriers, 836
- Population inversion factor, 847, 864
- Position vector, 6
- Positive birefringence, 267
- Positive carrier, 1153
- Potassium bromide (KBr), 708
- Potassium chloride (KCl), 708
- Potassium dihydrogen phosphate (KDP)
  - elastoopic properties of, 321
  - electrooptic properties of, 305, 316, 1018
- Power budget (requirement), 1130, 1144, 1148
- Power density handling capability of fiber amplifiers, 866
- Power density-interaction length for nonlinear effects, 816
- Power dividers, 673
- Power intensity, 114
- Power level parameter for nonlinearity, 1041
- Power required to establish a fundamental soliton, 1071
- Power saturation of EDFA, 838
- Power scrambler for optical networks, 677
- Power transmittance  $k$  of a polarizer, 485
- Poynting vector, 114, 117, 118, 124, 125, 275, 283
- ppb (parts per billion) ( $10^{-9}$ ), 695
- PPM (pulse position modulation), 1088, 1094
- PR, *see* Photorefractive effect
- Practical aspects of Fabry–Pérot interferometers, 234
- Practical aspects of optical fibers, 693
- Praseodymium-doped fiber amplifier (PDFA), 836
- Preform rod, optical fiber, 775, 777, 837
- Preheating ends of fiber before splicing, 790
- Preventing glare, 412, 419
- Primitive (basic) communication system, 1101
- Principal axes of an ellipse, 303, 431, 433, 434
- Principal mode number of graded-index fibers, 768, 771
- Principal section, 277, 278
- Principal strains, 318
- Principle of confection, 667
- Prisms, polarizing, 402
- Probability of spontaneous emission, 836
- Probes to detect evanescent fields, 154
- Projection, back, 469
- Propagation
  - constant, 4, 607, 612, 728, 729, 759, 768, 1055
  - direction of, 1, 2, 5, 7, 9
  - vector, 4, 5
- Propagation in anisotropic media, 263
  - in uniaxial crystals, 270, 272
- Pros and cons of 1.48- $\mu\text{m}$  and 0.98- $\mu\text{m}$  pump light, 853
- Proton-bombarded region, 935
- Pseudoscopic image, 85, 87, 89
- PSK (phase shift keying), 1089, 1095
- $p$ -type semiconductor, 1151, 1153
- Pulch's refractometer, 164
- Pulse amplitude modulation (PAM), 1088, 1094
- Pulse broadening compensation in optical fibers by four-wave mixing, 537
- Pulse code modulation (PCM), 1084, 1089, 1094
- Pulse duration modulation (PDM), 1088, 1094
- Pulse modulation, 1094
- Pulse position modulation (PPM), 1088, 1094
- Pump light of optical amplifiers, 834, 835, 837, 844
- Pyrometer, 800
- PZT (piezo transducer), 176, 207, 213, 215
- $q$  parameter, 209, 214, 216, 221, 222
- $Q$  of the cavity, 194
- QAM (quadrature amplitude modulation), 1087, 1090
- Quadratic electrooptic coefficients, 316
- Quadratic phase factor, 48, 49, 559
- Quadrature amplitude modulation (QAM), 1087, 1090
- Quadrature component, 810, 1090
- Qualitative explanation of laser oscillation, 908

- Quantization of the propagation constant in graded index fibers, 766
- Quantum dot laser, 1002
- Quantum efficiency, 797, 803, 804, 831, 951
- Quantum energy, 249
- Quantum limited, 1116
- Quantum size effect, 999
- Quantum-well laser, multi-, 933, 945, 984
- Quantum wire laser, 999
- Quarter-wave fiber loop, 382, 383
- Quarter-waveplate
  - function of, 371, 377, 386, 394, 480, 822
  - generate circular polarization by, 386
  - how to use, 386, 389, 392, 393
  - Jones matrix of, 424
  - optical fiber, 382
  - problems associated with, 394, 480, 483, 493
- Quartz crystal ( $\text{SiO}_2$ ), 412, 414, 447
  - electrooptic properties, 305
  - rotary power, 412, 414, 448
- Quasi-Fermi levels, 898, 994
- Quasi-Gaussian beam, 221
- Quasi single longitudinal mode laser, 909
  
- Radiation patterns
  - antenna, 13, 95
  - from a half wave dipole, 103
- Radiation pressure, 166
  - of laser light, 249
  - of photons, 254
- Radiation sensitive optical fiber, 698
- Radiation therapy, 698
- Radius of curvature of the wavefront of Gaussian beams, 208
- Raised resistivity by proton bombardment, 934
- Raman, 818
  - amplifier, 818
  - fiber laser, 1009
  - oscillator, 818
  - scattering, 816, 817
  - spectrum, 818
- Rate equations for the three-level model of  $\text{Er}^{3+}$ , 848
- Rate equations of semiconductor lasers, 909
- Rate of transitions of the carriers, 841
- Ray, 275
  - direction of, 275, 299
  - path, 277
  - velocity diagram, 579
- Ray theory, 759
- Rayleigh range of a Gaussian beam, 209
- Rayleigh resolution criteria, 151
- Rayleigh scattering, 694, 408, 448
- Rayleigh–Sommerfeld diffraction formula, 54, 58, 59, 545
- Real image, 85, 87
- Real time correlation, 77
  - of joint transform correlator (JTC), 77
  - of Vander Lugt correlator (VLC), 77
- Reciprocity theorem, 713
- Recombination of electrons and holes, 898
- Rectangle function, 20
  - Fourier transform of, 20
- Rectangular optical waveguide, 605, 655, 670
- Reflectance
  - at arbitrary incident angle, 124
  - at normal incidence, 117
- Reflected waves, 113
- Reflecting telescope, Cassegrain, 107, 108
- Reflection coefficients, 113, 114
  - at arbitrary incident angle, 118
  - electrical (at normal incidence), 113, 114
  - magnetic (at normal incidence), 113, 114
- Reflection coefficient for total internal reflection, 135
- Reflection finesse, 194
- Reflection of e-waves
  - from anisotropic boundaries, 294
  - in the case of total internal reflection, 295, 296
- Refractive index, *see* Index of refraction
- Refractive index gradient constant of Selfoc fibers, 763, 771
- Relative core index step  $\Delta$ , 758
- Relative magnetic permeability, 111
- Relaxation oscillation of laser diodes, 916, 917, 930
- Relaxation time of laser diodes, 1013
- Repeater stations, 833, 1081
- Required frequency bandwidth for amplifying digital signals, 1139
- Resolution
  - of lens-type microscopes, 150
  - of scanning near field optical microscope (SNOM), 154
- Resolving power of Fabry–Pérot resonators, 192, 194
- Resonance of Fabry–Pérot resonators, 167
  - condition, 174
  - frequency of  $p$ th longitudinal mode, 232, 233
  - wavelength, 178
- Responsivity  $R$ 
  - of photomultiplier tubes, 798
  - of PIN and APD photodiodes, 803, 805
- Retardance, 310, 365, 367, 431, 437, 579, 587
  - measurement of, 392, 393
  - microbes' pattern of, 363
- Retarded time frame, 1064
- Retarder, 310, 365, 378, 587
- Revere, Paul, 1085
- Return to zero (RZ) code, 774, 1096, 1141
- Rhodamine 6G dye, 357, 894
- Rib guide, 670
- Ribbon fiber cable, 785, 786, 790
- Ridge guide, 670

- Ring-type fiber laser, 1004
- Ring type solid state laser, 904, 967
- Rise time of laser diode turn-on, 930
- Rise-time requirement, 1132, 1145
- Rochon prism, 404
- Rotary power, 412, 414
  - dextrorotary (right-handed) or *d*-rotary, 412
  - levorotary (left-handed) or *l*-rotary, 412
- Rotation and scaling of the input image in signal processing, 73
- Rotation
  - of coordinates, 309, 314
  - of linearly polarized waves by the Faraday effect, 327
  - of major axes of an ellipse, 303
  - of polarization, 327, 412
- Rotators, 365, 412
  - Faraday effect, 326
  - Fresnel's explanation of, 413
  - optical activity, 412
  - saccharimeters, 417
- Rubber eraser, 303, 323
- Ruby laser, 894
- Rutile (TiO<sub>2</sub>), elastooptic properties of, 321
- RZ (return to zero) code, 774, 1096, 1141
  
- S (sulfur), 936
- S/N (signal to noise ratio), 1115, 1139
- s* wave (perpendicular, senkrecht in German) wave, 118, 157
- Saccharimeter, 414, 417
- SAM (stress-applying member), 707
- Sampled function, 31
- Saturated back-biased current, 1102, 1158
- Saturation signal power intensity, 853, 856, 857
- SBS (stimulated Brillouin scattering), 512, 602, 815, 817
- Scalar wave approach, 53
- Scanning electron microscope (SEM), 98, 161
- Scanning of Fabry–Pérot cavities, 176
  - by angle of incidence, 184
  - by frequency of incident light, 190
  - by index of refraction, 187
  - by reflector spacing, 177
- Scanning Fabry–Pérot spectrometer, 176
- Scanning near-field optical microscopes (SNOM), 154
- Scattering cross section, 254
- Schlieren camera, 63, 103
- Schrödinger equation, 985, 1067
- Scott-Russell, John, 1049
- Second harmonic generation (SHG), 299, 579, 1018
- Second order nonlinear susceptibility, 523, 525, 1018
- SE (surface emitting) laser, 956
- Selection of light sources, 1011
- Selfoc fiber, 763, 766, 770, 772
- Selfoc lens, 330
- Self-focusing in gain guiding laser diodes, 939, 941
- Self-induced transparency due to the soliton effect, 1076
- Self-oscillation of optical amplifiers, 838
- Self-phase modulation (SPM), 1051, 1052, 1053, 1069
- Self-pumped phase conjugation (SPPC), 518
- Self-tracking capability of phase conjugate waves, 514, 517
- Self-tracking of laser beams, 514
- Sellmeier formula, 702
- SEM (scanning electron microscope), 98, 161
- Semiconductors
  - acceptor atoms, 1153
  - bandgap energy, 804, 901, 925, 945, 996, 998
  - carrier concentration, 930
  - carrier confinement, 930
  - conduction band, 1151
  - density of states, 898, 987
  - donor atoms, 1152
  - effective mass, 924
  - Fermi energy level, 898, 1151, 1152
  - Fermi occupancy probability function, 1151
  - heterojunction, 930
  - intrinsic layer, 1151
  - n-type semiconductor, 1151, 1152
  - p-type semiconductor, 1151, 1153
  - p-n junction, 1154
  - quantum wells, 933, 984, 999, 1002
  - spontaneous emission, 254, 835, 836, 841, 842, 1007
  - stimulated emission, 835, 836
  - valence band, 1151
- Semiconductor laser amplifier (SLA), 837, 838, 847, 895, 1085
  - compared to EDFA, 838
- Semidegenerate four-wave mixing, 533
- Senarmont method for measuring retardance, 392, 491, 587
- Senarmont prism, 404
- Senkrecht wave (perpendicular, *s* wave), 118
- Sensing strain, vibration, and temperature by optical fibers, 747
- Sensitivity of photomultipliers, 797
- Sensors, 747, 1012
- Separation of variables, 1022, 1160
- SF<sub>6</sub> (sulfur hexafluoride) for chemical lasers, 895
- Shadowgrams, 97
- Shah function, 30
  - Fourier transform of, 31
- Shearing strain, 318
- SHG (second harmonic generation), 299, 579, 1018
- Shift keying, 1095
- Shifting theorem of the Fourier transform, 36
- Short-wavelength-loss edge (SLE), 697
- Shot noise, 1113
- Shot noise limited, 1116
- Shot noise power, 876



- SiCl<sub>4</sub> (silicon tetrachloride), 777
- Side pit fiber, 707
- Side scan sonar, 96
- Side tunnel fiber, 707
- Sifting property of the  $\delta$ -function, 29
- Sigma laser, 1004, 1005
- Sign conventions, 3, 368
- Sign functions, 25
  - Fourier transform of, 25
- Signal saturation intensity of EDFA, 853, 856
- Signal-spontaneous beat noise, 871
- Signal to noise ratio (S/N), 1115, 1139
  - for ASK modulation, 1121
  - for homodyne detection, 1122
  - for thermal noise limited case, 1131
  - of output from PIN photodiodes, 876
- Silica core fluorine-added cladding fiber, 705
- Silicon dioxide (SiO<sub>2</sub>)-based fiber, 708
- Silicon tetrachloride (SiCl<sub>4</sub>), 777
- SiO<sub>2</sub> (quartz), 305, 412, 681
- Sinc function, 21
- Sine-Gordon equation, 1076
- Single crystal mixer, 814
- Single heterojunction, 930
- Single longitudinal mode (SLM) laser, 907, 956
- Single-mode fiber (monomode), 700, 705, 728
- Single-mode laser, 909
- Single-mode optical guide, 612
- Single sideband (SSB) modulation, 1087, 1090
- Sketching hybrid mode patterns in optical fibers, 732
- Sketching linearly polarized mode patterns in optical fibers, 735
- Skew modes in optical fibers, 721
- Skew rate, 1125
- Skew ray in optical fibers, 693
- SLA, *see* Semiconductor laser amplifier
- Slab optical guide, *see* Optical slab guides
- SLE (short-wavelength-loss edge), 697
- Slipping-buffer layer in optical fiber cables, 783
- Slit, apodized, 22
- SLM (spatial light modulator), 349, 350, 351, 352
- SLM (single longitudinal mode) laser, 907, 956
- Slow axis of retarder, 367
- Slowly varying envelope approximation (Bohr approximation), 529
- Small signal amplitude modulation, 916
- Smectic liquid crystal, 341
  - "A" type, 343
  - "C" type, 343, 354, 356
- S/N (signal to noise ratio), *see* Signal to noise ratio
- Snell's law, 110, 112, 113, 121, 135, 292, 565, 566
  - in  $k$ -coordinates, 145, 164
- Snitzer proposal, 723
- SnO<sub>2</sub> (tin dioxide) transparent electrode, 311
- Sodium chlorate (NaClO<sub>3</sub>), optically active, 412
- Sodium chloride (NaCl), 341, 708
- Sodium oxide (Na<sub>2</sub>O) to lower the melting point of glass, 706
- SNOM (scanning near field optical microscope), 154
- Šolc filters, 385
- Soleil compensator, 382
- Solid-state laser, 893, 894, 895, 967
- Soliton, 1049
  - collisions of, 1070
  - envelope function, 1059, 1064
  - fundamental mode, 1069, 1071
  - generation of, 1050, 1052
  - history of, 1049
  - optical communication system, 1073, 1077
  - period, 1070, 1077
  - (pulse width)  $\times$  (amplitude) product, 1073, 1077
  - waves, 1017, 1052, 1056, 1081
- Sommerfeld, *see* Rayleigh–Sommerfeld diffraction formula
- Soot, 779
- Space charge polarization, 265
- Spatial derivative operation in image processing, 64
- Spatial filters, 61
  - derivative operation, 64
  - high pass, 63
  - low pass, 62
  - phase contrast, 63
- Spatial frequency, 1, 4, 8
  - approaches in Fourier optics, 52
  - components, 60
- Spatial hole burning, 968, 969, 1004, 1007
- Spatial light modulator (SLM), 349, 350, 351, 352
- Spatial mapping of microwave radiation, 343
- Spectral hole burning, 945
- Spectral lineshape, 839
- Spectral measurements by Fabry–Pérot resonator without reflector spacing, 203
- Spectroscopy, 4
- Spectrum of laser diode emission, 920
- Splicing fibers, 786, 866
- Splicing losses, 790, 1130, 1138, 1146
- Split field polarizer as an analyzer, 418
- SPM (self-phase modulation), 1051, 1052, 1053, 1058, 1069
- Spontaneous emission, 254, 835, 836, 841, 842, 1007
- Spontaneous emission lifetime, 254, 842, 926
- Spontaneous–spontaneous beat noise, 871, 872, 875
- SPPC (self-pumped phase conjugation), 518
- SRS (stimulated Raman scattering), 512, 818, 1009
- SSB (single sideband) modulation, 1087, 1090
- SSG (superstructure grating) laser diode, 977, 979
- Stability condition of cavity resonators, 231, 234
- Stable operation of optical tweezers, 253
- Standardized Japanese system for telephone bit rate, 1102

- Standardized U.S. system for telephone bit rates, 1102
- Standing-wave boundary condition, 1161, 1163
- Standing wave patterns, 89, 135, 235, 615, 636, 637, 969
- Star coupler, 678
- State of polarization, 371
  - graphical solution of, 365
- Static energy of induced polarization, 345
- Steady-state solutions of rate equations, 911
- Step and repeat function, 31, 64
- Step function, 25
  - Fourier transform of, 25
- Step index fiber, theory of, 709
- Step index multimode fiber, 703, 709, 1139
- Stereoscopic motion picture, 362
- Stimulated Brillouin scattering (SBS), 512, 602, 815, 817
- Stimulated effects, 816
- Stimulated emission, 835, 836, 842
- Stimulated emission cross section, 843, 859
- Stimulated Raman scattering (SRS), 512, 818, 1009
- Stokes radiation, 816, 1009
- Stopper layer of electrode structure, 681
- Strain, 318
  - fiber sensor, 747
  - free, 304
  - principal, 318
  - shearing, 318
- Stranded cable, 784, 786
- Stranding pitch, 784
- Streak camera, 798
- Streak pattern due to edge diffraction, 25
- Stress-applying member (SAM), 707
- Stripe substrate laser, 936
- Strip-loaded guide, 671
- Strongly coupled quantum wells, 988
- Subcarrier frequency, 1099
- Substrate, 606
- Sucrose ( $C_{12}H_{22}O_{11}$ ), 412
- Sulfur (S), 939
- Sulfur hexafluoride ( $SF_6$ ) for chemical lasers, 895
- Summary of essential formulas for calculating states of polarization, 439
- Summary of transformations of Gaussian beams by a lens, 219
- Sunglasses, 362
- Superheterodyne radio, 807
- Superposition, law of, 549, 1070
- Superstructure grating, 978
- Superstructure grating (SSG) laser diode, 977, 979
- Surface acoustic wave (SAW) light deflector, 324
- Surface acoustooptic modulator, 99
- Surface-emitting diode LED, 1008
- Surface-emitting (SE) laser, 956
- Surface wave, 135
- Susceptibility
  - electric, 266
  - nonlinear, 511, 523, 1018
  - tensor, 266
- Switching electrodes, 685
- Symmetric guide, 606
- Symmetric matrix, 430
- Synchronous homodyne receiver, 818
- Synthetic aperture holography, 97
- System loss, 1130
- 3Rs of repeaters, 833
- TAT 1 (Trans Atlantic Transmission), 693
- Taylor series expansion, 538, 1063
- TDM (time division multiplexing), 1085, 1094, 1100
- TE (transverse electric) wave, 607, 620, 719, 1030
- $TE_{0\mu}$  mode, 720, 721, 732
- Teleaxicon, 245
- Telephone bit rates, standardized U.S., 1102
- TE-like modes, 656
- Tellurium dioxide ( $TeO_2$ ), elastooptic properties of, 100, 322
- $TEM_{00}$  Gaussian mode, 226, 253
- $TEM_{11}$  Gaussian mode beam, 226, 253
- Temperature dependence of L-I curves of laser diodes, 951
- Temperature effect on the wavelength of laser diodes, 945
- Temperature fluctuations measured by optical fibers, 747
- Temporal frequency  $f$ , 4
- Tensor susceptibility, 266
- $TeO_2$  (tellurium dioxide), 100, 322
- Terminal contact resistance, 920
- Terminal potential, 928
- Terraced substrate (TS) laser diode, 936
- TE-TM converter, 502, 594, 685
- Tetrahedral substrate, 666
- TFT (thin film transistor), 350
- Thallium bromide (TlBr), 708
- Thallium monoxide ( $Tl_2O$ ) to lower the melting point of glass, 706
- Thermal noise, 876, 1114
- Thermal noise limited, 1116
- Thermister, 800
- Thin emulsion holograms, 88, 108
- Thin film transistor (TFT), 350
- Third-order dispersion effect, 755
- Third-order nonlinear electric susceptibility, 523, 527, 1018
- Three-dimensional displays, 92
- Three-layer optical guide with a linear core and nonlinear identical claddings, 1038
- Three-level material, 836
- Threshold carrier density, 927
- Threshold current, 909, 928, 930
- Threshold electron density, 928
- Threshold gain, 928

- Threshold light intensity of pump light, 860
- Thulium ( $\text{Tm}^{3+}$ ) for upconversion fiber amplifiers, 889
- Time constant of photomultipliers, 798
- Time constant of relaxation oscillation, 917
- Time degradation of LD output power, 1130
- Time-dependent solutions of rate equations, 859, 914
- Time division multiplexing (TDM), 1085, 1094, 1100
- Time reversed videotape, 504
- Time reversed wave, 507
- Tin dioxide ( $\text{SnO}_2$ ) transparent electrode, 311
- $\text{TiO}_2$  (rutile), 321
- Titanium doped indium phosphide ( $\text{InP:Ti}$ ), as a Kerr medium, 512
- TJS (transverse junction stripe) laser, 936
- $\text{Ti}_2\text{O}$  (thallium monoxide) to lower the melting point of glass, 706
- $\text{TlBr}$  (thallium bromide), 708
- $\text{Tm}^{3+}$  (thulium) for upconversion fiber amplifiers, 889
- TM (transverse magnetic) mode, 607, 719, 722
- TM-like modes, 656, 657, 659
- $\text{TM}_{0\mu}$  mode, 732
- $\text{TM}_0$  mode of optical guides (dominant mode), 612
- TM–TE converter, 497, 498
- TN (twisted nematic) liquid crystal, 344, 350, 351, 359
- TNSLM (twisted nematic liquid crystal spatial light modulator), 349
- Top layer of electrode structures, 680
- Topographic images obtained by AFM, 160
- Total internal reflection
  - of e-waves, 285, 296, 298
  - of o-waves, 130, 145, 147, 605
  - reflection coefficient for, 135
- Transcendental equations, 611, 639
- Transfer length of optical couplers, 651
- Transformation of Gaussian beams by lenses, 214
- Transformation of  $q$  parameters by lenses, 215
- Transimpedance circuit (TZ), 1109, 1110, 1136
- Transistor–transistor logic (TTL), 1124
- Transition energy, 254
- Transmission coefficients
  - at arbitrary incident angle, 118
  - at normal incidence, 114
  - electrical, 113, 114
  - magnetic, 113, 114
- Transmission loss of fibers, 694
- Transmission matrix method, 606, 622, 625, 626, 630
- Transmittance
  - at arbitrary incident angle, 124
  - at normal incidence, 117
- Transmitted waves, 113
- Transmitters, 893
- Transmitting satellite, 259
- Transoceanic fiberoptic submarine communication, 1017
- Transparent electrodes, 188, 311
- Transverse electric (TE) wave, 607, 620, 719, 1030
- Transverse external electric field to bulk waves, 681
- Transverse junction stripe (TJS) laser, 936
- Transverse magnetic (TM) wave, 607, 719
- Trapping micron-sized dielectric spheres, 249
- Triangle function, 21
  - Fourier transform of, 22
- Trimming electrodes, 684
- Triple-photon excitation, 889
- Trunk lines, 786
- TS (terraced substrate) laser diode, 936
- TTL (transistor–transistor logic), 1124
- Tunable optical coupler, 740
- Tunable optical filter
  - electrically, 188, 189
  - optically, 341
- Tuning of the wavelength of a laser diode
  - by Bragg reflector tuning current  $I_b$  alone, 973
  - by combining  $I_p$  and  $I_b$ , 975
  - by phase controller tuning current  $I_p$  alone, 973
- Turn-on characteristics of laser diodes, 920
- Turn-on delay time of laser diodes, 909, 914, 926, 930
- Turpentine ( $\text{C}_{10}\text{H}_{16}$ ), optical activity of, 412
- Twisted nematic (TN) liquid crystal, 344, 350, 351, 359
- Twisted nematic spatial light modulator (TNSLM) liquid crystal, 349
- Two-frequency method to remove phase jitter, 823
- Two-stage processes to fabricate optical fibers, 775, 837
- Two stage process to fabricate erbium doped fibers, 837
- Two-wave mixing gain of photorefractive materials, 518
- Tyndall, John, 692
- Types of optical fibers, 703
- TZ (transimpedance) circuit, 1109, 1110, 1136
- U-groove cable, 786
- Unbounded field, 627
- Unclamped condition, 304
- Undersea transmission cable, 833
- Unfolded, manipulation of confection, 666, 667
- Uniaxial crystals, 267
  - condition of propagation in, 272
  - graphical solution of propagation in, 270
  - propagation inside, 270
- Unit fiber cable, 784
- Unit vector for the direction of propagation, 7
- Unpolarized (depolarized) wave, 364
- Upatnieks hologram, *see* Leith–Upatnieks type hologram

- Upconversion fiber amplifier, 889
- Upper limit on the modulation frequency of a laser diode, 909, 920, 930
- U.S. standard rating DS-4 PCM, 1145
- UV laser beam, 744
- UV-light-cured resin, 697
- V shape fiber loss curve, 694
- VAD (vapor-phase axial deposition) method, 778, 780, 781
- Valence band, 899, 998, 1151
- Values of  $\sin \Delta$  to determine the handedness of elliptical polarization, 375
- Vanadium tetrachloride ( $\text{VCl}_4$ ), 777
- Van der Waals forces, 341
- Vander Lugt correlator (VLC), 64, 66
- Vapor-phase axial deposition (VAD) method, 778, 780, 781
- $\text{VCl}_4$  (vanadium tetrachloride), 777
- VCSEL (vertical cavity surface-emitting laser), 957, 981
- Vector propagation constant, 4
- Velocity matched Mach–Zehnder interferometer, 683
- Velocity of the envelope, 748
- Velocity surface of Huygens' wavelet ellipsoid, 578
- Verdet constant, 327
- Vernier effect, 977
- Vertical cavity surface-emitting laser (VCSEL), 957, 981
- Vertical external field in adjacent embedded guides, 683
- Vertical external field
  - in embedded guides, 683
  - periodic, 684
- Very near field, 150
- Vestigial sideband (VSB) modulation, 1087, 1091
- V-groove fiber, 786
- V-grooved substrate buried heterostructure (VSB) laser, 936
- Vibration fiber sensor, 747
- Vibration measurement by holography, 95
- Virtual image, 84
- VLC (Vander Lugt correlator), 64
  - compared to JTC, 72
- Voice channels, number of, 1102
- Voice recognition, 77
- Volume hologram, 87
- VSB (vestigial sideband), 1087, 1091
- VSB (V-grooved substrate buried heterostructure) laser, 936
- W guide, 635
- Waist location of Gaussian beams, 208
  - emergent from lenses, 217
- Waist size of Gaussian beams, 208
  - emergent from lenses, 216
- Water ( $\text{H}_2\text{O}$ )
  - as a nonlinear medium, 1017
  - as a polarized medium, 266
  - elasto-optic properties of, 320
  - Kerr constant of, 316, 317
- Wave equations in cylindrical coordinates, 709, 710
- Wave expressions of light, 132
- Wavefront, 276
- Waveguide, *see* Optical waveguides
- Waveguide dispersion of optical fibers, 699, 701, 752
- Waveguide index, optical fiber, 750
- Wavelength, 4, 8, 110, 112
- Wavelength converter, 352
- Wavelength division multiplexing (WDM), 191, 674, 676, 1085, 1098, 1175
- Wavelength filter, 684
- Wavelength matching, 113
- Wavelength-selective insertion into a WDM, 747, 1175
- Wavelength-selective tapping in a WDM, 747
- Wavelength shift of radiation from laser diodes, 943
- Wavenormal, 275, 295, 759, 761, 762
  - and Snell's law, 292
- Wavenumber, 177, 890
- Wave optics approach, propagation in planar optical guides, 606, 607
- Waveplate, 379
  - fiber type, 382, 383, 385
  - full, 385
  - half, 385
  - how to use, 385, 386, 389, 392, 393
  - quarter wave, 371, 377, 382, 386, 389, 393, 394, 480, 483, 493, 822
- Wavevector method to analyze waves in
  - anisotropic media, 264, 282
  - diagram of, 283, 284
- WDM (wavelength division multiplexing) system, 191, 674, 676, 1085, 1098, 1175
- Weakly coupled quantum wells, 988
- Weakly guiding approximation, 722, 726
- Weyl expansion theorem, 545
- White light hologram, 87
- Wollaston polarizing prism, 404
- Work function, 796
- Writing photoinduced Bragg gratings in optical fibers, 742, 744
- $\text{Xe}_2$  (Xenon) as medium for excimer lasers, 894
- X-ray analysis, 89, 97
- X-ray crystallography, 13
- Y-cut crystal, 307, 312
- Y junction, 673
- YAG (yttrium aluminum garnet) laser, 101, 894, 967
- Y-branch laser diode array, 983

- $\text{Y}_3\text{Al}_5\text{O}_{12}$  (YAG) yttrium aluminum garnet, 101, 894, 967  
 $\text{Y}_3\text{Fe}_5\text{O}_{12}$  (YIG) yttrium iron garnet, 329, 330  
YIG (yttrium iron garnet), 329, 330  
Yttrium aluminum garnet (YAG), 101, 894, 967  
Yttrium iron garnet (YIG), 329, 330
- ZBLAN fiber, 889  
Z-cut crystal, 307  
Zero gain electron density  $N_\alpha$  of laser media, 902  
Zeroth-order Bessel functions of the second kind, 714
- Zinc (Zn), 936  
Zinc chloride ( $\text{ZnCl}_2$ ), 708  
Zinc oxide ( $\text{ZnO}$ ), electrooptic properties of, 306  
Zinc sulfide ( $\text{ZnS}$ ), elastooptic properties of, 320  
Zinc telluride ( $\text{ZnTe}$ ), electrooptic properties of, 306  
Zn (zinc), 936  
 $\text{ZnCl}_2$  (zinc chloride), 708  
 $\text{ZnO}$ , *see* Zinc oxide  
 $\text{ZnS}$ , *see* Zinc sulfide  
 $\text{ZnTe}$ , *see* Zinc telluride