



Multi-functional, motor-driven injector for precise control of small volumes.

Setting the time and pressure in advance makes it possible to inject very small volumes of liquid with great precision. This model's numerous capabilities, including injection, filling up and holding, and varied functions such as foot switching, programming and air distribution, make it suitable for a wide variety of applications. Moreover, external control with the same action as the foot switch is possible via the input of TTL signals (negative logic).

Specifications:

Accessories included	Output Tube (with a tube connector, HI-7 Injection Holder) × 2 Input Hose (with a hose connector) AC Power Cord Foot Switch Silicone Rubber Gasket Cleaning Rod
Input pressure	Approx. 60 - 100 psi (= approx. 400 - 700 kPa)
Injection pressure	Approx. 0.1 - 60 psi (= approx. 0.7 - 400 kPa)
Balance pressure	Approx. 0 - 10 psi (= approx. 0 - 70 kPa, = approx. 0 - 0.07 MPa)
Time settings	10ms - 327.66 s
Count settings	1 - 255
Power source	AC 100 (±5%) - AC 120 (± 5 %), 50/60 Hz AC 220 (±5%) - AC 240 (± 5 %), 50/60 Hz
Power consumption	Approx. 25 W
Dimensions/Weight	W 425 × D 205 × H 90 mm, 3.7 kg

BioMedical Instruments Trading

Hofheimer Straße 63
D- 65719 Hofheim
Phone: +49 6192 2 91 88 66
Fax: +49 6192 90 13 98

Email: biomedical-instruments@science-products.com



in collaboration with:



Science Products Trading SPT AG
Käferholzstr. 142
CH- 4058 Basel
Phone +41 43 488 05 61
Fax: +41 43 488 05 62