

Exceptional value.
Results you can trust.

COULTER® AC-T™
Family of Hematology Analyzers



BR-12508A

COULTER® AC-T diff™ Instrument Specifications



PARAMETERS

WBC
RBC
Hgb
HCT
MCV
MCH
MCHC
RDW
PLT
MPV
PCT*
PDW*
LY %
LY #
MO %
MO #
GR %
GR #
Printed WBC, RBC,
PLT Histograms

SAMPLE ANALYSIS CHARACTERISTICS

- Whole blood 12 µL
- Predilute 20 µL, with on-board diluent dispense
- Automatic probe wipe
- Single-button operation with touch screen

DATA MANAGEMENT

- Patient ID auto-numbering
- 14-digit manual patient ID
- Three user-definable patient ranges
- Data storage for 250 patient results
- QC storage for 3 controls and 279 results
- Levey Jennings graphs

OPERATING RANGE	
Parameters	Range
WBC	0.0 - 150.0 x 10 ⁹ cells/µL
RBC	0.00 - 8.00 x 10 ⁶ cells/µL
Hgb	0.00 - 30.0 g/dL
MCV	50.0 - 130.0 fL
PLT	0 - 3000 x 10 ³ cells/µL
MPV	5.0 - 20.0 fL
LY%, MO%, GR%	0 - 100%
LY#, MO#, GR#	0 - 99.9 x 10 ³ cells/µL

SAMPLE STABILITY
- CBC/diff 24-hr room temperature

THROUGHPUT
- Minimum 50 samples/hour
- Results in less than 60 seconds

PRINTER
- Dot matrix graphics printer
- Single-ticket printer
- LED Page Printer

USER INTERFACE
- Touch screen
- Language-independent icons
- Single screen for all input
- One button sample aspiration
- ASTM, RS232 host communications

DIMENSIONS/WEIGHT		
Height:	42 cm (16.5 inches)	Depth: 39 cm (15.4 inches)
Width:	38 cm (15 inches)	Weight: 14 kg (30 lbs)

REAGENT ORDER INFORMATION		
AC-T diff	Configuration	Part Number
diff AC-T Tainer™	4 Liter	8547135
diff AC-T Pak™	15 Liter	8547134
AC-T Rinse™	500 mL	8547113
S-Cal® Calibrator	1 x 6 mL	7547005
4C®- ES Tri-Pack	12 x 3.3 mL	7547187
4C®- ES Tri-Pack	9 x 3.3 mL	7547189

COULTER® AC-T diff 2™ Instrument Specifications



PARAMETERS

WBC
RBC
Hgb
HCT
MCV
MCH
MCHC
RDW
PLT
MPV
PCT*
PDW*
LY %
LY #
MO %
MO #
GR %
GR #
Printed WBC, RBC,
PLT Histograms

SAMPLE ANALYSIS CHARACTERISTICS

- Closed- or open-vial sampling
- Whole blood closed- or open-vial mode 18 µL
- Predilute 20 µL with on-board diluent dispense
- Automatic probe wipe
- Single-button operation with touch screen

DATA MANAGEMENT

- Patient ID auto-numbering
- 14-digit manual patient ID
- Three user-definable patient ranges
- Data storage for 250 patient results
- QC storage for 3 controls and 279 results
- Levey Jennings graphs

OPERATING RANGE	
Parameters	Range
WBC	0.0 - 150.0 x 10 ⁹ cells/µL
RBC	0.00 - 8.00 x 10 ⁶ cells/µL
Hgb	0.00 - 30.0 g/dL
MCV	50.0 - 130.0 fL
PLT	0 - 3000 x 10 ³ cells/µL
MPV	5.0 - 20.0 fL
LY%, MO%, GR%	0 - 100%
LY#, MO#, GR#	0 - 99.9 x 10 ³ cells/µL

SAMPLE STABILITY
- CBC/diff 24-hr room temperature

THROUGHPUT
- Minimum 50 samples/hour
- Results in less than 60 seconds

PRINTER
- Single-ticket printer
- LED Page Printer

USER INTERFACE
- Touch screen
- Language independent icons
- Single screen display of all results
- Single screen for all input
- ASTM, RS232 host communications

DIMENSIONS/WEIGHT		
Height:	45 cm (18 inches)	Depth: 40 cm (16 inches)
Width:	49 cm (19 inches)	Weight: 20 kg (45 lbs)

REAGENT ORDER INFORMATION		
AC-T diff 2	Configuration	Part Number
diff AC-T Tainer™	4 Liter	8547135
diff AC-T Pak™	15 Liter	8547134
AC-T Rinse™	500 mL	8547113
S-Cal® Calibrator	1 x 6 mL	7547005
4C®- ES Tri-Pack	12 x 3.3 mL	7547187
4C®- ES Tri-Pack	9 x 3.3 mL	7547189

*For research use only. Not for use in diagnostic procedures in the United States.

COULTER® AC-T™ 5diff CP Instrument Specifications



PARAMETERS

WBC
NE#
NE%
LY#
LY%
MO#
MO%
EO#
EO%
BA#
BA%
ATL#*
ATL%*
IMM#*
IMM%*
RBC
Hgb
HCT
MCV
MCH

MCHC
RDW
PLT
MPV
PCT*
PDW*

SAMPLE ANALYSIS CHARACTERISTICS

- Closed- or open-vial sampling
- 53 µL whole blood CBC/diff Mode
- 30 µL whole blood CBC-only Mode

DATA MANAGEMENT

- Auto-sequence run number available
- 20 patient ranges with 5 programmable ranges for gender and age flagging
- Data storage for 10,000 patients
- 20 result action ranges with interpretive messages
- On-board Help files
- 24 Control files
- RS232 host transmission

OPERATING RANGE	
Parameters	Range
WBC	0-100 x 10 ⁹ cells/µL
RBC	0-10 x 10 ⁶ cells/µL
Hgb	0 - 30 g/dL
HCT	0 - 80%
PLT	0 - 1500 x 10 ³ cells/µL

SAMPLE STABILITY
- CBC 48-hr room temperature
- Diff 24-hr room temperature

THROUGHPUT
- Up to 60 samples/hour

PRINTER
- LED Page Printer

USER INTERFACE
- Stand-alone PC operating Windows[†] NT-based software
- On-board Quality Assurance, patient storage and worklists ASTM, RS232 host communications

DIMENSIONS/WEIGHT		
Height:	58.0 cm (23.0 inches)	Depth: 50.1 cm (19.8 inches)
Width:	44.4 cm (17.5 inches)	Weight: 36.2 kg (80 lbs)

REAGENT ORDER INFORMATION		
AC-T 5diff CP	Configuration	Part Number
AC-T™ 5diff Diluent	20 Liter	8547169
AC-T™ 5diff Hgb Lyse	400 mL	8547168
AC-T™ 5diff Fix	1 Liter	8547171
AC-T™ 5diff WBC Lyse	1 Liter	8547170
AC-T™ 5diff Rinse	1 Liter	8547167
AC-T™ 5diff Calibrator	2 x 2 mL	7547175
AC-T™ 5diff Control Plus	6 x 2.3 mL	7547198

*For research use only. Not for use in diagnostic procedures in the United States.
† Windows is a trademark of Microsoft Corporation.

COULTER® AC-T™ 5diff AL Instrument Specifications



PARAMETERS

WBC
NE#
NE%
LY#
LY%
MO#
MO%
EO#
EO%
BA#
BA%
ATL#*
ATL%*
IMM#*
IMM%*
RBC
Hgb
HCT
MCV
MCH

MCHC
RDW
PLT
MPV
PCT*
PDW*

SAMPLE ANALYSIS CHARACTERISTICS

- 100-sample autoloader
- Closed- or open-vial sampling via manual (stat) mode
- 53 µL whole blood CBC/diff Mode
- 30 µL whole blood CBC-only Mode
- Internal, and optional external, barcode reader

DATA MANAGEMENT

- Auto-sequence run number available
- 20 patient ranges with 5 programmable ranges for gender and age flagging
- Data storage for 10,000 patients
- 20 result action ranges with interpretive messages
- On-board Help files
- 24 Control files
- RS232 host transmission

OPERATING RANGE	
Parameters	Range
WBC	0-100 x 10 ⁹ cells/µL
RBC	0-10 x 10 ⁶ cells/µL
Hgb	0 - 30 g/dL
HCT	0 - 80%
PLT	0 - 1500 x 10 ³ cells/µL

SAMPLE STABILITY
- CBC 48-hr room temperature
- Diff 24-hr room temperature

THROUGHPUT
- Up to 80 samples/hour

PRINTER
- LED Page Printer

USER INTERFACE
- Stand-alone PC operating Windows NT-based software
- On-board Quality Assurance, patient storage and worklists ASTM, RS232 host communications

DIMENSIONS/WEIGHT		
Height:	54.0 cm (21.5 inches)	Depth: 58 cm (22.5 inches)
Width:	81.5 cm (32. inches)	Weight: 55 kg (121.3 lbs)

REAGENT ORDER INFORMATION		
AC-T 5diff AL	Configuration	Part Number
AC-T™ 5diff Diluent	20 Liter	8547169
AC-T™ 5diff Hgb Lyse	400 mL	8547168
AC-T™ 5diff Fix	1 Liter	8547171
AC-T™ 5diff WBC Lyse	1 Liter	8547170
AC-T™ 5diff Rinse	1 Liter	8547167
AC-T™ 5diff Calibrator	2 x 2 mL	7547175
AC-T™ 5diff Control Plus	6 x 2.3 mL	7547198

*For research use only. Not for use in diagnostic procedures in the United States.

*For research use only. Not for use in diagnostic procedures in the United States.

Performance You Can Count On

Our AC•T family of hematology analyzers delivers an unmatched combination of simplicity, affordability and compact design. From our proven 3-part histogram differential analysis to our full 5-part differential analysis, each analyzer delivers consistently accurate test results. Plus, our systems are backed by our superior service and support for maximum uptime.

- Proven technologies in affordable systems
- High-quality analyzers that provide results you can trust
- Complete system of superior reagents and controls
- Unparalleled level of customer service and support

COULTER® AC•T™ 5diff Auto Loader (AL) Hematology Analyzer



CBC with 5-part Differential

- 100-sample auto loader and open- or closed-vial manual (STAT) sampling with multiple tube size capability
- Extensive data management capabilities for optimal record keeping
- On-board Help files assist operator training
- 53 µL sample size for CBC with 5-part differential
- 80 samples-per-hour throughput ensures productivity
- Zero routine maintenance requirements and high system reliability help contain costs

Target volume: Ideal for customers performing 10-100 CBCs a day.

COULTER® AC•T™ 5diff Cap Pierce (CP) Hematology Analyzers



CBC with 5-part Differential

- Closed-vial sampling, automatic cap-piercing with multiple tube size capability
- Extensive data management capabilities for optimal record keeping
- On-board Help files assist operator training
- 53 µL sample size for CBC with 5-part differential
- 60 samples-per-hour throughput ensures productivity
- Zero routine maintenance requirements and high system reliability help contain costs

Target volume: Ideal for customers performing 10-100 CBCs a day.

COULTER® AC•T diff 2™ Hematology Analyzer



CBC with 3-part Differential

- Closed-vial sampling accommodates a variety of collection tube sizes
- Small 18 µL sample size in either closed- or open-vial modes
- Compact – Only two square feet of counter space required
- Efficient data management meets your laboratory's needs
- Automated quality assurance functions improve productivity
- Controls and calibrators designed for closed-vial sampling
- Zero routine maintenance requirements and high system reliability help contain costs

Target volume: Ideal for customers performing 1-100 CBCs a day.

COULTER® AC•T diff™ Hematology Analyzer



CBC with 3-part Differential

- One-step sample processing with touch screen user interface
- Automated probe wipe safely cleans the probe
- Small 12 µL sample size permits whole blood analysis from both venous and capillary collections
- Compact design lets you put the AC•T diff anywhere
- Results available in less than 60 seconds
- Efficient data management with patient and control storage
- Optional Veterinary software
- Zero routine maintenance requirements and high system reliability help contain costs

Target volume: Ideal for customers performing 1-50 CBCs a day.

To help maintain optimal system performance, each hematology analyzer is backed by Beckman Coulter's:

- Superior customer service and support to increase laboratory productivity
- Specially formulated reagents, controls and calibrators to ensure consistently reliable results
- Interlaboratory Quality Assurance Program (IQAP), which complements in-house quality control efforts and increases confidence in results