

Fluoride Ion Monitor HC-200F/HC-300F

4-Wire Analyzer

2-Wire Transmitter

Ideal for the continuous measurement of wastewater discharged from semi-conductor plants.

The HC-200F Simple Fluoride Ion Monitor for use in industry provides continuous measurements of the free fluoride ion concentration in wastewater using the fluoride ion electrode method. The unit can be used on a range of wastewater with varying concentrations from 0.0 to 10.0 mg/L up to 0 to 10,000 mg/L. This makes the HC-200F the ideal unit for monitoring the treatment of wastewater and effluent resulting from the semiconductor production process, as well as electronic and glass factories using fluoride in the production process.



Ideal for wastewater treatment at semi-conductor / FPD plants and glass factories

Suitable for on-site continuous measurement of fluoride ions at treatment facilities discharging large volumes of wastewater.

Wide range of measurements

This one unit is capable of measuring in a range from 0 to 10,000 mg/L. (measurement can be switched across a range of 10 levels)

Implementing a silver ion trap structure

The silver ion trap prevents blocking at the liquid junction resulting in more stable measurements.

Internal cleaning timer

The cleaning solenoid valve can be operated directly. A water jet cleaner can be supplied as an optional extra.

■ Converter

■ Sensor

Cautions

1. This sensor detects the free fluoride ions contained in liquids, it does not detect all fluorides.
2. Measurements may vary depending upon the pH level. Use this monitor in close to neutral pH conditions.



Please read the operation manual before using this product to assure safe and proper handling of the product.

- The contents of this catalog are subject to change without prior notice, and without any subsequent liability to this company.
- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.

HORIBA Advanced Techno

HORIBA Advanced Techno, Co., Ltd.


Head Office

31 Miyanonishicho, Kisshoin Minami-ku, Kyoto, Japan 601-8306
Phone: (81)75-321-7184 Fax: (81)75-321-7291
<http://www.horiba-adt.jp>

■ Converter



■ Flow Type Holder
CF-301 (pressure type)



Model	Length: L
CH-101 (Material: PP)	0.5 m
	1.0 m
	1.5 m
CH-101P (Material: PVC)	2.0 m
	2.5 m
	3.0 m

Contact Address



Printed in Japan 1906SK00