

SPECIFICATIONS.

HydroSpeed™ Plate Washer.



The table below lists the specifications[#] for the HydroSpeed high speed microplate washer for 96 and 384 well plates.

General Specifications.

Parameters	Characteristics
Number of dispensing channels	1 – 4 (depending on the instrument configuration) Wash buffer bottle volume: 5 l or 10 l (large volume option, only with LLD) Waste bottle volume: 10 l (with or without LLD) or 20 l (large volume option, only with LLD)
Wash head types	96HT for high speed washing in 96-well format 384HT for high speed washing in 384-well format 96-indexing for flexible washing in 96- and 384-well formats

96-well microplates Specifications.

Parameters	Characteristics
Wash volume	50 – 3,000 µl in increments of 50 µl
Wash time	15 seconds for 1-cycle wash incl. crosswise asp. step 25 seconds for 3-cycle wash incl. crosswise asp. step (disp. vol.: 300 µl/well, disp. rate: 5, asp. rate: 5, 96HT head)
Dispense volume	50 – 400 µl in increments of 50 µl
Dispensing accuracy	≤ 5 % across plate, gravimetric measurement (disp. volume: 300 µl, disp. rate: 5, respectively asp. rate: 5, 96HT head, wash buffer plus 0.1 % Tween, Greiner® 96-well flat-bottom plate)
Dispensing uniformity	≤ 3 % across plate (disp. volume: 300 µl, disp. rate: 5, respectively asp. rate: 5, 96HT head, wash buffer plus 0.1 % Tween, Greiner 96-well flat-bottom plate)
Residual volume	≤ 2 µl per well, crosswise asp. (disp. rate: 5, respectively asp. rate: 5, asp. time: 5 s, 96HT head, wash buffer plus 0.1 % Tween, Greiner 96-well flat-bottom plate) ≤ 5 µl per well, single asp. point (disp. rate: 5, respectively asp. rate: 5, asp. time: 5 s, 96HT head, wash buffer plus 0.1 % Tween, Greiner 96-well round- and v-shaped bottom plates)
Carry over	Less than 1 ppm (parts per million) between plates

384-well microplates Specifications.

Parameters	Characteristics
Wash volume	10 – 1,000 µl in increments of 10 µl
Wash time	15 seconds for 1-cycle wash incl. asp. step 25 seconds for 3-cycle wash incl. asp. step (disp. vol.: 100 µl/well, disp. rate: 5, asp. rate: 5, 384HT head)
Dispense volume	10 – 120 µl in increments of 10 µl
Dispensing accuracy	≤ 5 % across plate, gravimetric measurement (disp. volume: 100 µl, disp. rate: 5, respectively asp. rate: 5, 384HT head, wash buffer plus 0.1 % Tween, Greiner 384-well flat-bottom plate)

Parameters	Characteristics
Dispensing uniformity	≤ 4 % across plate, gravimetric measurement (disp. volume: 100 µl, disp. rate: 5, respectively asp. rate: 5, 384HT head, wash buffer plus 0.1 % Tween, Greiner 384-well flat-bottom plate)
Residual volume	≤ 2 % per well, single asp. point (disp. rate: 5, respectively asp. rate: 5, 384HT head, wash buffer plus 0.1 % Tween, Greiner 384-well flat-bottom plate)
Carry over	Less than 1 ppm (parts per million) between plates, respectively between plate quadrants when working with the indexing wash head.

Additional Features and Software.

Parameters	Characteristics
Computer interface	USB
Shaking	Linear shaking; high, medium and low settings
Software	HydroControl (incl. FDA 21 CFR Part 11 functionality)
Colors	White (standard), red, blue

Dimensions and operating conditions.

Parameters	Characteristics
Outside dimensions	Width: 38.8 cm (15.3 inch) Depth: 43 cm (16.9 inch) Height: 28.8 cm (11.3 inch) Max. height of loading position (10.15 cm): Greater depth and height in service position
Weight	15 kg
Power supply	115 V / 60 Hz 230 V / 50 Hz
Operating conditions	Ambient temperature: Operation: 15°C to 35°C (59°F to 95°F); Storage: -30°C to 60°C (-32°F to 140°F) Relative humidity: Operation: 20 % to 80 % (non-condensing); Storage: 10 % to 80 % (non-condensing)

Options and Instrument Accessories.

Parameters	Characteristics
Liquid Level Detection (LLD, swimmer-based)	4-inlet channels large volume LLD incl. wash bottles LLD and waste bottle LLD
Magnetic bead washing	• Plate Carrier Smart-2 MBS 96 • Plate Carrier MBS 96 • Plate Carrier MBS 384
Vacuum filtration	Vacuum range: -50 to -300 mbar • Vacuum pump: 115 V • Vacuum pump: 230 V
For robotic integration	Shallow integration feet


Available Product Versions.

HydroSpeed (GP) # 30087536

Instrument specifications have been defined using Greiner flat-bottom compact 96-well and 384-well microplates and may vary using other 96-well microplates.

For further information and availability in your country please contact your local Tecan sales representative.

LEARN MORE



Australia +61 3 9647 4100 **Austria** +43 62 46 89 330 **Belgium** +32 15 42 13 19 **China** +86 21 220 63 206 **France** +33 4 72 76 04 80 **Germany** +49 79 51 94 170 **Italy** +39 02 92 44 790 **Japan** +81 44 556 73 11 **Netherlands** +31 18 34 48 17 4 **Nordic** +46 8 750 39 40 **Singapore** +65 644 41 886 **Spain** +34 93 595 25 31 **Switzerland** +41 44 922 89 22 **UK** +44 118 9300 300 **USA** +1 919 361 5200 **Other countries** +41 44 922 81 11

www.tecan.com

