



## **Rheology Solutions**

*Rheology Solutions is the sole Australian distributor of this product range and we welcome the opportunity of discussing your application requirements.*

*We hope the information you are seeking is contained within this file.  
If you have any questions, or require further information please contact us.  
We look forward to being of further service.*

*Regards from the Team at Rheology Solutions.*

**RHEOLOGY SOLUTIONS PTY LTD.** ACN 082 479 632

**HEAD OFFICE:** 15-19 Hillside Street, Bacchus Marsh, Victoria 3340 Australia. PO Box 754, Bacchus Marsh, Victoria 3340 Australia.

**Telephone:** +61 3 5367 7477 **Facsimile:** +61 3 5367 6477 **Email:** [info@rheologysolutions.com](mailto:info@rheologysolutions.com) **Website:** [www.rheologysolutions.com](http://www.rheologysolutions.com)

# Thermo Scientific SAHARA Series Heating Bath Circulators



**The SAHARA heating bath circulators** are ergonomically designed for ease of use and provide multiple certifications for exceptional safety.

Available in capacities from 5 to 49 liters, thermostats are attached by a sturdy bath bridge and can be positioned 90° on all four sides of the bath for easy viewing.

To meet all of your application requirements, these baths are constructed in a range of sizes and materials. Choose from transparent acrylic, polyphenylene oxide (PPO), or stainless steel.

#### Typical applications:

- Viscometers
- Spectrophotometers
- Refractometers
- Metrology



**Now select your bath below.**  
To see all thermostat specifications,  
please refer to Page 3

## Transparent Acrylic Baths

These baths are ideal for applications requiring good visibility. Temperatures are maintained from ambient plus 13°C to 60°C.



SC150-S6T acrylic bath circulator

AC150-S12T acrylic bath circulator

AC150-S19T acrylic bath circulator

| Model                           |                   | S6T heated bath circulator | S12T heated bath circulator | S19T heated bath circulator |
|---------------------------------|-------------------|----------------------------|-----------------------------|-----------------------------|
| Temp range                      | SC100 thermostat  | Amb +13 to 60°C            | Amb +13 to 60°C             | Amb +13 to 60°C             |
| Dimensions (HxWxL) mm           |                   | 353 x 170 x 400            | 353 x 310 x 340             | 353 x 310 x 510             |
| Temp range                      | SC150 thermostat  | Amb +13 to 60°C            | Amb +13 to 60°C             | Amb +13 to 60°C             |
| Dimensions (HxWxL) mm           |                   | 353 x 170 x 400            | 353 x 310 x 340             | 353 x 310 x 510             |
| Temp range                      | SC150L thermostat | —                          | —                           | —                           |
| Dimensions (HxWxL) mm           |                   | —                          | —                           | —                           |
| Temp range                      | AC150 thermostat  | —                          | Amb +13 to 60°C             | Amb +13 to 60°C             |
| Dimensions (HxWxL)              |                   | —                          | 388 x 310 x 340             | 388 x 310 x 510             |
| Temp range                      | AC200 thermostat  | —                          | Amb +13 to 60°C             | Amb +13 to 60°C             |
| Dimensions (HxWxL) mm           |                   | —                          | 388 x 310 x 340             | 388 x 310 x 510             |
| Bath capacity (liters)          |                   | 4-6                        | 8-12                        | 12-19                       |
| Reservoir dimensions (DxWxL) mm |                   | 150 x 138 x 210            | 150 x 300 x 140             | 150 x 300 x 310             |
| Net weight (kg)                 |                   | 6.3                        | 7.3                         | 8.7                         |

**Ordering information:** Find the part number by matching the thermostat to the bath size and voltage you need

| Model             |           | S6T heated bath circulator |                        |                           | S12T heated bath circulator |                        |                           | S19T heated bath circulator |                        |                           |
|-------------------|-----------|----------------------------|------------------------|---------------------------|-----------------------------|------------------------|---------------------------|-----------------------------|------------------------|---------------------------|
| Voltages          |           | 115V/60Hz <sup>1,3</sup>   | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,3</sup>    | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,3</sup>    | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> |
| SC100 thermostat  | Order no. | 152-2062                   | 152-2061               | 152-2066                  | 152-2122                    | 152-2121               | 152-2126                  | 152-2192                    | 152-2191               | 152-2196                  |
| SC150 thermostat  | Order no. | 153-2062                   | 153-2061               | 153-2066                  | 153-2122                    | 153-2121               | 153-2126                  | 153-2192                    | 153-2191               | 153-2196                  |
| SC150L thermostat | Order no. | —                          | —                      | —                         | —                           | —                      | —                         | —                           | —                      | —                         |
| AC150 thermostat  | Order no. | —                          | —                      | —                         | 155-2122                    | 155-2121               | 155-2126                  | 155-2192                    | 155-2192               | 155-2196                  |
| AC200 thermostat  | Order no. | —                          | —                      | —                         | 156-2122                    | 156-2121               | 156-2126                  | 156-2192                    | 156-2192               | 156-2196                  |

\*Bath volume varies depending on the fluid used, temperature range, and items inserted into the reservoir.

Certification: <sup>1</sup>CE <sup>2</sup>UL<sub>us</sub> <sup>3</sup>UL<sub>us</sub>

Visit <http://www.ul.com/global/eng/pages/> to view the UL listings for Thermo Fisher Scientific. Reference file #E164214 for these products.

# Thermo Scientific SAHARA Series Heating Bath Circulators

## Polyphenylene Oxide (PPO)

An economical alternative to stainless steel, these modified polyphenylene oxide baths are thermally resistant up to 100° C and deliver exceptional temperature performance with operational savings. Temperatures are maintained from ambient plus 13°C to 100°C.



*SC150-S5P PPO bath circulator    AC150-S14P PPO bath circulator    AC150-S21P PPO bath circulator*



**Now select your bath below.**  
To see all thermostat specifications, please refer to page 3

| Model                           |                   | S5P heated bath  | S14P heated bath | S21P heated bath |
|---------------------------------|-------------------|------------------|------------------|------------------|
| Temp range                      | SC100 thermostat  | Amb +13 to 100°C | Amb +13 to 100°C | Amb +13 to 100°C |
| Dimensions (HxWxL) mm           |                   | 160 x 360 x 330  | 330 x 400 x 380  | 330 x 400 x 540  |
| Temp range                      | SC150 thermostat  | Amb +13 to 100°C | Amb +13 to 100°C | Amb +13 to 100°C |
| Dimensions (HxWxL) mm           |                   | 160 x 360 x 330  | 330 x 400 x 380  | 330 x 400 x 540  |
| Temp range                      | SC150L thermostat | —                | —                | —                |
| Dimensions (HxWxL) mm           |                   | —                | —                | —                |
| Temp range                      | AC150 thermostat  | —                | Amb +13 to 100°C | Amb +13 to 100°C |
| Dimensions (HxWxL) mm           |                   | —                | 330 x 400 x 380  | 330 x 400 x 540  |
| Temp range                      | AC200 thermostat  | —                | Amb +13 to 100°C | Amb +13 to 100°C |
| Dimensions (HxWxL) mm           |                   | —                | 330 x 400 x 380  | 330 x 400 x 540  |
| Bath capacity (liters)          |                   | 3-5              | 8-14             | 13-21            |
| Reservoir dimensions (DxWxL) mm |                   | 130 x 160 x 297  | 300 x 160 x 157  | 300 x 160 x 347  |
| Net weight (kg)                 |                   | 5.1              | 6.3              | 6.6              |

**Ordering information:** Find the part number by matching the thermostat to the bath size and voltage you need

| Model             |           | S5P heated bath          |                        |                           | S14P heated bath         |                        |                           | S21P heated bath         |                        |                           |
|-------------------|-----------|--------------------------|------------------------|---------------------------|--------------------------|------------------------|---------------------------|--------------------------|------------------------|---------------------------|
| Voltages          |           | 115V/60Hz <sup>1,3</sup> | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,3</sup> | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,3</sup> | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> |
| SC100 thermostat  | Order no. | 152-3058                 | 152-3051               | 152-3056                  | 152-3148                 | 152-3141               | 152-3146                  | 152-3218                 | 152-3211               | 152-3216                  |
| SC150 thermostat  | Order no. | 153-3058                 | 153-3051               | 153-3056                  | 153-3148                 | 153-3141               | 153-3146                  | 153-3218                 | 153-3211               | 153-3216                  |
| SC150L thermostat | Order no. | —                        | —                      | —                         | —                        | —                      | —                         | —                        | —                      | —                         |
| AC150 thermostat  | Order no. | —                        | —                      | —                         | 155-3148                 | 155-3141               | 155-3146                  | 155-3218                 | 155-3211               | 155-3216                  |
| AC200 thermostat  | Order no. | —                        | —                      | —                         | 156-3148                 | 156-3141               | 156-3146                  | 156-3218                 | 156-3211               | 156-3216                  |

<sup>1</sup>Bath volume varies depending on the fluid used, temperature range, and items inserted into the reservoir.

Certification: <sup>1</sup>CE <sup>2</sup>UL <sup>3</sup>UL

Visit <http://www.ul.com/global/eng/pages/> to view the UL listings for Thermo Fisher Scientific. Reference file #E164214 for these products.



## Stainless Steel

Powerful heating circulators with a stainless steel reservoir can be configured with different temperature ranges and volumes with efficient heating for open and closed applications. Rugged and corrosion-resistant for high temperature applications up to 200°C.

Choose from space-saving vertical baths or ergonomically flat baths to fit your lab.



**AC150-S15 heated bath circulator**  
Bath cover purchased separately

## Step 2



**Now select your bath below.**

To see all thermostat specifications, please refer to Page 3

| Model                                    |                   | S3 stainless steel heated bath | S7 stainless steel heated bath |
|------------------------------------------|-------------------|--------------------------------|--------------------------------|
| Temp range                               | SC100 thermostat  | Amb +13 to 100°C               | Amb +13 to 100°C               |
| Dimensions (HxWxL) mm                    |                   | 387 x 228 x 409                | 438 x 228 x 401                |
| Temp range                               | SC150 thermostat  | Amb +13 to 150°C               | Amb +13 to 150°C               |
| Dimensions (HxWxL) mm                    |                   | 387 x 228 x 409                | 438 x 228 x 401                |
| Temp range                               | SC150L thermostat | —                              | —                              |
| Dimensions (HxWxL) mm                    |                   | —                              | —                              |
| Temp range                               | AC150 thermostat  | Amb +13 to 150°C               | Amb +13 to 150°C               |
| Dimensions (HxWxL) mm                    |                   | 420 x 228 x 409                | 471 x 228 x 401                |
| Temp range                               | AC200 thermostat  | Amb +13 to 200°C               | Amb +13 to 200°C               |
| Dimensions (HxWxL) mm                    |                   | 420 x 228 x 409                | 471 x 228 x 401                |
| With tap water cooling coil option added |                   | +20°C to 100/150/200°C         | +20°C to 100/150/200°C         |
| Bath capacity (liters)                   |                   | 3-5                            | 4-7                            |
| Reservoir dimensions (DxWxL) mm          |                   | 134 x 139 x 303                | 185 x 143 x 345                |
| Net weight (kg)                          |                   | 10.3                           | 11.4                           |

**Ordering information:** Find the part number by matching the thermostat to the bath size and voltage you need

| Model             |           | S3 stainless steel heated bath |                        |                           | S7 stainless steel heated bath |                        |                           |
|-------------------|-----------|--------------------------------|------------------------|---------------------------|--------------------------------|------------------------|---------------------------|
| Voltages          |           | 115V/60Hz <sup>1,2</sup>       | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,2</sup>       | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> |
| SC100 thermostat  | Order no. | 152-1038                       | 152-1031               | 152-1036                  | 152-1078                       | 152-1071               | 152-1076                  |
| SC150 thermostat  | Order no. | 153-1038                       | 153-1031               | 153-1036                  | 153-1078                       | 153-1071               | 153-1076                  |
| SC150L thermostat | Order no. | —                              | —                      | —                         | 154-1078                       | 154-1071               | 154-1076                  |
| AC150 thermostat  | Order no. | 155-1038                       | 155-1031               | 155-1036                  | 155-1078                       | 155-1071               | 155-1076                  |
| AC200 thermostat  | Order no. | 156-1038                       | 156-1031               | 156-1036                  | 156-1078                       | 156-1071               | 156-1076                  |

\*Bath volume varies depending on the fluid used, temperature range, and items inserted into the reservoir.

Certification: <sup>1</sup>CE <sup>2</sup>UL <sup>3</sup>RU

Visit <http://www.ul.com/global/eng/pages/> to view the UL listings for Thermo Fisher Scientific. Reference file #E164214 for these products.

# Thermo Scientific SAHARA Series Heating Bath Circulators

(Stainless Steel continued)

Step 2



Now select your bath below.

To see all thermostat specifications, please refer to Page 3

| Model                                    |                   | S13 stainless steel heated bath | S15 stainless steel heated bath | S21 stainless steel heated bath |
|------------------------------------------|-------------------|---------------------------------|---------------------------------|---------------------------------|
| Temp range                               | SC100 thermostat  | Amb +13 to 100°C                | Amb +13 to 100°C                | Amb +13 to 100°C                |
| Dimensions (HxWxL) mm                    |                   | 438 x 312 x 441                 | 455 x 392 x 476                 | 404 x 392 x 652                 |
| Temp range                               | SC150 thermostat  | Amb +13 to 150°C                | Amb +13 to 150°C                | Amb +13 to 150°C                |
| Dimensions (HxWxL) mm                    |                   | 438 x 312 x 441                 | 455 x 392 x 476                 | 404 x 392 x 652                 |
| Temp range                               | SC150L thermostat | Amb +13 to 150°C                | Amb +13 to 150°C                | —                               |
| Dimensions (HxWxL) mm                    |                   | 438 x 312 x 441                 | 455 x 392 x 476                 | —                               |
| Temp range                               | AC150 thermostat  | Amb +13 to 150°C                | Amb +13 to 150°C                | Amb +13 to 150°C                |
| Dimensions (HxWxL) mm                    |                   | 471 x 312 x 441                 | 488 x 392 x 476                 | 437 x 392 x 652                 |
| Temp range                               | AC200 thermostat  | Amb +13 to 200°C                | Amb +13 to 200°C                | Amb +13 to 200°C                |
| Dimensions (HxWxL) mm                    |                   | 471 x 312 x 441                 | 488 x 392 x 476                 | 437 x 392 x 652                 |
| With tap water cooling coil option added |                   | +20°C to 100/150/200°C          | +20°C to 100/150/200°C          | +20°C to 100/150/200°C          |
| Bath capacity (liters)                   |                   | 8-13                            | 11-20                           | 21-Sep                          |
| Reservoir dimensions (DxWxL) mm          |                   | 200 x 223 x 335                 | 202 x 303 x 370                 | 151 x 303 x 546                 |
| Net weight (kg)                          |                   | 13.9                            | 16.9                            | 18.2                            |

**Ordering information:** Find the part number by matching the thermostat to the bath size and voltage you need

| Model             |           | S13 stainless steel heated bath |                        |                           | S15 stainless steel heated bath |                        |                           | S21 stainless steel heated bath |                        |                           |
|-------------------|-----------|---------------------------------|------------------------|---------------------------|---------------------------------|------------------------|---------------------------|---------------------------------|------------------------|---------------------------|
| Voltages          |           | 115V/60Hz <sup>1,2</sup>        | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,2</sup>        | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,2</sup>        | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> |
| SC100 thermostat  | Order no. | 152-1138                        | 152-1131               | 152-1136                  | 152-1158                        | 152-1151               | 152-1156                  | 152-1218                        | 152-1211               | 152-1216                  |
| SC150 thermostat  | Order no. | 153-1138                        | 153-1131               | 153-1136                  | 153-1158                        | 153-1151               | 153-1156                  | 153-1218                        | 153-1211               | 153-1216                  |
| SC150L thermostat | Order no. | 154-1138                        | 154-1131               | 154-1136                  | 154-1158                        | 154-1151               | 154-1156                  | —                               | —                      | —                         |
| AC150 thermostat  | Order no. | 155-1138                        | 155-1131               | 155-1136                  | 155-1158                        | 155-1151               | 155-1156                  | 155-1218                        | 155-1211               | 155-1216                  |
| AC200 thermostat  | Order no. | 156-1138                        | 156-1131               | 156-1136                  | 156-1158                        | 156-1151               | 156-1156                  | 156-1218                        | 156-1211               | 156-1216                  |

<sup>1</sup>Bath volume varies depending on the fluid used, temperature range, and items inserted into the reservoir.

Certification: <sup>1</sup>CE <sup>2</sup>cULus <sup>3</sup>cRUus

Visit <http://www.ul.com/global/eng/pages/> to view the UL listings for Thermo Fisher Scientific. Reference file #E164214 for these products.



| Model                                    |                        | S30 stainless steel heated bath | S45 stainless steel heated bath | S49 stainless steel heated bath |
|------------------------------------------|------------------------|---------------------------------|---------------------------------|---------------------------------|
| Temp range                               | SC100 thermostat       | Amb +13 to 100°C                | Amb +13 to 100°C                | Amb +13 to 100°C                |
| Dimensions (HxWxL) mm                    |                        | 455 x 392 x 652                 | 554 x 392 x 652                 | 455 x 392 x 1002                |
| Temp range                               | SC150 thermostat       | Amb +13 to 150°C                | Amb +13 to 150°C                | Amb +13 to 150°C                |
| Dimensions (HxWxL) mm                    |                        | 455 x 392 x 652                 | 554 x 392 x 652                 | 455 x 392 x 1002                |
| Temp range                               | SC150L thermo-<br>stat | Amb +13 to 150°C                | Amb +13 to 150°C                | Amb +13 to 150°C                |
| Dimensions (HxWxL) mm                    |                        | 455 x 392 x 652                 | 554 x 392 x 652                 | 455 x 392 x 1002                |
| Temp range                               | AC150 thermostat       | Amb +13 to 150°C                | Amb +13 to 150°C                | Amb +13 to 150°C                |
| Dimensions (HxWxL) mm                    |                        | 488 x 392 x 652                 | 587 x 392 x 652                 | 488 x 392 x 1002                |
| Temp range                               | AC200 thermostat       | Amb +13 to 200°C                | Amb +13 to 200°C                | Amb +13 to 200°C                |
| Dimensions (HxWxL) mm                    |                        | 488 x 392 x 652                 | 587 x 392 x 652                 | 488 x 392 x 1002                |
| With tap water cooling coil option added |                        | +20°C to 100/150/200°C          | +20°C to 100/150/200°C          | +20°C to 100/150/200°C          |
| Bath capacity (liters)*                  |                        | 17-30                           | 34-45                           | 29-49                           |
| Reservoir dimensions (DxWxL) mm          |                        | 201 x 303 x 546                 | 301 x 303 x 546                 | 202 x 303 x 896                 |
| Net weight (kg)                          |                        | 20.4                            | 24.8                            | 27.6                            |

**Ordering information:** Find the part number by matching the thermostat to the bath size and voltage you need

| Model             |           | S30 stainless steel heated bath |                        |                           | S45 stainless steel heated bath |                        |                           | S49 stainless steel heated bath |                        |                           |
|-------------------|-----------|---------------------------------|------------------------|---------------------------|---------------------------------|------------------------|---------------------------|---------------------------------|------------------------|---------------------------|
| Voltages          |           | 115V/60Hz <sup>1,2</sup>        | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,2</sup>        | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> | 115V/60Hz <sup>1,2</sup>        | 230V/50Hz <sup>1</sup> | 100V/50-60Hz <sup>1</sup> |
| SC100 thermostat  | Order no. | 152-1308                        | 152-1301               | 152-1306                  | 152-1458                        | 152-1451               | 152-1456                  | 152-1498                        | 152-1491               | 152-1496                  |
| SC150 thermostat  | Order no. | 153-1308                        | 153-1301               | 153-1306                  | 153-1458                        | 153-1451               | 153-1456                  | 153-1498                        | 153-1491               | 143-1496                  |
| SC150L thermostat | Order no. | 154-1308                        | 154-1301               | 154-1306                  | 154-1458                        | 154-1451               | 154-1456                  | 154-1498                        | 154-1491               | 154-1496                  |
| AC150 thermostat  | Order no. | 155-1308                        | 155-1301               | 155-1306                  | 155-1458                        | 155-1451               | 155-1456                  | 155-1498                        | 155-1491               | 155-1496                  |
| AC200 thermostat  | Order no. | 156-1308                        | 156-1301               | 156-1306                  | 156-1458                        | 156-1451               | 156-1456                  | 156-1498                        | 156-1491               | 156-1496                  |

\*Bath volume varies depending on the fluid used, temperature range, and items inserted into the reservoir.

Certification: <sup>1</sup> CE <sup>2</sup> cULus <sup>3</sup> cRUus

Visit <http://www.ul.com/global/eng/pages/> to view the UL listings for Thermo Fisher Scientific. Reference file #E164214 for these products.

