

cobas[®] 8000 modular analyzer series

Technical specifications

Configurations	The system offers more than 150 scalable configurations. A configuration consists from the core unit and 1 up to 4 analytical modules (excluding the optional cobas ISE module). The analytical modules are: cobas ISE module, cobas c 701 module, cobas c 702 module, cobas c 502 module, cobas e 801 module, cobas e 602 module.	
Detection methods	Clinical Chemistry:	Photometric
	Immunochemistry:	Electrochemiluminescence (ECL)
Maximum throughput	up to 9800 tests/hour/configuration cobas ISE module: up to 1800 tests/hour cobas c 701 module: up to 2000 tests/hour cobas c 702 module: up to 2000 tests/hour cobas c 502 module: up to 600 tests/hour cobas e 801 module: up to 300 tests/hour cobas e 602 module: up to 170 tests/hour	
Sample types	Serum, Plasma, Urine, CSF, Supernatant, Whole blood (not applicable for the cobas c 701 module and the cobas c 702 module)	
Sample tubes	∅ 13 x 75 mm, ∅ 13 x 100 mm, ∅ 16 x 75 mm, ∅ 16 x 100 mm, Hitachi standard cup 2.5 ml, cobas sample cup 2.5 ml, Hitachi microcup* 1.5 ml ∅ 11-16 x 63-102 mm (for cobas e 602 module: ∅ 13-16 mm)	
Pediatric sample tube	Yes (Hitachi microcup*: 50 µl dead volume)	
Sample capacity	core unit loading capacity:	300 samples
	Module Sample Buffer (MSB) capacity:	100 samples
	core unit throughput:	up to 1000 samples/hour
Sample volume	cobas c 701 module:	Average 5.5 µl
	cobas c 702 module:	Average 5.5 µl
	cobas c 502 module:	Average 7.0 µl
	cobas e 801 module:	Average 19.4 µl
	cobas e 602 module:	Average 26.8 µl
Automatic dilution	Yes	
Reagent capacity	up to 280 reagent channels/configuration cobas ISE module: Na, K and Cl cobas c 701 module: 70 reagent channels cobas c 702 module: 70 reagent channels cobas c 502 module: 60 reagent channels cobas e 801 module: 48 reagent channels cobas e 602 module: 25 reagent channels	



Life needs answers

cobas[®] 8000 modular analyzer series

Technical specifications

Reagent concept	Ready to use
Reagent loading	Continuous reagent loading during operation (valid for cobas c 702 module, cobas c 502 module and cobas e 801 module)
Sample clot detection	Yes
Sample interference measurement	Serum indices (icterus, hemolysis, lipemia) measured on the clinical chemistry modules
Remote diagnostics	Yes
Connectivity to smart phones and tablets	up to 3 systems can be connected to smart phones and tablets (iOS and Android) using cobas mobicheck application. The application allows the monitoring of the systems, alarms and reagent information.
Dimensions (W x D x H)	core unit (including STAT port): 102 x 114 x 93 cm cobas ISE module: 45 x 114 x 115 cm cobas c 701 module (including MSB): 150 x 114 x 135 cm cobas c 702 module (including MSB): 150 x 114 x 135 cm cobas c 502 module (including MSB): 150 x 114 x 130 cm cobas e 801 module (including MSB): 150 x 114 x 162 cm cobas e 602 module (including MSB): 150 x 106 x 114 cm
Weight	core unit: 197 kg cobas ISE module: 180 kg (ISE 1800), 170 kg (ISE 900) cobas c 701 module (including MSB): 697 kg cobas c 702 module (including MSB): 759 kg cobas c 502 module (including MSB): 535 kg cobas e 801 module (including MSB): 610 kg cobas e 602 module (including MSB): 585 kg
Electrical requirements	200/208/220/230 VAC, 50/60 Hz
Noise level	≤ 65 dB
Pre-Analytics connectivity	unidirectional, bidirectional
Power consumption	core unit (including the control unit): 1 kVA (actual maximum: 0.4 kVA) cobas ISE module: 0.5 kVA (actual maximum: 0.2 kVA) cobas c 701 module (including MSB): 3 kVA (actual maximum: 2.3 kVA) cobas c 702 module (including MSB): 3 kVA (actual maximum: 2.3 kVA) cobas c 502 module (including MSB): 2.5 kVA (actual maximum: 1.7 kVA) cobas e 801 module (including MSB): 2 kVA (actual maximum: 1.5 kVA) cobas e 602 module (including MSB): 3 kVA (actual maximum: 1.5 kVA)
Heat generation	core unit (including the control unit): 3600 kJ/h (actual maximum: 1440 kJ/h) cobas ISE module: 1800 kJ/h (actual maximum: 720 kJ/h) cobas c 701 module (including MSB): 10800 kJ/h (actual maximum: 8280 kJ/h) cobas c 702 module (including MSB): 10800 kJ/h (actual maximum: 8280 kJ/h) cobas c 502 module (including MSB): 9000 kJ/h (actual maximum: 6120 kJ/h) cobas e 801 module (including MSB): 7200 kJ/h (actual maximum: 5400 kJ/h) cobas e 602 module (including MSB): 10800 kJ/h (actual maximum: 5400 kJ/h)

* not applicable for the **cobas e** 602 module

COBAS, COBAS C, COBAS E and LIFE NEEDS ANSWERS are trademarks of Roche.

All other trademarks are property of their respective owners.

©2016 Roche

Roche Diagnostics International Ltd.
CH-6343 Rotkreuz
Switzerland
www.cobas.com