

Other analyzers



Non-Contact Infrared Thermometer
IT-545

■ Temperature

This is an easy-to-use portable thermometer with the highest level of accuracy in the industry*. Useful for various experiments and maintenance, food temperature management, etc.



Gloss Checker
IG series

■ Gloss

This gloss checker provides easy measurement of surface gloss levels, by quantifying the surface appearance visual inspection. Ideal for automotive coating inspections, floor waxing coating inspections, etc.



Environmental Radiation Monitor
PA series

■ γ (gamma) rays

This is a portable monitor that allows easy and accurate measurement of gamma rays. It is equipped with data communication function, enabling automatic recording of measured data and dose mapping, in linkage with a smartphone or computer.



Oil Content Analyzer
OCMA-500 series

■ Oil content

This analyzer measures oil content in water or seawater, residual oil on machine parts, and oil content in soil, etc. Easy to operate, this analyzer delivers speedy measurements.



Multi Parameter Water Quality Checker
U-50 series

pH / Dissolved oxygen / Electrical conductivity / Turbidity / Oxidation-reduction potential / Salt content / Specific gravity of seawater / Total dissolved solid quantity / Water temperature / Water depth / GPS

Many items can be measured simultaneously with one probe. This portable checker is best for outdoor use, such as measurements of river water, lake water, well water, and ground water.

■ Measurement items
■ Features

IMS The HORIBA Group adopts IMS (Integrated Management System) which integrates Quality Management System ISO9001, Environmental Management System ISO14001, and Occupational Health and Safety Management System OHSAS18001. We have now integrated Business Continuity Management System ISO22301 in order to provide our products and services in a stable manner, even in emergencies.

⚠ Please read the operation manual before using this product to assure safe and proper handling of the product.

- The specifications, appearance or other aspects of products in this catalog are subject to change without notice.
- Please contact us with enquiries concerning further details on the products in this catalog.
- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.
- The screen displays shown on products in this catalog have been inserted into the photographs through compositing.
- All brand names, product names and service names in this catalog are trademarks or registered trademarks of their respective companies.

<http://www.horiba.com> e-mail: info@horiba.co.jp

HORIBA, Ltd. **Japan**
Head Office
2 Miyano Higashi, Kisshoin, Minami-ku, Kyoto, Japan
Phone: 81 (75) 313-8121 Fax: 81 (75) 321-5725

HORIBA (China) Trading Co., Ltd. **China**
Shanghai
Unit D, 1F, Building A, Synnex International Park, 1068 West Tianshan Road, Shanghai, 200335, China
Phone: 86 (21) 6289-6060 Fax: 86 (21) 6289-5553
Beijing
12F, Metropolis Tower, No.2, Haidian Dong 3 Street, Beijing, 100080, China
Phone: 86 (10) 8567-9966 Fax: 86 (10) 8567-9066

HORIBA Korea Ltd. **Korea**
10, Dogok-Ro, 6-Gil, Gangnam-Gu, Seoul-Si, 06259, Korea
Phone: 82 (2) 753-7911 Fax: 82 (2) 756-4972

HORIBA Instruments (Singapore) Pte Ltd. **Singapore**
3 Changi Business Park Vista #01-01 Akzonobel House, Singapore 496051
Phone: 65 (6) 745-8300 Fax: 65 (6) 745-8155

HORIBA Vietnam Co., Ltd. **Vietnam**
Unit 6, 10 Floor, CMC Tower, Duy Tan Street, Dich Vong Hau Ward, Cau Giay District, Hanoi, Vietnam
Phone: 84 (4) 3795-8552 Fax: 84 (4) 3795-8553

HORIBA (Thailand) Ltd. **Thailand**
East Office
850 / 7 Soi Lat Krabang 30 / 5, Lat Krabang Road, Lat Krabang, Bangkok 10520, Thailand
Phone: 66 (0) 2734 4434 Fax: 66 (0) 2734 4438

PT HORIBA Indonesia **Indonesia**
Jl. Jalur Sutera Blok 20A, No.16-17, Kel. Kunciran, Kec. Pinang Tangerang-15144, Indonesia
Phone: 62 (21) 3044-8525 Fax: 62 (21) 3044-8521

HORIBA India Private Limited **India**
Delhi
246, Okhla Industrial Estate, Phase 3 New Delhi-110020, India
Phone: 91 (11) 4646-5000 Fax: 91 (11) 4646-5020
Technical Center
D-255, Chakan MIDC Phase-II, Bhambolli Village, Pune-410501, India
Phone: 91 (21) 3567-6000
Bangalore
No.55, 12th Main, Behind BDA Complex, 6th sector, HSR Layout, Bangalore South, Bangalore-560102, India
Phone: 91 (80) 4127-3637

HORIBA Instruments Inc. **USA**
Head Office
9755 Research Drive, Irvine, CA 92618, U.S.A.
Phone: 1 (949) 250-4811 Fax: 1 (949) 250-0924
Alvin, TX
5318 W.FM517 Rd, Alvin, TX 77511, U.S.A.
Phone: 1 (281) 482- 4334 Fax: 1 (281) 614-0303

HORIBA Instruments Brazil, Ltda. **Brazil**
Head Office
Rua:Presbitero Plinio Alves de Souza, 645, Loteamento Polo Multvias Bairro Medeiros-Jundiai Sao Paulo CEP 13.212-181 Brazil
Phone: 55 (11) 2923-5400 Fax: 55 (11) 2923-5490

HORIBA France SAS **France**
Les Ulis
12. Av des Tropiques Hightec Sud, F-91955 Les Ulis, France
Phone: 33 (1) 69-29-96-23 Fax: 33 (1) 69-29-95-77

HORIBA UK Limited **UK**
Northampton
Kyoto Close Moulton Park, Northampton NN3 6FL, UK
Phone: 44 (1604) 542-500 Fax: 44 (1604) 542-699

HORIBA Europe GmbH **Germany**
Head Office
Hans-Mess-Str.6 D-61440 Oberursel Germany
Phone: 49 (6172) 1396-0 Fax: 49 (6172) 1373-85
Leichlingen
Julius-kronenberg Str.9 D-42799 Leichlingen Germany
Phone: 49 (2175) 8978-0 Fax: 49 (2175) 8978-50

HORIBA Czech **Czech**
Prumyslova 1306 / 7, CZ-10200, Praha 10, Czech Republic
Phone: 420 (2) 460-392-65


HORIBA (Austria) GmbH **Austria**
Kaplanstrasse 5 A-3430 Tulln, Austria
Phone: 43 (2272) 65225 Fax: 43 (2272) 65230

Bulletin:HRE-1942B


Printed in Japan 1701SK53

HORIBA

Process & Environmental




CEMS




AQMS

Analytical System Integration





PROCESS



WQMS


AQMS as the doctor for "Human Health"




Mobile / Fixed Monitoring Stations

The measured data can be remotely monitored and exported in various formats to the local/central authorities. The data can be published via the Internet for easy public access to raise awareness on current air pollution levels. This way, the public can prevent outdoor activities and reduce health impacts during heavy polluted days.

Sample measurement points of a general small/medium sized power facility with HORIBA analyzers



Required parameters by law are measured continuously at a stack and reported to the government by the Continuous Emission Monitoring System (CEMS). De-NOx process (SCR) needs to monitor NOx and NH₃, and De-SOx (FGD) process needs to monitor SO₂ to optimize the process operation.



CEMS as the eye for "Various Plants"

Overview The Air Quality Monitoring System (AQMS) is a facility to measure wind speed, direction, other weather parameters, concentration of air pollutants (such as SO₂, NOx, CO, O₂, THC etc), and particulate matters continuously all year round. Mobile AQMS can also be customized to monitor multiple sites via one system.

Main Products

AP-370 series	APDA-371	APMC-370
PX-375	APDA-372	


Main Products

ENDA-5000 series	GI-700 series	PG-300 series
ENDA-7000 series	ENDA-C9000 series	EM-D/F5000

Overview The Continuous Emission Monitoring System (CEMS) is a facility to measure flow, dust, concentration of air pollutants (such as SO₂, NOx, CO etc), and other parameters according to requirements. Required parameters depend on the type of stationary source.

Understanding the life cycle of water is essential for us to live on the earth. Water will be consumed, polluted, treated, discharged, and then returned as our water resource again through various sources such as rain. It is especially critical to monitor the waste water discharge from a factory to protect our water resources.


WQMS as the gardian to protect nature life source "Water"



Overview Water Quality Monitoring System (WQMS) is a facility to measure pollutants such as Chemical Oxygen Demand (COD), Total Phosphates (TP), Total Nitrogen (TN), etc. The required parameters are customized according to the type of factory and discharge regulations.

Main Products


H-1 series	OPSA-150	TPNA-500
48/96 series	CODA-500	



The example of sample measurement point of refinery plant with HORIBA analyzers

In an oil refinery, the crude oil will be converted to final products (Gasoline, Naphtha, etc.) through several processes such as distilling, cracking etc. HORIBA analyzers are utilized to optimize the process and increase production efficiency.

The system as the facilitator to optimize "Industrial Process"



Overview Process Analyzer System is a facility to measure necessary parameters such as hydrocarbons to help optimize the manufacturing process. The analyzer is chosen that best meets the customer requirements.

Main Products

VA-5000 series	51 series	TX-100
GA-370E	NZ-5000	

■ Air Pollution Analyzer
AP-370 series

■ NO_x, SO₂, CO, CO₂, O₃, H₂S, NH₃, THC, NMTHC, CH₄, NMVOC

■ NO_x: 0-0.1/0.2/0.5/1.0 ppm
■ SO₂: 0-0.05/0.1/0.2/0.5 ppm
■ CO: 0-5/10/20/50 ppm
■ CO₂: 0-500/1000 ppm
■ O₃: 0-0.1/0.2/0.5/1.0 ppm
■ H₂S: 0-0.05/0.1/0.2/0.5 ppm
■ NH₃: 0-0.1/0.2/0.5/1.0 ppm
■ THC, NMTHC, CH₄: 0-5/10/20/50 ppmC
■ NMVOC: 0-2000ppm
■ * Other ranges are also available. Please consult HORIBA.

- Long term stable drift by Cross Flow Modulation technology.
- Automatic calibration function enables setting of start time and the interval to reduce operation.
- Multi-range function automatically switches the range to the best suited, depending on measured gas concentration.

■ CE, TÜV, FCC, MCERTs, GOST, KC, JAPAN etc



■ Continuous Particulate Monitor with X-ray Fluorescence
PX-375

■ Particulate Matter (PM10/PM2.5/TSP)
■ Particulate mass concentration and element concentration

■ 0-200/500/1000 µg/m³
■ * Other ranges are also available. Please consult HORIBA.

- Continuous hourly analysis of PM mass and the elemental concentration by a single unit directly in the field.
- Adoption of world proven technologies: X-ray fluorescence & Beta-ray attenuation, advanced analysis for prevention of air pollution.
- Remote Operation via internet connection enables user to check status and acquire data without going on site.



■ Measurement items
■ Range
■ Features
■ Certificates & Compliance

■ Beta-Ray Attenuation type Dust Analyzer
APDA-371

■ PM2.5, PM10, TSP

■ Standard: 0-1000µg/m³
■ * Other ranges are also available. Please consult HORIBA.

- Long term unattended remote operation of up to 60 days between site visits.
- Hourly filter advances minimize effects of volatile compounds.
- Integrated data logger allows the connection of up to six additional meteorological sensors.

■ CE, TÜV, US EPA etc



■ Light Scattering type Dust Analyzer
APDA-372

■ PM1, PM2.5, PM10, TSP

■ Particle size: 0.18 - 100 µm
■ Number: 1 - 20000 particle/cm³
■ Mass: <0 - 1500 µg/m³
■ * Other ranges are also available. Please consult HORIBA.

- Continuous real-time measurement of PM values simultaneously with additional information through particle number concentration.
- Time resolution adjustable from 1sec up to 24hr.
- LED light source with high stability, long lifetime and durability.

■ CE, TÜV etc



■ Multi Gas Calibrator
APMC-370

■ NO, SO₂, CO, CO₂, O₃, H₂S, NH₃

■ * Other parameters are also available. Please consult HORIBA.

- Dynamic generation of span gas by dilution system. Integrated zero gas generator or external zero gas generator (ZNV-7) is also available.
- Multipoint calibration: 8 individually adjustable cycles, each with up to 20 calibration points and each calibration cycle runs also automatically.
- Precision of span gas concentration: better than 1%, Linearity of span gas concentration: better than 1%.

■ CE etc



Related Products	Clean Room Ambient Air Analyzer : AP-365 series
	Data Acquisition & Management Software : IDA-2000, IDA-ZRW

■ On-line Industrial Water Quality Analyzer
H-1 series

■ pH, ORP, Conductivity, Resistivity, Residual chlorine, Dissolved oxygen, Turbidity, MLSS, Fluoride ion, NH₄-N

■ pH: 0 to 14pH ORP: -2000 to 2000 mV
■ Conductivity: 0.0 to 200.0 mS/cm 0.00 to 20.00, 0 to 2000 µS/cm
■ Resistivity: 0.000 to 2.000 MΩ·cm 0.00 ot20.00 kΩ·m
■ Residual chlorine: 0 to 3 mg/L
■ Dissolved oxygen: 0 to 20 mg/L
■ Turbidity: 0 to 2 degree(min.), 0 to 4000 degree(max)
■ MLSS: 0 to 2000mg/L
■ Fluoride ion: 0 to 10000mg/L
■ NH₄-N: 0 to 1000mg/L
■ * Other ranges are also available. Please consult HORIBA.

- H-1 series comprehensively suits all kinds of water applications, ranging from purified water monitoring to waste water monitoring.
- Lineup with focus on robustness, functionality and maintainability that responds to harsh conditions at the installation sites.
- Essential functions for water analyzer management such as noise resistance, auto calibration, self-diagnosis, and full interface.

■ CE, FCC etc



■ Panel Types Water Quality Measuring Instruments
48/96 series

■ pH/ORP/Conductivity/Resistivity/Dissolved Oxygen/Residual Chlorine

■ Please consult HORIBA.

- Well-developed status indicator icons.
- Setting with the front-panel keys.
- Utilization of lead-free solder.

■ CE, FCC etc



■ Organic Pollutant Monitor
OPSA-150

■ UV absorbance, VIS absorbance, Converted COD level, Converted BOD level, Converted TURB level

■ UV absorbance, VIS absorbance

■ 0-0.1 Abs to 0-5.0 Abs (Can be set 0.1 Abs increments)

- HORIBA's unique rotary cell length modulation sensor ensures no zero-drift as well as covers a wide measurement range from as low as 0 to 0.1 Abs, up to 0 to 5.0 Abs, while providing a minimum resolution of 0.0001Abs.
- Sample error alarm comes as a standard feature.
- OPSA-150 offers data storage to save up to one year of data and continuous cell wiper system which greatly reduces maintenance.

■ CE, FCC, CPA, KC etc



■ Measurement items
■ Range
■ Features
■ Certificates & Compliance

Related Products	Automatic Calibration/Cleaning Industrial pH Analyzer : AH-151
	Continuous Oil Film Analyzer : LO-300

■ Automatic COD Monitor
CODA-500

■ COD concentration in water

■ 0-20 mg/L
■ 0-30, 40, 50, 100, 200, 500, 1000, 2000 mg/L (1-dilution type)
■ * Other ranges are also available. Please consult HORIBA.

- Small amount of reagent consumption (0.5-2ml/measurement) and innovative reagent delivery service provides easy handling and low running cost.
- 2 measurement methods for different sample types and applications.
- Direct heating method requires no cooling water.

■ CE, FCC, KC etc



■ Automatic Total Nitrogen/Phosphorus Monitoring System
TPNA-500

■ Total Nitrogen and phosphorus

■ Total nitrogen: 0-2, 5, 10, 20, 50, 100, 200, 500, 1000 mg/NL
■ Total phosphorus: 0-0.5, 1, 2, 5, 10 20, 50, 100, 250 mg/P/L
■ * Other ranges are also available. Please consult HORIBA.

- Adoption of meniscus measurement method and enhanced automatic washing functions (option) contributes to the lengthening the maintenance cycle.
- Reduction in power consumption by approx. 30%, with pure water usage and waste water generated reduced to 1/2.
- HORIBA's state-of-the-art technology and measurement methods delivers high reliability.

■ CE, FCC, KC etc



Air Quality Monitoring System

AQMS

HORIBA has more than 50 years experience providing ambient monitoring solutions, recognized around the world. HORIBA has supplied over 15,000 units with the major share in many regions. The monitoring station is tailor-made according to the customer's request. HORIBA can provide several types of stations, cabinets, calibration equipment and more to meet your challenging monitoring requirements.



Water Quality Monitoring System

WQMS

HORIBA produced the first national pH meter in 1950 in Japan. Since then, we have been producing a variety of water quality analyzers and systems which are designed according to the customer's request. HORIBA has unrivaled knowledge and expertise to provide a suitable system to meet your regulation requirement. To date, approximately 200 WQMS have been installed in Korea alone.



CEMS

Continuous Emission Monitoring System

HORIBA has been supplying stack gas analyzers for more than 50 years and have invented several analyzer technologies and sampling systems. HORIBA has supplied more than 100,000 units so far around the world and has the largest market share in Japan for power plant applications*. We can supply systems that comply with regulations in various regions such as Europe, US, China and Korea with our wealth of knowledge and experience.

*As of 2014, based on our company's research.



Stack Gas Analyzer ENDA-5000 series

NO_x, SO₂, CO₂, CO, O₂

NO_x: 0-200 to 5000ppm
SO₂: 0-200 to 5000ppm
CO₂: 0-5 to 25vol%

CO: 0-200 to 5000ppm
O₂: 0-10 to 25vol%

* It can be set to dual ranges. Range ratio shall be within factor 10 as standard.
* Other ranges are also available. Please consult HORIBA.

- Cross Flow Modulation type NDIR stabilizes operation with no optical adjustment and zero drift to give longer life time.
- Integrated analyzer with promised performance sampling unit established from more than 50 years experience in this field.
- Special magneto-pneumatic O₂ detector providing non carrier gas and non direct contact with sample gas provides less running cost and longer life time.

CE, TÜV, US EPA, FCC, KC, JAPAN etc



Stack Gas Analyzer ENDA-7000 series

NO_x, SO₂, CO, CO₂, O₂, NH₃

NO_x: 0-10 to 5000ppm
SO₂: 0-10 to 5000ppm
CO: 0-50 to 5000ppm

CO₂: 0-5 to 25 vol%
O₂: 0-10 to 25vol%
NH₃: 0- 10 to 100ppm

* It can be set to dual ranges. Range ratio shall be within factor 10 as standard.
* Other ranges are also available. Please consult HORIBA.

- Reliable, accurate and sensitive range measurement with accepted methods including Cross Flow Modulation type - NDIR, Chemiluminescence, Ultraviolet, and Magneto-pneumatic technology.
- 6 components can be measured simultaneously with multiple detector in a single analyzer.
- Easy to operate the test for US EPA such as CGA, Linearity, RATA etc with the integrated software's.

CE, FCC, US EPA etc



Related Products	Dilution CEMS : AP-370 series
	Multi-Component Gas Analyzer : VA-5000 series

Stack Gas Analyzer (Special model with CFM technology for System Integrator)

GI-700 series

NO_x, SO₂, CO, CO₂, O₂, NH₃

NO_x: 0-10 to 5000ppm
SO₂: 0-10 to 5000ppm
CO: 0-50 to 5000ppm

CO₂: 0-5 to 25 vol%
O₂: 0-10 to 25vol%
NH₃: 0- 10 to 100ppm

* It can be set to dual ranges. Range ratio shall be within factor 10 as standard.

* Other ranges are also available. Please consult HORIBA.

- Reliable, accurate and sensitive range measurement with accepted methods including Cross Flow Modulation type - NDIR, Chemiluminescence, Ultraviolet, and Magneto-pneumatic technology.
- 6 components can be measured simultaneously with multiple detectors in a single analyzer.
- Capability of combining with other system utilizes combustion measurement in variety of industries.

CE, FCC etc



Stack Gas Dust & Flow Analyzer EM-D/F 5000 series

Dust, Opacity, Gas velocity, Volume flow

Dust: 0- 0.5 to 10,000 mg/m³
Opacity: 0-100%
Velocity: 0- 3 to 50 m/s
Volume flow: 0-3000000 Nm³/h

* Other ranges are also available. Please consult HORIBA.

- Automatic calibration function to reduce operation work load
- Certified performance analyzer in the world.
- Volume flow measurement is available with combination of pressure and temperature monitors.

CE, KC, TÜV, US EPA etc



De-NO_x Process Gas Analyzer

ENDA-C9000

NH₃, NO_x, O₂

NH₃: 0-20 to 100ppm
NO_x: 0-20 to 100ppm
O₂: 0-5 to 25 vol%

* It can be set to dual ranges. Range ratio shall be within factor 10 as standard.

* Other ranges are also available. Please consult HORIBA.

- Accurate measurement with sensitive range for NH₃.
- Zero drift free Chemiluminescence detector (NH₃/NO_x) and Magneto-pneumatic detector (O₂)
- Various useful functions such as hour meter, data logger, or trend graphs enhance maintenance performance

JAPAN etc



Transportable Gas Analyzer PG-300 series

NO_x, SO₂, CO, CO₂, O₂, CH₄

NO_x: 0-25/50/100/250/500/1000/2500ppm
SO₂: 0-200/500/1000ppm
CO: 0-200/500/1000/2000/5000ppm

CO₂: 0-5/10/20vol%
O₂: 0-5/10/25vol% (Zirconia or Galvanic), 0-10/25 vol% (Paramagnetic)
CH₄: 0-2000/5000ppm or 0-50/100%

* There are several combinations and ranges available. Please consult HORIBA for more information.

- Capable of up to 5 component measurement simultaneously with built-in sampling unit.
- Max 5 days continuous measurement is available and necessary data and trend graph can be stored in an integrated data logging function.
- User-friendly functions such as an integrated instruction manual can be accessed from the LCD display

CE, TÜV, FCC, MCERTS, GOST, CPA, KC, JAPAN etc



PROCESS

Process Analyzer System

HORIBA's facility in Texas, United States has an advantage of process analysis. We obtained the system integration facility in Houston USA which was previously well known as PAAI. We can offer a total package such as system design, engineering, application development, and on-site maintenance services. We are able to provide process analytical systems which not only use HORIBA's analyzers but also other brand's analyzers as per the customer's requirements.



Multi-Component Gas Analyzer VA-5000 series

CO, CO₂, NO_x, SO₂, CH₄, N₂O, NH₃, O₂

CO: 0-50 to 100vol%
CO₂: 0-50 to 100vol%
NO_x: 0-20 to 0-5000ppm
SO₂: 0-100 to 10vol%
CH₄: 0-200 to 100vol%
N₂O: 0-100 to 5000ppm
NH₃: 0-100 to 0-5000ppm

O₂: 0-5 to 100vol% (MPA and Paramagnetic which is only available in Europe)
0-5 to 25vol% (Galvanic and Zirconia)

* It can be set 5 ranges. Range ratio shall be within factor 10 as standard.
* Other ranges are also available. Please consult HORIBA.

- A single analyzer can contain three small sensor modules out of more than seven different gases to provide many combinations of measurement.
- Multiple gas components with wide selection of ranges (from ppm to %) assure high precision and flexibility for many applications.
- Capability of combining with other system utilizes any measurement in variety of industries.

CE, FCC, KC



Trace Gas Analyzer GA-370

CO, CO₂, CH₄, N₂O

0-1/2/5/10 ppm

* It can be set 4 ranges. Range ratio shall be within factor 10 as standard.
* Other ranges are also available. Please consult HORIBA.

- Measures impurities in bulk gas used in semiconductor and other high-purity gases used in clean rooms, medical facilities and manufacturing processes.
- Assured minimum detection sensitivity 10 ppb provides high precise measurement values.
- All metal tubing employed internally to prevent dirt and to enhance safety in handling H₂ and O₂ gas.

CE, FCC



Explosion-proof Gas Analyzer 51 series (EIA-51d/p, TIA-51d/p, TCA-51d/p, MPA-51d/p, PMA-51d)

CO, CO₂, CH₄ etc (EIA, TIA)
H₂ (TCA)
O₂ (MPA, PMA)

EIA: 0-0.11 to 100 vol%
TIA: 0-50 to 2000 ppm
TCA: 0-10 to 100vol%
MPA/PMA: 0-5 to 25vol%

* It can be set to multiple ranges. Range ratio shall be within factor 10 as standard.
* Other ranges are also available. Please consult HORIBA.

- Hydrogen explosion proof (IIB+H₂), IEC60079 compatible.
- Self diagnosis and daily management function.
- Design features high visible LED light indicating operation status for instant recognition.

CE, FCC, JAPAN (Explosion proof) etc



Related Products	Process Gas Chromatograph : Other brand
	Any process analyzer can be integrated in the system

■ Measurement items
■ Range
■ Features
■ Certificates & Compliance

Tunable Laser Hydrogen Chloride Analyzer TX-100

HCl

Please consult HORIBA.

- Laser analyzer requires non-sampling which enables direct measurement and quick response.
- Probe type optical system saves installation cost and maintenance cost.
- HORIBA's original calibration mechanism allows analyzer to calibrate without any disruption to the facility's operations.
- * Will be released in spring 2017.



In Situ Oxygen Monitor NZ-5000

O₂

0-ppm to 100%

- Continuous measurement of O₂ in stack gas with deviation of only 0.2% from the measured value.
- Electronically monitored pneumatic unit for reference air and calibration gas. (optional)
- Explosion-proof type is also available.

CE, TÜV etc

