

Name: Sciddhanto Sinha

Roll no: 2213111

Batch: A

Experiment No:4

4) (d) Write a JavaScript code to apply font color and background color to Heading from dropdown, if font color and background color is same no changes should be reflected.

Objective: To learn about concept and implementation of JAVASCRIPT

Theory:

What is Javascript. Why it is called Client side Scripting language Client side: JavaScript is a client-side language, which means it gets executed at the client side (i.e, user side). On contrary, PHP is a server-side scripting language, as it gets executed at server. Whenever you browse the web, all the HTML,CSS & JS files are fetched from the server & then executed/interpreted at your side by your browser. Scripting language: Since it is interpreted rather than compiled & are used to execute tasks one-by-one. More professionally, A scripting or script language is a programming language that supports scripts: programs written for a special run-time environment that automate the execution of tasks that could alternatively be executed one-by-one by a human operator. Scripting languages are often interpreted.

Explain Javascript functions used in above programs like with syntax and example:-

getElementById()

The getElementById() method returns an element with a specified value. The getElementById() method returns null if the element does not exist.

```
document.getElementById("demo").style.color  
= "red";
```

•innerHTML()

The innerHTML property sets or returns the HTML content (inner HTML) of an element. let html

```
= document.getElementById("myList").innerHTML;
```

•value()

The Object.values() method returns an array of a given object's own enumerable property values, in the same order as that provided by a for...in loop. (The only difference is that a for...in loop enumerates properties in the prototype chain as well.)

```
console.log(Object.values(object1))
```

•parseInt()

The parseInt() function parses a string argument and returns an integer of the specified radix (the base in mathematical numeral systems).
function roughScale(x, base) { const parsed = parseInt(x, base); if (isNaN(parsed)) { return 0; } return parsed * 100;

DOM

- It is an application programming interface.
- Dom represents a document as a hierarchical tree of nodes allowing dev to add, remove, and modify individual part of the page.
- Document node represents every document as a root. In this example only child of document node is html which is called as document element.
- Every piece of markup can be represented by a node in the tree: HTML elements are represented by element nodes, attributes are represented by attribute nodes, the document type is represented by a document type node, and comments are represented by comment nodes.
- In total, there are 12 node types, all of which inherit from a base type.
- DOM Level 1 describes an interface called Node that is to be implemented by all node types in the DOM.
- Every node has a nodeType property that indicates the type of node that it is. Node types are represented by one of the following 12 numeric constants on the Node type:

- a. Node.ELEMENT_NODE (1)
- b. Node.ATTRIBUTE_NODE (2)

- c. Node.TEXT_NODE (3)
- d. Node.CDATA_SECTION_NODE (4)
- e. Node.ENTITY_REFERENCE_NODE (5)
- f. Node.ENTITY_NODE (6)
- g. Node.PROCESSING_INSTRUCTION_NODE (7)
- h. Node.COMMENT_NODE (8)
- i. Node.DOCUMENT_NODE (9)
- j. Node.DOCUMENT_TYPE_NODE (10)
- k. Node.DOCUMENT_FRAGMENT_NODE (11)
- l. Node.NOTATION_NODE (12)

```

if (someNode.nodeType == Node.ELEMENT_NODE)
{
    alert("Node is an element."); //won't work in IE < 9
}

```

This example compares the `someNode.nodeType` to the `Node.ELEMENT_NODE` constant. If they're equal, it means `someNode` is actually an element. Unfortunately, since Internet Explorer 8 and earlier doesn't expose the Node type constructor, this code will cause an error. For cross-browser compatibility, it's best to compare the `nodeType` property against a numeric value, as in the following:

```

if (someNode.nodeType == 1)
{
    alert("Node is an element."); //works in all
    browsers
}

```

Properties of node type

- Two properties, `nodeName` and `nodeValue`, give specific information about the node. The values of these properties are completely dependent on the node type.
- `nodeName` is always equal to the element's tag name, and `nodeValue` is

always null.

- Each node has a `childNodes` property containing a `NodeList`. A `NodeList` is an array-like object used to store an ordered list of nodes that are accessible by position. Keep in mind that a `NodeList` is not an instance of `Array` even though its values can be accessed using bracket notation and the `length` property is present.
- Node Relationship child parent.

Conclusion:

Thus, we have successfully implemented the program.

Code:

```
<html>
<head>
  <title>Font and Background Color</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      text-align: center;
      padding: 50px;
    }
    select {
      padding: 10px;
      font-size: 16px;
    }
    h1 {
      padding: 20px;
    }
  </style>
</head>
<body>

  <select id="fontColor">
    <option value="black">Black</option>
    <option value="red">Red</option>
    <option value="green">Green</option>
    <option value="blue">Blue</option>
  </select>

  <select id="bgColor">
    <option value="white">White</option>
    <option value="red">Red</option>
    <option value="green">Green</option>
    <option value="blue">Blue</option>
  </select>

  <h1 id="heading">Heading Example</h1>

  <script>
    var fontColorSelect = document.getElementById("fontColor");
    var bgColorSelect = document.getElementById("bgColor");
    var heading = document.getElementById("heading");
```

```
fontColorSelect.addEventListener("change", applyColors);
bgColorSelect.addEventListener("change", applyColors);

function applyColors() {
    var selectedFontColor = fontColorSelect.value;
    var selectedBgColor = bgColorSelect.value;

    if (selectedFontColor !== selectedBgColor) {
        heading.style.color = selectedFontColor;
        heading.style.backgroundColor = selectedBgColor;
    }
}
</script>
</body>
</html>
```

Output(Screenshots):

Red ▾ Green ▾

Heading Example