

Benchmark Report

# Benchmarking of NQCH's quantum computer

November 23, 2025

## 1. Report of Changes

**Platform:** sinq20

**Calibration-id:** 1e1f7e1d1af58009eda1986bb3689e6b9b2356b6

**Calibration date:** 2025-11-20 03:59:33

**Calibration note:** chore(sinq20): Update CZ for Q4-Q5

**Experiment-id:** None

**Experiment date:** 2025-11-23 02:38:14

**Experiment note:** Scheduled runs of experiments

**Platform:** sinq20

**Calibration-id:** 2447f0fad33dfea493b4e7bc4143c8bd2e28d979

**Calibration date:** 2025-11-05 08:58:37

**Calibration note:** chore(sinq20): Retune CZ for Q5-Q6 and Q17-Q18

**Experiment-id:** 20251108115234

**Experiment date:** 2025-11-08 11:54:43

**Experiment note:** First execution after malfunctioning of cables.


## 2. Version Comparison

Library	Version	Library	Version
qibo	0.2.19	numpy	2.2.6
qibolab	0.2.9	qibocal	0.2.3
matplotlib	3.10.3	scipy	1.15.3
scikit-learn	1.6.1	pandas	2.2.3
networkx	3.4.2	sympy	1.14.0
torch	2.7.0		

Library	Version	Library	Version
qibo	0.2.19	numpy	2.2.6
qibolab	0.2.9	qibocal	0.2.3
matplotlib	3.10.3	scipy	1.15.3
scikit-learn	1.6.1	pandas	2.2.3
networkx	3.4.2	sympy	1.14.0
torch	2.7.0		

## 3. One and two qubit fidelities

The single qubit fidelity is obtained via Randomized-Benchmarking. The two-qubit fidelity is the "Bell-state fidelity".



## 4. Statistics

	Average	Median	Min	Max
T1 (ns)	1.28e+04	1.23e+04	646	3.65e+04
T2 (ns)	2.36e+25	4.11e+03	125	9.43e+26
Fidelity	None	None	None	None
RO fidelity	0.794	0.777	0.777	0.927

	Average	Median	Min	Max
T1 (ns)	1.28e+04	1.23e+04	646	3.65e+04
T2 (ns)	2.36e+25	4.11e+03	125	9.43e+26
Fidelity	None	None	None	None
RO Fidelity	0.794	0.777	0.777	0.927

## 5. Best Qubits Selection

k-qubits	Best Qubits	Fidelity
2	2, 3	0.914
3	2, 3, 8	0.878
4	2, 3, 8, 9	0.869
5	0, 2, 3, 8, 9	0.858

k-qubits	Best Qubits	Fidelity
2	13, 17	0.945
3	13, 17, 18	0.938
4	3, 8, 13, 17	0.936
5	3, 8, 9, 13, 17	0.935

## 6. Benchmark Results

Qubit n	Fidelity	Error Bars
0	0.997	$\pm 0.00041$
1	0.998	$\pm 0.0006$
2	0.996	$\pm 0.000236$
3	0.998	$\pm 0.000236$
4	0.995	$\pm 0.000486$
5	0.996	$\pm 0.000826$
6	0.999	$\pm 0.000308$
7	0.983	$\pm 0.00219$
8	0.995	$\pm 0.00054$
9	0.996	$\pm 0.000782$
10	0.995	$\pm 0.000441$
11	0.998	$\pm 0.000246$
12	0.998	$\pm 0.000396$
13	0.998	$\pm 0.000344$
14	0.997	$\pm 0.000357$
15	0.995	$\pm 0.000647$
16	0.997	$\pm 0.000463$
17	0.991	$\pm 0.0006$
18	0.987	$\pm 0.00163$
19	0.998	$\pm 0.00042$

Qubit n	Fidelity	Error Bars
0	0.997	$\pm 0.00041$
1	0.998	$\pm 0.0006$
2	0.996	$\pm 0.000236$
3	0.998	$\pm 0.000236$
4	0.99	$\pm 0.00167$
5	0.996	$\pm 0.000826$
6	0.999	$\pm 0.000308$
7	0.983	$\pm 0.00219$
8	0.995	$\pm 0.00054$
9	0.996	$\pm 0.000782$
10	0.995	$\pm 0.000441$
11	0.998	$\pm 0.000246$
12	0.998	$\pm 0.000396$
13	0.998	$\pm 0.000344$
14	0.996	$\pm 0.000846$
15	0.995	$\pm 0.000647$
16	0.997	$\pm 0.000463$
17	0.991	$\pm 0.0006$
18	0.987	$\pm 0.00163$
19	0.998	$\pm 0.00042$

## 7. Mermin

- Runtime:
- Qubits used:




- Runtime:
- Qubits used:




## 8. Grover - 2 qubits

Grover's algorithm for 2 qubits executed on sinq20 backend with 1000 shots per circuit. We measure the success rate of finding the target state '11' for each pair of qubits in [[2, 3]].

- Runtime: 10.07918095588684
- Qubits used: [[2, 3]]




- Runtime:
- Qubits used:



## 9. Grover - 3 qubits

Grover's algorithm for 3 qubits executed on `siq20` backend with 1000 shots per circuit. We measure the success rate of finding the target state '111' for each pair of qubits in `[[8, 3], [2, 3]]`.

- **Runtime:** 4.534881830215454
- **Qubits used:** [8, 2, 3]




- **Runtime:**
- **Qubits used:**




## 10. GHZ state preparation

GHZ circuit with 3 qubits executed on `siq20` backend with 1000 shots.

- **Runtime:** 9.70 seconds.
- **Qubits used:** [8, 3, 2]








- **Runtime:** 4.32 seconds.
- **Qubits used:** [13, 17, 18]








## 11. Process Tomography state preparation

Process tomography involves preparing a circuit particular set of states, appending a gate (process) to the circuit, and measuring the circuit in the Pauli basis. The data is processed to get the Pauli Liouville representation of a process (gate). - Single qubit process tomography executed on qubits: [2, 3] - Two qubit process tomography on coupled qubits: [[2, 3]]

- **Runtime:** 680.07 seconds.
- **Qubits used:**




- **Runtime:** 705.76 seconds.
- **Qubits used:**




## 12. Reuploading Classifier

Reuploading classifier with 1 qubits, 10 layers, depth of 20, 500 shots.

- **Runtime:** None
- **Qubits used:** [7]




- **Runtime:** None
- **Qubits used:** — No “qubits\_used” provided. —



### 13. QML: Yeast dataset (3 qubits)

- **Duration:** 144.28315591812134
- **Accuracy:** 0.63
- **Qubits used:** 8, 3, 2

QML Confusion Matrices



- **Duration:** 793 seconds
- **Accuracy:** 0.56
- **Qubits used:** 0, 1, 2, 3

QML Confusion Matrices

