

Benchmark Report

Benchmarking of NQCH's quantum computer

April 30, 2026

1. Report of Changes

Platform: sinq20
Calibration-id: `ec305fcaf377a05f4fb391a8ee18282bfae18df6`
Calibration date: 2026-04-28 07:58:51
Calibration note: chore(sinq20): update readout parameters

Experiment-id: 20260428212203
Experiment date: 2026-04-28 21:22:04
Experiment note: temporary note!!!

Platform: sinq20
Calibration-id: `4dc4082f38a53222b3956c22202d32a520d4bc78`
Calibration date: 2026-01-15 02:03:03
Calibration note: chore(sinq20): 2q gates cal 0-1, 0-3, 2-3, 3-4, 1-4, 4-5, 4-9, 3-8, 8-9

Experiment-id: 20260118161538
Experiment date: 2026-01-18 16:15:38
Experiment note: temporary note!!!


2. Version Comparison

Library	Version	Library	Version
qibo	0.2.23	numpy	2.4.4
qibolab	0.2.9	qibocal	0.2.5
matplotlib	3.10.8	scipy	1.17.1
scikit-learn	1.8.0	pandas	2.3.3
networkx	3.6.1	sympy	1.14.0
torch	2.11.0		

Library	Version	Library	Version
qibo	0.2.22	numpy	2.2.6
qibolab	0.2.9	qibocal	0.2.4
matplotlib	3.10.3	scipy	1.15.3
scikit-learn	1.6.1	pandas	2.2.3
networkx	3.4.2	sympy	1.14.0
torch	2.7.0		

3. One and two qubit fidelities

The single qubit fidelity is obtained via Randomized-Benchmarking. The two-qubit fidelity is the "Bell-state fidelity".



Q7

97.51

Q8

99.83

Q9

99.85

Q10

99.65

Q11

99.69

Q2

99.76

Q3

99.8

Q4

99.09

Q5

99.72

Q6

99.38

Q0

99.47

Q1

99.14

Q17

98.96

Q18

99.72

Q19

99.85

Q12

99.79

Q13

99.79

Q14

98.53

Q15

99.52

Q16

99.26

Q7

98.74

Q8

99.86

Q9

99.76

Q10

98.91

Q11

99.63

Q2

99.82

Q3

99.52

Q4

99.56

Q5

99.46

Q6

99.81

Q0

99.71

Q1

99.76

95.60

96.05

96.50

96.95

97.40

97.85

98.30

98.75

99.20

99.65

1Q Fidelity

88.65

89.85

91.05

92.25

93.45

94.65

95.85

97.05

98.25

99.45

1Q Fidelity

4. Statistics

	Average	Median	Min	Max
T1 (ns)	23.1	24.5	13	30.5
T2 (ns)	11.4	11.7	2.18	23.9
Fidelity	0.951	0.993	0.855	0.999
RO Fidelity	0.986	0.986	0.976	0.99
2q RB Fidelity	-	-	-	-
2q CZ Fidelity	-	-	-	-

	Average	Median	Min	Max
T1 (ns)	1.28e+04	1.23e+04	646	3.65e+04
T2 (ns)	2.36e+25	3.68e+03	125	9.43e+26
Fidelity	0.99	0.997	0.887	0.999
RO Fidelity	0.794	0.777	0.777	0.927
2q RB Fidelity	0.965	0.972	0.923	0.981
2q CZ Fidelity	0.975	0.974	0.967	0.991

5. Best Qubits Selection

k-qubits	Best Qubits	Fidelity
2	5, 6	0.935
3	5, 6, 10	0.929
4	5, 6, 10, 15	0.929
5	5, 6, 10, 15, 16	0.928

k-qubits	Best Qubits	Fidelity
2	2, 3	0.981
3	0, 2, 3	0.976
4	0, 1, 2, 3	0.970
5	0, 1, 2, 3, 4	0.965

6. Summary metrics

Benchmark	Metric	Value	Runtime
Mermin	Max	3.358	227.53 sec
Grover 2q	Max prob	0.874	3.13 sec
Grover 3q	Max prob	0.225	2.44 sec
GHZ state prep.	Success	0.903	3.17 sec

Benchmark	Metric	Value	Runtime
Mermin	Max	-3.316	1.02 sec
Grover 2q	Max prob	0.89	2.36 sec
Grover 3q	Max prob	0.385	2.43 sec
GHZ state prep.	Success	0.910	3.95 sec

7. Randomized Benchmarking Results

Qubit n	Fidelity	Error Bars	Qubit n	Fidelity	Error Bars
0	0.995	± 0.000224	10	0.996	± 0.00012
1	0.991	± 0.000662	11	0.997	± 0.000156
2	0.998	± 8.9e-05	12	0.998	± 7.26e-05
3	0.998	± 7.97e-05	13	0.998	± 9.89e-05
4	0.991	± 0.000559	14	0.998	± 5.64e-05
5	0.997	± 0.000197	15	0.998	± 0.000118
6	0.994	± 0.00018	16	0.982	± 0.00376
7	0.976	± 0.00421	17	0.956	± 0.0121
8	0.998	± 6.71e-05	18	0.995	± 0.000286
9	0.998	± 8.32e-05	19	0.996	± 0.000122

Qubit n	Fidelity	Error Bars	Qubit n	Fidelity	Error Bars
0	0.997	± 0.000131	10	0.989	± 0.000582
1	0.998	± 7.47e-05	11	0.996	± 0.000218
2	0.998	± 7.57e-05	12	0.998	± 0.000126
3	0.995	± 0.000163	13	0.998	± 7.15e-05
4	0.996	± 0.000185	14	0.985	± 0.00183
5	0.995	± 0.000147	15	0.995	± 0.000469
6	0.998	± 8.34e-05	16	0.993	± 0.000558
7	0.887	± 0.0287	17	0.99	± 0.000502
8	0.999	± 4.48e-05	18	0.997	± 0.00026
9	0.998	± 7.2e-05	19	0.998	± 9.05e-05

8. Mermin

Mermin's algorithm for 3 qubits.

Runtime	Qubits	Max
227.53 sec	10, 5, 6	3.358



Runtime	Qubits	Max
1.02 sec	0, 2, 3	-3.316



9. Grover - 2 qubits

Grover's algorithm for 2 qubits executed on sinq20 backend with 1000 shots per circuit. We measure the success rate of finding the target state '11' for each pair of qubits in $[[5, 6]]$.

Runtime	Qubits	Max prob
3.13 sec	5, 6	0.874



Runtime	Qubits	Max prob
2.36 sec	2, 3	0.89



10. Grover - 3 qubits

Grover's algorithm for 3 qubits executed on sinq20 backend with 1000 shots per circuit. We measure the success rate of finding the target state '111' for each pair of qubits in $[[10, 5], [5, 6]]$.

Runtime	Qubits	Max prob
2.44 sec	10, 6, 5	0.225



Runtime	Qubits	Max prob
2.43 sec	0, 2, 3	0.385



11. GHZ state preparation

GHZ circuit with 3 qubits executed on sinq20 backend with 1000 shots.

Runtime	Qubits	Success
3.17 sec	10, 5, 6	0.903



Runtime	Qubits	Success
3.95 sec	0, 3, 2	0.910

