

# Benchmarking of NQCH's quantum computer

May 2, 2026

## 1. Report of Changes

**Platform:** sinq20

**Calibration-id:** *ec305fcaf377a05f4fb391a8ee18282bfae18df6*

**Calibration date:** 2026-04-28 07:58:51

**Calibration note:** chore(sinq20): update readout parameters

  

**Experiment-id:** 20260429212203

**Experiment date:** 2026-04-29 21:22:04

**Experiment note:** *temporary note!!!*

**Platform:** sinq20

**Calibration-id:** *4dc4082f38a53222b3956c22202d32a520d4bc78*

**Calibration date:** 2026-01-15 02:03:03

**Calibration note:** chore(sinq20): 2q gates cal 0-1, 0-3, 2-3, 3-4, 1-4, 4-5, 4-9, 3-8, 8-9

  

**Experiment-id:** 20260118161538

**Experiment date:** 2026-01-18 16:15:38

**Experiment note:** *temporary note!!!*

## 2. Version Comparison

| Library      | Version | Library | Version |
|--------------|---------|---------|---------|
| qibo         | 0.2.23  | numpy   | 2.4.4   |
| qibolab      | 0.2.9   | qibocal | 0.2.5   |
| matplotlib   | 3.10.8  | scipy   | 1.17.1  |
| scikit-learn | 1.8.0   | pandas  | 2.3.3   |
| networkx     | 3.6.1   | sympy   | 1.14.0  |
| torch        | 2.11.0  |         |         |

| Library      | Version | Library | Version |
|--------------|---------|---------|---------|
| qibo         | 0.2.22  | numpy   | 2.2.6   |
| qibolab      | 0.2.9   | qibocal | 0.2.4   |
| matplotlib   | 3.10.3  | scipy   | 1.15.3  |
| scikit-learn | 1.6.1   | pandas  | 2.2.3   |
| networkx     | 3.4.2   | sympy   | 1.14.0  |
| torch        | 2.7.0   |         |         |

## 3. One and two qubit fidelities

The single qubit fidelity is obtained via Randomized-Benchmarking. The two-qubit fidelity is the "Bell-state fidelity".



#### 4. Statistics

|                | Average | Median | Min   | Max   |
|----------------|---------|--------|-------|-------|
| T1 (ns)        | 22.5    | 23.1   | 12.1  | 36    |
| T2 (ns)        | 9.83    | 10.4   | 2.2   | 25.2  |
| Fidelity       | 0.98    | 0.997  | 0.937 | 0.998 |
| RO Fidelity    | 0.973   | 0.975  | 0.965 | 0.981 |
| 2q RB Fidelity | -       | -      | -     | -     |
| 2q CZ Fidelity | -       | -      | -     | -     |

|                | Average  | Median   | Min   | Max      |
|----------------|----------|----------|-------|----------|
| T1 (ns)        | 1.28e+04 | 1.23e+04 | 646   | 3.65e+04 |
| T2 (ns)        | 2.36e+25 | 3.68e+03 | 125   | 9.43e+26 |
| Fidelity       | 0.99     | 0.997    | 0.887 | 0.999    |
| RO Fidelity    | 0.794    | 0.777    | 0.777 | 0.927    |
| 2q RB Fidelity | 0.965    | 0.972    | 0.923 | 0.981    |
| 2q CZ Fidelity | 0.975    | 0.974    | 0.967 | 0.991    |

#### 5. Best Qubits Selection

| k-qubits | Best Qubits      | Fidelity |
|----------|------------------|----------|
| 2        | 6, 11            | 0.926    |
| 3        | 5, 6, 11         | 0.924    |
| 4        | 5, 6, 10, 15     | 0.921    |
| 5        | 5, 6, 10, 11, 15 | 0.921    |

| k-qubits | Best Qubits   | Fidelity |
|----------|---------------|----------|
| 2        | 2, 3          | 0.981    |
| 3        | 0, 2, 3       | 0.976    |
| 4        | 0, 1, 2, 3    | 0.970    |
| 5        | 0, 1, 2, 3, 4 | 0.965    |

#### 6. Summary metrics

| Benchmark | Metric   | Value | Runtime  |
|-----------|----------|-------|----------|
| Mermin    | Max      | -     | -        |
| Grover 2q | Max prob | 0.86  | 6.10 sec |

| Benchmark | Metric   | Value  | Runtime  |
|-----------|----------|--------|----------|
| Mermin    | Max      | -3.316 | 1.02 sec |
| Grover 2q | Max prob | 0.89   | 2.36 sec |

#### 7. Randomized Benchmarking Results

| Qubit n | Fidelity | Error Bars     | Qubit n | Fidelity | Error Bars     |
|---------|----------|----------------|---------|----------|----------------|
| 0       | 0.995    | $\pm 0.000224$ | 10      | 0.996    | $\pm 0.00012$  |
| 1       | 0.991    | $\pm 0.000662$ | 11      | 0.997    | $\pm 0.000156$ |
| 2       | 0.998    | $\pm 8.9e-05$  | 12      | 0.998    | $\pm 7.26e-05$ |
| 3       | 0.998    | $\pm 7.97e-05$ | 13      | 0.998    | $\pm 9.89e-05$ |
| 4       | 0.991    | $\pm 0.000559$ | 14      | 0.998    | $\pm 5.64e-05$ |
| 5       | 0.997    | $\pm 0.000197$ | 15      | 0.998    | $\pm 0.000118$ |
| 6       | 0.994    | $\pm 0.00018$  | 16      | 0.982    | $\pm 0.00376$  |
| 7       | 0.976    | $\pm 0.00421$  | 17      | 0.956    | $\pm 0.0121$   |
| 8       | 0.998    | $\pm 6.71e-05$ | 18      | 0.995    | $\pm 0.000286$ |
| 9       | 0.998    | $\pm 8.32e-05$ | 19      | 0.996    | $\pm 0.000122$ |

| Qubit n | Fidelity | Error Bars     | Qubit n | Fidelity | Error Bars     |
|---------|----------|----------------|---------|----------|----------------|
| 0       | 0.997    | $\pm 0.000131$ | 10      | 0.989    | $\pm 0.000582$ |
| 1       | 0.998    | $\pm 7.47e-05$ | 11      | 0.996    | $\pm 0.000218$ |
| 2       | 0.998    | $\pm 7.57e-05$ | 12      | 0.998    | $\pm 0.000126$ |
| 3       | 0.995    | $\pm 0.000163$ | 13      | 0.998    | $\pm 7.15e-05$ |
| 4       | 0.996    | $\pm 0.000185$ | 14      | 0.985    | $\pm 0.00183$  |
| 5       | 0.995    | $\pm 0.000147$ | 15      | 0.995    | $\pm 0.000469$ |
| 6       | 0.998    | $\pm 8.34e-05$ | 16      | 0.993    | $\pm 0.000558$ |
| 7       | 0.887    | $\pm 0.0287$   | 17      | 0.99     | $\pm 0.000502$ |
| 8       | 0.999    | $\pm 4.48e-05$ | 18      | 0.997    | $\pm 0.00026$  |
| 9       | 0.998    | $\pm 7.2e-05$  | 19      | 0.998    | $\pm 9.05e-05$ |

## 8. Mermin

| Runtime | Qubits | Max |
|---------|--------|-----|
| -       | -      | -   |



| Runtime  | Qubits  | Max    |
|----------|---------|--------|
| 1.02 sec | 0, 2, 3 | -3.316 |



## 9. Grover - 2 qubits

Grover's algorithm for 2 qubits executed on sinq20 backend with 1000 shots per circuit. We measure the success rate of finding the target state '11' for each pair of qubits in [[11, 6]].

| Runtime  | Qubits | Max prob |
|----------|--------|----------|
| 6.10 sec | 11, 6  | 0.86     |



| Runtime  | Qubits | Max prob |
|----------|--------|----------|
| 2.36 sec | 2, 3   | 0.89     |

