

Symmetric Key Cryptography

Daniel Mancia

University of Texas at Austin

November 20, 2019

Table of Contents

- 1 Symmetric Key Cryptography
- 2 Stream Ciphers
- 3 Block Ciphers
- 4 Key Distribution

Table of Contents

1 Symmetric Key Cryptography

2 Stream Ciphers

3 Block Ciphers

4 Key Distribution

What is Symmetric Key Cryptography

- Symmetric key cryptography consists of algorithms that use a shared key for encryption and decryption.

What is Symmetric Key Cryptography

- Symmetric key cryptography consists of algorithms that use a shared key for encryption and decryption.
- There are two types of symmetric key encryption ciphers: Block Ciphers and Stream Ciphers.

What is Symmetric Key Cryptography

- Symmetric key cryptography consists of algorithms that use a shared key for encryption and decryption.
- There are two types of symmetric key encryption ciphers: Block Ciphers and Stream Ciphers.
- For simplicity we are going to assume that there exists a secure communication channel where the two parties can share their key.

Symmetric Key Cryptography




Figure 1: The general idea

Table of Contents

1 Symmetric Key Cryptography

2 Stream Ciphers

3 Block Ciphers

4 Key Distribution

What is a Stream Cipher?

- A stream cipher encrypts the bits of the plaintext with some pseudorandom bit stream called the keystream.

What is a Stream Cipher?

- A stream cipher encrypts the bits of the plaintext with some pseudorandom bit stream called the keystream.
- The keystream is generated from a random seed value.

What is a Stream Cipher?

- A stream cipher encrypts the bits of the plaintext with some pseudorandom bit stream called the keystream.
- The keystream is generated from a random seed value.
- The key is therefore the seed value used to generate the random values.

What is a Stream Cipher?

- A stream cipher encrypts the bits of the plaintext with some pseudorandom bit stream called the keystream.
- The keystream is generated from a random seed value.
- The key is therefore the seed value used to generate the random values.
- More efficient than block ciphers but much easier to mess up security.

- The most popular stream cipher designed by Ron Rivest in 1987.

- The most popular stream cipher designed by Ron Rivest in 1987.
- Used in WEP (1987), WPA (2003/2004), SSL (1995), TLS (1999) until it was prohibited in 2015 because of its insecurity.

- The most popular stream cipher designed by Ron Rivest in 1987.
- Used in WEP (1987), WPA (2003/2004), SSL (1995), TLS (1999) until it was prohibited in 2015 because of its insecurity.




Figure 2: RC4 keystream

Stream Ciphers Attacks

- Keys should have a large period and should not have any subtle biases within them.
- Keys should never be used more than once (Reused Key attack)
- Valid decryption does not imply authenticity (Bit flipping attack).

Table of Contents

1 Symmetric Key Cryptography

2 Stream Ciphers

3 Block Ciphers

4 Key Distribution

Block Ciphers

- A block cipher encrypts a block of bits using a specified key.

- A block cipher encrypts a block of bits using a specified key.
- Formally we have the following functions
 - 1 $E_K(P) := E(K, P) : \{0, 1\}^k \times \{0, 1\}^n \rightarrow \{0, 1\}^n$
 - 2 $E_K(C)^{-1} := D_K(C) := D(K, C) : \{0, 1\}^k \times \{0, 1\}^n \rightarrow \{0, 1\}^n$
 - 3 $\forall K \quad D_K(E_K(P)) = P$

- A block cipher encrypts a block of bits using a specified key.
- Formally we have the following functions
 - 1 $E_K(P) := E(K, P) : \{0, 1\}^k \times \{0, 1\}^n \rightarrow \{0, 1\}^n$
 - 2 $E_K(C)^{-1} := D_K(C) := D(K, C) : \{0, 1\}^k \times \{0, 1\}^n \rightarrow \{0, 1\}^n$
 - 3 $\forall K \quad D_K(E_K(P)) = P$
- Famous block ciphers: DES, AES, Blowfish.

- "Advanced Encryption Standard"

- "Advanced Encryption Standard"
- Was adopted by the U.S. government in 2001 and is currently used worldwide.

- "Advanced Encryption Standard"
- Was adopted by the U.S. government in 2001 and is currently used worldwide.
- AES is a substitution–permutation network (AES is annoying to explain, if you want more details on implementation just read the Wikipedia page or the spec).

- "Advanced Encryption Standard"
- Was adopted by the U.S. government in 2001 and is currently used worldwide.
- AES is a substitution–permutation network (AES is annoying to explain, if you want more details on implementation just read the Wikipedia page or the spec).
- AES works on fixed block size of 128 bits and key size of 128, 192, or 256 bits

Modes of Operation

- How can we encrypt arbitrary data if we can only encrypt 128 bits with AES?


Modes of Operation

- How can we encrypt arbitrary data if we can only encrypt 128 bits with AES?
- There are multiple ways but we will only cover ECB and CBC today.

- The simplest way to encrypt, just do AES on 128 bit chunks of the data.


- The simplest way to encrypt, just do AES on 128 bit chunks of the data.
- Requires data to be padded.

- The simplest way to encrypt, just do AES on 128 bit chunks of the data.
- Requires data to be padded.
- Unfortunately the same plaintext blocks will encrypt to the same ciphertext blocks.



Electronic Codebook (ECB) mode encryption

Figure 3: ECB encryption



Electronic Codebook (ECB) mode decryption

Figure 4: ECB decryption




Figure 5: Fatal flaw of ECB

- Most commonly used mode of operation.


- Most commonly used mode of operation.
- Requires padding.

- Most commonly used mode of operation.
- Requires padding.
- Each block of the plaintext is XORed with the previous ciphertext block.

- Most commonly used mode of operation.
- Requires padding.
- Each block of the plaintext is XORed with the previous ciphertext block.
- What about the first plaintext block???


- Most commonly used mode of operation.
- Requires padding.
- Each block of the plaintext is XORed with the previous ciphertext block.
- What about the first plaintext block???
- Need to specify an IV (Initialization Vector).

- Most commonly used mode of operation.
- Requires padding.
- Each block of the plaintext is XORed with the previous ciphertext block.
- What about the first plaintext block???
- Need to specify an IV (Initialization Vector).
- Math formulas:
 - $C_i = E_K(P_i \oplus C_{i-1}), C_0 = IV$
 - $P_i = D_K(C_i) \oplus C_{i-1}, C_0 = IV$



Cipher Block Chaining (CBC) mode encryption

Figure 6: CBC encryption



Cipher Block Chaining (CBC) mode decryption

Figure 7: CBC Decryption

Block Cipher Attacks

- ECB is susceptible to a chosen plaintext attack.
- CBC is susceptible to bit flipping and padding oracle attacks.

Table of Contents

- 1 Symmetric Key Cryptography
- 2 Stream Ciphers
- 3 Block Ciphers
- 4 Key Distribution

Key Distribution

- What if we don't have access to a completely secure communication channel?

Key Distribution

- What if we don't have access to a completely secure communication channel?
- Need some way to share keys.

Diffie-Hellman

- 1 Alice and Bob agree on a prime number p .
- 2 Alice chooses a secret integer a and sends Bob $A = g^a \bmod p$.
- 3 Bob chooses a secret integer b and sends Alice $B = g^b \bmod p$.
- 4 Alice computes $B^a \bmod p$ and Bob computes $A^b \bmod p$.
- 5 Notice that Alice and Bob now share the same number because $A^b = B^a = g^{ab} \bmod p$.

Diffie-Hellman

- ① Alice and Bob agree on a prime number p .
 - ② Alice chooses a secret integer a and sends Bob $A = g^a \bmod p$.
 - ③ Bob chooses a secret integer b and sends Alice $B = g^b \bmod p$.
 - ④ Alice computes $B^a \bmod p$ and Bob computes $A^b \bmod p$.
 - ⑤ Notice that Alice and Bob now share the same number because $A^b = B^a = g^{ab} \bmod p$.
- Secret values: a, b
 - Public values: g, p, A, B

- Hardness assumption: Discrete logarithm
- Works the same over Elliptic Curves.