A Checked Evidence Interface for Paired Closed-Loop SNN Fault Assessment

Shuchao Gao
Waseda University
Tokyo, Japan

***Abstract*—Closed-loop fault experiments must distinguish neural activity from task failure while preserving pairing and causal timing. We present an executable evidence interface that checks campaign invariants and delegates input and plant semantics to native replay. A fly-connectome controller and an independent delayed tank reuse the same checker. Each adapter detects eleven predefined challenges through common checks and three through native replay; a passing synthetic logger exposes the absence of execution authentication. Two prospective receptive-field realizations, independently recalibrated and tested, qualify a retained 24-seed-cluster baseline. At 50% connection-row deletion, the secondary relay-minus-proportional net-loss contrast changes from -22.9 percentage points to -4.2 in each new map. Both new 95% intervals include zero, with four-test Holm $p = 1$. Sparse failures, unequal healthy clearance and warning errors prevent universal controller-protection claims. The contribution is executable, bounded cross-plant evidence checking and conditional transfer assessment.**

***Index Terms*—spiking neural networks, fault assessment, closed-loop control, reproducibility**

I. Introduction and Positioning

Fault assessment for a spiking controller depends on both the neural network and its feedback system. A neural-output criterion may pass before a later collision. Early stopping can change measured activity, while delayed actuation separates a logged decision from its physical consequence. Simulation engineers therefore need to check what records actually paired and observed before interpreting fault loss.

Closed-loop fault evaluation is established. DriveFI mines faults and scenarios that violate autonomous-driving safety constraints [1]. SpikeFI, SpikingJET and enpheeph provide configurable SNN fault campaigns [2]–[4]. CRN synchronization [5], hybrid-trajectory monitoring [6] and task/resource benchmarking [7], [8] also precede this work. Cross-layer NoC fault analysis links hardware routing defects to SNN behavior [9]; functional row deletion alone supplies no comparable hardware evidence.

We contribute a plant-neutral campaign checker, two native replay adapters, and prospective same-prior receptive-field (RF) assessments. The evaluated increment is a testable agreement about pairing, clocks, exposure and task labels, with explicit failure cases and blind spots. A delayed tank establishes limited cross-plant reuse; independent RF campaigns test the conditionality of a fly-connectome controller contrast. We do not claim a new injector, pairing estimator or general closed-loop verification method.

II. Executable Evidence Contract

A campaign declares the Cartesian product of seed, condition, law and fault, together with horizon H, frame duration and resource units. An adapter normalizes each native record into its condition key, saved-source/map/calibration hashes, input and mask digests, timestamped observations, cumulative resource and first failure. Hashes bind bytes to saved snapshots; they do not attest execution.

The common checker returns an issue code, record key and explanation for incomplete or duplicate matrices, inconsistent bindings, mismatched paired variates/masks, invalid clocks, premature decisions, resource errors and contradictory outcomes. Inputs share variates within seed; each dose shares its mask across laws and bearings. Native replay separately regenerates input events and plant transitions. Feedback-dependent rates and realized events need not match despite shared variates. Warning prefixes expose only observations completed by their stated time, excluding future labels.

Fig. 2 evaluates the same checker on a distinct tank schema. Its normalized level obeys $\dot{h} = I - u - 0.04h$, initially $h = 0.5$, with safe interval $[0.2, 0.8]$. Eight seeds cross two nominal inflows (0.15/0.28), two laws and three sensor-sample deletion levels, yielding 96 episodes over 4 s. Inflow varies uniformly by ± 0.04 per frame; measurement noise is uniform over ± 0.01. Deleted measurements hold their last value. From measurement m, proportional outflow is $\mathrm{clip}(0.18 + 1.2(m - 0.5), 0, 0.4)$; relay outflow is 0.35 if $m > 0.5$, otherwise 0.05. Analytic transitions split at delayed outflow changes, 150 ms after decisions on a 100-ms grid; generator and replayer use separate algebraic implementations. Resource counts valid sensor updates, not neural spikes.

Each adapter detects eleven predefined cases through common checks and three only through native replay: native-schema, exact-event and geometry/dynamics defects. Real V8 probes independently find six wrong horizon flags, 17 delays of 260 rather than 250 ms and four completed bursts of 440 rather than 450 ms. These historical records are excluded from current inference. The challenges are regression evidence, not coverage estimates. A synthetic zero-neural-readout logger passes input/plant checks without neural dynamics, establishing that consistent traces cannot authenticate execution, unlogged neural states or safety.




Fig. 1. System and checked assessment interface. (a,b) Representative model anchors, an illustrative fly and a selected 410-cell/1,050-connection graph. The layout is schematic, not measured neurites or the complete recurrent graph. (c) Sampled feedback and exact burst events; $t_d = 200\,\text{ms}$ is illustrative. (d) Native traces enter common checks and independent replay before endpoint analysis.




Fig. 2. Cross-plant reuse and predefined error challenges. (a) First registered tank seed, high inflow, proportional law; level axis is zoomed, safe interval $[0.2, 0.8]$. All 96 example tasks remain safe. (b) A requested outflow first changes at 0.60 s and applies at 0.75 s, between 100-ms frame boundaries. (c) Eleven common-checker and three native-only cases are detected per adapter, not a general coverage estimate.

III. Neural Experiment and Statistical Design

A. Network, Feedback and Calibration

The FlyWire v783-derived model [10] has 138,639 LIF neurons and 15,091,983 signed, contact-weighted connection rows. We use Shiu parameters [11] in Brian 2 [12], with 0.1-ms steps, 2.2-ms sensory refractoriness and state/weight restoration before each episode. Assumed Gaussian RFs stimulate 104 LC4 and 210 LPLC2 cells at up to 150 Hz; other external rates are zero. Eight descending cells provide control features.

Between events, $\dot{v} = (v_0 - v + g)/(20\,\text{ms})$ and $\dot{g} = -g/(5\,\text{ms})$. Threshold $-45\,\text{mV}$ resets v to $v_0 = -52\,\text{mV}$ and g to zero; both equations pause during refractoriness. Recurrent events add signed contact count times 0.275 mV to g after 1.8 ms. External events add 68.75 mV to voltage. These are functional model parameters, not measured device-fault characteristics.

Input begins at 100 ms; sensing and feedback update every 20 ms. Bearing is world-relative angle minus heading; looming is the change of $\arctan(0.05/d)$ at actual separation d. The pursuer starts 0.25 m away at $\pm 30°$ and moves at 0.3 m/s. Each motion segment aims it at the agent's segment-start position. Both positions advance linearly using the agent's starting heading; heading updates at segment end, capped at $\pm 100°$. A frame-end decision affects the next frame. The first trigger schedules a 0.35-m/s, heading-fixed burst 250 ms later for 450 ms; otherwise speed is 0.05 m/s. Segments split at exact actuator events; first contact with radius 0.05 m is solved within each segment. Failure latches, while traces continue to $H = 1\,\text{s}$ for resource accounting. Post-contact activity is counterfactual and excluded from warnings.

For each map, 20 passive development episodes (four seeds, five bearings from $-60°$ to $60°$) fit an affine steering score z. Standardized five-frame means of eight command rates over 200–400 ms predict bearing/60°, using ridge penalty 10 and an unpenalized intercept. The trigger threshold is half the tenth percentile of development episode mean command rates over 200–300 ms, floored at 2.5 Hz. Before the cue or below threshold, steering is zero. Otherwise proportional/relay laws apply $-600\,\text{clip}(z, -1, 1)/-600\,\text{sgn}(z)$ deg/s outside the burst. Healthy held-out validation RMSE is $65.9°/67.8°/67.2°$ for RF-0/A/B, over eight seed clusters each: z is not an accurate closed-loop bearing estimate.

B. Pairing, Cohorts and Endpoints

Shared uniforms give nested deletions $w_j^{(f)} = w_j \mathbf{1}[V_{sj} \geq f]$ and input events $\mathbf{1}[U_{sk\tau i} < \lambda_{ki}\Delta t]$. Indices denote seed




Fig. 3. Independent RF campaigns. (a) Primary healthy-to-fault losses and P/R loss counts; all healthy tasks succeed and no gains occur. (b) Prespecified secondary relay-minus-proportional net-loss contrast at 50% deletion, in percentage points. Pointwise 95% CIs resample whole seeds within each map ($n = 24/12/12$), conditional on saved calibrations. (c) All paired healthy minimum-clearance observations, with median bars, show unequal reserve. Maps share a prior but differ in draws, recalibration and test cohorts; differences are not an isolated RF effect.

s, frame k, neural step τ, cell i and connection row j; $\Delta t = 10^{-4}$ s. Feedback changes λ, while input variates and row masks remain paired. Seeds and hashes are traceable, without cross-platform bit-identity guarantees.

RF-0 uses 24 test seed clusters; RF-A/B each use 12 new clusters. Every cluster contains both bearings, two laws and healthy/25%/50% deletion: 288/144/144 episodes. New maps independently redraw all 314 azimuths from the same hemisphere prior (left 10–90°, right -90–-10°), preserving identities, vertical mapping and gradients. Each separately fits the frozen development recipe, uses 32 healthy validation episodes in eight further clusters, then freezes thresholds before testing. All maps, seeds and failures are retained; no test tuning or efficacy stopping occurs. This is transfer with recalibration, not zero-shot transfer or an RF-isolated causal experiment.

With $Y = 1$ meaning no contact through H, registered primary endpoints are paired loss $L = Y_H(1 - Y_F)$, gain $G = (1-Y_H)Y_F$ and activity exposure. Net loss $D = L-G$ is derived. The relay-minus-proportional contrast and warnings are prespecified secondary; clearance/heading diagnostics are post-hoc. For cumulative spikes S and $T_* = \min(T_F, T_H)$, own-stop and common-duration ratios are

$$R_{\text{stop}} = \frac{S_F(T_F)}{S_H(T_H)}, \qquad R_{\text{common}} = \frac{S_F(T_*)}{S_H(T_*)}. \tag{1}$$

Here T is contact-frame end or H, at 20-ms resolution. Common duration remains outcome-dependent and does not equate sensory histories; fixed 400-ms/1-s windows are separate endpoints.

Estimates average both bearings within seed. Pointwise 95% CIs use 20,000 whole-seed percentile resamples, conditional on stored map/calibration/thresholds (RNG 20261022 for RF-0; 20261023 for transfer). Symmetric-null sign-flip sensitivity tests are Holm-adjusted over two baseline doses, separately from four new map/dose contrasts. Maps and separate angle/action cohorts are not pooled.

Warnings use only data through 400 ms: unsmoothed 20-ms command rates averaged over 100–400 ms, or the absolute log spike-count ratio to a law/bearing-specific healthy reference. Healthy validation sets fifth-percentile command/forecast and 95th-percentile two-sided activity cutoffs; an upper-only comparator flags activity above twice its healthy reference. A held-command forecast uses exact simulated geometry and pending actuation, retaining the current turn; its schedule-only baseline sets future turn to zero. These information-rich forecasts are not neural-only detectors.

IV. Results and Conditional Interpretation

A. RF Transfer Weakens the Baseline Law Contrast

Fig. 3 reports primary loss counts and whole-seed uncertainty. All healthy tasks succeed, and no gains occur. The baseline 50%-dose secondary contrast is -22.9 pp (95% CI $[-33.3, -12.5]$; Holm $p = 0.00195$). Both new contrasts are -4.2 pp, CI $[-12.5, 0]$; all four new map/dose tests have Holm $p = 1$. Each new 50% contrast has only one nonzero cluster. These data neither precisely reproduce the large baseline advantage nor establish equivalence. The baseline 25% contrast remains uncertain ($p = 0.50$); no 25% loss is observed in A/B. With twelve event-free clusters, the one-sided 95% upper bound for any loss in a new identically defined two-bearing cluster is 22.1%, not zero trial risk.

All four new failures are retained: A has P/50% contacts at seed 3011/-30° and 3009/$+30$°, plus R/50% at 3009/$+30$°; B has P/50% at 3110/-30°. Healthy minimum clearance and executed heading differ between laws. RF-0 median P/R clearance is 33.1/41.4 mm, with absolute heading at 400 ms of 88.3°/100°. This whole-system comparison does not isolate fault-specific tolerance from healthy reserve. Separate map calibrations and test cohorts further preclude attributing the weaker contrasts solely to RF changes.




Fig. 4. Frozen secondary warning operating points. Rows state contact/success denominators; RF-0/A/B contain 24/12/12 independent seed clusters. Markers show missed-contact and false-alarm rates with pointwise 95% whole-seed bootstrap CIs. Activity is two-sided; the forecast holds the current command using exact simulated state. Zero observed misses and class-conditional intervals do not establish zero population risk.

B. Warning Errors and Exposure Limits

Fig. 4 shows that neural warnings retain misses and false alarms. Command criteria detect 2/13, 2/3 and 0/1 contacts in RF-0/A/B, respectively. The upper-only activity rule detects none in any map. The exact-state held-command forecast detects all observed contacts but flags 57/275, 25/141 and 33/143 successful tasks. Baseline schedule-only false alarms are 84/275. New sensitivities have only two/one failure clusters; 2,217/7,099 of 20,000 resamples lack a positive class. Intervals omit those draws only for the corresponding conditional rate. Zero-miss empirical intervals do not establish deployable protection.

Own-stop/common-duration medians coincide in all three maps, with maximum paired differences below 0.006. The historical large stopping-time effect does not recur. Fixed windows still differ: P/50% median 400-ms/1-s ratios are 0.981/1.505, 0.961/1.212 and 0.956/1.139. The separate eight-cluster $\pm 45^{\circ}$ test flags 22/32 healthy activity records and has an uncertain 50% law contrast. The historical six-cluster 25% post-hoc $p = 0.25$ remains separate, without confirmatory reinterpretation.

V. Scope, Artifacts and Conclusion

The interface adds executable checks for declared pairing, causal timing and exposure across two native schemas; it does not prove arbitrary fault coverage or authentic neural execution. Neural evidence remains conditional on one graph, an assumed RF family, a synthetic plant, unmatched healthy reserve and sparse failures. Walk-only contact by 0.8 s follows from this plant's speed construction, not connectome-specific advantage. Functional row deletions establish no biological tolerance, physical upset rate, hardware safety, energy or area benefit.

The matching V10 source and saved-record package is prepared for versioned public access; the V9 parent alone does not identify it. Saved-data replay requires no external matrices; fresh neural simulation requires separately obtained, hash-matched inputs. Third-party tables with unresolved redistribution terms are excluded from the public layer. A fresh checkout and clean dependency installation previously reproduced 448 V9 saved traces on the same host, without establishing second-host neural replication. New RF tests used four Xeon W-2223 workers, about 179 s median episode wall time and at most 1.21 GiB lifetime working set per worker.

Checked evidence and independent RF tests support a bounded engineering conclusion: valid pairing and clocks make conditional fault results interpretable, while neither preserved activity nor a successful baseline establishes a universal protection policy.

REFERENCES

[1] S. Jha, S. S. Banerjee, T. Tsai, S. K. S. Hari, M. B. Sullivan, Z. T. Kalbarczyk *et al.*, "ML-based fault injection for autonomous vehicles: A case for bayesian fault injection," in *2019 49th Annual IEEE/IFIP International Conference on Dependable Systems and Networks (DSN)*, 2019, pp. 112–124. [Online]. Available: https://doi.org/10.1109/DSN.2019.00025

[2] T. Spyrou, S. Hamdioui, and H.-G. Stratigopoulos, "SpikeFI: A fault injection framework for spiking neural networks," arXiv:2412.06795, 2024. [Online]. Available: https://arxiv.org/abs/2412.06795

[3] A. B. Göğebakan, E. Magliano, A. Carpegna, A. Ruospo, A. Savino, and S. Di Carlo, "SpikingJET: Enhancing fault injection for fully and convolutional spiking neural networks," in *2024 IEEE 30th International Symposium on On-Line Testing and Robust System Design (IOLTS)*. IEEE, 2024, pp. 1–7.

[4] A. Colucci, A. Steininger, and M. Shafique, "enpheeph: A fault injection framework for spiking and compressed deep neural networks," in *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. IEEE, Oct. 2022, pp. 5155–5162. [Online]. Available: https://doi.org/10.1109/IROS47612.2022.9982181

[5] P. Glasserman and D. D. Yao, "Some guidelines and guarantees for common random numbers," *Management Science*, vol. 38, no. 6, pp. 884–908, 1992.

[6] A. Donzé, "Breach, a toolbox for verification and parameter synthesis of hybrid systems," in *Computer Aided Verification (CAV)*. Springer, 2010, pp. 167–170.

[7] J. Yik, K. Van den Berghe, D. den Blanken, Y. Bouhadjar, M. Fabre, P. Hueber *et al.*, "The NeuroBench framework for benchmarking neuromorphic computing algorithms and systems," *Nature Communications*, vol. 16, no. 1, p. 1545, Feb. 2025. [Online]. Available: https://doi.org/10.1038/s41467-025-56739-4

[8] G. D'Angelo, J. E. Pedersen, T. Hassan, M. Cianchetti, J. Bongard, F. Iida *et al.*, "A benchmarking framework for embodied neuromorphic agents," *Nature Machine Intelligence*, vol. 8, no. 3, pp. 300–312, Mar. 2026. [Online]. Available: http://dx.doi.org/10.1038/s42256-026-01197-w

[9] G. Chessa, Y. Yang, E. Jones, M. Favalli, and D. Bertozzi, "Cross-layer analysis of permanent faults in asynchronous NoCs for neuromorphic computing," in *Proceedings of the International Conference on Neuromorphic Systems*. ACM, 2026, pp. 31–38.

[10] S. Dorkenwald, A. Matsliah, A. R. Sterling, P. Schlegel, S.-C. Yu, C. E. McKellar *et al.*, "Neuronal wiring diagram of an adult brain," *Nature*, vol. 634, no. 8032, pp. 124–138, 2024.

[11] P. K. Shiu, G. R. Sterne, N. Spiller, R. Franconville, A. M. Sandoval, J. Zhou *et al.*, "A Drosophila computational brain model reveals sensorimotor processing," *Nature*, vol. 634, no. 8032, pp. 210–219, 2024.

[12] M. Stimberg, R. Brette, and D. F. Goodman, "Brian 2, an intuitive and efficient neural simulator," *eLife*, vol. 8, p. e47314, Aug. 2019. [Online]. Available: https://doi.org/10.7554/eLife.47314