How Much Fault Tolerance Is in a Fly Brain?

Fault-Injection Analysis of a Whole-Connectome Spiking Controller for Physical Intelligence

Shuchao Gao
Waseda University
Tokyo, Japan

***Abstract*—Whole-brain point-neuron models built from complete wiring diagrams now serve as controllers in embodied settings, yet their fault tolerance has been probed only on subnetworks and via targeted silencings. We take the released leaky integrate-and-fire (LIF) whole-brain model of *Drosophila melanogaster* (138,639 neurons, 15.1M signed connections, 54.5M contacts) and inject five hardware-motivated fault classes—weight variability, connection loss, random-unit and hub output silencing, and sensory deafferentation—scoring the population response of descending command neurons at three to four doses, 12 seeded trials each, on the biological graph and on an edge-permuted null. Under escape-grade drive the connectome absorbs 50% lognormal weight variability; 50% connection loss retains 76.5% of command rate at a 33% latency cost; 10% random-unit output silencing leaves the median unchanged; silencing the top-1% hubs produces a 2.5× over-activity rather than silence. The null, which preserves weights and degrees but reassigns every target, never reaches threshold and decays at the same relative rate, so robustness tracks threshold amplification on convergence structure rather than redundancy alone. A synthetic closed-loop escape task then exposes the limit of these metrics: at 50% loss open-loop transmission is retained while escape collapses to 0/12, because the readout reaches its trigger only when the threat is 7–11 cm away. Five candidate design implications follow.**

***Index Terms*—neuromorphic computing, connectome, fault tolerance, fault injection, Drosophila**

I. Introduction

PHYSICAL intelligence—agents whose perception, decision, and action loops close in the physical world under tight energy and latency budgets—demands controllers that remain robust on imperfect hardware [1], [2]. Neuromorphic systems promise the required efficiency [3], and spiking implementations on Loihi 2 and FPGA substrates now cover vision and control workloads [4]–[6]. How *wiring* determines robustness remains poorly quantified: engineered networks are designed task-by-task, so their fault tolerance must be re-measured per design [7], [8]. Complete signed wiring diagrams of whole brains are public, and point-neuron models built on them reproduce realistic dynamics without training [9], [10]; an evolved connectome is thus a field-tested controller and a reference for engineered fault tolerance.

The released leaky integrate-and-fire (LIF) whole-brain model of *Drosophila melanogaster* [9][1], which instantiates the complete FlyWire connectome [10], has already been used for targeted computational silencings [9] and for network-dismantling studies of a derived sugar-sensing subnetwork [11]; we sweep five *hardware-motivated fault classes* on the fixed whole-brain model, scored jointly for transmission and activity-envelope compliance. We instrument the visuomotor escape pathway: looming-sensitive visual interneurons (LC4, LPLC2) converge onto descending command neurons (DNp01, DNa02, DNp04, DNb01) whose activation evokes take-off and escape steering [12]. Its failure modes map onto hardware fault classes: weight imprecision, broken interconnect, dead cores, dead sensors.

We inject five fault families (Section III-C), each over 12 seeded 600 ms trials, against an edge-permuted null and an analytic pathway-mass control. Our contributions: (i) a fault-injection framework mapping hardware failure modes onto a connectome-constrained 138k-neuron LIF model; and (ii) tolerance curves of descending-neuron output in a complete connectome (50% weight noise absorbed; 50% connection loss retains 76.5% of command rate; 10% random-unit silencing leaves the median unchanged), while top-1% hub silencing produces a 2.5× *over-activity* that passes transmission yet violates the activity envelope, and deafferentation fails both criteria. We further (iii) show that graph redundancy alone explains neither specificity nor graceful degradation (threshold amplification is a candidate account), (iv) distill five design implications, and (v) demonstrate in a synthetic closed loop that preserved transmission can still fail the task.

II. Related Work

The release of complete wiring diagrams for the adult *Drosophila* brain [10] has shifted connectome research from static graph analysis to executable models: visual-system convolutions [13], neuron-level response prediction [14], learned tasks and whole-body locomotion on whole-CNS wiring [15]–[17], biofidelic processing units [18], and descending-neuron input sharing [19], [20]. Closest to our substrate, the released LIF whole-brain model (footnote 1) reproduces global activity and has been ported to Loihi 2 [4]. Dismantling studies have deleted critical nodes from connectome-derived circuits—including an SNN sugar-sensing subnetwork of the same released model, scored by a sensory firing-rate threshold [11]—but none sweeps hardware-motivated fault classes on a fixed whole-brain controller or separates output transmission from activity-envelope compliance; we do both.

Graph-theoretic lesion studies score the structural attack tolerance of brain networks [21], not dynamics; spiking-network weight-noise robustness is mostly characterized on small

[1]https://github.com/philshiu/Drosophila_brain_model

trained architectures [7], [8], with adaptive mitigation now studied at the edge [22]; purpose-built fault-injection frameworks for trained SNNs—SpikeFI [23], SpikingJET [24]—automate this but score task accuracy on human-designed networks, with follow-up work on STDP-trained robustness and population-coded redundancy [25], [26]. Hardware platforms expose complementary constraints: on-chip variability co-design [5], FPGA precision–capacity trade-offs [6], permanent interconnect faults [27], and trained-CNN dependability [28]. Insect-inspired collision-aversion circuits are robust by construction but small and hand-designed [29], and fault-injection benchmarking of neuromorphic systems is only beginning [30], [31]; a complete connectome enables it at the scale of an entire evolved controller.

III. Fault-Injection Framework

A. Whole-Brain Spiking Substrate

We adopt the released whole-brain LIF model of *Drosophila* [9] (Section I), implemented in Brian2 [32] and built on the FlyWire connectome [10]. Every neuron is a current-based LIF unit (threshold -45 mV, reset -52 mV, membrane time constant 20 ms, refractory 2.2 ms, axonal delay 1.8 ms). Each connection in the released table becomes a delta-conductance synapse whose jump is 0.275 mV per counted contact and decays with a 5 ms synaptic time constant, signed by the presynaptic cell's neurotransmitter; the table yields 15,091,983 connections between 138,639 neurons (54.5M contacts), 40% inhibitory. As in the released model, baseline firing is zero and the only external input is the stimulus group, so every recorded spike traces back to the stimulated cells. Our engine restores the full network state before every trial, so conditions share initial states while the stimulus draws a fresh realization: reported dispersion includes stimulus variability. One 600 ms trial runs in $\approx$3.5 s on one CPU core.

B. Task: Visuomotor Escape

The instrumented pathway (Fig. 1) is the fly's looming-triggered escape circuit: looming-sensitive visual projection neurons LC4 (104) and LPLC2 (210) converge on descending neurons [12], [29], [33]. Because collision-sensing models treat looming as sustained high-rate drive, we drive the sensory cells (and, as a control, an equal-sized random set) with independent 150 Hz Poisson trains rather than modeling looming kinetics. The primary readout is the population rate of the command set {DNp01, DNa02, DNp04, DNb01} (8 neurons); all 1,299 descending neurons are a secondary readout. Calibration drove the command population to 94.6 Hz (interdecile 93.6–95.8 Hz, first-spike latency 4.4 ms; 10-trial set) under escape stimulation but only 8.2 Hz (6.4–9.2 Hz) under random stimulation; $\theta = 51.4$ Hz (the 94.6/8.2 Hz midpoint); every pass/fail classification below is unchanged for thresholds between the observed trial extremes (9.2–63.1 Hz).

C. Fault Taxonomy

Five fault families cover the hardware-relevant failure modes. F1 multiplies every synaptic weight by an i.i.d.




Fig. 1. The instrumented escape pathway, drawn from the connectome. Left: the 314 driven sensory cells (LC4, LPLC2); center: the 90 top-ranked of 849 two-hop relays; right: the 8 command DNs. Line width and opacity scale with synapse count (594 direct sensory→DN edges); dashed red marks the fault-injection points (F5 channels; F1/F2 synapses; F3/F4 units). Inset: reconstructed adult brain, adapted from Dorkenwald et al. [34] (CC BY 4.0).

mean-preserving lognormal factor ($\sigma \in \{0.05, 0.1, 0.2, 0.5\}$), modeling analog weight variability and bit-level imprecision. F2 deletes a random fraction $f \in \{0.05, 0.10, 0.25, 0.50\}$ of connections ($\approx f$ of contacts in expectation), modeling interconnect or memristor failures. F3 silences all outgoing connections of a random fraction $f \in \{0.01, 0.02, 0.05, 0.10\}$ of units, excluding input and readout cells (silenced cells still receive input and spike), modeling dead cores at the output boundary. F4 applies the same operation to the top 1%, 2%, or 5% of units ranked by total outgoing contact count, modeling failure of high-fanout components; these cells carry 9–22% of all connections, a targeted, correlated version of F3. F5 zeroes all outgoing connections of one (LC4 or LPLC2) or both sensory channels, modeling sensor or afferent-path failure. All faults are applied after state restoration; F4 and F5 act on fixed cell sets, while F1–F3 redraw their realization each trial from SHA-256 seeds over (phase, condition, trial)—12 independent draws per condition; fault masks are bit-reproducible, whereas the stimulus is not re-seeded, so whole re-runs are statistically equivalent rather than bit-identical.[2]

D. Controls

Two controls isolate what the biological wiring contributes. The first is an edge-permuted null: every synapse keeps its presynaptic partner, weight, and sign, but its postsynaptic target is randomly reassigned. This preserves out-degrees, weights, and the global in-degree histogram while destroying which inputs converge onto each target—and with them all multi-hop structure; the identical sweep runs on it. The second is analytic: for both graphs we compute the *pathway mass* $m_k = \mathbf{1}_{\mathrm{DN}}^{\top} A^k \mathbf{1}_{\mathrm{in}}$, the synapse-weighted total of all k-hop directed paths from LC4∪LPLC2 into the full descending layer (m_k sums k-step walks of either sign—a density proxy, not signal flow), on the intact graph and after the F2 deletion levels; comparing its decay with the output decay separates topological redundancy from dynamical amplification.

IV. Results

A. Baseline: The Connectome Is a Specific, Low-Latency Controller

Driving LC4 and LPLC2 at 150 Hz produces a command rate of 94.7 Hz (median over 12 trials) with 4.05 ms first-spike latency, far above θ (Fig. 2). An equal-sized random

[2]Code, connectome-derived edge lists, and per-trial records: https://github.com/Scophield/drosophila-fault-injection.




Fig. 2. Readout specificity. Command rate under escape stimulation (LC4+LPLC2) versus matched random-site stimulation (314 cells); dashed line: θ.

set, driven identically, yields only 8.2 Hz on the same readout while producing *more* total activity (293k vs. 40k spikes): the readout is pathway-specific, not generic arousal. With both channels silenced ($F5_{\text{both}}$) it collapses to zero in every trial, and the residual 21.2k spikes are the stimulated sensory cells themselves, so the score measures transmission through the pathway.

B. Tolerance Curves: Noise Is Absorbed, Disconnection Degrades Gracefully

Figure 3 shows dose–response curves for the two most consequential families; F1 and F3 are flat in median (Section V). At σ=0.5 weight variability leaves the median unchanged (94.2 vs. 94.7 Hz) but widens trial dispersion (interdecile 90.4–100.8 vs. 94.0–95.6 Hz) and raises total activity only from 39.7k to 41.6k spikes. Random connection deletion degrades gracefully: 5% and 10% loss leave 91.9 and 93.1 Hz, 25% retains 84.5 Hz (89.2%), and 50% retains 72.4 Hz (76.5%), with all 12 trials passing transmission in every condition (weakest 63.1 and 68.1 Hz, $\geq$22% above θ). The cost appears predominantly in latency—4.05 to 5.4 ms at 50% loss (+33%)—consistent with weakened aggregate drive rather than longer residual routes; which dominates a task-level error budget is workload-dependent. Silencing 10% of units at random—nearly 14,000 neurons cut off from their targets—also leaves the median unchanged (95.1 Hz): command drive integrates over hundreds of converging populations, and no tested random slice is load-bearing. The 1,299-neuron descending layer tracks the same pattern (2,941 vs. 1,918 spikes at 50%), so the graded response belongs to command encoding, not to the eight-neuron readout.

C. Hub Silencing Produces Over-Activity, Not Silence

The dose–response of hub silencing (F4) is non-monotonic and qualitatively different from every distributed fault (Figs. 3b, 4b). Silencing the top 1% of cells by outgoing contact count (1,386 neurons, 9.1% of connections) *increases* the command rate to 122.3 Hz (+29%, interdecile 121.1–123.9 Hz across trials) and more than doubles global activity (99.9k spikes, 2.52$\times$ healthy; Mann–Whitney $p < 10^{-4}$, as for $F2_{50}$ and $F5_{\text{both}}$); at 2% the rate stays elevated (117.1 Hz, 42.4k); at 5% (22.4% of connections) both metrics return to near-baseline (94.2 Hz, 36.5k). The effect is not disconnection alone: random 10% unit silencing disconnects 10.0% of connections (more than the hub set's 9.1%) yet leaves the readout unchanged (95.1 Hz), although a control matching cell count and E/I composition is still needed. Because the removed output is inhibitory-rich (62% vs. 40% network-wide), de-inhibition is the leading hypothesis. We therefore score *transmission* (rate $\geq \theta$) and an *activity envelope* (rate and total activity within 2$\times$ healthy) separately: 1% hub silencing passes transmission while violating the envelope in all 12 trials (persists for multipliers 1.5$\times$–2$\times$); every distributed fault passes both; $F5_{\text{both}}$ fails both. The envelope violation is the dangerous mode: output exceeds its envelope while every per-unit monitor reads "active," and the null shows no such signature.

D. What the Wiring Contributes: Null Network and Pathway Analysis

The permuted null dissociates specificity from redundancy: out-degrees, weights, and the in-degree histogram survive, convergence is reassigned, and its median command rate is 0.0 Hz in every tested condition, with no trial reaching θ. Its 1,299-neuron readout falls to background (45.5 spikes per trial vs. 2,941 healthy) and global activity to 60% of the biological level (23.8k vs. 39.7k)—barely above the 21.2k the driven cells produce with all outputs severed, so only $\sim$2.6k spikes propagate. Pathway mass quantifies the convergence advantage: 5.8$\times$ (1-hop) and 17.7$\times$ (4-hop) more route mass into the descending layer. Yet *relative* pathway-mass decay is nearly identical (at f=0.5, k=8: 0.3% vs. 0.4% of baseline; Fig. 4a), while output degrades far more slowly (76.5% at f=0.5 against 5.8% four-hop route mass), ruling out graph redundancy alone. A candidate account is threshold amplification: with N converging afferents and per-synapse survival p, aggregate drive scales as Np while k-hop route mass decays as p^k in expectation (6.25% at k=4, p=0.5), and the saturating threshold compresses drive changes into small rate changes. Retention above proportional scaling (76.5% at p=0.5, 89.2% at p=0.75) is consistent with this account but does not establish it: in an E/I network even linear signal flow need not scale with p, since deleting inhibitory connections offsets excitatory loss. Disentangling these requires E/I-balanced deletion and drive-strength sweeps.

E. From Transmission to Behavior: A Closed-Loop Escape Demo

Transmission retention need not imply task capability, so we close the loop: looming rates over the 314 LC4/LPLC2 cells (assumed receptive fields) drive the full network, a frozen left–right difference across the eight command cells steers a planar agent away from a pursuing threat, and a ballistic takeoff fires when the 8-cell mean rate crosses θ_{demo}=25.6 Hz (the median peak of six two-azimuth training episodes over 250–300 ms; the open-loop θ=51.4 Hz was calibrated for full-pool drive and does not transfer). It escapes 24/24 across four azimuths ($\pm$30°, $\pm$60°; six seeds; median miss 0.09–0.11 m against a 0.05 m contact radius; Fig. 5), including 12/12 at the two untrained azimuths ($+$30°, $+$60°), and 0/3 for a




Fig. 3. Tolerance curves of descending-neuron output (medians over 12 trials; blue: rate; orange: latency (a) / total spikes (b); dotted grey: healthy medians). (a) Connection dropout: 76.5% of command rate retained at 50% loss, latency +33%. (b) Hub silencing: over-activity.




Fig. 4. Topology contrast. (a) Route mass under edge loss, normalized per graph (connectome solid, null dashed): relative decay nearly identical, absolute mass 5.8–17.7× higher. (b) Activity under hub silencing: over-activity only in biological wiring; null readout 0.0 Hz (median).




Fig. 5. Synthetic closed-loop escape at −30° (seed 0, one threat script). Blue: agent path; grey: threat path; red dot: threat endpoint. Columns: healthy, $F2_{50}$, $F4_{1\%}$, steering disabled; the distance in each label is the closest approach. Success: separation > 0.05 m.

frontal approach (blind spot). Every control collapses (0/12 for steering disabled, readout disabled, and reversed sides), while a scene-reading hand rule reaches 12/12. Faults transfer as a threshold cliff rather than a graded rate loss: 25% loss escapes 10/12 and 50% escapes 0/12, although the same 50% loss retains 72.4 Hz open-loop. Under single-target drive the $F2_{50}$ readout peaks at ≈38 Hz and first reaches θ_{demo} only at 420–500 ms, when the threat is 7–11 cm away—too late for the 250 ms aiming delay and 450 ms takeoff—so preserved transmission does not imply preserved behavior and the open-loop criterion is the wrong certificate for a closed loop. Hub silencing, by contrast, preserves escape (12/12) at 1.7× healthy activity, inside the 2× envelope. This is a preliminary synthetic demonstration, not a behavioral validation (assumed encoding, scripted envelope, kinematic agent).

V. Candidate Design Implications for Embodied Neuromorphic Controllers

Three of the five implications concern where redundancy pays. Because 50% weight variability and 10% unit-output silencing both leave the median command rate unchanged (99.4% and 100.4% of baseline), precision and per-unit yield can be traded against wiring redundancy: such a controller needs many converging routes, not accurate synapses, consistent with hardware observations [5], [7]. Disconnection is instead paid in latency rather than rate—76.5% of the rate survives at 50% loss while latency rises 33%—so a real-time loop should budget the latency curve (Fig. 3a).

The other two implications concern failure modes that per-unit monitoring misses. Hub silencing is the only *amplifying* class: it passes transmission while doubling activity, so controllers should monitor the activity envelope rather than liveness and should regulate high-fanout units before deployment. Deafferentation is the opposite extreme: either channel alone retains 68–79% of the median rate, but losing both drives the pathway to zero, making the sensor interface—not the synaptic fabric—the first redundancy candidate. Because relative pathway decay is identical while only the biological graph yields a decodable command, fault injection belongs pre-deployment [30], [31].

VI. Limitations and Conclusion

Our LIF abstraction fixes one drive rate, the hub analysis is descriptive, and correlated damage and recovery are excluded. The instrumented pathway is one of many, so the tolerance ordering is a hypothesis for other pathways rather than a whole-brain law, and its documented vulnerability to aging [35] suggests tolerance is not a fixed property of the wiring either. Under the tested drive the median command rate survives weight noise and unit silencing and retains 76.5% at 50% loss; the dangerous failure is hub over-activity, and a synthetic loop shows preserved transmission need not preserve behavior.

REFERENCES

[1] Y. Yuan, Y. Huang, X. Yao, Y. Li, S. Zhang, L. Han *et al.*, "Embodied-r1.5: Evolving physical intelligence via embodied foundation models," arXiv:2606.11324, 2026.

[2] W. Guo, H. Zhang, P. Li, T. Cai, Z. Chen, Y. Guo *et al.*, "Neurovla: A brain-inspired embodied intelligence for fluid and fast reflexive robotics control," arXiv:2601.14628, 2026.

[3] M. van Gerven, "Neuromorphic intelligence," arXiv:2509.11940, 2025.

[4] F. Wang, B. H. Theilman, F. Rothganger, W. Severa, C. M. Vineyard, and J. B. Aimone, "Neuromorphic simulation of drosophila melanogaster brain connectome on loihi 2," arXiv:2508.16792, 2025.

[5] S. Arfa, B. Vogginger, and C. Mayr, "Hardware-aware fine-tuning of spiking q-networks on the spinnaker2 neuromorphic platform," ACM ICONS 2025 - International Conference on Neuromorphic Systems, 2025.

[6] A. Gautam, P. Date, S. Kulkarni, R. Patton, and T. Potok, "Neurocorex: An open-source fpga-based spiking neural network emulator with on-chip learning," arXiv:2506.14138, 2025.

[7] T. K. T. Thieu and R. Melnik, "Effects of noise on leaky integrate-and-fire neuron models for neuromorphic computing applications," arXiv:2202.09482, 2022.

[8] A. Yunusoglu, D. Le, M. Isik, I. C. Dikmen, and T. Karadag, "Neuromorphic circuits with spiking astrocytes for increased energy efficiency, fault tolerance, and memory capacitance," arXiv:2502.20492, 2025.

[9] P. K. Shiu, G. R. Sterne, N. Spiller, R. Franconville, A. M. Sandoval, J. Zhou *et al.*, "A drosophila computational brain model reveals sensorimotor processing," *Nature*, vol. 634, no. 8032, pp. 210–219, 2024.

[10] A. Lin, R. Yang, S. Dorkenwald, A. Matsliah, A. R. Sterling, P. Schlegel *et al.*, "Network statistics of the whole-brain connectome of drosophila." in *Nature*, 2024.

[11] T. Adler, M. Grassia, Z. Liao, G. Mangioni, and C. V. Cannistraci, "Latent geometry-driven network automata for complex network dismantling," Preprint (ICLR 2026), 2025.

[12] J. H. Simpson, "Descending control of motor sequences in drosophila," *Current Opinion in Neurobiology*, vol. 84, p. 102822, 2023.

[13] J.-N. Liew, S. Lin, B. Chen, W. Zhang, X. Zhu, W. Zhang *et al.*, "Connectome-based modelling reveals orientation maps in the drosophila optic lobe," arXiv:2609.01330, 2026.

[14] J. Xie, R. Ren, X. Zhou, A. Zheng, J. Zhu, W. Jiang *et al.*, "Visual function profiles via multi-path aggregation reveal neuron-level responses in the drosophila brain," arXiv:2512.06934, 2025.

[15] J. Cho, M. Kang, and D. Kim, "A drosophila whole-connectome network can learn human-designed cognitive tasks," arXiv:2610.10014, 2026.

[16] S. Senge, "A connectome test of the fly hashing algorithm," arXiv:2610.09114, 2026.

[17] Z. Jin, Y. Zhu, C. Zhang, and Y. Sui, "Whole-brain connectomic graph model enables whole-body locomotion control in fruit fly," arXiv:2602.17997, 2026.

[18] S. Yu, Z. Qin, T. Liu, B. Xu, R. J. Vogelstein, J. Brown *et al.*, "Biological processing units: Leveraging an insect connectome to pioneer biofidelic neural architectures," arXiv:2507.10951, 2025.

[19] X. Zhang, "Synaptic placement reflects shared input in drosophila descending neurons," arXiv:2610.00690, 2026.

[20] N. Drummond, A. Zhao, and A. Borst, "Population morphology implies a common developmental blueprint for drosophila motion detectors." in *PLoS computational biology*, 2026.

[21] H. Aerts, W. Fias, K. Caeyenberghs, and D. Marinazzo, "Brain networks under attack: robustness properties and the impact of lesions," *Brain*, vol. 139, no. 12, pp. 3063–3083, 2016.

[22] S. Luca, T. P. Xiao, F. S. Chance, S. Agarwal, C. Teeter, and G. W. Chapman, "Learned adaptive properties for mitigation of weight perturbations in embedded spiking networks," *Frontiers in Neuroscience*, vol. 20, p. 1766765, 2026.

[23] T. Spyrou, S. Hamdioui, and H.-G. Stratigopoulos, "Spikefi: A fault injection framework for spiking neural networks," arXiv:2412.06795, 2024.

[24] A. B. Göğebakan, E. Magliano, A. Carpegna, A. Ruospo, A. Savino, and S. D. Carlo, "Spikingjet: Enhancing fault injection for fully and convolutional spiking neural networks," in *2024 IEEE 30th International Symposium on On-Line Testing and Robust System Design (IOLTS)*. IEEE, 2024, pp. 1–7.

[25] Z. Jouni and H.-G. Stratigopoulos, "STDP-trained spiking neural network reliability assessment through fault injections," in *2025 IEEE 31st International Symposium on On-Line Testing and Robust System Design (IOLTS)*. IEEE, 2025, pp. 1–8.

[26] A. Gleyo and B. Girau, "Population coding to improve fault tolerance of neuromorphic networks in regression tasks," in *2026 Design, Automation and Test in Europe Conference (DATE)*. IEEE, 2026, pp. 1–7.

[27] G. Chessa, Y. Yang, E. Jones, M. Favalli, and D. Bertozzi, "Cross-layer analysis of permanent faults in asynchronous NoCs for neuromorphic computing," in *Proceedings of the International Conference on Neuromorphic Systems*. ACM, 2026, pp. 31–38.

[28] J. Gracia-Morán, J. C. Baraza-Calvo, J.-C. Ruiz, D. de Andrés, D. Gil-Tomás, and L.-J. Saiz-Adalid, "Dependability analysis of a spiking convolutional neural network (S-CNN)," *Lecture Notes in Computer Science*, pp. 147–161, 2026.

[29] F. Shuang, Y. Zhu, Y. Xie, L. Zhao, Q. Xie, J. Zhao *et al.*, "Opplod: the opponency based looming detector, model extension of looming sensitivity from lgmd to lplc2," arXiv:2302.10284, 2023.

[30] J. Yik, K. V. den Berghe, D. den Blanken, Y. Bouhadjar, M. Fabre, P. Hueber *et al.*, "Neurobench: A framework for benchmarking neuromorphic computing algorithms and systems," arXiv:2304.04640, 2023.

[31] T. Medvedeva, A. Franci, and F. Castaños, "Formalizing neuromorphic control systems: A general proposal and a rhythmic case study," arXiv:2506.10203, 2025.

[32] D. F. M. Goodman, "The brian simulator," *Frontiers in Neuroscience*, vol. 3, no. 2, pp. 192–197, 2009.

[33] H. Jang, D. P. Goodman, J. Ausborn, and C. R. von Reyn, "Azimuthal invariance to looming stimuli in the drosophila giant fiber escape circuit," *Journal of Experimental Biology*, vol. 226, no. 8, 2023.

[34] S. Dorkenwald, A. Matsliah, A. R. Sterling, P. Schlegel, S.-C. Yu, C. E. McKellar *et al.*, "Neuronal wiring diagram of an adult brain." *Nature*, vol. 634, no. 8032, pp. 124–138, 2024.

[35] A. Gaitanidis, V. Pampanin, J. Thiem, G. Kalaras, L. Huthmacher, S. Hürkey, D. Kadas, A. Dimitriadou, A. Ntogka, S. Sanyal, C. Consoulas, and C. Duch, "The drosophila escape motor circuit shows differential vulnerability to aging linked to functional decay," *PLoS Biology*, vol. 23, no. 12, p. e3003553, 2025.