

Blocked Area Calculation Report (Step-wise)

File: 3.2b 1hz 30um.csv

Pressure: 3.2 bar

Device: 30um

Date: 2026-01-02 16:51:54


1) Selected window

Window start = 21.318657 s, Window end = 25.765170 s

2) Picked points (NO averaging; single raw datapoint)

| Point | Snapped time (s) | Snapped current (A) |
|-------|------------------|---------------------|
| OPEN | 24.069902 | 2.150000000000e-06 |
| CLOSE | 25.227775 | 1.310000000000e-06 |

3) Window plot with selected points



4) Experimental blocked area (exact order)

```
V = 1.0 V
ρ = 0.0896 Ω·m, l = 0.000145 m, w = 0.0001 m, d = 3e-05 m
A = wxd = 3e-09 m², ρl = ρxl = 1.2992e-05 Ω·m²
G_open = |I_open/V| = |2.150000000000e-06/1.0| = 2.150000000000e-06 S
G_closed = |I_close/V| = |1.310000000000e-06/1.0| = 1.310000000000e-06 S
R_open = 1/G_open = 465116 Ω
R_closed = 1/G_closed = 763359 Ω
ΔR = R_closed - R_open = 298242 Ω
k = (AΔR)/(ρl) = 68.8676
A'/A = 1/(1+k) = 0.0143128
Blocked% = 100×(1 - A'/A) = 98.5687 %
```

5) Theoretical blocked area (PDF-style: sector – triangle)

[1] Input Parameters

```
Pressure (P) = 3.2 bar = 320000 Pa
Membrane radius (a) = 50.00 μm = 0.00500 cm
Membrane thickness (t) = 1.50 μm = 0.00015 cm
Young's modulus (E) = 7.00e+06 Pa
Poisson's ratio (ν) = 0.3
Constant (C_f) = 2.67
Effective modulus (E') = E/(1-ν) = 1.00e+07 Pa
Channel cross-section A = 3.00000e-05 cm²
```

[2] Intermediate Calculations

```
Factor = (a × P × Cf) / (E' × t)
        = (0.00500 × 320000 × 2.67) / (1.00e+07 × 0.00015)
        = 2.84800
w = a × factor(1/3)
    = 0.00500 × (2.84800)(1/3)
    = 0.00709 cm = 70.87 μm
r = (a2 + w2) / (2w)
    = (5.00000e-03 + 5.02304e-05) / (2 × 0.00709)
    = 0.00531 cm
θ = 2 × arcsin(a / r)
    = 2 × arcsin(0.00500 / 0.00531)
    = 2.45759 rad
Triangle Area = a × (r - w)
               = 0.00500 × (0.00531 - 0.00709)
               = -8.89981e-06 cm2
Sector Area = 0.5 × r2 × θ
             = 0.5 × 0.005312 × 2.45759
             = 3.46130e-05 cm2
Arc (Blocked) Area = Sector - Triangle
                   = 3.46130e-05 - -8.89981e-06
                   = 4.35128e-05 cm2
```

[3] Final Result

```
Blocked Area (%) = (Arc Area / Channel Area) × 100
                 = (4.35128e-05 / 3.00000e-05) × 100
                 = 145.04 %
```