
UML Diagrams

Sequence Diagram

25 August 2023






A sequence diagram:

- is used to model how objects interact with one another in terms of the messages (method calls) they pass to one another.
- emphasises the order of message execution as a reaction to some event.
- arranged interactions from top to bottom, following their order of

Sequence diagrams are drawn in *frames* - a rectangle with a heading




- Name to name the diagram or
- Keyword to indicate the scope of loop structures, conditional statements or parallel flows.

A *lifeline* represents an individual participant in the interaction (object instances).



The Integer class is a wrapper for an integer value




```
Integer* topNumber = new Integer();
Integer bottomNumber;
```



Objects in the system form the lifelines, the order of these lifelines is not significant.

sd Lifelines		
: Client	topNumber : Integer	bottomNumber : Integer
	i	i
· · · · · ·	ļ	ļ
į į	j	į
	<u> </u>	-
į į	j	į
	- H	ł
į į	į	į
	ł	<u> </u>
!	ļ.	ļ
	+	ļ

Creation and Destruction



```
Integer* topNumber = new Integer();
delete topNumber;
```



Aynchronous - e.g. set value


```
Star P Set Value Standard Edition(University of Pretoria)

: Client topNumber : Integer

1: setValue(theValue : double)
```

```
double aValue = 2.66;
topNumber->setValue(aValue);
```

Synchornous - e.g. get value




int aValue = bottomNumber.getValue();





Reflexive messages (self message), when an object calls a method that is defined in its own class.

Assume operarator++ is a private function define in Integer and increase calls the operator increment times.




Example






Branching happens when the program flow contains conditional statements.





For example, connection to a modem




If a diagram becomes complex, it is advisable to model it in **fragments**.

: Conne	ctionController : Timer	: Modem
	Start(timeout: int)	
	Open()	
[modem r	esponds]	
ref	Modem Responds	
[timer res	oondsj	






Iteration happens when the program flow contains looping statements.



Syntax for a loop structure



Parallel actions model interactions that are executed at the same time (in parallel).



Syntax for parallel actions



