

Lecture 4: Functions

Curtin FIRST Robotics Club (FRC) Pre-season Training

Scott Day

265815F@curtin.edu.au

November 11, 2016

Curtin University

Insert Mandatory Programming Joke




Table of contents

1. Function Justification
2. Function Definition
3. Example of Function Definition, Declaration and Call
4. Function Header and Body
5. Function Declaration
6. Function Call and Execution
7. Function Arguments
8. Passing by Value or Reference
9. Recursion - just to f*** with you

Function Justification

In C++ we can subdivide the functional features of a program into blocks of code known as functions. In effect these are subprograms that can be used to avoid the repetition of similar code and allow complicated tasks to be broken down into parts, making the program modular.

Until now you have encountered programs where all the code (statements) has been written inside a single function called `main()`. Every executable C++ program has at least this function. In the next sections we will learn how to write additional functions.

Function Definition

In C++, a function is a group of statements that is given a name, and which can be called from some point of the program. The most common syntax to define a function is:

```
1 returnType functionName(type parameter1, type parameter2, ...)  
2 {  
3     statements;  
4 }
```

Where:

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------|
| return-value-type | Is the type of the value returned by the function. |
| function-name | Is the identifier by which the function can be called. |
| parameters | Each parameter consists of a type followed by an identifier, with each parameter being separated from the next by a comma. |
| statements | Is the function's body. It is a block of statements surrounded by braces { } that specify what the function actually does. |



Example of Function Definition, Declaration and Call

Example 1 - Addition

- A very basic example of using a function
- Note: Both examples do the exact same thing.

```
1 // Function Example
2 #include <iostream>
3 using namespace std;
4
5 int addition(int a, int b)
6 {
7     int result;
8
9     result = a + b;
10
11     return result;
12 }
13
14 int main()
15 {
16     int temp;
17
18     temp = addition(5, 3);
19     cout << "The result is: " << temp << endl;
20
21     return 0;
22 }
23
```

```
1 // Function Example
2 #include <iostream>
3 using namespace std;
4
5 int addition(int a, int b)
6 {
7     return a + b;
8 }
9
10 int main()
11 {
12     cout << "The result is: " << addition(5, 3) <<
13         ↪ endl;
14
15     return 0;
16 }
```

Example 2 - Factorial

Let us first look at an example of a program written entirely with the function `main()` and then we will modify it to use an additional **function call**.

We will illustrate this with a program to calculate the factorial ($n!$) of an integer number (n) using a for loop to compute:

$$n! = 1 \times 2 \times 3 \dots (n-2) \times (n-1) \times n$$

Example 2 - Factorial

```
1 // Program to calculate factorial of a number
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     int ii, number = 0, factorial = 1;
8
9     // User input must be an integer number between 1 and 10
10    while(number < 1 || number > 10)
11    {
12        cout << "Enter integer number (1-10) = ";
13        cin >> number;
14    }
15
16    // Calculate the factorial with a FOR loop
17    for(ii = 1; ii <= number; ii++)
18    {
19        factorial = factorial * ii;
20    }
21
22    // Output result
23    cout << "Factorial = " << factorial << endl;
24    return 0;
25 }
26
```

Even though the program is very short, the code to calculate the factorial is best placed inside a function since it is likely to be executed many times in the same program.

Example 2 - Factorial

```
1 // Program to calculate factorial of a number with
  ↳ function call
2 #include <iostream>
3 using namespace std;
4
5 // Function declaration (prototype)
6 int factorial(int number);
7
8 int main()
9 {
10     int number = 0, result;
11
12     // User input must be an integer number between
13     ↳ 1 and 10
14     while(number < 1 || number > 10)
15     {
16         cout << "Integer number = ";
17         cin >> number;
18     }
19
20     // Function call and assignment of return value
21     ↳ to result
22     result = factorial(number);
23
24     // Output result
25     cout << "Factorial = " << result << endl;
26     return 0;
27 }
28
29 // An integer, number, is passed from caller
30 ↳ function.
31 int factorial(int number)
32 {
33     int ii, factorial = 1;
34
35     // Calculate the factorial with a FOR loop
36     for(ii = 1; ii <= number; ii++)
37     {
38         factorial = factorial * ii;
39     }
40
41     return factorial; // This value is returned to
42     ↳ caller
```

Example 2 - Factorial Discussion

Three modifications have been made to incorporate a function:

- The **declaration** of the function above `int main()`.
The declaration (A.K.A the prototype) tells the compiler about the function and the type of data it requires and will return on completion.
- The **function call** in the main body of the program determines when to branch to the function and how to return the value of the data computed back to the main program.
- The **definition** of the function `int factorial(int number)` below the main program.
The definition consists of a **header** which specifies how the function will interface with the main program and a **body** which lists the statements to be executed when the function is called.

Remember the Cuteness - A nose so sharp it could fly



Function Header and Body

t

t

t

Function Declaration

t

t

t

Function Call and Execution

t

t

t

Function Arguments

t

t

t

Passing by Value or Reference

t

t

t

Recursion - just to f*** with you

t

t

t

