
CROSS SECTION PROFILE

	LENGTH	ELEV.	SLOPE	ROUGHNESS
1	-396.0	-24.0	.00	1.00
2	-390.0	-23.7		
3	-320.0	-15.6	8.64	1.00
4	-284.0	-14.0	22.50	1.00
5	-282.0	-5.0	.22	1.00
6	-178.0	-4.5	231.11	1.00
7	-40.0	-4.5	FLAT	1.00
8	32.0	3.5	9.00	1.00
9	56.0	8.1	5.22	1.00
10	90.0	11.3	10.49	1.00
11	148.0	14.4	18.77	1.00
			14.84	1.00
12	186.0	17.0	8.08	1.00
13	202.0	19.0	17.26	1.00
14	260.0	22.3	9.75	1.00
15	318.0	28.3	30.38	1.00
16	342.0	29.0	13.62	1.00
17	380.0	31.8	11.47	1.00
18	426.0	35.8	7.56	1.00
19	448.0	38.8		
20	500.0	42.0	16.25	1.00

LAST SLOPE 17.00 LAST ROUGHNESS 1.00

OUTPUT TABLE

INPUT PARAMETERS RUNUP RESULTS

WATER LEVEL ABOVE DATUM (FT.)	DEEP WATER WAVE HEIGHT (FT.)	WAVE PERIOD (SEC.)	BREAKING SLOPE NUMBER	RUNUP SLOPE NUMBER	RUNUP ABOVE WATER LEVEL (FT.)	BREAKER DEPTH (FT.)
8.80	2.70	8.43	8	10	3.59	4.10
8.80 COMPOSITE SLOPE USED	2.70 BUT WAVE MAY	8.88 REFLECT, NOT BREAK	8	10	3.69	4.19
8.80 COMPOSITE SLOPE USED	2.70	9.32	8	10	3.87	4.27
8.80	2.84	8.43	8	10	3.67	4.27
8.80 COMPOSITE SLOPE USED	2.84 BUT WAVE MAY	8.88 REFLECT, NOT BREAK	8	10	3.83	4.36
8.80 COMPOSITE SLOPE USED	2.84 BUT WAVE MAY	9.32 REFLECT, NOT BREAK	8	10	3.94	4.45
8.80	2.98	8.43	8	10	3.75	4.45
8.80	2.98	8.88	8	10	3.92	4.53
8.80 COMPOSITE SLOPE USED	2.98 BUT WAVE MAY	9.32 REFLECT, NOT BREAK	8	10	4.06	4.62