```
PART 5: RUNUP2
        for transect: YK-109
Station locations shifted by: -4.62 feet from their
original location to set the shoreline to
elevation 0 for RUNUP2 input
              _RUNUP2 INPUT CONVERSIONS_
        for transect: YK-109
Incident significant wave height: 7.56 feet
Peak wave period: 13.81 seconds
Mean wave height: 4.73 feet
Local Depth below SWEL: 14.61 feet
Mean wave height deshoaled using Hunt approximation for
celerity assuming constant wave energy flux.
 References: R.G. Dean and R.A. Dalrymple. 2000. Water
             Wave Mechanics for Engineers and Scientists. World
              Scientific Publishing Company, River Edge New Jersy
             USACE (1985), Direct Methods for Calculating Wavelength, CETN-1-17
             US Army Engineer Waterways Experiment Station Coastel Engineering
             Research Center, Vicksburg, MS
             also see Coastal Engineering Manual Part II-3
             for discussion of shoaling coefficient
    Depth, D = 14.61
    Period, T = 11.74
    Waveheight, H = 4.73
Deep water wavelength, L0 (ft)
    L0 = g*T*T/twopi
    L0 = 32.17*11.74*11.74/6.28 = 705.57
Deep water wave celerity, CO (ft/s)
    C0 = L0/T
    C0 = 705.57/11.74 = 60.11
Angular frequency, sigma (rad/s)
    sigma = twopi/T
    sigma = 6.28/11.74 = 0.54
Hunts (1979) approximation for Celerity C1H (ft/s) at Depth D (ft)
    y = sigma.*sigma.*D./g
    y = 0.54*0.54*14.61/32.17 = 0.13
    \texttt{C1H} = \texttt{sqrt}( \texttt{g.*D.}/(\texttt{y+1.}/(\texttt{1} + \texttt{0.6522.*y} + \texttt{0.4622.*y.^2} + \texttt{0.0864.*y.^4} + \texttt{0.0675.*y.^5})) \ )
    C1H = 21.21
Shoaling Coefficient KsH
    KsH = sqrt(C0/C1H)
    KsH = sqrt(60.11/21.21) = 1.68
Deepwater Wave Height HO_H (ft)
    H0_H = H/KsH
    H0_H = 4.73/1.68 = 2.81
Deepwater mean wave height: 2.81 feet
              END RUNUP2 CONVERSIONS
              _RUNUP2 RESULTS
        for transect: YK-109
RUNUP2 SWEL:
9.00
```

9.00 9.00 9.00

```
9.00
9.00
9.00
9.00
9.00
RUNUP2 deepwater mean wave heights:
2.67
2.67
2.67
2.81
2.81
2.81
2.95
2.95
2.95
RUNUP2 mean wave periods:
11.15
11.74
12.33
11.15
11.74
12.33
11.15
11.74
12.33
RUNUP2 runup above SWEL:
0.81
0.83
0.85
0.80
0.83
0.84
0.81
0.82
0.84
RUNUP2 Mean runup height above SWEL: 0.83 feet
RUNUP2 2-percent runup height above SWEL: 1.82 feet
RUNUP2 2-percent runup elevation: 10.82 feet-NAVD88
RUNUP2 Messages:
No Messages
             __END RUNUP2 RESULTS_
               __ACES BEACH RUNUP_
Incident significant wave height: 7.56 feet
Significant wave height is mean wave height divided by 0.626
Reference: D.2.8.1.2.1 Atlanic and Gulf of Mexico G&S Feb. 2007
Deepwater significant wave height: 4.49 feet
Peak wave period: 13.81 seconds
Average beach Slope: 1:39.94 (H:V)
ACES IRREGULAR WAVE RUNUP ON BEACHES
# Reference:
# Leenknecht, David A., Andre Szuwaiski, and Ann Sherlock. 1992.
# "Automated Coastal Engineering System Technical Reference",
# Coastal Engineering Research Center, Department of the Army
```

Waterways Experiments Station, Corps of Eniggneers, 3909 Halls # Ferry Road, Vicksburg, Mississippi 39180-6199.

INPUTS:

Acceleration Due to Gravity, g=32.174 Deepwater Significant Wave height, Hs=4.49 Wave Period, T=13.81 Beach Slope, S=0.025

EQUATIONS:

Runup, R = $Hs * a * Irb^b$ Iribarren, Irb = S/sqrt(Hs/L0)Wavelength, L0 = $g * T^2 / 2 / pi$

COEFFICIENTS:

(Mase, H. 1989, "Random Wave Runup Height on Gentle Slopes," j. Waterway, Port, Coastal and Ocean Engineering Division, ASCE, Vol 115, No. 5, pp 649-661.)

RESULTS:

RUNUP = [4.8, 4.1, 3.8, 3.1, 2.0]

ACES RUNUP CALCULATED USING 'Aces_Beach_Runup.m'

ACES Beach 2-percent runup height above SWEL: 4.12 feet

ACES Beach 2-percent runup elevation: 13.12 feet-NAVD88

ACES BEACH RUNUP is valid

____END ACES BEACH RESULTS_____

PART 5 COMPLETE_____