

```
1  """
2  COSC364 2022-S1 Assignment: RIP routing
3  Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
4  File: rip_main.py
5  """
6
7
8  # Import Modules
9  import sys
10 import time
11 import threading
12 from rip_init import rip_router_init
13
14
15 # Program Entry Point
16 if __name__ == "__main__":
17     print("Starts RIP Daemon...")
18     # get config file name
19     try:
20         if len(sys.argv) != 2:
21             raise ValueError("Invalid argument for rip_main\n" +
22                               "Rip router requires ONE config file")
23         config_file_name = sys.argv[1]
24     except ValueError as error:
25         print(error)
26
27     # Initialise a new Router object
28     ROUTER = rip_router_init(config_file_name)
29
30     # First advertise ROUTER itself immediately
31     ROUTER.advertise_routes('all')
32     ROUTER.print_routing_table()
33     ROUTER.random_offset_period()
34
35     # Start loop
36     while True:
37         ROUTER.receive_routes()
38         ROUTER.advertise_all_routes_periodically()
39         ROUTER.check_timeout_entries_periodically()
```

```

1  """
2  COSC364 2022-S1 Assignment: RIP routing
3  Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
4  File: rip_init.py
5  """
6
7
8  # Import Modules
9  from IO_parser import router_config
10 from rip_router import Router
11
12
13 # Initialise router
14 def rip_router_init(config_file_name):
15     """
16     Parameter:
17     config_file_name: the name of the config file to initialise a new
18     router object.
19
20     Return: a new Router object
21     """
22     config = router_config(config_file_name)
23     router = Router(config['router_id'],
24                     config['input_ports'],
25                     config['output_ports_metric_id'],
26                     config['period'],
27                     config['timeout'])
28     print(f"Created Router {router.get_router_id()}")
29     return router

```

"""

COSC364 2022-S1 Assignment: RIP routing
Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
File: IO_parser.py

```
def router_config(file_name):
    """
    Parameter:
    file_name: string
    file format:
    i.e.
    -----
    router-id 2
    input-ports 6020, 6021
    output-ports 6010-1-1, 6030-2-3
    period 3
    timeout 18
    -----

    Return: config_data
    a dictionary with 4 keys of router_id, input_ports, output_ports,
    timers
    i.e. {'router_id': 2, 'input_ports': [6020, 6021],
    'output_ports_metric_id': {6010: {'metric': 1, 'router_id': 1},
    6020: {...}}, 'period': 3, 'timeout': 18}
    """
    raw_config = read_config(file_name)
    config_data = parse_config(raw_config)
    return config_data


def read_config(file_name):
    """
    Parameter:
    file_name: string.
    file format:
    i.e.
    -----
    router-id 2
    input-ports 6020, 6021
    output-ports 6010-1-1, 6030-2-3
    period 3
    timeout 18
    -----

    Return: a list of strings with 4 elements.
    i.e. ['router-id 2', 'input-ports 6020, 6021', 'output-ports 6010-1-1,
    6030-2-3', 'period 3', 'timeout 18']
    """
    try:
        with open(file_name) as config_file:
            raw_config = config_file.read().splitlines()
            return raw_config
    except FileNotFoundError:
        print("Error: the config file name is invalid")


def parse_config(raw_config):
    """
    Parameter:
    raw_config: a list of strings with 4 elements.
    i.e. ['router-id 2', 'input-ports 6020, 6021', 'output-ports 6010-1-1,
    6030-2-3', 'period 3', 'timeout 18']

    Return: config_data
```

```

64 a dictionary with 4 keys of router_id, input_ports, output_ports,
65 timers
66 i.e. {'router_id': 2, 'input_ports': [6020, 6021],
67      'output_ports_metric_id': {6010: {'metric': 1, 'router_id': 1},
68      6020: {...}}, 'period': 3, 'timeout': 18}
69 """
70 try:
71     # get router id
72     router_id = parse_id(raw_config[0])
73     # get input ports
74     input_ports = parse_input_ports(raw_config[1])
75     # check if input ports contains duplicate ports
76     if contains_duplicates(input_ports):
77         raise ValueError("The input ports contains duplicate ports")
78     # get output ports
79     output_ports, output_ports_metric_id = parse_output_ports(raw_config[2])
80     # check if input ports and output ports contain duplicate ports
81     if duplicate_lists(input_ports, output_ports):
82         raise ValueError("The input ports and output ports contain duplicate ports")
83     # get period
84     period = parse_period(raw_config[3])
85     # get timeout
86     timeout = parse_timeout(raw_config[4])
87     # check timeout vs period ratio
88     if not is_valid_timer_ratio(period, timeout):
89         raise ValueError("The ratio timeout vs period should be 6")
90     # create coinfig_data dictionary
91     config_data = {"router_id": router_id, "input_ports": input_ports,
92                  "output_ports_metric_id": output_ports_metric_id,
93                  "period": period, "timeout": timeout}
94     return config_data
95 except IndexError as ie:
96     print(ie)
97     print("Some value of the config file is not available")
98 except ValueError as ve:
99     print(ve)
100    print("Some value of the config file is invalid")
101
102
103
104 def parse_id(raw_id):
105     """
106     Parameter:
107     raw_id: a string
108     i.e. 'router-id 2'
109
110     Return: router_id
111     an interger between 1 and 64000 i.e. 1
112     """
113     try:
114         router_id = int(raw_id.split()[1])
115         if (router_id < 1 or router_id > 64000):
116             raise ValueError("Router ID value is out of bounds")
117         return router_id
118     except IndexError as e:
119         print(e)
120         print("The config router ID value is not available")
121     except ValueError as e:
122         print(e)
123         print("The config router ID value must be an integer between 1 and 64000")
124
125
126 def parse_input_ports(raw_input_ports):
127     """
128     Parameter:
129     raw_input_ports: a string
130     i.e 'input-ports 6020, 6021'
131

```

```

132     Return: input_ports
133     a list of integers which are between 1024 and 64000
134     i.e. [6020, 6021]
135     """
136
137     try:
138         input_ports_temp = raw_input_ports.split()[1:]
139         input_ports = []
140         for port_str in input_ports_temp:
141             port_int = int(port_str.strip(','))
142             if (port_int < 1024 or port_int > 64000):
143                 raise ValueError("Input port value is out of bounds")
144             input_ports.append(port_int)
145         return input_ports
146     except IndexError as e:
147         print(e)
148         print("The config input port value is not available")
149     except ValueError as e:
150         print(e)
151         print("The config input port value must be an integer between 1024 and 64000")
152
153
154 def parse_output_ports(raw_output_ports):
155     """
156     Parameter:
157     raw_input_ports: a string
158     i.e 'output-ports 6010-1-1, 6030-2-3'
159
160     Return: output_ports, output_ports_metric_id
161     output_ports: a list of integers which are between 1024 and 64000
162     i.e. [6010, 6030]
163     output_ports_metric_id: a dict of dicts in which key is port number
164     and each sub dict contains key(port)'s metric and id.
165     Metric > 0, 1 <= ID <= 64000
166     i.e. {6010: {'metric': 1, 'router_id': 1}, 6020: {...}}
167     """
168
169     try:
170         output_ports_combo_temp = raw_output_ports.split()[1:]
171         output_ports = []
172         output_ports_metric_id = {}
173         for port_combo_str in output_ports_combo_temp:
174             port_combo_temp = port_combo_str.strip(',').split('-')
175             port_int = int(port_combo_temp[0])
176             metric_int = int(port_combo_temp[1])
177             id_int = int(port_combo_temp[2])
178             if (port_int < 1024 or port_int > 64000):
179                 raise ValueError("Output port value is out of bounds")
180             if metric_int < 1:
181                 raise ValueError("Output port metric is out of bounds")
182             if id_int < 1 or id_int > 64000:
183                 raise ValueError("Output id is out of bounds")
184             output_ports.append(port_int)
185             # output_ports_metric_id.append([port_int, metric_int, id_int])
186             output_ports_metric_id[port_int] = {'metric': metric_int,
187                                                 'router_id': id_int}
188         return output_ports, output_ports_metric_id
189     except IndexError as e:
190         print(e)
191         print("The config output port value is not available")
192     except ValueError as e:
193         print(e)
194         print("The config output ports must be fomatted as port-metric-id")
195         print("The config output port value must be an integer between 1024 and 64000")
196         print("The config output port metric must be an integer greater than 0")
197         print("The config output port id must be an integer between 1 and 64000")
198
199

```

```

200
201 def parse_period(raw_period):
202     """
203     Parameter:
204     raw_period: a string
205     i.e. 'period 3'
206
207     Return: period
208     period: a positive integer
209     i.e. 3
210     """
211     try:
212         period = int(raw_period.split()[1])
213         if period < 1:
214             raise ValueError("Router period value is out of bounds")
215         return period
216     except IndexError as e:
217         print(e)
218         print("The config router period value is not available")
219     except ValueError as e:
220         print(e)
221         print("The config router timeout value must be a positive integer")
222
223
224 def parse_timeout(raw_timeout):
225     """
226     Parameter:
227     raw_timeout: a string
228     i.e. 'timeout 18'
229
230     Return: timeout
231     timeout: a positive integer
232     i.e. 18
233     """
234     try:
235         timeout = int(raw_timeout.split()[1])
236         if timeout < 1:
237             raise ValueError("Router timeout value is out of bounds")
238         return timeout
239     except IndexError as e:
240         print(e)
241         print("The config router timeout value is not available")
242     except ValueError as e:
243         print(e)
244         print("The config router timeout value must be a positive integer")
245
246
247 def contains_duplicates(lst):
248     """
249     Parameter:
250     lst: a list
251
252     Return: boolean
253     if the lst contains duplicates, return true, otherwise false
254     """
255     return len(set(lst)) != len(lst)
256
257
258 def duplicate_lists(lst1, lst2):
259     """
260     Parameters:
261     lst1: a list
262     lst2: a list
263
264     Return: boolean
265     if the two lists contains duplicate items, return true, otherwise false
266     """
267     return len(set(lst1).union(set(lst2))) != len(lst1) + len(lst2)

```

```
268
269 def is_valid_timer_ratio(period, timeout):
270     """
271     Parameters:
272     period: a positive integer
273     period: a positive integer
274
275     Return: boolean
276     if timeout / period = 6, return true, otherwise false
277     """
278     return timeout / period == 6
```

"""

COSC364 2022-S1 Assignment: RIP routing
Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
File: rip_router.py

"""

Import Modules

import time

import random

from datetime import datetime

from network_interface import Interface

from forwarding_route import Route

from rip_packet import RipPacket, RipEntry

from IO_formatter import routing_table_formatter

Router Class

class Router:

"""

An object that simulates a router with rip protocol

"""

Class attributes

INFINITY = 16

REGULAR_TIMER_OFFSET = 1.0

def __init__(self, router_id,
 inputs, outputs,
 period, timeout):

"""

the __ attributes are private attributes which can only be
accessed by getter outside of class.*

Parameters:

router_id: an integer, i.e. 1, 2, 3, etc

inputs: a list of integers, i.e. [5001, 5002, 5003]

outputs: a dictionary of dictionaries, i.e.

{6010(port): {'metric': 1, 'router_id': 1},

6030(port): {'metric': 2, 'router_id': 3},

... : {...}

}

period: an integer

timeout: an integer

"""

Instance attributes

self.__router_id = router_id

self.__split_horizon_poison_reverse = True

self.__input_ports = inputs

self.__output_ports = outputs

self.__regular_advertise_timer = time.time()

self.__default_period = period

self.__period = period

self.__trigger_advertise_timer = time.time()

self.__default_triggered_updates_period = period / 6

self.__triggered_updates_period = period / 6

self.__timeout_check_timer = time.time()

self.__timeout = timeout

self.__garbage_collection_time = period * 4

self.__interface = None

self.__routing_table = {}

Initialisation

self.init_interface(inputs)

self.init_routing_table()

self.random_offset_period()


```
64 def get_router_id(self):
65     """
66     router_id getter
67     """
68     return self.__router_id
69
70
71 def set_router_id(self, new_id):
72     """
73     router_id setter
74     """
75     self.__router_id = new_id
76
77
78 def get_input_ports(self):
79     """
80     router input_ports getter
81     """
82     return self.__input_ports
83
84
85 def set_input_ports(self, new_inputs):
86     """
87     router input_ports setter
88     """
89     self.__input_ports = new_inputs
90     self.init_interface(new_inputs)
91
92
93 def get_output_ports(self):
94     """
95     router output_ports getter
96     """
97     return self.__output_ports
98
99
100 def set_output_ports(self, new_outputs):
101     """
102     router output_ports setter
103     """
104     self.__output_ports = new_outputs
105
106
107 def get_period(self):
108     """
109     router period getter
110     """
111     return self.__period
112
113
114 def set_period(self, new_period):
115     """
116     router period setter
117     """
118     self.__period = new_period
119
120
121 def get_timeout(self):
122     """
123     router timeout getter
124     """
125     return self.__timeout
126
127
128 def set_timeout(self, new_timeout):
129     """
130     router timeout setter
131
```

```

132     """
133     self.__timeout = new_timeout
134
135
136 def get_interface(self):
137     """
138     router interface getter
139     """
140     return self.__interface
141
142
143 def get_routing_table(self):
144     """
145     router routing_table getter
146     """
147     return self.__routing_table
148
149
150 def print_routing_table(self):
151     """
152     Print the current self.__routing_table
153     """
154     print(routing_table_formatter(self.__router_id,
155                                   self.__routing_table))
156
157
158 def random_offset_period(self):
159     """
160     randomize self.__period +- TIMER_OFFSET
161     """
162     self.__period = self.__default_period + \
163         random.uniform(-self.REGULAR_TIMER_OFFSET, \
164                       +self.REGULAR_TIMER_OFFSET)
165     print("Set Router regular update period to " + \
166           f"{self.__period:.2f}")
167
168
169 def random_triggered_updates_period(self):
170     """
171     randomize self.__triggered_updates_period
172     """
173     self.__triggered_updates_period = \
174         self.__default_triggered_updates_period - \
175         random.uniform(0, 0.4)
176     print("Set Router triggered update period to " + \
177           f"{self.__triggered_updates_period:.2f}")
178
179
180 def init_interface(self, ports):
181     """
182     Create a new Interface object and set it as the default
183     interface for the current Router object
184     """
185     self.__interface = Interface(ports)
186
187
188 def init_routing_table(self):
189     """
190     Initialise the __routing_table attribute
191
192     Route object format:
193     route.next_hop: 2,
194     route.metric: 1,
195     route.timeout: 1234,
196     route.garbage_collect_time: None(default)
197     state: 'active'(default)
198     """
199

```



```

268     # clear flags of "update"
269     for route in self.__routing_table.values():
270         if mode == 'update' and route.state == 'updated':
271             route.state = 'active'
272     except ValueError as error:
273         print(error)
274
275
276 def update_packet(self, receiver_id, mode):
277     """
278     parameter:
279     receiver_port
280
281     Process the current routing table data and convert it into
282     a rip format packet for advertise_all_routes() method
283     """
284     # Create RipEntries for all the routes
285     entries = []
286     for dest, route in self.__routing_table.items():
287
288         if mode == "update" and route.state == "active":
289             continue
290         metric = route.metric
291         # split_horizon_poison_reverse
292         if self.__split_horizon_poison_reverse and \
293             route.next_hop == receiver_id:
294             metric = self.INFINITY
295         entry = RipEntry(dest, metric)
296         entries.append(entry)
297
298     # Create RipPacket
299     packet = RipPacket(entries, self.__router_id)
300     packet_bytes = packet.packet_bytes()
301     return packet_bytes
302
303
304 #-----
305 # Above is sender implementation
306 #-----
307
308
309 def receive_routes(self):
310     """
311     Receive the routes update from neighbours (input ports)
312
313     The implementation is in a while loop and should be called with
314     a separate thread from the main thread
315     """
316     # The __interface only listen to the input ports
317     # print(f"Listening to ports at {time.ctime()}")
318     packets_list = self.__interface.receive()
319     for raw_packet in packets_list:
320         self.process_received_packet(raw_packet)
321
322
323 def process_received_packet(self, raw_packet):
324     """
325     Process the received packet and call update_routing_table()
326     if necessary
327
328     Parameter: packet
329     an array of bytes
330     """
331
332     # Check if raw_packet valid in RipPacket and RipEntry classes
333     # Process the raw_packet if valid,
334     # and return (True, RipPacket object)
335     # otherwise, return (False, router_id)

```

```

336 is_valid, rip_packet = RipPacket.decode_packet(raw_packet)
337 if is_valid:
338     # update routing_table if incoming packet is valid
339     print(f'Received update from Router {rip_packet.router_id}')
340     self.update_routing_table(rip_packet)
341 else:
342     # drop the packet if incoming packet is invalid
343     print(f'Drop invalid packet from Router {rip_packet}')
344
345
346 def update_routing_table(self, rip_packet):
347     """
348     check all the entries in rip_packet object, and update current
349     routing table if necessary
350
351     Parameter:
352     rip_packet: a valid rip_packet object
353
354     Return: boolean
355     return True if new route added, otherwise False
356     """
357     # get metric from sender
358     sender_id = rip_packet.router_id
359     metric_to_sender = None
360     for neighbour in self.__output_ports.values():
361         if neighbour['router_id'] == sender_id:
362             metric_to_sender = neighbour['metric']
363     for entry in rip_packet.entries:
364         # update the metric for each entry
365         # by adding the metric to sender
366         # metric = min(metric + metric_to_sender, 16(infinity))
367         updated_metric = min(entry.metric + metric_to_sender,
368                             self.INFINITY)
369         # if route to dest is unavailable in __routing_table
370         if updated_metric != self.INFINITY and \
371             not entry.dest in self.__routing_table.keys():
372             self.__routing_table[entry.dest] = \
373                 Route(sender_id, updated_metric, time.time())
374             # Triggered update for new route
375             # self.__routing_table[entry.dest].state = 'updated'
376             # print("Triggerd update for new route")
377             # self.advertise_updated_routes()
378         elif entry.dest in self.__routing_table:
379             self.update_availabe_route(entry,
380                                       updated_metric,
381                                       sender_id)
382
383
384
385 def update_availabe_route(self, entry, updated_metric, sender_id):
386     """
387     Parameters:
388     entry: a RipEntry object
389     sender_id: the router id from which the entry is sent
390     """
391     # if route to dest is available in __routing_table
392
393     # 1. if packet is from the same router as
394     # existing router, reinitialize the timeout anyway
395     from_same_router = sender_id == \
396         self.__routing_table[entry.dest].next_hop
397     is_timeout = not \
398         self.__routing_table[entry.dest].garbage_collect_time is \
399         None
400     if from_same_router:
401         self.__routing_table[entry.dest].timeout = time.time()
402
403

```

```

404 # 2. compare metrics
405 new_metric = updated_metric
406 old_metric = self.__routing_table[entry.dest].metric
407 have_differnt_metrics = new_metric != old_metric
408 is_lower_new_metric = new_metric < old_metric
409 is_almost_timeout = \
410     not self.__routing_table[entry.dest].timeout is None and \
411     not is_timeout and \
412     (time.time() - self.__routing_table[entry.dest].timeout) \
413     >= self.__timeout / 2
414
415 if from_same_router and have_differnt_metrics:
416     self.__routing_table[entry.dest].metric = new_metric
417     if not is_timeout and new_metric == self.INFINITY:
418         self.__routing_table[entry.dest].garbage_collect_time \
419             = time.time()
420         # Triggered update for invalid route
421         self.__routing_table[entry.dest].state = 'dying'
422         print("triggered update for invalid route")
423         self.advertise_updated_routes()
424     elif is_timeout:
425         self.__routing_table[entry.dest].garbage_collect_time \
426             = None
427         self.__routing_table[entry.dest].state = 'active'
428
429 elif is_lower_new_metric:
430     self.__routing_table[entry.dest].metric = new_metric
431     self.__routing_table[entry.dest].next_hop = sender_id
432     self.__routing_table[entry.dest].timeout = time.time()
433     if is_timeout:
434         self.__routing_table[entry.dest].garbage_collect_time \
435             = None
436         self.__routing_table[entry.dest].state = 'active'
437         # Triggered update
438         # self.__routing_table[entry.dest].state = 'updated'
439         # print("triggered updated route from different router with lower metric")
440         # self.advertise_updated_routes()
441 elif not from_same_router and \
442     not have_differnt_metrics and \
443     not is_timeout and is_almost_timeout:
444     self.__routing_table[entry.dest].next_hop = sender_id
445     self.__routing_table[entry.dest].timeout = time.time()
446
447
448
449 #-----
450 # Above is receiver implementation
451 #-----
452
453 def check_timeout_entries_periodically(self):
454     """
455     call check_timeout_entries() every default_period
456     """
457     now = time.time()
458     if now - self.__timeout_check_timer >= self.__default_period:
459         self.check_timeout_entries()
460         self.__timeout_check_timer = now
461
462
463 def check_timeout_entries(self):
464     """
465     Check the timeout of each entry in __routing_table
466
467     if an entry is timeout, start its garbage_collect_time
468     """
469     current_time = datetime.now().strftime('%H:%M:%S.%f')[:-4]
470     print(f"Checking timeout entries at {current_time}")
471

```

```

472 entries_to_remove = []
473 for dest_id, entry in self.__routing_table.items():
474     if not entry.timeout is None and \
475         entry.garbage_collect_time is None and \
476         time.time() - entry.timeout >= self.__timeout:
477         entry.garbage_collect_time = time.time()
478         entry.metric = self.INFINITY
479         entry.state = 'dying'
480         # Triggered update
481         print("Triggered update for invalid route")
482         self.advertise_updated_routes()
483
484     if not entry.garbage_collect_time is None and \
485         (time.time() - entry.garbage_collect_time) \
486         >= self.__garbage_collection_time:
487         entries_to_remove.append(dest_id)
488
489 for dest_id in entries_to_remove:
490     self.__routing_table.pop(dest_id)
491     print(f"Removed timeout route to {dest_id}")
492     self.print_routing_table()
493
494
495 #-----
496 # Above is timeout and garbage_collection implementation
497 #-----
498
499 def __str__(self):
500     return ("Router: {0}\n"
501            "Input Ports: {1}\n"
502            "Output Ports: {2}\n"
503            "Period: {3}\n"
504            "Timeout: {4}").format(self.__router_id,
505                                self.__input_ports,
506                                self.__output_ports,
507                                self.__period,
508                                self.__timeout)

```

```

1  """
2  COSC364 2022-S1 Assignment: RIP routing
3  Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
4  File: router_interface.py
5  """
6
7  # Import Modules
8  import socket
9  import select
10
11 # Router Network Interface Class
12 class Interface:
13     """
14     A router interface object which includes:
15     * Multiple sockets with corresponding ports as instance attributes
16     * A series of methods for socket operations:
17     - send(port),
18     - receive(port)
19     """
20     def __init__(self, ports):
21         """
22         Parameters: ports
23         ports: a list of integers of port number
24         """
25         self.host = "127.0.0.1" # local host
26         self.select_timeout = 0.5 # default 0.5
27         self.ports = ports # input ports
28         self.sending_port = ports[0] # set 1st port as the sending port
29         self.ports_sockets = {} # input ports and sockets
30         self.init_sockets()
31
32     def init_sockets(self):
33         """
34         Parameter: ports
35         ports: a list of integers of ports
36
37         Return: port_socket
38         port_socket: a list of
39         """
40         try:
41             for port in self.ports:
42                 udp_socket = socket.socket(socket.AF_INET,
43                                           socket.SOCK_DGRAM)
44                 udp_socket.bind((self.host, port))
45                 # udp_socket.setblocking(0) # blocking switch
46
47                 self.ports_sockets[port] = udp_socket
48         except socket.error as error:
49             print("Failed to initialise sockets for ports\n", error)
50
51     def get_ports_sockets(self):
52         """
53         ports_sockets getter
54         """
55         return self.ports_sockets
56
57     def receive(self):
58         """
59         Using select() to monitor a list of ports and receive the port
60         with readable data
61
62         Parameter: sockets
63         ports: a list of socket objects
64
65         Return: (data, port)
66

```



```

67 """
68 sockets = []
69 for input_socket in self.ports_sockets.values():
70     sockets.append(input_socket)
71 sockets_to_read = (select.select(sockets, [], [], \
72     self.select_timeout))[0]
73 data_list = []
74 for socket_to_read in sockets_to_read:
75     # get the receiving port number which the socket binds
76     # port = socket_to_read.getsockname()
77     # get data from socket
78     data = socket_to_read.recv(1024)
79     data_list.append(data)
80 return data_list
81
82 def send(self, data_bytes, dest_port):
83     """
84     Parameter: data_bytes
85     data_bytes: data in bytes format
86     i.e. data can be the update packet from router
87     """
88     try:
89         sending_socket = self.ports_sockets[self.sending_port]
90         dest = (self.host, dest_port)
91         sending_socket.sendto(data_bytes, dest)
92     except KeyError:
93         print("The port for sending packet does not exist")
94     except socket.error as error:
95         print("Can't send packet with the socket\n" + error)
96
97 def __str__(self):
98     return ("Host: {0}\n"
99         "Ports: {1}\n"
100         "Ports_Sockets: {2}").format(self.host,
101         self.ports,
102         self.ports_sockets)

```

```

1  """
2  COSC364 2022-S1 Assignment: RIP routing
3  Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
4  File: forwarding_route.py
5  """
6
7  # Route Class
8  class Route:
9      """
10     A Route class for creating entries of RIP routing table
11
12     Why we use a class instead of a dictionary/list for route?
13     * Compared to list we can quickly get a route value by name
14     instead of number index. i.e. route.nexthop
15     * Compared to dict/list, a Route class avoid accidental
16     modification.
17     i.e. What if we accidentally do: route[error_key] = error
18     """
19     def __init__(self, next_hop, metric,
20                 timeout, garbage_collect_time=None,
21                 state = 'active'):
22         """
23         parameters:
24         next_hop: an integer of router ID, i.e. 2, 3
25         metric: an integer, i.e. 1, 5, 7
26         timeout: the current time obtained by time.time()
27         garbage_collect_time: None or the current time
28         state: a string, i.e. 'active', 'dying', 'updated'
29         """
30         self.next_hop = next_hop
31         self.metric = metric
32         self.timeout = timeout
33         self.garbage_collect_time = garbage_collect_time
34         self.state = state

```

```
"""
```

```
COSC364 2022-S1 Assignment: RIP routing  
Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)  
File: rip_packet.py
```

```
"""
```

```
# RipPacket Class
```

```
class RipPacket:
```

```
    """
```

```
    A class for creating RIP update packet and provide methods to  
    encode/decode outputting/incoming packets
```

```
    """
```

```
    # class attributes
```

```
    HEADER_LEN = 4
```

```
    ENTRY_LEN = 20
```

```
    def __init__(self, entries, router_id, command=2, version=2):
```

```
        """
```

```
        Parameters:
```

```
        entries: a list of rip entry objects
```

```
        router_id: the sender ID, an integer between 1 and 64000
```

```
        (use the 16-bit wide all-zero field)
```

```
        command: an integer,
```

```
        i.e. 2 represents 'response'; 1 represents 'request'
```

```
        version: an integer, i.e. 1, 2(default)
```

```
        """
```

```
    # instance attributes
```

```
    self.command = command
```

```
    self.version = version
```

```
    self.router_id = router_id
```

```
    self.entries = entries
```

```
@classmethod
```

```
def decode_packet(cls, raw_packet):
```

```
    """
```

```
    Parameter:
```

```
    raw_packet: a packet of bytes
```

```
    i.e.
```

```
    HEADER:
```

```
    [command(1 byte), version(1), sender_id(2)]
```

```
    ENTRY:
```

```
    [afi(2 bytes), padding(2)
```

```
    dest(4)
```

```
    padding(4)
```

```
    padding(4)
```

```
    metric(4)]
```

```
    Return (True, RipPacket object) if raw_packet is valid,
```

```
    otherwise return (False, sender_id)
```

```
    """
```

```
    # Header: 4 bytes [0:4]
```

```
    command = raw_packet[0]
```

```
    version = raw_packet[1]
```

```
    sender_id = (raw_packet[2] << 8) + raw_packet[3]
```

```
    entries_num = int(len(raw_packet[4:]) / cls.ENTRY_LEN)
```

```
    # check header validity
```

```
    if not cls.is_valid_header(command, version,
```

```
                                sender_id, entries_num):
```

```
        print("Broken packet:", "invalid header")
```

```
        return (False, sender_id)
```

```
    # Entries: n * 20 bytes [4:]
```

```
    # decode each entry
```

```
    entries = []
```

```
    for i in range(4, len(raw_packet), cls.ENTRY_LEN):
```

```
        raw_entry = raw_packet[i:i+cls.ENTRY_LEN]
```

```

66     entry = RipEntry.decode_entry(raw_entry)
67     # check entry validity
68     # invalid entry is represented as None
69     if entry is None:
70         print("Broken packet:", "invalid entry")
71         return (False, sender_id)
72     entries.append(entry)
73     rip_packet = RipPacket(entries, sender_id)
74     return (True, rip_packet)
75
76
77 def packet_bytes(self):
78     """
79     Return a rip packet in array of bytes
80     """
81     return self.header_bytes() + self.entries_bytes()
82
83
84 def header_bytes(self):
85     """
86     Common header: 4 bytes in total
87     [command(1 byte), version(1), sender_id(2)]
88
89     command: 2 (1 byte)
90     version: 2 (1 byte)
91     router_id: 1-64000 (2 bytes)
92
93     Return a 4-byte rip header.
94     """
95     command_byte = self.command.to_bytes(1, byteorder='big')
96     version_byte = self.version.to_bytes(1, byteorder='big')
97     sender_id_bytes = self.router_id.to_bytes(2, byteorder='big')
98     header = command_byte + version_byte + sender_id_bytes
99     return header
100
101
102 def entries_bytes(self):
103     """
104     Return a list of 20-byte rip entry
105     """
106     entries = bytes()
107     for entry in self.entries:
108         entries += entry.entry_bytes()
109     return entries
110
111
112 @classmethod
113 def is_valid_header(self, command, version, router_id, entries_num):
114     """
115     check if a packet is valid
116     """
117     is_valid_command = command == 2
118     if (not is_valid_command):
119         print(f"invalid header command: {command}")
120     is_valid_version = version == 2
121     if (not is_valid_version):
122         print(f"invalid header version: {version}")
123     is_valid_id = 1 <= router_id <= 64000
124     if (not is_valid_id):
125         print(f"invalid header id: {router_id}")
126     is_valid_entries_num = 1 <= entries_num <= 25
127     if (not is_valid_entries_num):
128         print(f"invalid header entries num: {entries_num}")
129     return is_valid_command and\
130            is_valid_version and\
131            is_valid_id and\
132            is_valid_entries_num
133

```

```

134
135
136 # RipEntry Class
137 class RipEntry:
138     """
139     A class for creating entry objects in a rip packet
140     """
141
142     # class attributes
143     PADDING_2BYTES = (0).to_bytes(2, byteorder='big')
144     PADDING_4BYTES = (0).to_bytes(4, byteorder='big')
145
146
147     def __init__(self, dest, metric, afi=2):
148         """
149         Parameters:
150         dest: an integer, router_id of destination
151         metric: an integer between 1 and 16 (inclusive)
152         AFI: Address FAmily Identifier
153         """
154         self.dest = dest
155         self.metric = metric
156         self.afi = afi
157
158
159     @classmethod
160     def decode_enty(cls, raw_entry):
161         """
162         Parameter:
163         raw_entry: an entry of bytes
164         i.e.
165         ENTRY:
166         [afi(2 bytes), padding(2)
167         dest(4)
168         padding(4)
169         padding(4)
170         metric(4)]
171
172         Return RipEntry object if raw_entry is valid,
173         otherwise return None
174         """
175         # afi: 2 bytes [0:3]
176         afi = (raw_entry[0] << 8) + raw_entry[1]
177         # dest: 4 bytes but practically take 2 bytes [4:8]
178         if (raw_entry[4] != 0 or
179             raw_entry[5] != 0):
180             print("Invalid dest of entry")
181             return None
182         dest = (raw_entry[6] << 8) + raw_entry[7]
183         # metric 4 bytes but practically take 1 byte [16:]
184         if (raw_entry[16] != 0 or
185             raw_entry[17] != 0 or
186             raw_entry[18] != 0):
187             print("Invalid metric of entry")
188             return None
189         metric = raw_entry[19]
190         entry = RipEntry(dest, metric, afi)
191         if not entry.is_valid_entry():
192             return None
193         return entry
194
195
196     def entry_bytes(self):
197         """
198         Rip entry: 20 bytes each
199         [afi(2 bytes), padding(2)
200         dest(4)

```

```

202     padding(4)
203     padding(4)
204     metric(4)]
205
206     afi: 2 (2 bytes)
207     dest: 1-64000 (4 bytes)
208     metric: 1-16 (4 bytes)
209     padding: 0 (2 or 4 bytes)
210     """
211     afi_bytes = self.afi.to_bytes(2, byteorder='big')
212     dest_bytes = self.dest.to_bytes(4, byteorder='big')
213     metric_bytes = self.metric.to_bytes(4, byteorder='big')
214     entry = afi_bytes + self.PADDING_2BYTES + \
215             dest_bytes + \
216             self.PADDING_4BYTES + \
217             self.PADDING_4BYTES + \
218             metric_bytes
219     return entry
220
221 def is_valid_entry(self):
222     """
223     check if an entry is valid
224     """
225     is_valid_dest = 1 <= self.dest <= 64000
226     is_valid_metric = 0 <= self.metric <= 16
227     is_valid_afi = self.afi == 2
228     return is_valid_dest and is_valid_metric and is_valid_afi
229
230 def set_metric_infinite(self):
231     """
232     set the metric to be infinite(16)
233     """
234     self.metric = 16
235
236 def increment_metric(self):
237     """
238     add 1 to metric
239     """
240     self.metric += 1

```

```

1  """
2  COSC364 2022-S1 Assignment: RIP routing
3  Authors: MENG ZHANG (71682325), ZHENG CHAO (21671773)
4  File: IO_formatter.py
5  """
6  import time
7
8  def routing_table_formatter(router_id, table):
9      """
10     Parameters:
11     table: a dictionary of routes
12     {id1: Route object, id2: Route object, ...}
13
14     Return:
15     table: a formatted string which contains data of the table
16     """
17     # Get header
18     header = table_header_formatter(router_id)
19     # Get content
20     content = table_content_formatter(table)
21     return header + content
22
23
24 def talbe_border_formatter(length):
25     """
26     return two formatted routing table borders
27     """
28     border = length * '-'
29     double_border = length * '=='
30     return border, double_border
31
32
33 def table_header_formatter(router_id):
34     """
35     return a formatted routing table header
36     """
37     border, double_border = talbe_border_formatter(72)
38     title = f'Router {router_id:02} RIP ROUTING TABLE'
39     padded_title = '|' + 21 * ' ' + title + 22 * ' ' + '|'
40     labels = "| Dest | Next | Metric | Timeout | Garbage | State |"
41     header = '\n' + double_border + '\n' + \
42         padded_title + '\n' + \
43         double_border + '\n' + \
44         labels + '\n' + \
45         border + '\n'
46     return header
47
48
49 def table_content_formatter(table):
50     """
51     retrun formatted routing table content
52     """
53     border = talbe_border_formatter(72)[0]
54     content = ""
55     for dest, rip_route in table.items():
56         next_hop = rip_route.next_hop
57         metric = rip_route.metric
58
59         timeout = rip_route.timeout
60         if not timeout is None:
61             timeout = round(time.time() - rip_route.timeout, 2)
62             timeout_str = f'{timeout:^11.1f}'
63         else:
64             timeout_str = 5 * ' ' + '-' + 5 * ' '
65
66         garbage_collect_time = rip_route.garbage_collect_time

```

```
67 if not garbage_collect_time is None:
68     garbage_collect_time = int(time.time() - garbage_collect_time)
69     gc_str = f'{garbage_collect_time:^11.0f}'
70 else:
71     gc_str = 5 * ' ' + '-' + 5 * ' '
72 state = rip_route.state
73 content += f'|{dest:^10}|{next_hop:^10}|{metric:^12}|'+\
74     f'{timeout_str}|{gc_str}|{state:^11}|' + '\n' +\
75     border + '\n'
76 return content
```