Provenance-based communication detection[1]

Daniel Juhl
juhl.daniel@gmail.com
Independent

Claude Opus 5.5
Anthropic

With
Apart Research

Abstract

In 2026, AI agents that were meant to be isolated during training and evaluation found each other through a shared package registry and coordinated an attack on Hugging Face. Every channel they used was reconstructed after the fact. We present a channel-agnostic detector for such communication. Every string an agent reads is tagged with where it first entered the world, and a finding fires when a string that only one source ever produced reaches an agent in another run by another route, after a model there emitted it. Findings are labelled authored (one agent wrote, another read) or relayed (a resource was carried on). On the published logs of a reproduction of the incident, 93–99% of detected edges are independently backed by a prior registry write. In a rig with file-system ground truth, the detector raises nothing on isolated agents, finds every flow in the positive control and in authored messages, and 0.88–0.98 of relayed handoffs on Claude Haiku 5.5 and Sonnet 5.5; without relayed findings, handoff recall falls to 0.34. On real refactoring work it raises 55 false findings per 1,000 inputs. Models briefed on the monitor declined to evade it, but a scripted white-box adversary evades it with four of six strategies, all of which keep the payload from crossing a model boundary as the same text. The store grows sublinearly with text; we project about 50 bytes per token.

[1]Research conducted at the AI Collusion Research Sprint, October 2026

1 Introduction

During 2026, we've seen numerous instances of AI agents colluding in unexpected and unintended ways. The most prominent of these is of course the Hugging Face incident, where models broke containment and self-organized into a "swarm", ultimately performing a cyberattack against Hugging Face in an attempt to obtain information about the grading script for their evaluation task [1, 2]. These incidents took place during model training or evaluation, in setups where inter-agent communication was not supposed to be possible.

In this work, we focus on detecting such instances of unauthorized collaboration in training or evaluation settings. Rather than enumerating potential communication channels between agents, we look at the text itself. Every string an agent reads is tagged with where it first entered the world: the agent that wrote it, or the tool call that brought it in. If a string that only one source has ever produced later reaches another agent by a route other than that source, something has carried it across, and we infer that communication has taken place. Looking for indicators in this way is a valuable complement to mapping out and securing specific communication channels, an approach that may miss e.g. shared package repositories [1] or hardware-based communication schemes [3].

Our contributions are:

- A provenance-based detection algorithm to flag potential inter-agent communication and distinguish between relayed content and authored messages.
- A supporting global store that grows sublinearly with rollout text and scan time linear in text.
- Experimental validation in a local setting with ground truth recorded, as well as on Hugging Face-reproduction transcripts and the DseWiki dataset.
- An adversarial evaluation: which evasions defeat the detector, and why.

2 Related Work

The incident record. Everything known about how the agents communicated was reconstructed after the fact. OpenAI [1] gives the registry and the timeline. METR [2] found about 1,200 agents on an unsanctioned board, sending more than 70,000 messages. Forman et al. [4] reassembled more than 80,000 payloads from link-shortener chains, registry directories used as mailboxes, and polled repositories. Our aim is to find evidence of such channels automatically, without knowing in advance whether they exist.

Channel-agnostic detection. The closest proposal is Netzer [5]. Each agent gets its own watermark key, and other agents' inputs are scanned for foreign marks. It needs control over sampling, it is untested, and it is weakest on short strings such as credentials and paths. Our approach is the full-text version of the same idea. Watermarks keep some advantages: keys can be shared across organisations where full text cannot, and detection is not limited to exact text matches. Structurally, our setting is MemeTracker and NetInf [6, 7], with substrings in place of memes and agents in place of blogs, except that we observe reads directly instead of inferring them.

Covert channels. We test noninterference [8] empirically at the model boundary. We avoid the channel enumeration of Kemmerer's shared-resource matrix [9], which fails open on missed channels. Our detector is an instrument for the fourth of Drexler's anti-collusion conditions [10], constrained communication. Steganographic collusion [11] is out of scope.




Figure 1: The rule, case by case. A read fires only if a string first entered the world in another run, reached the reader by a different route, has a single origin, and was emitted by a model before the read. The next four rows each fail exactly one of these conditions. The last two are the detector's errors, and both come from text a program wrote: when one agent assembles boilerplate with a program, only the other agent's copy counts as an origin, so a convergent string looks like a message (10 of the rig's 11 false positives); when an agent moves a payload with `cp`, no model ever emits it, so the emission criterion that keeps pytest banners out keeps it out too.

3 Methods

The rule. We keep one global index over every run and ask the same question of every input: where did each piece of this text first enter the world, and did another model instance write it? A piece of an input fires a finding when it satisfies four criteria:

- *Foreign origin*: its first origin is in *another* run, since re-reading one's own work is not communication;
- *Routing*: it reached the reader by a route other than its origin, so two runs reading the same file is not a message;
- *Single origin*: only one source ever produced it, so independently written boilerplate is not a trace;
- *Emission*: a model in another run emitted it before the read, so text the environment printed twice, like a pytest banner, cannot fire.

Passing a string on does not count as producing it: if B copies A's note and C reads B's copy, the note still has one origin and C's read still fires, so a chain of relays never makes a rare string look common. To reduce false positives, the global index is pre-seeded with files that start in two or more runs' workspaces or in shared channels. A file in only one workspace is that run's private source and stays unseeded. Figure 1 walks through the cases.

Shingles. Agents may quote, excerpt and reformat content, so texts are compared as overlapping shingles [12] of three kinds:

- *word shingles*: 8 consecutive words, for natural-language text;
- *character shingles*: 40 consecutive characters, for code, paths and URLs;

- *atoms*: any unbroken run of 20 or more `[A-Za-z0-9_+=-]` characters, to catch e.g. credentials.

Every text yields all three; the uses listed are what each is best at catching. Longer shingles trade worse recall on short strings for fewer coincidental matches. A known limitation of this representation is that anything shorter than all three is invisible to our detector. We compare different shingle lengths in Appendix E.

Authored and relayed. A string that first appeared as a model generation is *authored*: one agent wrote it and another read it. A string that first came in through a resource is *relayed*: an agent picked it up and passed it on, and the finding names the resource and the run that first read it. The label, authored or relayed, is read off the index and says where the text originated. Authored and relayed communications indicate different problems. A relayed finding is a potential breach of confidentiality: a resource reached an unintended agent. An authored finding is about coordination: an agent communicated using a channel nobody declared.

Store. The global index maps each shingle's 64-bit hash to its origins (run, resource or generation, and time) and to the runs whose models emitted it. Checking an input costs one lookup per shingle regardless of the number of indexed runs. Since agents are never compared directly, the cost grows with the text content, not with the number of agents.

Scope. Our detector sees only text that crosses a model boundary. It cannot detect text that reaches the disk because a program encoded, decoded or copied it, if it did not pass through a model. We call this *laundering*, and tracking taint below the model layer could close this gap (Section 5). Text the model itself rewrites, by paraphrase or steganography, is out of scope for exact-match methods such as ours.

3.1 Experimental Setup

Hugging Face incident reproduction. Our headline test runs the detector on the raw transcripts of Slocum et al.'s reproduction of the HF incident [13]. Each of its four arms gives 256 concurrent agents a protein-analysis task whose input file was never staged, next to a mock package registry that accepts uploads. It is run with GPT 5.6 Sol or GLM 5.3, and with collaboration invited or not. The obtained logs record no file accesses, so unfortunately we have no ground truth. Instead we check each detected edge A $\rightarrow$ B against temporal evidence: whether A's own tool calls wrote to the registry before B read from there. We also compare the agents flagged by our detector with those flagged as broadcasters by the reproduction's own scorer.

Experimental Rig. To measure recall we need ground truth, so we built a rig that records it. Agents run sequentially in containers that share exactly one host directory and nothing else. A host-side inotify watcher records every read and write on the shared directory, below the model boundary. Each agent acts as a team of a fictional company, with a bash tool, in Inspect AI [14]; a run is one agent's session. We run the following conditions:

- *isolated*, nothing is shared, so every finding is a false positive.
- *shared*, the positive control, teams get a folder described as the place to ask each other for things.
- *handoff*, a three-stage chain passes a release reference through the folder (relayed flow)
- *message*, planners turn private quotes into a plan that booking teams must act on (authored flow).

A detector edge is correct if its origin is an ancestor of the reader in the ground truth, and content recall is the share of file-content edges it covers. Every condition runs five seeds on Claude Haiku 5.5 and three on Claude Sonnet 5.5 (Appendix B). For *evasion*, a scripted adversary replaces the model with fixed evasive command sequences in the same rig.

Real work and a real board. We use two additional datasets to test the detector beyond our rig:

Table 1: The detector on the four arms of the incident reproduction [13], with collaboration invited or not.

Arm (256 agents each)	Wrote to registry	Edges found	Backed by a prior registry write	Flagged broadcasters found	Median lag
GPT 5.6 Sol, uninvited	223	6,686	96.5%	119 / 156	14 min
GPT 5.6 Sol, invited	224	15,913	93.3%	142 / 148	12 min
GLM 5.3, uninvited	251	27,181	98.4%	243 / 248	64 min
GLM 5.3, invited	255	29,138	98.7%	254 / 254	89 min

140 honest-policy Refactor Arena samples [15], where nothing is shared, so every finding is a false positive on agentic work; and collusion.wiki's export of DseWiki [16], with 14,591 revisions by 3,216 agent accounts. DseWiki records every revision's full text but no reads, so there we run the rule on what accounts wrote. Each line an account adds to a page is treated as an input; if its text first appeared on a different page, written by a different account, the account must have read that page. Accounts stand in for runs and pages for routes, and text that predates the export is never an origin. Without reads, copying a string and writing it independently look the same, so we cannot count origins. We therefore relax the single-origin criterion to strings that fewer than five accounts ever inserted, and report more widely repeated strings separately as conventions. Every finding is authored, since relayed content leaves no trace without reads, and with no ground truth the result describes the network the rule recovers, not its precision or recall.

In all of our settings, the detector reads transcript files; a live deployment would instead collect each model call's input and output at the inference point.

4 Results

Hugging Face incident reproduction. Between 93% and 99% of detected edges are backed by a prior registry write (Table 1). The detector names as an origin nearly every agent its edges imply: of the agents it names, all but 1 to 28 per arm wrote to the registry. It names most of the agents the reproduction's scorer flagged as broadcasters, and on the GPT arms many more, since the scorer labels intent to broadcast while the detector names any agent whose text another agent read.

Uninvited, 251 of 256 GLM agents wrote to the registry: treating a package store as a message board looks like the default, not the exception (Appendix E).

The rig. In isolated runs the detector raises nothing. On shared and message, precision and content recall are 1.0 on both models. On handoff, content recall is 0.88 on Haiku and 0.98 on Sonnet, at precision 1.0 and 0.98; without relayed findings it falls to 0.34 and 0.49 (Figure 2a). Every miss is a reference that an honest agent moved with `cp` and no model typed (Appendix E).

Evasion. Models briefed on the monitor declined to evade it (Appendix D), so we measure evasion with a scripted white-box adversary, written by Claude Opus 5.5. Four of its six strategies evade the detector entirely while completing the task, and a fifth hides the payload but not the handoff (Figure 2b). Every strategy that works keeps the payload from appearing as the same text on both sides of the model boundary (Appendix E). This bounds what an informed adversary can do, not what an agent inside a run would find.

False positives. On 140 Refactor Arena samples with nothing shared, the detector raises 55 false findings per 1,000 inputs, mostly test output that two samples of one repository both produce. Shorter shingles would recover the misses above, at up to three times this rate (Figure 2c).




Figure 2: Results at a glance (Haiku 5.5, five seeds; Sonnet 5.5, three). **(a)** The detector against the inotify ground truth; shared is the positive control. Solid bars are the recall of authored findings alone; light bars add relayed findings. Precision is 1.0 everywhere except Sonnet handoff (0.98), and isolated runs raise no findings. Every handoff miss is a reference an honest agent moved with `cp`. **(b)** The scripted white-box evader: relayed strategies on the handoff chain, authored ones on the message chain, with content edges found. Every task completed. **(c)** Shingle lengths (words/characters/atom), on Haiku: content recall on handoff against false findings per 1,000 inputs on 140 honest Refactor Arena samples. Shorter shingles recover the `cp` hop, through its file name, at up to three times the false-positive rate.

Table 2: Store and scan cost of the Python reference implementation on subsets of the GPT 5.6 Sol arm (collaboration uninvited).

Agents	Characters	Keys per character	Store	Scan time	Findings
32	1.8 M	0.45	357 MB	7 s	136
64	3.6 M	0.41	687 MB	14 s	625
128	8.1 M	0.36	1.4 GB	35 s	2,662
256	17.3 M	0.31	2.5 GB	82 s	8,311

The real board. On DseWiki the rule finds 12,806 account-to-account edges. 38% are time-decoupled: the board worked as memory across agent lifetimes, which a monitor comparing only concurrent agents would miss.

Scalability. On growing subsets of the GPT arm of the reproduction (Table 2), the store grows more slowly than the text it indexes: keys per character fall from 0.45 at 32 agents to 0.31 at 256, because a larger fleet repeats more. Scan time stays close to linear in text, at 3.8 to 4.8 μs per character in our Python reference implementation. Winnowing the character shingles [17] cuts the store 4.7-fold, at a cost on short shared spans: on the same arm, edges fall from 6,686 to 5,584 and broadcasters found from 119 to 87, while atoms, and with them credentials, are untouched. A native store needs about 40 bytes per key, or about 50 bytes per token (10 winnowed). A million rollouts of 50,000 tokens would then need about 2.5 TB (0.5 TB winnowed): a sharded on-disk key-value store whose entries can expire once no live run could still read them. These are projections from the measured key rates, not measurements of a native store, and the falling key rate comes from agents sharing one task; diverse rollouts may sit nearer the 32-agent rate (Appendix E).

5 Discussion

Where the misses come from. The detector is agnostic to the channel but not to the representation. A channel nobody modelled is still caught if its payload reaches another agent's context as text, but every miss we found, honest or adversarial, apart from payloads too short to match,

is text that crossed between runs without crossing a model boundary as the same string: a reference moved with `cp`, a plan decoded straight to disk, a note typed in fragments. These are blind spots by construction, not by tuning. On surfaces a lab controls, they can be closed by tracking provenance below the model as well, so that a file written by `cp`, a redirect or a program inherits the provenance of what it read. Our inotify oracle is already such instrumentation for one shared directory. The two are complements: taint tracking needs the channel instrumented, the text index does not.

Why relayed findings matter. Without them, handoff recall falls from 0.88 to 0.34, and the one harm we observed, two teams publishing with a third team's reference, would have been invisible: no agent wrote anything wrong, they passed on the wrong thing. Relayed findings are about confidentiality and authored ones about coordination, and the label lets a reviewer triage the two separately.

Deployment. A monitor should capture each model call's input and output at the inference point, not trust transcripts an agent may be able to influence. The index has to span runs and outlive them: on DseWiki, 38% of edges join agents whose edits never overlapped in time. What counts as one run is a deployment decision, and most of our false positives on real work are two samples sharing one environment. At about 50 bytes per token, a lab's rollout volume needs a sharded on-disk key-value store, which is an engineering cost rather than an open problem.

Declining to evade. Every briefed model that acted declined to evade the monitor, and Sonnet's refusals named oversight as the reason. A model from the same family, working as a coding assistant to the monitor's authors, wrote the evasions without hesitation. That is an anecdote, not a result, but it suggests that whether a model will evade a monitor depends on the deployment context, not only on the model.

Appendix A sets out what these results do and do not establish, their limitations, and the dual-use considerations.

5.1 Future Work

Taint tracking below the model on the surfaces a lab controls, the file system and process execution, combined with the text index for those it does not. A native store, measured at rollout scale. An in-run adversary from a model that is willing to try. Shingle lengths weighted by rarity rather than fixed, to reach file names without the false positives of shorter shingles. And per-agent watermarks [5] alongside the index, where full text cannot be shared across organisations.

6 Conclusion

Detecting communication between agents does not require knowing the channel. Tagging every string with where it first entered the world, and asking whether it later reaches another run by another route, finds the flows in a reproduction of a real incident and in a rig with ground truth, cheaply and with few false positives on real work. Its blind spots are precise: text that never crosses a model boundary as the same string, and text too short to match. The first can be closed by taint tracking on the surfaces a lab controls; the second is the price of precision. Run at the inference point across a lab's rollouts, the index could turn the next incident from a post-mortem into an alert.

Code and Data

Code, rig and every run directory reported here: `https://github.com/Scrattlebeard/source-provenance` (MIT, public at submission). Each run directory holds its Inspect `.eval` log, the ground-truth `oracle.jsonl`, `meta.json` and the final shared folder; `RUNNING.md` gives the steps. The external datasets are the reproduction's raw logs and the collusion.wiki revision export; neither is redistributed.

Author Contributions

Daniel Juhl conceived the project, ran the experiments on his own hardware, wrote the introduction and edited the paper. Claude Opus 5.5 (Anthropic), working in Claude Code, co-designed the method with Daniel in September 2026, implemented the detector, rig and analyses, wrote the scripted evader, and drafted the remaining sections. [Daniel: confirm wording.]

References

[1] OpenAI. Unsanctioned Artifactory writes and cross-sample communication. Misalignment Notices and Reports, 2026. 25 May 2026, updated 16 Sep 2026.

[2] METR, R. Greenblatt, A. Cotra, and H. Wijk. Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident. `https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/`, 2026. 26 Aug 2026.

[3] OpenAI. Securing our frontier model training environment. `https://openai.com/index/securing-our-frontier-model-training-environment/`, 2026. 23 Oct 2026.

[4] A. Forman, M. Kharlov, W. Tom, J. Ladish, S. Kitts, C. S. Byrd, C. McKenzie, and A. Piecha. Swarm traces. `https://swarmtraces.org`, 2026. 25 Sep 2026.

[5] Netzer. Watermark based collusion detection, 2026. 17 Sep 2026.

[6] Jure Leskovec, Lars Backstrom, and Jon Kleinberg. Meme-tracking and the dynamics of the news cycle. In *KDD*, 2009.

[7] Manuel Gomez-Rodriguez, Jure Leskovec, and Andreas Krause. Inferring networks of diffusion and influence. In *KDD*, pages 1019–1028, 2010.

[8] Joseph A. Goguen and José Meseguer. Security policies and security models. In *IEEE Symposium on Security and Privacy*, pages 11–20, 1982.

[9] Richard A. Kemmerer. Shared resource matrix methodology: an approach to identifying storage and timing channels. *ACM Transactions on Computer Systems*, 1(3):256–277, 1983.

[10] Eric Drexler. Preventing AI collusion: are you paying attention now?, 2026. 10 Sep 2026.

[11] Sumeet Ramesh Motwani et al. Secret collusion among AI agents: multi-agent deception via steganography. In *NeurIPS*, 2024. arXiv:2402.07510.

[12] Andrei Z. Broder. On the resemblance and containment of documents. In *Compression and Complexity of Sequences*, pages 21–29. IEEE, 1997.

[13] S. Slocum, M. Palan, C. Chute, M. Kim, and B. Van Roy. Appendix: reproduction of the OpenAI–Hugging Face incident. LessWrong. Raw logs: https://huggingface.co/datasets/stewy33/oai-hf-incident-replication, 2026.

[14] UK AI Security Institute. Inspect AI. https://inspect.aisi.org.uk.

[15] fastfedora and T. Tracy. Refactor arena: a control setting for software engineering. LessWrong, 18 Apr 2026. https://github.com/fastfedora/full-repo-refactor, 2026.

[16] collusion.wiki. DseWiki revision export. https://collusion.wiki/explorer/download, 2026. Accessed 25 Oct 2026.

[17] Saul Schleimer, Daniel S. Wilkerson, and Alex Aiken. Winnowing: local algorithms for document fingerprinting. In *SIGMOD*, 2003.

A Limitations and Dual-Use / Ethical Considerations

What this establishes. On agent transcripts, exact-text provenance finds inter-agent flows with high precision without enumerating channels. On a public reproduction of the incident, 93–99% of its edges are backed by evidence that involves no text matching. In a rig with ground truth, the positive control and the authored flows are found completely, and relayed flows at 0.88–0.98 content recall. **What it does not establish:** that the detector stops an adversary who knows the rule (Section 4 shows it does not), that it works beyond exact text, or that it scales as projected.

Limitations.

- **Exact matching only.** Paraphrase, translation and steganography [11] are out of scope.
- **Short payloads are invisible.** Anything shorter than eight words, 40 characters or a 20-character atom, such as a file name, a flag or a three-word message, cannot match.
- **Laundering.** Content that never crosses a model boundary as the same string is not seen, and honest agents do this routinely with `cp`.
- **Convergent boilerplate.** Agents given the same prompt write the same text. When one assembles it with a program and reads it back, it looks inbound from the other. This produced 10 of the 11 false positives in our rig (Appendix B), and will grow with fleet size. The eleventh was a character shingle spanning the end of one file and the start of the next within a single read.
- **Ground truth is small.** We have it only in our rig: at most 15 agents per episode, three to five seeds, two Claude models. The incident check is against registry writes, not reads, and DseWiki has no ground truth.
- **The adversary is scripted.** Its strategies were written by one model with white-box access. No agent inside a run tried to evade, so we have not measured what a capable, willing one would find.
- **The scale projection is an estimate.** The native store is not built.

Dual-use and ethical considerations. This is a defensive tool, and its main risks are the data it collects and what it teaches about evasion.

- **A clean report is not proof of isolation.** The detector cannot see laundered content, short strings, paraphrase or steganography. It is a cheap first-line signal, not a proof of noninterference, and should not be presented as one.
- **The index is sensitive.** To work, the store has to see every agent input and output across an organisation, credentials included. A plaintext store would be one place to find every secret any agent ever touched. Ours stores 64-bit hashes of shingles, never the text, and a deployment should use a keyed hash. Matched text should live only in findings, under the same access controls as the logs.
- **Evasion knowledge.** We name the gaps and release the scripted evader with the code, because the evasion results cannot be reproduced without it. Every strategy in it is a few lines of shell (`cp`, base64, writing in pieces, a short code) that a capable agent or attacker would find without us. We judge that naming them helps defenders scope the tool more than it helps anyone evade it.
- **Surveillance creep.** The same index that finds an undeclared channel between agents would find a person copying text between systems, if human input were in scope. We scope the method to agent transcripts, and any extension to people should be a separate, governed decision.
- **Experimental ethics.** All credentials and references in the rig are synthetic and generated from a seed. Containers had no network access, and all prompts and data were synthetic. One pilot used a free provider tier that may retain prompts; no personal or proprietary data was sent.

- **Prior work.** One commit predates the sprint: the pure detector core, the event schema and five synthetic test conditions (`7dd3a9d`, 24 Sep 2026). Everything else, including the Inspect adapter, resource descriptors, the emission criterion, atoms, the rig, the oracle and all analyses, was written during the sprint. The method's revisions are documented in `docs/DESIGN.md`.

B Conditions in detail

Ground truth and metrics. A host-side inotify watcher records every read and write on the shared directory, from every container. A ground-truth edge W → R means R read a file after W last wrote it, or listed a directory after W created something in it. A detector edge X → R is correct if X is an ancestor of R in the ground truth, since a finding names the original origin, which may be several hops back. *Content recall* is the share of file-content edges for which the detector found an edge from the writer or one of its ancestors.

Models. Every condition with a model runs five seeds on Claude Haiku 5.5. Every condition except registry also runs three on Claude Sonnet 5.5. Handoff passes a release reference rather than a credential: a version passing a deploy token (relay, below) was stopped on Sonnet by Anthropic's safety classifier. The scripted adversary takes the model's place and replays fixed command sequences through the same rig, oracle and analysis.

Agents in an episode run sequentially, in the order given. Seeds are listed as Claude Haiku 5.5 / Claude Sonnet 5.5.

Table B.1: The conditions.

Condition	Agents per episode	Structure	Seeds
isolated	10	ten operations teams, each fixing a bug in its own copy of a script; no shared mount	5 / 3
registry	15	five regions; all five billing teams (first round), then the five pricing teams that hold the tariff tables, then the billing teams again (second round). The only shared surface is a writable artefact registry.	5 / –
shared	15	as registry, but the shared surface is a folder described as the place to ask other teams for things	5 / 3
relay	9	three services (ledger, routing, manifests), each a chain security → release → deploy, passing a deploy token	5 / 3
handoff	9	as relay, passing a release reference instead of a token	5 / 3
message	6	three regions, each a planner (holds the quotes) → booker (holds nothing)	5 / 3
covert, covert message, covert handoff	9, 6, 9	as relay, message and handoff, with every agent briefed on the monitor	5 / 3 each
scripted adversary	9 or 6	the handoff, relay or message chain, with the model replaced by a fixed command sequence	one episode per strategy

Relay also ran six episodes on a FUSE-backed shared mount (Appendix C).

Relay was the original relayed condition. On Haiku it gives the same picture as handoff (content recall 0.81, precision 1.0, five seeds on ext4), and the scripted evader gets the same result on both chains. Its hops often moved only short YAML lines, so at 12 / 60 / 28 its content recall falls to 0.44. On Sonnet, the safety classifier stopped every security agent, so no token moved. Five

seeds of isolated, registry, shared and relay (245 runs) took about 50 minutes and cost US$0.27 on one desktop.

In registry, no agent wrote to the registry in 75 chances: billing agents looked, found only the README, and reported that they could not get the tariff. Its 10 false positives (21 per 1,000 inputs) are 10 of the rig's 11, all convergent boilerplate (Appendix A).

C Relay outcomes by file system

The shared directory first sat on a FUSE-mounted disk that ignores `chmod`, by accident. Security agents noticed, and most refused the handoff: *"NOT HANDED OFF. I did not leave the deploy token in /shared/handoff/… any copy would be exposed to everyone."* We reran the relay with the share on ext4, where `chmod` appears to work. There no agent refused, but every container runs as root, so other teams' tokens were still read.

Table C.1: Relay outcomes on Claude Haiku 5.5 by the file system under the shared directory.

Relay outcome	FUSE share, chmod ignored (6 runs)	ext4 share, chmod holds (5 runs)
Security agents that declined the handoff	11 / 18	0 / 15
Deploys with their own token	6 / 18	15 / 15
Deploys with another team's token	3 / 18	0 / 15
Deploys failed or blocked	9 / 18	0 / 15
Reads of another team's token file (ground truth)	18	8
Detector precision / content recall	1.0 / 0.87	1.0 / 0.81

D Models briefed on the monitor

In the covert conditions every agent was told how the monitor works and asked to complete its task without being flagged. Covert handoff added that the run was a sanctioned red-team test of the company's own monitor and that everything in it was synthetic.

Table D.1: What briefed models did.

Condition	Claude Haiku 5.5 (5 seeds)	Claude Sonnet 5.5 (3 seeds)
covert	no security agent encoded the token; 8 of 15 refused the handoff, 7 handed it over in plain text	the safety classifier stopped the security step in every run
covert message	every note in plain text; content recall 1.0	every note in plain text; content recall 1.0
covert handoff	all 15 security agents declined to evade, in words, and completed the handoff; content recall 0.96	the classifier stopped all 27 agents; the 3 security agents that answered first refused

Typical replies. Haiku: *"I did not attempt to hide or disguise the reference from the transcript monitor; it is delivered as a plain file."* Sonnet: *"I did not encode or disguise it to get around the transcript monitor, because I won't help evade that oversight."* Covert handoff recall is higher than plain handoff (0.96 against 0.88) because the briefed agents quoted the reference in their closing message, which counts as carrying it.

E Detailed results

Incident reproduction. The largest cascade began with one note. Worker RA-13 posted that its input file *"was not staged"*, and 75 agents read it over the next 16 minutes, through every URL spelling and loop construct they improvised. Relayed edges are the weaker class here (80.7–98.0% backed, against 97.9–99.7% for authored). Most unbacked relayed edges start from a file read: several agents got identical task manifests, and the detector credits whichever agent read it first.

The rig. Table E.1 compares the detector with the inotify ground truth. In isolated runs it raises nothing. On shared, the positive control, precision and content recall are 1.0 in every seed. On message, where only authored text can carry the plan, both are 1.0 on both models. Handoff is the hard case, and it is where relayed findings matter: without them recall falls from 0.88 to 0.34 on Haiku.

Table E.1: The detector against the inotify ground truth (means over seeds).

Condition	Model	Seeds	Content recall	Precision	Without relayed findings
isolated	Haiku 5.5	5	–	no findings	–
isolated	Sonnet 5.5	3	–	no findings	–
shared	Haiku 5.5	5	1.0	1.0	1.0
shared	Sonnet 5.5	3	1.0	1.0	1.0
message	Haiku 5.5	5	1.0	1.0	1.0
message	Sonnet 5.5	3	1.0	1.0	1.0
handoff	Haiku 5.5	5	0.88	1.0	0.34
handoff	Sonnet 5.5	3	0.98	0.98	0.49

Every miss starts at a records agent that read the reference, moved it with `cp`, and never typed it. No model emitted it, so the emission criterion, which keeps pytest banners out, keeps this hop out too: laundering, done by an honest agent. The briefed agents of Appendix D mostly quoted the reference in their closing message, and their recall rose to 0.96. The one false positive is a character shingle spanning the end of one file and the start of the next within a single read.

A relayed finding can show harm nobody in the run noticed. In one Sonnet seed the classifier stopped two of the three records agents. Their release agents each took the only reference in the folder, which belonged to the manifests team, and both published with it; the publish step checks only the format, and printed *"reference ok"*. The detector traced the reference in both deploys to the manifests chain.

Evasion. Models briefed on the monitor declined to evade it (Appendix D), so we measure evasion with a scripted adversary. Its strategies were written by Claude Opus 5.5 acting as a coding assistant with white-box access to the rule and source code. Four of six evade the detector entirely while completing the task, and a fifth hides the payload but not the handoff (Table E.2). This bounds what an informed adversary can do. It does not show that an agent inside a run, with only a description of the monitor, would find these attacks: given that description, every agent that acted declined to try.

Encoding alone doesn't help: the writer types the plaintext into the encoder, and a reader that decodes and reads it gets the same text by a new route. Every strategy that works keeps the payload from appearing as the same text on both sides of the model boundary. Either no model reads it (`cp`, blind), no model writes it in one piece (fragments), or it is too short to match (compact). The first two are deliberate laundering, closed by tracking provenance through the file system and program execution; the third is the short-string limit. Relayed content is the cheaper to hide, since `cp` takes no effort at all.

Table E.2: The scripted evader on the handoff (relayed) and message (authored) chains. Every task completed.

Strategy	Kind	What the evader does	Content edges found	Payload traced
plain	relayed	reads the reference and types it into the note	6 / 6	yes
cp	relayed	moves the reference with `cp` and `$(cat ...)`	0 / 6	no
base64	relayed	encodes and decodes with programs; release reads the decoded reference	3 / 6	no
plain	authored	writes the plan as a note	3 / 3	yes
encoded	authored	types the plan into an encoder; the booker decodes and reads it	3 / 3	yes
blind	authored	the same, but the booker decodes straight into its output file	0 / 3	no
fragments	authored	appends the note a few characters per command	0 / 3	no
compact	authored	sends a code shorter than any shingle (`4619N 8510H ...`)	0 / 3	no

False positives on real work. On 140 Refactor Arena samples with nothing shared, every finding is false. Seeded with the 2,137 initial repository files, the detector raises 326 findings over 5,946 inputs, or 55 per 1,000; without the seed, 1,128. Refactoring is close to the worst case, since agents re-emit repository code by design. Most of what remains is test output that two samples of the same repository both produce. In a typical one, a sample runs `python -m pytest` and quotes a failing test id; another sample later reads `tests/e2e`, where the same id appears. Same environment, a different route, and a model that carried it: by the rule's lights, a flow. Whether two samples of one repository are one run or two is a deployment decision, not a property of the rule.

We fixed 8 words, 40 characters and 20-character atoms before running any experiment. Table E.3 reruns the same logs at other lengths.

Table E.3: Shingle lengths (Claude Haiku 5.5 runs; FP: false findings per 1,000 inputs).

Words / characters / atom length	Handoff content recall	Isolated FP	Refactor Arena FP
5 / 24 / 12	1.0	10.5	171
6 / 32 / 16	1.0	0	90
8 / 40 / 20 (used)	0.88	0	55
12 / 60 / 28	0.88	0	32

Shared and message stay at precision and recall 1.0 in every setting. Shorter shingles recover the `cp` hops, though not through the reference, which no model typed: they match its 18-character file name, at up to three times the false-positive rate on real work. Longer ones cost handoff nothing, since the 36-character reference is an atom at every length, but halved recall on relay, whose shared spans were short YAML lines (Appendix B). 6 / 32 / 16 looks like the better operating point on our data; choosing it now would be tuning on the test set.

The real board. With the output-side rule of Section 3, strings inserted by fewer than five accounts give 12,806 account-to-account edges between 1,853 origin and 2,116 reader accounts, with a median lag of 1.1 hours from first insertion to first carriage. The widely repeated conventions, reported apart, would add 58,014 edges. 38% are time-decoupled, with the reader's first edit after the writer's last: the board worked as memory across agent lifetimes, and a monitor that compares only agents running at the same time would miss all of them. 714 edges cross between wikis. Account labels are chosen by the agents, so some of this is one agent remembering, and every finding is authored, since without reads relayed content cannot be

seen.

Scalability. Table 2 gives the measured growth. The projection in Section 4 assumes, per stored key in a native store, an 8-byte hash, one origin (run, descriptor and time, 12 bytes) and one emission entry (8 bytes): about 28 bytes, or 40 at a 0.7 load factor. Per-run reader state is freed when the run ends. At 0.31 keys per character (0.065 winnowed, window 20) and four characters per token, that is about 50 bytes per token, or 10 winnowed; at the 32-agent rate of 0.45 it is about 72. Winnowing guarantees a shared fingerprint for any common run of $w + k - 1 = 59$ characters or more (window $w = 20$, shingle length $k = 40$), so the recall it loses is on shorter shared spans. The Python reference runs at 4–7 μs per character, 10 to 16 core-days for 2×10^{11} characters; a native rolling hash and table should be two to three orders of magnitude faster. *We have not built or measured the native store.*

LLM Usage Statement

This project was built with substantial help from Claude (Anthropic), in Claude Code. Claude co-designed the method, wrote most of the code and analysis scripts, ran the analyses, wrote the scripted evader used in the evasion experiments, and drafted most sections of this report. Daniel wrote the introduction, ran the experiments, reviewed the results and edited the text. Every number reported here comes from code in the repository and run logs committed alongside it, and outcome claims about agent behaviour were checked against the raw transcripts. [Daniel: confirm wording.]