

# Convolutional Neural Networks in Medical Imaging

Mitchell Finzel

Division of Science and Mathematics  
University of Minnesota, Morris  
Morris, Minnesota, USA

15 April 2017,  
Senior Seminar Conference

# Introduction

- Convolutional neural networks or CNNs, have seen a rise in popularity in image related fields.
- CNNs have been having great success in biological segmentation tasks.
- These tasks include:
  - The automated detection of lymph nodes
  - Segmentation of knee cartilage
  - Detection of Alzheimer's

# Introduction

- Convolutional neural networks or CNNs, have seen a rise in popularity in image related fields.
- CNNs have been having great success in biological segmentation tasks.
- These tasks include:
  - The automated detection of lymph nodes
  - Segmentation of knee cartilage
  - Detection of Alzheimer's

# Introduction

- Convolutional neural networks or CNNs, have seen a rise in popularity in image related fields.
- CNNs have been having great success in biological segmentation tasks.
- These tasks include:
  - The automated detection of lymph nodes
  - Segmentation of knee cartilage
  - Detection of Alzheimer's

# Introduction

- Convolutional neural networks or CNNs, have seen a rise in popularity in image related fields.
- CNNs have been having great success in biological segmentation tasks.
- These tasks include:
  - The automated detection of lymph nodes
  - Segmentation of knee cartilage
  - Detection of Alzheimer's

# Introduction

- Convolutional neural networks or CNNs, have seen a rise in popularity in image related fields.
- CNNs have been having great success in biological segmentation tasks.
- These tasks include:
  - The automated detection of lymph nodes
  - Segmentation of knee cartilage
  - Detection of Alzheimer's

# Introduction Continued


- We will be looking at two approaches to brain MRI segmentation.
- The goal of this work is to provide unsegmented MRIs to the network and receive properly segmented MRIs as output.
- Currently this requires time consuming labor from a skilled medical professional.

# Introduction Continued

- We will be looking at two approaches to brain MRI segmentation.
- The goal of this work is to provide unsegmented MRIs to the network and receive properly segmented MRIs as output.
- Currently this requires time consuming labor from a skilled medical professional.



# Input Output Example



# Outline

- Background - Information about basic structural concepts for CNNs
- Methods used by Havaei, et al.
- Methods used by Kamnitsas, et al.
- Results
- Conclusions

# Biological Segmentation

- Segmentation is the process of identifying the boundaries of different structures and classifying them
- Segmentation is loosely defined and can have a wide range of granularities.
  - Rough granularity such as identifying the different bones in a leg xray.
  - Smooth granularity such as determining the differing regions of a tumor.

# Biological Segmentation

- Segmentation is the process of identifying the boundaries of different structures and classifying them
- Segmentation is loosely defined and can have a wide range of granularities.
  - Rough granularity such as identifying the different bones in a leg xray.
  - Smooth granularity such as determining the differing regions of a tumor.

# Biological Segmentation

- Segmentation is the process of identifying the boundaries of different structures and classifying them
- Segmentation is loosely defined and can have a wide range of granularities.
  - Rough granularity such as identifying the different bones in a leg xray.
  - Smooth granularity such as determining the differing regions of a tumor.

# Biological Segmentation

- Segmentation is the process of identifying the boundaries of different structures and classifying them
- Segmentation is loosely defined and can have a wide range of granularities.
  - Rough granularity such as identifying the different bones in a leg xray.
  - Smooth granularity such as determining the differing regions of a tumor.

# Neural Networks

- Neural Networks are a form of machine learning
- Neural Networks can be thought of as pattern recognizers.
- They are loosely based on the neuronal structure of the cerebral cortex, the part of the brain that takes in sensory data.

# Neural Networks

- Neural Networks are a form of machine learning
- Neural Networks can be thought of as pattern recognizers.
- They are loosely based on the neuronal structure of the cerebral cortex, the part of the brain that takes in sensory data.



# Neural Networks

- Neural Networks are a form of machine learning
- Neural Networks can be thought of as pattern recognizers.
- They are loosely based on the neuronal structure of the cerebral cortex, the part of the brain that takes in sensory data.

# Neural Network Structure

- Comprised of layers of nodes
- Each node has an activation function that triggers when it recognizes something in the input.
- These activations are then passed to neighboring nodes through weighted connections eventually leading to some type of output.
- The network can 'learn' by altering the weights of its connections based on the accuracy of the output to the goal result.

# Neural Network Structure


- Comprised of layers of nodes
- Each node has an activation function that triggers when it recognizes something in the input.
- These activations are then passed to neighboring nodes through weighted connections eventually leading to some type of output.
- The network can 'learn' by altering the weights of its connections based on the accuracy of the output to the goal result.

# Neural Network Structure

- Comprised of layers of nodes
- Each node has an activation function that triggers when it recognizes something in the input.
- These activations are then passed to neighboring nodes through weighted connections eventually leading to some type of output.
- The network can 'learn' by altering the weights of its connections based on the accuracy of the output to the goal result.

# Neural Network Structure

- Comprised of layers of nodes
- Each node has an activation function that triggers when it recognizes something in the input.
- These activations are then passed to neighboring nodes through weighted connections eventually leading to some type of output.
- The network can 'learn' by altering the weights of its connections based on the accuracy of the output to the goal result.



# Kernels

- Kernels, neurons and filters are interchangeable names
- Kernels are an array based representation of image features

# Kernels

- Kernels, neurons and filters are interchangeable names
- Kernels are an array based representation of image features



# Kernels

0	0	0	0	0	30	0
0	0	0	0	30	0	0
0	0	0	30	0	0	0
0	0	0	30	0	0	0
0	0	0	30	0	0	0
0	0	0	30	0	0	0
0	0	0	0	0	0	0

Pixel representation of filter



Visualization of a curve detector filter

Kernel

<https://adeshpande3.github.io/>

# Convolutional Layers

- Convolutional Layers are where CNNs get their name
- Every CNN starts with a convolutional layer
- The Kernel slides or "convolves" around the input image
- The results of the convolutions are stored in the feature map

# Convolutional Layers

- Convolutional Layers are where CNNs get their name
- Every CNN starts with a convolutional layer
- The Kernel slides or "convolves" around the input image
- The results of the convolutions are stored in the feature map


# Convolutional Layers

- Convolutional Layers are where CNNs get their name
- Every CNN starts with a convolutional layer
- The Kernel slides or "convolves" around the input image
- The results of the convolutions are stored in the feature map

# Convolutional Layers

- Convolutional Layers are where CNNs get their name
- Every CNN starts with a convolutional layer
- The Kernel slides or "convolves" around the input image
- The results of the convolutions are stored in the feature map

# Convolutional Layers



Visualization of 5 x 5 filter convolving around an input volume and producing an activation map

Feature Map

<https://adeshpande3.github.io/>

# Fully Connected Layers

- Can be thought of as the final layers in the network
- Their job is to convert the feature maps from previous layers into label probabilities.
- these probabilities come in the form of a vector that adds up to 1.

# Fully Connected Layers

- Can be thought of as the final layers in the network
- Their job is to convert the feature maps from previous layers into label probabilities.
- these probabilities come in the form of a vector that adds up to 1.



# Fully Connected Layers

- Can be thought of as the final layers in the network
- Their job is to convert the feature maps from previous layers into label probabilities.
- these probabilities come in the form of a vector that adds up to 1.

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update



# Training

- Training is the crux that makes everything work
- Training requires data that has already been properly segmented.
- Network is initialized with random kernel weights
- Training has four main steps:
  - The forward pass
  - The loss calculation
  - The backward pass
  - Weight update

# Overview of Havaei, et al.

- Havaei, et al proposes a two pathway approach to the BRATS 2013 brain tumor segmentation challenge.
- Their approach has three main components
  - Two pathways
  - Two CNNs concatenated together
  - A two phase approach to training

# Overview of Havaei, et al.

- Havaei, et al proposes a two pathway approach to the BRATS 2013 brain tumor segmentation challenge.
- Their approach has three main components
  - Two pathways
  - Two CNNs concatenated together
  - A two phase approach to training

# Overview of Havaei, et al.

- Havaei, et al proposes a two pathway approach to the BRATS 2013 brain tumor segmentation challenge.
- Their approach has three main components
  - Two pathways
    - Two CNNs concatenated together
    - A two phase approach to training

# Overview of Havaei, et al.

- Havaei, et al proposes a two pathway approach to the BRATS 2013 brain tumor segmentation challenge.
- Their approach has three main components
  - Two pathways
  - Two CNNs concatenated together
  - A two phase approach to training

# Overview of Havaei, et al.

- Havaei, et al proposes a two pathway approach to the BRATS 2013 brain tumor segmentation challenge.
- Their approach has three main components
  - Two pathways
  - Two CNNs concatenated together
  - A two phase approach to training

# Two Pathways

- Havaei, et al. setup their network with two pathways
  - The local pathway with a smaller 7x7 receptive field'
  - The global pathway with a larger 13x13 receptive field.
- These two pathways allow the combination of finite detail with greater locational context.

# Two Pathways


- Havaei, et al. setup their network with two pathways
  - The local pathway with a smaller 7x7 receptive field'
  - The global pathway with a larger 13x13 receptive field.
- These two pathways allow the combination of finite detail with greater locational context.



# Two Pathways

- Havaei, et al. setup their network with two pathways
  - The local pathway with a smaller 7x7 receptive field'
  - The global pathway with a larger 13x13 receptive field.
- These two pathways allow the combination of finite detail with greater locational context.

# Two Pathways



# Cascaded Architectures

- The second approach implemented by Havaei, et al. is their use of a 'cascaded architecture'.
- In this approach they take the output one of one CNN and concatenate it into a layer of another.
- The goal is to allow for joint segmentation models where different labels are allowed to correlate with one another.


# Cascaded Architectures

- The second approach implemented by Havaei, et al. is their use of a 'cascaded architecture'.
- In this approach they take the output one of one CNN and concatenate it into a layer of another.
- The goal is to allow for joint segmentation models where different labels are allowed to correlate with one another.


# Cascaded Architectures

- The second approach implemented by Havaei, et al. is their use of a 'cascaded architecture'.
- In this approach they take the output one of one CNN and concatenate it into a layer of another.
- The goal is to allow for joint segmentation models where different labels are allowed to correlate with one another.


# Cascaded Architectures



(a) Cascaded architecture, using input concatenation (INPUTCASCADECNN).



(b) Cascaded architecture, using local pathway concatenation (LOCALCASCADECNN).



(c) Cascaded architecture, using pre-output concatenation, which is an architecture with properties similar to that of learning using a limited number of mean-field inference iterations in a CRF (MFCASCADECNN).

# Two Phase Training

- The last approach implemented by Havaei, et al. is a two phase training system.
- This is done to alleviate the relative abundance of healthy tissue versus the small quantity of tumor tissue in each image.
- The two phases consist of:
  - First they train the network on image patches where the probability of each label being present is equal.
  - Then they retrain the final layer with the relative probabilities of each label.
- This allows for better label discrimination while maintaining proper output probabilities.

# Two Phase Training

- The last approach implemented by Havaei, et al. is a two phase training system.
- This is done to alleviate the relative abundance of healthy tissue versus the small quantity of tumor tissue in each image.
- The two phases consist of:
  - First they train the network on image patches where the probability of each label being present is equal.
  - Then they retrain the final layer with the relative probabilities of each label.
- This allows for better label discrimination while maintaining proper output probabilities.



# Two Phase Training

- The last approach implemented by Havaei, et al. is a two phase training system.
- This is done to alleviate the relative abundance of healthy tissue versus the small quantity of tumor tissue in each image.
- The two phases consist of:
  - First they train the network on image patches where the probability of each label being present is equal.
  - Then they retrain the final layer with the relative probabilities of each label.
- This allows for better label discrimination while maintaining proper output probabilities.

# Two Phase Training

- The last approach implemented by Havaei, et al. is a two phase training system.
- This is done to alleviate the relative abundance of healthy tissue versus the small quantity of tumor tissue in each image.
- The two phases consist of:
  - First they train the network on image patches where the probability of each label being present is equal.
  - Then they retrain the final layer with the relative probabilities of each label.
- This allows for better label discrimination while maintaining proper output probabilities.

# Overview of Kamnitsas, et al.

- Kamnitsas, et al have five different architecture approaches
  - 3D kernels
  - Dense training
  - Two pathways
  - Deeper networks
  - 3D conditional random fields on the output

# Overview of Kamnitsas, et al.

- Kamnitsas, et al have five different architecture approaches
  - 3D kernels
    - Dense training
    - Two pathways
    - Deeper networks
    - 3D conditional random fields on the output

# Overview of Kamnitsas, et al.

- Kamnitsas, et al have five different architecture approaches
  - 3D kernels
  - Dense training
  - Two pathways
  - Deeper networks
  - 3D conditional random fields on the output

# Overview of Kamnitsas, et al.

- Kamnitsas, et al have five different architecture approaches
  - 3D kernels
  - Dense training
  - Two pathways
  - Deeper networks
  - 3D conditional random fields on the output

# Overview of Kamnitsas, et al.

- Kamnitsas, et al have five different architecture approaches
  - 3D kernels
  - Dense training
  - Two pathways
  - Deeper networks
  - 3D conditional random fields on the output

# Overview of Kamnitsas, et al.

- Kamnitsas, et al have five different architecture approaches
  - 3D kernels
  - Dense training
  - Two pathways
  - Deeper networks
  - 3D conditional random fields on the output