

NEW FROM SOLAX X3-NEO-LV



X3-NEO-LV

5.0kW/8.0kW/10.0kW/12.0kW/15.0kW

Features

High-efficiency

- 200% PV oversized and up to 110% AC output
- 200% peak EPS apparent power, 10 s
- Built-in shadow tracking

Economical

- Max. DC input current 18A per channel, supports high power solar panels
- Low start up voltage brings longer operation time

Intelligent

- Single unit UPS-level switching time < 6 ms
- CT compatible, loads respond within 0.3 s
- Max. 10 units parallel for on-grid and off-grid operation^①
- Max. charging / discharging current of 300 A
- Generator compatible^②

Safe

- IP65 protection degree
- Integrated SPD
- AFCI protection(optional)

info@solaxpower.com
service@solaxpower.com



Contact Us More Information

www.solaxpower.com

AU: +61 1300 476529

DE: +49 6142 4091664

Global: +86 571-56260008

UK: +44 2476 586998

NL: +31 (0) 852 737932

DC INPUT

Max. PV Input Power [Wp] ^③	10000	16000	20000	24000	30000
Max. PV Input Voltage [V] ^④			1000		
Start Output Voltage [V]			150		
Nominal Input Voltage [V]			640		
Operating Voltage Range [V] ^⑤			160 ~ 950		
MPPT Voltage Range [V]			160 ~ 950		
No. of MPPT / Strings per MPPT	2 / (2 / 1)			2 / (2 / 2)	
Max. Input Current [A] ^⑥	36 / 18			36 / 36	
Max. Short Circuit Current [A]	50 / 25			50 / 50	

AC INPUT & OUTPUT

Nominal AC Output Power [W]	5000	8000	10000	12000	15000
Max. AC Output Apparent Power [VA]	5500	8800	11000	13200	16500
Max. AC Output Current [A]	8.4	13.4	16.8	20.0	25.0
Max. AC output current [A]@230V/400V	8.0	12.9	16.0	19.2	24.0
Max. AC Input Apparent Power [VA]	10000	16000	20000	24000	30000
Max. AC Input Current [A]	15.3	24.3	30.4	36.5	45.6
Nominal AC voltage [V], Frequency [Hz]	3L / N / PE; 220 / 380, 230 / 400; 50/60				
Displacement Power Factor	0.8 leading ~ 0.8 lagging				
THDi (rated power) [%]	< 3				

BATTERY DATA

Battery Type	Lithium / Lead-Acid				
Battery Voltage Range [V]	40 ~ 60				
Nominal Battery Voltage [V]	48				
Max. Charging / Discharging Current [A]	125	200	235	280	300

EPS OUTPUT (WITH BATTERY)

Nominal output power [W]	5000	8000	10000	12000	15000
Peak Apparent Power [VA , s] ^⑦	10000, 10	16000, 10	20000, 10	24000, 10	30000, 10
Nominal AC Output Current[A]	7.2	11.6	14.5	17.4	21.7
Nominal Voltage [V], Frequency [Hz]	220/380, 230 /400, 50/60				
Switch Time [ms]	< 6				
THDv (linear load) [%]	< 2				

SYSTEM DATA

MPPT Efficiency [%]	> 99.9				
Max. Efficiency [%]	97.6				
Euro. Efficiency [%]	97.0				
Self Consumption [W]	< 15				

ENVIRONMENT LIMIT

Degree of Protection	IP65				
Operating Temperature Range [C]	-25 ~ +60 (derating above +45)				
Relative Humidity [%]	4 ~ 100 (condensing)				
Max. Operation Altitude [m]	< 3000				
Storage Temperature [C]	-25 ~ +70				
Noise Emission (typical) [dB]	≤ 55				

GENERAL

Dimensions(WxHxD) [mm]	706 x 491 x 263				
Net Weight [kg]	43				
Cooling Concept	Smart Cooling				
Topology	Transformerless for PV side / HF for battery side				
HMI / Communication Interfaces	LED+LCD / CAN, RS485, CT, Meter, USB, NTC, WiFi+Lan				
Warranty [years]	5				

STANDARD

Safety	EN IEC 62109-1 / -2 , EN IEC62040				
EMC	EN61000-6 / 1 / 2 / 3 / 4				
Certification	NRS 097-2-1, IEC 61727, IEC 62116, PEA, MEA, BIS				

① ② To be released in Q4 2024; ③ Derating occurs above +45 C, reducing the maximum PV input power;

*V1.0 Information may be subject to modify without notice.

④ The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage inverter;

650.00061.00

⑤ Input voltage exceeding the operating voltage range may triggers inverter protection;

⑥ When one MPPT has two string inputs, if both strings are connected to the PV, the maximum current per string must not exceed 18A. If only one PV string is connected, the maximum current per string must not exceed 20A.

⑦ Depend on PV and battery capacity.

Disclaimer: The values presented above were obtained in controlled conditions by SolaX's laboratory. Actual performance may differ due to product variations, software updates, operating conditions, and environmental influences.