

```

--
=====
=====
-- れもにーHUB (LemonHUB) - 日本語版(再起動防止ブロッカー付き)
-- オブジェクトタブ/バリア破壊機能削除済み / 制限時間なし / パスワード認証なし
-- 全UI日本語化
--
=====
=====

-- =====
-- ★★★ 再起動防止ブロッカー(初回のみ実行) ★★★
-- =====

local CoreGui = game:GetService("CoreGui")
if CoreGui:FindFirstChild("LemonHub_Blocker") then
    pcall(function()
        game:GetService("StarterGui"):SetCore("SendNotification", {
            Title = "🚫 ブロック済み",
            Text = "れもにーHUBは既に起動しています。再起動はできません。",
            Duration = 3,
        })
    end)
    return
end

local blocker = Instance.new("BoolValue")
blocker.Name = "LemonHub_Blocker"
blocker.Parent = CoreGui

-- =====
-- メインスクリプト開始
-- =====

local Players = game:GetService("Players")
local LocalPlayer = Players.LocalPlayer
local TweenService = game:GetService("TweenService")
local RunService = game:GetService("RunService")
local HttpService = game:GetService("HttpService")
local UserInputService = game:GetService("UserInputService")
local Lighting = game:GetService("Lighting")

print("✅ れもにーHUB 起動: " .. LocalPlayer.Name)

-- =====
-- 関数定義
-- =====

local function showHackMessage(text, color, duration)
    color = color or Color3.fromRGB(0,255,0)
    duration = duration or 2

```

```

local screenGui = Instance.new("ScreenGui")
screenGui.Name = "HackMessage"
screenGui.ResetOnSpawn = false
screenGui.Parent = game:GetService("CoreGui")
local frame = Instance.new("Frame")
frame.Size = UDim2.new(1,0,0,60)
frame.Position = UDim2.new(0,0,0,0)
frame.BackgroundTransparency = 0.2
frame.BackgroundColor3 = Color3.fromRGB(0,0,0)
frame.BorderSizePixel = 2
frame.BorderColor3 = color
frame.Parent = screenGui
local label = Instance.new("TextLabel")
label.Size = UDim2.new(1,0,1,0)
label.BackgroundTransparency = 1
label.Text = text
label.TextColor3 = color
label.TextScaled = true
label.Font = Enum.Font.Code
label.TextWrapped = true
label.Parent = frame
task.delay(duration, function()
    frame:TweenSize(UDim2.new(1,0,0,0), "Out", "Quad", 0.5, true)
    task.wait(0.6)
    screenGui:Destroy()
end)
end

local function screenFlash(color, duration)
    color = color or Color3.fromRGB(255,0,0)
    duration = duration or 0.3
    local flash = Instance.new("Frame")
    flash.Size = UDim2.new(1,0,1,0)
    flash.BackgroundColor3 = color
    flash.BackgroundTransparency = 0.8
    flash.BorderSizePixel = 0
    flash.Parent = game:GetService("CoreGui")
    flash.ZIndex = 999
    TweenService:Create(flash, TweenInfo.new(duration, Enum.EasingStyle.Linear,
Enum.EasingDirection.Out), {
    BackgroundTransparency = 1
}):Play()
    task.delay(duration + 0.1, function() flash:Destroy() end)
end

local function shakeScreen(intensity, duration)
    intensity = intensity or 5
    duration = duration or 0.5

```

```

local cam = workspace.CurrentCamera
local origPos = cam.CFrame.Position
local start = tick()
local connection
connection = RunService.RenderStepped:Connect(function()
    if tick() - start > duration then
        connection:Disconnect()
        cam.CFrame = CFrame.new(origPos)
        return
    end
    local offset = Vector3.new((math.random()-0.5)*intensity, (math.random()-0.5)*intensity,
(math.random()-0.5)*intensity)
    cam.CFrame = CFrame.new(origPos + offset)
end)
end

local function createBloodMoon()
    local lighting = game:GetService("Lighting")
    lighting.Ambient = Color3.fromRGB(60,10,10)
    lighting.ColorShift_Top = Color3.fromRGB(200,40,40)
    lighting.ColorShift_Bottom = Color3.fromRGB(80,10,10)
    lighting.Brightness = 0.7
    lighting.OutdoorAmbient = Color3.fromRGB(100,20,20)
    lighting.SunTextureId = "rbxassetid://14588417062"
    lighting.SunAngularSize = 30
    lighting.MoonTextureId = "rbxassetid://14588417062"
    lighting.MoonAngularSize = 30
    local moonPart = Instance.new("Part")
    moonPart.Name = "BloodMoonPart"
    moonPart.Size = Vector3.new(150,150,150)
    moonPart.Shape = Enum.PartType.Ball
    moonPart.BrickColor = BrickColor.new("Really red")
    moonPart.Material = Enum.Material.Neon
    moonPart.Anchored = true
    moonPart.CanCollide = false
    moonPart.CFrame = CFrame.new(Vector3.new(0,900,-2000))
    moonPart.Parent = workspace
    local pointLight = Instance.new("PointLight")
    pointLight.Color = Color3.fromRGB(255,50,50)
    pointLight.Range = 3000
    pointLight.Brightness = 3
    pointLight.Parent = moonPart
    local atmosphere = lighting:FindFirstChild("Atmosphere")
    if not atmosphere then
        atmosphere = Instance.new("Atmosphere")
        atmosphere.Parent = lighting
    end
    atmosphere.Density = 0.6

```

```

atmosphere.Color = Color3.fromRGB(120,20,20)
atmosphere.Decay = 0.4
atmosphere.Glare = 0.3
local stars = Instance.new("ParticleEmitter")
stars.Name = "BloodStars"
stars.Texture = "rbxassetid://10828533857"
stars.Color = ColorSequence.new({ColorSequenceKeypoint.new(0,
Color3.fromRGB(200,50,50)), ColorSequenceKeypoint.new(1, Color3.fromRGB(100,0,0))})
stars.Size = NumberSequence.new({NumberSequenceKeypoint.new(0,2),
NumberSequenceKeypoint.new(1,6)})
stars.Transparency = NumberSequence.new({NumberSequenceKeypoint.new(0,0.6),
NumberSequenceKeypoint.new(1,1)})
stars.Lifetime = NumberRange.new(5,10)
stars.Rate = 20
stars.SpreadAngle = Vector2.new(360,360)
stars.VelocityInheritance = 0
stars.Acceleration = Vector3.new(0,0.5,0)
stars.Enabled = true
local starContainer = Instance.new("Part")
starContainer.Name = "BloodStarContainer"
starContainer.Size = Vector3.new(1,1,1)
starContainer.Anchored = true
starContainer.CanCollide = false
starContainer.Transparency = 1
starContainer.CFrame = CFrame.new(0,500,0)
starContainer.Parent = workspace
stars.Parent = starContainer
print("🌕 ブラッドムーンエフェクト適用")
end
task.spawn(createBloodMoon)

```

```

loadstring(game:HttpGet('https://raw.githubusercontent.com/EdgeY/infiniteyield/master/source'))()

```

```

local function sendChatMessage(msg)
    local TextChatService = game:GetService("TextChatService")
    local ReplicatedStorage = game:GetService("ReplicatedStorage")
    if TextChatService.ChatVersion == Enum.ChatVersion.TextChatService then
        local generalChannel = TextChatService.TextChannels:FindFirstChild("RBXGeneral")
        if generalChannel then generalChannel:SendAsync(msg) end
    else
        local defaultChat = ReplicatedStorage:FindFirstChild("DefaultChatSystemChatEvents")
        if defaultChat then
            local sayMessage = defaultChat:FindFirstChild("SayMessageRequest")
            if sayMessage then sayMessage:FireServer(msg, "All") end
        end
    end
end
end

```

```
sendChatMessage("👉れもにー")
```

```
local repo = "https://raw.githubusercontent.com/deividcomsono/Obsidian/main/"
local Library = loadstring(game:HttpGet(repo .. "Library.lua"))()
local ThemeManager = loadstring(game:HttpGet(repo .. "addons/ThemeManager.lua"))()
local SaveManager = loadstring(game:HttpGet(repo .. "addons/SaveManager.lua"))()
```

```
local Options = Library.Options
local Toggles = Library.Toggles
Library.ForceCheckbox = false
```

```
local Window = Library.CreateWindow({
    Title = "👉れもにーHUB",
    Footer = "Made by GR",
    NotifySide = "Right",
    ShowCustomCursor = true,
})
```

```
local Tabs = {
    Defense = Window:AddTab("defense", "🛡️ 防御"),
    Target = Window:AddTab("target", "🎯 ターゲット"),
    Grab = Window:AddTab("grab", "👉 掴み"),
    Player = Window:AddTab("player", "👤 プレイヤー"),
    Misc = Window:AddTab("misc", "📦 その他"),
    Build = Window:AddTab("build", "🔧 ビルド"),
    LagKick = Window:AddTab("lagkick", "🕒 ラグキック"),
    Backpack = Window:AddTab("おんぶ", "🎒 おんぶ"),
    PlotBreak = Window:AddTab("プロットブレイク", "🏠 プロット破壊"),
    ["UI Settings"] = Window:AddTab("UI Settings", "⚙️ UI設定")
}
```

```
-- タブ名を日本語に設定(表示用)
```

```
Tabs.Defense.Label = "🛡️ 防御"
Tabs.Target.Label = "🎯 ターゲット"
Tabs.Grab.Label = "👉 掴み"
Tabs.Player.Label = "👤 プレイヤー"
Tabs.Misc.Label = "📦 その他"
Tabs.Build.Label = "🔧 ビルド"
Tabs.LagKick.Label = "🕒 ラグキック"
Tabs.Backpack.Label = "🎒 おんぶ"
Tabs.PlotBreak.Label = "🏠 プロット破壊"
Tabs["UI Settings"].Label = "⚙️ UI設定"
```

```
local ReplicatedStorage = game:GetService("ReplicatedStorage")
local StarterGui = game:GetService("StarterGui")
local PS = game:GetService("Players")
local RS = game:GetService("ReplicatedStorage")
local R = game:GetService("RunService")
```

```

local Workspace = workspace
local Player = PS.LocalPlayer
local Camera = Workspace.CurrentCamera
local CE = RS:WaitForChild("CharacterEvents", 10)
local BeingHeld = Player:WaitForChild("IsHeld", 10)
local StruggleEvent = CE and CE:WaitForChild("Struggle")

local function notify(title, content, duration)
    Library:Notify({ Title = title or "通知", Description = content or "", Time = duration or 5 })
end

local function sendHubLoadedMessage()
    local message = "👉 れもに一HUB | 読み込み完了 "
    local sent = false
    pcall(function()
        local chatEvents = ReplicatedStorage:FindFirstChild("DefaultChatSystemChatEvents")
        if chatEvents then
            local say = chatEvents:FindFirstChild("SayMessageRequest")
            if say and typeof(say.FireServer) == "function" then
                say:FireServer(message, "All")
                sent = true
            end
        end
    end)
    if not sent then
        pcall(function()
            StarterGui:SetCore("ChatMakeSystemMessage", {
                Text = message,
                Color = Color3.fromRGB(255,170,0),
                Font = Enum.Font.SourceSansBold,
                FontSize = Enum.FontSize.Size18,
            })
        end)
    end
end

task.spawn(function() task.wait(1) sendHubLoadedMessage() end)

```

-- ペイント削除関連

```

local paintPartsBackup = {}
local paintConnections = {}
local function deleteAllPaintParts()
    for _, obj in ipairs(Workspace:GetDescendants()) do
        if obj:IsA("BasePart") and obj.Name == "PaintPlayerPart" then
            local clone = obj:Clone()
            clone.Archivable = true
            paintPartsBackup[obj.GetDebugId()] = { clone = clone, parent = obj.Parent }
            obj:Destroy()
        end
    end
end

```

```

    end
end
local function restorePaintParts()
    for _, data in pairs(paintPartsBackup) do
        if data.clone and data.parent then data.clone.Parent = data.parent end
    end
    paintPartsBackup = {}
end
local function watchNewPaintParts()
    table.insert(paintConnections, Workspace.DescendantAdded:Connect(function(obj)
        if obj:IsA("BasePart") and obj.Name == "PaintPlayerPart" then
            task.defer(function()
                if obj and obj.Parent then
                    local clone = obj.Clone()
                    clone.Archivable = true
                    paintPartsBackup[obj.GetDebugId()] = { clone = clone, parent = obj.Parent }
                    obj.Destroy()
                end
            end)
        end
    end))
end
local function disconnectWatchers()
    for _, conn in ipairs(paintConnections) do if conn.Connected then conn:Disconnect() end
end
    paintConnections = {}
end
local function setTouchQuery(state)
    local char = Workspace:FindFirstChild(Player.Name)
    if not char then return end
    for _, v in ipairs(char:GetChildren()) do
        if v:IsA("Part") or v:IsA("BasePart") then v.CanTouch = state v.CanQuery = state end
    end
end
end

-- Anti Gucci (Blobman)
local antiGucciConnection
local safePosition
local restoreFrames = 0
local function spawnBlobman()
    local args = {[1] = "CreatureBlobman", [2] = CFrame.new(0,5000000,0), [3] =
Vector3.new(0,60,0)}
    pcall(function()
        ReplicatedStorage.MenuToys.SpawnToyRemoteFunction:InvokeServer(unpack(args)) end)
    local folder = Workspace:WaitForChild(Player.Name.."SpawnedInToys", 5)
    if folder and folder:FindFirstChild("CreatureBlobman") then
        local blob = folder.CreatureBlobman
    end
end

```

```

        if blob:FindFirstChild("Head") then blob.Head.CFrame = CFrame.new(0,50000,0)
blob.Head.Anchored = true end
        notify("成功", "ブロブマンを召喚しました！", 3)
    end
end
local function startAntiGucci()
    local character = Player.Character or Player.CharacterAdded:Wait()
    local humanoid = character:WaitForChild("Humanoid")
    local rootPart = character:WaitForChild("HumanoidRootPart")
    safePosition = rootPart.Position
    local folder = Workspace:FindFirstChild(Player.Name.."SpawnedInToys")
    local blob = folder and folder:FindFirstChild("CreatureBlobman")
    local seat = blob and blob:FindFirstChild("VehicleSeat")
    if not blob then spawnBlobman() task.wait(1) folder =
Workspace:FindFirstChild(Player.Name.."SpawnedInToys") blob = folder and
folder:FindFirstChild("CreatureBlobman") seat = blob and blob:FindFirstChild("VehicleSeat")
end
        if seat and seat:IsA("VehicleSeat") then rootPart.CFrame = seat.CFrame +
Vector3.new(0,2,0) seat:Sit(humanoid) end
        humanoid:GetPropertyChangedSignal("Jump"):Connect(function() if humanoid.Jump and
humanoid.Sit then restoreFrames = 15 safePosition = rootPart.Position end end)
        if antiGucciConnection then antiGucciConnection:Disconnect() end
        antiGucciConnection = R.Heartbeat:Connect(function()
            if not rootPart or not humanoid then return end
            ReplicatedStorage.CharacterEvents.RagdollRemote:FireServer(rootPart, 0)
            if restoreFrames > 0 then rootPart.CFrame = CFrame.new(safePosition) restoreFrames
= restoreFrames - 1 end
        end)
        task.spawn(function() while humanoid.Sit do task.wait(1) end task.wait(0.5)
rootPart.CFrame = CFrame.new(safePosition) end)
end
local function stopAntiGucci()
    if antiGucciConnection then antiGucciConnection:Disconnect() antiGucciConnection = nil
end
    local blobFolder = Workspace:FindFirstChild(Player.Name.."SpawnedInToys")
    if blobFolder and blobFolder:FindFirstChild("CreatureBlobman") then
blobFolder.CreatureBlobman:Destroy() end
end

-- Anti Gucci (Train)
local antiGucciConnectionTrain
local safePositionTrain
local restoreFramesTrain = 0
local function startAntiGucciTrain()
    local character = Player.Character or Player.CharacterAdded:Wait()
    local humanoid = character:WaitForChild("Humanoid")
    local rootPart = character:WaitForChild("HumanoidRootPart")
    safePositionTrain = rootPart.Position

```

```

local folder = workspace.Map.AlwaysHereTweenedObjects
local train = folder and folder:FindFirstChild("Train")
local seat
if train then
    for _, d in ipairs(train:GetDescendants()) do
        if d:IsA("Seat") then seat = d break end
    end
end
if seat then rootPart.CFrame = seat.CFrame + Vector3.new(0,2,0) seat:Sit(humanoid) end
humanoid:GetPropertyChangedSignal("Jump"):Connect(function() if humanoid.Jump and
humanoid.Sit then restoreFramesTrain = 15 safePositionTrain = rootPart.Position end end)
if antiGucciConnectionTrain then antiGucciConnectionTrain:Disconnect() end
antiGucciConnectionTrain = R.Heartbeat:Connect(function()
    if not rootPart or not humanoid then return end
    ReplicatedStorage.CharacterEvents.RagdollRemote:FireServer(rootPart, 0)
    if restoreFramesTrain > 0 then rootPart.CFrame = CFrame.new(safePositionTrain)
restoreFramesTrain = restoreFramesTrain - 1 end
end)
task.spawn(function() while humanoid.Sit do task.wait(1) end task.wait(0.5)
rootPart.CFrame = CFrame.new(safePositionTrain) end)
end
local function stopAntiGucciTrain()
    if antiGucciConnectionTrain then antiGucciConnectionTrain:Disconnect()
antiGucciConnectionTrain = nil end
    local trainFolder = workspace.Map.AlwaysHereTweenedObjects
    if trainFolder and trainFolder:FindFirstChild("Train") then
ResetPlayer(game.Players.LocalPlayer) end
end

-- =====
-- Defense Tab (防御)
-- =====
local DefenseGroup = Tabs.Defense:AddLeftGroupbox("🛡️ メイン防御")
local DefenseExtra = Tabs.Defense:AddRightGroupbox("🔧 追加防御")

local autoStruggleConn = nil
DefenseGroup:AddToggle("AntiGrabObsidian", {
    Text = "アンチグラブ",
    Default = false,
    Callback = function(Value)
        local RunService = game:GetService("RunService")
        local localPlayer = game:GetService("Players").LocalPlayer
        local Struggle = ReplicatedStorage:FindFirstChild("CharacterEvents") and
ReplicatedStorage.CharacterEvents:FindFirstChild("Struggle")
        if Value then
            if autoStruggleConn then autoStruggleConn:Disconnect() end
            autoStruggleConn = RunService.Heartbeat:Connect(function()
                local character = localPlayer.Character

```

```

        if character and character:FindFirstChild("Head") then
            local head = character.Head
            if head:FindFirstChild("PartOwner") then
                task.spawn(function()
                    if Struggle then Struggle:FireServer(localPlayer) end
                    pcall(function()
ReplicatedStorage.GameCorrectionEvents.StopAllVelocity:FireServer() end)
                    for _, part in pairs(character:GetChildren()) do
                        if part:IsA("BasePart") then part.Anchored = true end
                    end
                    local isHeld = localPlayer:FindFirstChild("IsHeld")
                    while isHeld and isHeld.Value do task.wait() end
                    for _, part in pairs(character:GetChildren()) do
                        if part:IsA("BasePart") then part.Anchored = false end
                    end
                end)
            end
        end
    end)
else
    if autoStruggleConn then autoStruggleConn:Disconnect() autoStruggleConn = nil end
    local char = localPlayer.Character
    if char then
        for _, part in pairs(char:GetChildren()) do
            if part:IsA("BasePart") then part.Anchored = false end
        end
    end
end
end
end
}))

```

```

local antiBlob1T=false
local function antiBlob1F()
    antiBlob1T=true
    workspace.DescendantAdded:Connect(function(toy)
        if toy.Name=="CreatureBlobman" and antiBlob1T then
            toy.LeftDetector:Destroy()
            toy.RightDetector:Destroy()
        end
    end)
end
end
DefenseGroup:AddToggle("AntiBlobmanToggle", {Text="アンチブロブマン", Default=false,
Callback=function(on) if on then antiBlob1F() else antiBlob1T=false end end})

```

```

local antiExplodeT=false
local function antiExplodeF()
    antiExplodeT=true
    local char=Player.Character

```

```

if not char then return end
local hrp=char:WaitForChild("HumanoidRootPart")
workspace.ChildAdded:Connect(function(model)
    if model.Name=="Part" and antiExplodeT then
        local mag=(model.Position-hrp.Position).Magnitude
        if mag<=20 then
            hrp.Anchored=true
            wait(0.01)
            while char["Right Arm"].RagdollLimbPart.CanCollide do wait(0.001) end
            hrp.Anchored=false
        end
    end
end)
end
DefenseGroup:AddToggle("AntiExplosionToggle", {Text="アンチ爆発", Default=false,
Callback=function(on) if on then antiExplodeF() else antiExplodeT=false end end})

local hookBurnConn
local function hookBurn(char)
    local hum = char:WaitForChild("Humanoid")
    local hrp = char:WaitForChild("HumanoidRootPart")
    char.PrimaryPart = hrp
    if hookBurnConn then hookBurnConn:Disconnect() end
    hookBurnConn = hum.FireDebounce.Changed:Connect(function(isBurning)
        if isBurning then
            local me = char
            local oldCF = hrp.CFrame
            local plots = workspace.FindFirstChild("Plots")
            if plots and plots.FindFirstChild("Plot2") then
                local plot2 = plots.Plot2
                local barrier = plot2.FindFirstChild("Barrier")
                local pb = barrier and barrier.FindFirstChild("PlotBarrier")
                if pb and pb:IsA("BasePart") then
                    local safeCF = pb.CFrame * CFrame.new(0,6,0)
                    me:SetPrimaryPartCFrame(safeCF)
                    task.wait(0.3)
                    local firePart = me:FindFirstChild("FirePlayerPart", true)
                    if firePart then
                        for _, obj in ipairs(firePart:GetChildren()) do
                            if obj:IsA("Sound") then obj:Stop() end
                            if obj:IsA("Light") or obj:IsA("ParticleEmitter") then obj.Enabled = false end
                        end
                        if firePart:FindFirstChild("CanBurn") then firePart.CanBurn.Value = false end
                        if hum:FindFirstChild("FireDebounce") then hum.FireDebounce.Value = false
                    end
                end
            end
            task.wait(0.6)
            if me and me.PrimaryPart then me:SetPrimaryPartCFrame(oldCF) end
        end
    end)
end

```

```

        end
    end
end
end)
end
DefenseGroup:AddToggle("AntiBurnToggle", {Text="アンチ炎上", Default=false,
Callback=function(on) if on then hookBurn(Player.Character) elseif hookBurnConn then
hookBurnConn:Disconnect() end end})

```

```

local antiVoidConn
local VOID_THRESHOLD = -50
local SAFE_HEIGHT = 100
DefenseGroup:AddToggle("AntiVoidToggle", {Text="アンチ落下", Default=false,
Callback=function(on)
    if on then
        if antiVoidConn then antiVoidConn:Disconnect() end
        antiVoidConn = R.Heartbeat:Connect(function()
            local char = Player.Character
            if char and char.PrimaryPart then
                local pos = char.PrimaryPart.Position
                if pos.Y < VOID_THRESHOLD then
                    local safePos = Vector3.new(pos.X, pos.Y + SAFE_HEIGHT, pos.Z)
                    char:SetPrimaryPartCFrame(CFrame.new(safePos))
                    char.PrimaryPart.AssemblyLinearVelocity = Vector3.zero
                end
            end
        end)
    else
        if antiVoidConn then antiVoidConn:Disconnect() antiVoidConn = nil end
    end
end})

```

```

local antiStickyT = false
DefenseGroup:AddToggle("AntiStickyToggle", {Text="アンチ粘着", Default=false,
Callback=function(Value)
    antiStickyT = Value
    if Player.PlayerScripts:FindFirstChild("StickyPartsTouchDetection") then
        Player.PlayerScripts.StickyPartsTouchDetection.Disabled = Value
    end
end})

```

```

local createGrabLineCopy, extendGrabLineCopy
local grabFolder = ReplicatedStorage:FindFirstChild("GrabEvents")
if grabFolder then
    local originalCreate = grabFolder:FindFirstChild("CreateGrabLine")
    local originalExtend = grabFolder:FindFirstChild("ExtendGrabLine")
    if originalCreate then createGrabLineCopy = originalCreate:Clone() end
    if originalExtend then extendGrabLineCopy = originalExtend:Clone() end
end

```

```

end
DefenseGroup:AddToggle("AntiLagToggle", {Text="アンチラグ", Default=false,
Callback=function(Value)
    if Value then
        local grabFolder = ReplicatedStorage:FindFirstChild("GrabEvents")
        if grabFolder then
            local create = grabFolder:FindFirstChild("CreateGrabLine")
            local extend = grabFolder:FindFirstChild("ExtendGrabLine")
            if create and create:IsA("RemoteEvent") then create:Destroy() end
            if extend and extend:IsA("RemoteEvent") then extend:Destroy() end
        end
        for _, v in ipairs(workspace:GetDescendants()) do
            if v:IsA("Beam") or v.Name:lower():find("line") then v:Destroy() end
        end
    end
else
    local grabFolder = ReplicatedStorage:FindFirstChild("GrabEvents")
    if grabFolder then
        if createGrabLineCopy and not grabFolder:FindFirstChild("CreateGrabLine") then
            local restoredCreate = createGrabLineCopy:Clone()
            restoredCreate.Parent = grabFolder
        end
        if extendGrabLineCopy and not grabFolder:FindFirstChild("ExtendGrabLine") then
            local restoredExtend = extendGrabLineCopy:Clone()
            restoredExtend.Parent = grabFolder
        end
    end
end
end
end}})

```

```

DefenseExtra:AddToggle("PaintDeleteToggle", {Text="アンチペイント", Default=false,
Callback=function(state)
    if state then deleteAllPaintParts() watchNewPaintParts() setTouchQuery(false)
    else restorePaintParts() disconnectWatchers() setTouchQuery(true) end
end}})

```

```

local autoGucciActive = false
DefenseExtra:AddToggle("AutoGucciToggle", {Text="アンチグッチ (ブロブマン)",
Default=false, Callback=function(Value)
    autoGucciActive = Value
    if Value then
        startAntiGucci()
        notify("システム", "アンチグッチ 起動中", 3)
        task.spawn(function()
            while autoGucciActive do
                local toysFolder = Workspace:FindFirstChild(Player.Name.."SpawnedInToys")
                local blobExists = toysFolder and toysFolder:FindFirstChild("CreatureBlobman")
                if not blobExists then
                    stopAntiGucci()
                end
            end
        end)
    end
end

```

```

spawnBlobman()
notify("システム", "ブロブマン消失、再召喚", 3)
local retries = 0
repeat
    task.wait(0.2)
    retries = retries + 1
    toysFolder = Workspace:FindFirstChild(Player.Name.."SpawnedInToys")
until (toysFolder and toysFolder:FindFirstChild("CreatureBlobman")) or retries >
25 or not autoGucciActive
    if autoGucciActive and toysFolder and
toysFolder:FindFirstChild("CreatureBlobman") then
        startAntiGucci()
        notify("システム", "ブロブマン復活", 3)
    end
end
task.wait(0.5)
end
end)
else
    autoGucciActive = false
    stopAntiGucci()
    notify("システム", "アンチグッチ 停止", 3)
end
end})

```

```

local autoGucciActiveTrain = false
DefenseExtra:AddToggle("AutoGucciToggle", {Text="アンチグッチ (電車)", Default=false,
Callback=function(Value)
    autoGucciActiveTrain = Value
    if Value then
        startAntiGucciTrain()
        notify("システム", "アンチグッチ(電車) 起動中", 3)
        task.spawn(function()
            while autoGucciActiveTrain do
                local trainFolder = workspace.Map.AlwaysHereTweenedObjects
                local trainExists = trainFolder and trainFolder:FindFirstChild("Train")
                if not trainExists then
                    stopAntiGucciTrain()
                    notify("システム", "電車消失", 3)
                    local retries = 0
                    repeat
                        task.wait(0.2)
                        retries = retries + 1
                        trainFolder = workspace.Map.AlwaysHereTweenedObjects
                    until (trainFolder and trainFolder:FindFirstChild("Train")) or retries > 25 or not
autoGucciActiveTrain
                    if autoGucciActiveTrain and trainFolder and trainFolder:FindFirstChild("Train")
then

```

```

        startAntiGucciTrain()
        notify("システム", "電車復活", 3)
    end
end
task.wait(0.5)
end
end)
else
    autoGucciActiveTrain = false
    stopAntiGucciTrain()
    notify("システム", "アンチグッチ(電車) 停止", 3)
end
end})
end})

```

-- Anti Input Lag (Item Loop)

```

local ToyList = {
    ["ココナッツ"]="FoodCoconut", ["バナナ"]="FoodBanana", ["ポテト"]="FoodFrenchFries", ["肉串"]="FoodMeatStick",
    ["うんち"]="PoopPile", ["ドーナツ"]="FoodDonut", ["ケーキ"]="FoodCakePink", ["ハンバーガー"]="FoodHamburger",
    ["ピザ"]="FoodPizzaCheese", ["ホットドッグ"]="FoodHotdog", ["キノコ"]="FoodMushroomPoison",
    ["バンジョー"]="InstrumentGuitarBanjo", ["バイオリン"]="InstrumentGuitarViolin", ["ウクレレ"]="InstrumentGuitarUkulele",
    ["サクソス"]="InstrumentWoodwindSaxophone", ["ブブゼラ"]="InstrumentBrassVuvuzela", ["ボンゴ"]="InstrumentDrumBongos",
    ["マイク"]="InstrumentVoiceMicrophone", ["ペパロニ"]="FoodPizzaPepperoni", ["ピアノ"]="InstrumentPianoMelodica",
    ["パン"]="FoodBread", ["卵"]="FoodDippyEgg", ["マヨネーズ"]="FoodMayonnaise", ["白マグカップ"]="CupMugWhite",
    ["オカリナ"]="InstrumentWoodwindOcarina", ["キラキラうんち"]="PoopPileSparkle", ["茶マグカップ"]="CupMugBrown",
    ["トランペット"]="InstrumentBrassTrumpet", ["スネアドラム"]="InstrumentDrumSnare",
}
local displayNames = {}
for name,_ in pairs(ToyList) do table.insert(displayNames, name) end
table.sort(displayNames)
_G.AntiInputLagItem = ToyList["ハンバーガー"]
_G.AntiInputLagRunning = false
local AntiInputLagTask = nil

```

```

DefenseExtra:AddDropdown("AntiInputLagToy", {
    Values = displayNames,
    Default = 1,
    Multi = false,
    Text = "使用アイテム",
    Callback = function(Value)
        local selected = Value or "ハンバーガー"
    end
})

```

```

    if ToyList[selected] then
        _G.AntiInputLagItem = ToyList[selected]
        notify("アイテム変更", selected.." に設定", 2)
    end
end,
}))

local function AntiInputLagLoop()
    local plr = LocalPlayer
    local SpawnRemote = ReplicatedStorage:FindFirstChild("MenuToys") and
ReplicatedStorage.MenuToys:FindFirstChild("SpawnToyRemoteFunction")
    if not SpawnRemote then notify("エラー", "SpawnToyRemoteFunction が見つかりません",
3) return end
    while _G.AntiInputLagRunning do
        local char = plr.Character
        local hrp = char and char:FindFirstChild("HumanoidRootPart")
        if not hrp then task.wait() continue end
        local toysFolder = Workspace:FindFirstChild(plr.Name.."SpawnedInToys")
        if not toysFolder then task.wait() continue end
        local toy = toysFolder:FindFirstChild(_G.AntiInputLagItem)
        if not toy then
            pcall(function() SpawnRemote:InvokeServer(_G.AntiInputLagItem, hrp.CFrame *
CFrame.new(0,5,0), Vector3.zero) end)
            task.wait()
            continue
        end
        local holdPart = toy:FindFirstChild("HoldPart")
        if holdPart then
            local holdingPlayer = holdPart:FindFirstChild("HoldingPlayer")
            holdingPlayer = holdingPlayer and holdingPlayer.Value
            if holdingPlayer and holdingPlayer ~= plr then
                pcall(function()
                    if holdPart:FindFirstChild("DropItemRemoteFunction") then
                        holdPart.DropItemRemoteFunction:InvokeServer(toy, hrp.CFrame *
CFrame.new(0,2000,0), Vector3.zero)
                    end
                end)
                if toy and toy.Parent then pcall(function() toy:Destroy() end) end
            else
                pcall(function()
                    if holdPart:FindFirstChild("HoldItemRemoteFunction") then
                        holdPart.HoldItemRemoteFunction:InvokeServer(toy, char)
                        task.wait()
                    end
                    if holdPart:FindFirstChild("DropItemRemoteFunction") then
                        holdPart.DropItemRemoteFunction:InvokeServer(toy, hrp.CFrame *
CFrame.new(0,2000,0), Vector3.zero)
                    end
                end)
            end
        end
    end
end

```

```

        end)
    end
end
task.wait()
end
end

local AntiInputLagToggleObj = DefenseExtra:AddToggle("AntiInputLagLoopToggle", {
    Text = "アンチ入カラグ (アイテムループ)",
    Default = false,
    Callback = function(Value)
        _G.AntiInputLagRunning = Value
        if Value then
            if AntiInputLagTask then task.cancel(AntiInputLagTask) AntiInputLagTask = nil end
            AntiInputLagTask = task.spawn(AntiInputLagLoop)
            notify("アンチ入カラグ", "開始", 2)
        else
            if AntiInputLagTask then task.cancel(AntiInputLagTask) AntiInputLagTask = nil end
            pcall(function()
                local toysFolder =
Workspace:FindFirstChild(LocalPlayer.Name.."SpawnedInToys")
                if toysFolder then
                    local toy = toysFolder:FindFirstChild(_G.AntiInputLagItem)
                    if toy then
                        local DestroyToy = ReplicatedStorage:FindFirstChild("MenuToys") and
ReplicatedStorage.MenuToys:FindFirstChild("DestroyToy")
                        if DestroyToy then DestroyToy:FireServer(toy) end
                    end
                end
            end)
            notify("アンチ入カラグ", "停止", 2)
        end
    end,
})

```

```

-- Shuriken Anti Kick
local tpActive = false
DefenseExtra:AddToggle("ShurikenAntiKick", {
    Text = "アンチキック",
    Default = false,
    Callback = function(Value)
        _G.ShurikenAntiKick = Value
        local function ClearKunai()
            local plr = game.Players.LocalPlayer
            local inv = workspace:FindFirstChild(plr.Name.."SpawnedInToys")
            local destroyrem = game.ReplicatedStorage:FindFirstChild("MenuToys") and
game.ReplicatedStorage.MenuToys:FindFirstChild("DestroyToy")
            if inv and destroyrem then

```

```

        for _, v in pairs(inv:GetChildren()) do
            if v.Name == "AntiKick" or v.Name == "NinjaShuriken" then
                pcall(function() destroyrem:FireServer(v) end)
            end
        end
    end
end
end
if Value then
    task.spawn(function()
        local plr = game.Players.LocalPlayer
        local ReplicatedStorage = game:GetService("ReplicatedStorage")
        local setOwner =
ReplicatedStorage:WaitForChild("GrabEvents"):WaitForChild("SetNetworkOwner")
        local stickyEvent =
ReplicatedStorage:WaitForChild("PlayerEvents"):WaitForChild("StickyPartEvent")
        local spawnRemote = ReplicatedStorage.MenuToys.SpawnToyRemoteFunction
        local destroyrem =
ReplicatedStorage:WaitForChild("MenuToys"):WaitForChild("DestroyToy")
        local canSpawn = plr:WaitForChild("CanSpawnToy")
        local function getHRP()
            if plr.Character and plr.Character:FindFirstChild("HumanoidRootPart") then
return plr.Character.HumanoidRootPart
            else local character = plr.CharacterAdded:Wait() return
character:WaitForChild("HumanoidRootPart") end
        end
        local function CheckForHome()
            if not workspace.PlotItems.PlayersInPlots:FindFirstChild(plr.Name) then return
false end
        end
        for _, v in pairs(workspace.Plots:GetChildren()) do
            local sign = v:FindFirstChild("PlotSign")
            local owners = sign and sign:FindFirstChild("ThisPlotsOwners")
            if owners then
                for _, b in pairs(owners:GetChildren()) do
                    if b.Value == plr.Name then
                        local folder = workspace.PlotItems:FindFirstChild(v.Name)
                        if folder then return true, folder end
                    end
                end
            end
        end
        return false
    end)
    local function StickKunai(kunai)
        if not kunai or not kunai:FindFirstChild("StickyPart") then return end
        local currentHRP = getHRP()
        if not currentHRP then return end
        if kunai:FindFirstChild("SoundPart") then

```

```

        if not kunai.SoundPart:FindFirstChild("PartOwner") or
kunai.SoundPart.PartOwner.Value ~= plr.Name then
            setOwner:FireServer(kunai.SoundPart, kunai.SoundPart.CFrame)
        end
    end
    local firePart = currentHRP:FindFirstChild("FirePlayerPart") or
currentHRP:WaitForChild("FirePlayerPart", 5)
    if firePart then
        stickyEvent:FireServer(kunai.StickyPart, firePart,
CFrame.new(0,0,0)*CFrame.Angles(0,math.rad(90),math.rad(90)))
    end
    for _, obj in pairs(kunai:GetChildren()) do
        if obj.Name == "Pyramid" then
            obj.CanTouch=false; obj.CanCollide=false; obj.CanQuery=false;
obj.Transparency=0
            if not obj:FindFirstChild("Highlight") then
                local high = Instance.new("Highlight", obj)
                high.FillColor = Color3.fromRGB(0,0,0)
            end
            elseif obj.Name == "Main" then
                obj.CanTouch=false; obj.CanCollide=false; obj.CanQuery=false;
obj.Transparency=0
                if not obj:FindFirstChild("Highlight") then
                    local high = Instance.new("Highlight", obj)
                    high.FillColor = Color3.fromRGB(255,255,255)
                end
                elseif obj:IsA("BasePart") then
                    obj.CanTouch=false; obj.CanCollide=false; obj.CanQuery=false;
obj.Transparency=1
                end
            end
        end
        local function SpawnToy(name)
            local t = tick()
            while not canSpawn.Value do
                if not _G.ShurikenAntiKick or tick() - t > 5 then return nil end
                task.wait(0.1)
            end
            local currentHRP = getHRP()
            if currentHRP then
                task.spawn(function()
                    pcall(function() spawnRemote:InvokeServer(name, currentHRP.CFrame *
CFrame.new(0,12,20), Vector3.zero) end)
                end)
            end
            local boolik, house = CheckForHome()
            local inv = workspace:FindFirstChild(plr.Name.."SpawnedInToys")
            if boolik and house then return house:WaitForChild(name, 2)

```

```

        elseif not workspace.PlotItems.PlayersInPlots:FindFirstChild(plr.Name) and inv
then return inv:WaitForChild(name, 2) end
        return nil
    end
    while _G.ShurikenAntiKick do
        task.wait(0.005)
        if not plr.Character or not plr.Character:FindFirstChild("Humanoid") or
plr.Character.Humanoid.Health <= 0 then continue end
        local inv = workspace:FindFirstChild(plr.Name.."SpawnedInToys")
        local kunai = inv and inv:FindFirstChild("NinjaShuriken")
        if workspace.PlotItems.PlayersInPlots:FindFirstChild(plr.Name) then
            local boolik, house = CheckForHome()
            if boolik and house and workspace.Plots:FindFirstChild(house.Name) then
                local sign = workspace.Plots[house.Name]:FindFirstChild("PlotSign")
                if sign and sign.ThisPlotsOwners.Value.TimeRemainingNum.Value > 89
then
                    kunai = SpawnToy("NinjaShuriken")
                    if kunai == nil then continue end
                    kunai.Name = "AntiKick"
                    StickKunai(kunai)
                end
            end
            if not kunai then
                if workspace.PlotItems.PlayersInPlots:FindFirstChild(plr.Name) then continue
end
                kunai = SpawnToy("NinjaShuriken")
                if kunai == nil then continue end
                kunai.Name = "AntiKick"
                if not kunai then continue end
            end
            repeat
                if kunai and kunai:FindFirstChild("StickyPart") and kunai.StickyPart.CanTouch
== true then
                    StickKunai(kunai)
                    kunai.Name = "AntiKick"
                end
                task.wait(0.3)
            until not kunai or not _G.ShurikenAntiKick or not
kunai:FindFirstChild("StickyPart") or kunai.StickyPart.CanTouch == false or not plr.Character
or not plr.Character:FindFirstChild("HumanoidRootPart") or not
kunai:FindFirstChild("StickyPart") or (plr.Character.HumanoidRootPart.Position -
kunai.StickyPart.Position).Magnitude >= 20
                if not kunai or not kunai:FindFirstChild("StickyPart") or not plr.Character or not
plr.Character:FindFirstChild("HumanoidRootPart") or
(plr.Character.HumanoidRootPart.Position - kunai.StickyPart.Position).Magnitude >= 20 then
ClearKunai() end
            pcall(function()

```

```

        repeat task.wait(0.05) until not _G.ShurikenAntiKick or notplr.Character or
notplr.Character:FindFirstChild("Humanoid") or not kunai or not
kunai:FindFirstChild("StickyPart") or not kunai.StickyPart:FindFirstChild("StickyWeld") or not
kunai.StickyPart.StickyWeld.Part1
        if not kunai or not kunai:FindFirstChild("StickyPart") or (plr.Character and
plr.Character:FindFirstChild("Humanoid") and plr.Character.Humanoid.Health <= 0) or not
kunai["StickyPart"]:FindFirstChild("StickyWeld").Part1 then ClearKunai() end
        end)
    end
end)
else
    _G.ShurikenAntiKick = false
    ClearKunai()
end
end
})

```

```

DefenseExtra:AddToggle("LoopTP", {Text="ループテレポート", Default=false,
Callback=function(Value)
    tpActive = Value
    local char = Player.Character or Player.CharacterAdded:Wait()
    local hrp = char:WaitForChild("HumanoidRootPart")
    local hum = char:FindFirstChildOfClass("Humanoid")
    if Value then
        if hum then hum.PlatformStand = true end
        task.spawn(function()
            while tpActive and hrp do
                local x = math.random(-500,500)
                local y = math.random(30,480)
                local z = math.random(-500,500)
                hrp.CFrame = CFrame.new(x,y,z)
                task.wait(0.03)
            end
        end)
    else
        if hum then hum.PlatformStand = false end
    end
end})

```

```

-- =====
-- Target Tab (ターゲット)
-- =====
local TargetGroup = Tabs.Target:AddLeftGroupbox("🎯 ターゲット操作")
local BlobGroup = Tabs.Target:AddRightGroupbox("💜 ブロブマン操作")
local WhitelistGroup = Tabs.Target:AddRightGroupbox("✅ ホワイティスト")

local selectedKickPlayer = nil
local kickLoopEnabled = false

```

```

local loopKillEnabled = false
local loopKickDualActive = false
local playerFlingActive = false
local flingBAV = nil
local originalPos = nil
local DestroyTargetGucciActive = false
local antiAntiKickActive = false
local antiAntiLagEnabled = false
local updownKickActive = false
local updownKickTask = nil

local function getPlayerList()
    local list = {}
    for _, plr in ipairs(PS:GetPlayers()) do
        if plr ~= Player then table.insert(list, plr.DisplayName .. " (" .. plr.Name .. ")") end
    end
    return list
end

local function getPlayerFromSelection(selection)
    if not selection then return nil end
    local username = selection:match("%((.-)%)")
    if username then return PS:FindFirstChild(username) end
    return nil
end

TargetGroup:AddDropdown("KickPlayerDropdown", {
    Values = getPlayerList(),
    Default = 1,
    Multi = false,
    Text = "ターゲット選択",
    Callback = function(Value) selectedKickPlayer = getPlayerFromSelection(Value) end,
})

TargetGroup:AddButton({Text="🔄 プレイヤーリスト更新", Func=function()
    Options.KickPlayerDropdown:SetValues(getPlayerList())
    Options.KickPlayerDropdown:SetValue(nil)
    selectedKickPlayer = nil
end})

TargetGroup:AddToggle("LoopKickToggle", {
    Text = "キック (クラブ連打)",
    Default = false,
    Callback = function(on)
        kickLoopEnabled = on
        local target = selectedKickPlayer
        if on and not target then if Toggles.LoopKickToggle then
Toggles.LoopKickToggle:SetValue(false) end return end
        if not on then kickLoopEnabled = false return end
        task.spawn(function()

```

```

local RS = game:GetService("ReplicatedStorage")
local RunService = game:GetService("RunService")
local GE = RS:WaitForChild("GrabEvents")
local myChar = Player.Character
local myRoot = myChar and myChar:FindFirstChild("HumanoidRootPart")
if not myRoot then return end
local savedPos = myRoot.CFrame
local dragging = false
local grabStartTime = 0
while kickLoopEnabled do
    if not target or not target.Parent then
        kickLoopEnabled = false
        if Toggles.LoopKickToggle then Toggles.LoopKickToggle:SetValue(false) end
        break
    end
    local tChar = target.Character
    local tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
    local tHum = tChar and tChar:FindFirstChild("Humanoid")
    myChar = Player.Character
    myRoot = myChar and myChar:FindFirstChild("HumanoidRootPart")
    if tRoot and tHum and tHum.Health > 0 and myRoot then
        tRoot.AssemblyLinearVelocity = Vector3.zero
        tRoot.AssemblyAngularVelocity = Vector3.zero
        tRoot.Velocity = Vector3.zero
        if not dragging then
            myRoot.CFrame = tRoot.CFrame
            myRoot.Velocity = Vector3.zero
            pcall(function()
                tHum.PlatformStand = true
                tHum.Sit = true
                GE.SetNetworkOwner:FireServer(tRoot, myRoot.CFrame)
                GE.CreateGrabLine:FireServer(tRoot, Vector3.zero, tRoot.Position, false)
            end)
            if grabStartTime == 0 then grabStartTime = tick() end
            if tick() - grabStartTime > 0.35 then
                dragging = true
                grabStartTime = 0
            end
        end
    else
        myRoot.CFrame = savedPos
        myRoot.Velocity = Vector3.zero
        local lockPos = savedPos * CFrame.new(0,17,0)
        tRoot.CFrame = lockPos
        tRoot.Velocity = Vector3.zero
        tRoot.RotVelocity = Vector3.zero
        tHum.PlatformStand = true
        tHum.Sit = false
        pcall(function()

```



```

        local attackStart = tick()
        while tick() - attackStart < 0.35 do
            if not loopKillEnabled or not tRoot.Parent then break end
            myRoot.CFrame = tRoot.CFrame * CFrame.new(0,0,2)
            myRoot.Velocity = Vector3.zero
            pcall(function()
                GE.SetNetworkOwner:FireServer(tRoot, myRoot.CFrame)
                tHum:ChangeState(Enum.HumanoidStateType.Dead)
                tHum.Health = 0
                GE.CreateGrabLine:FireServer(tRoot, Vector3.zero, tRoot.Position,
false)
                GE.DestroyGrabLine:FireServer(tRoot)
            end)
            RunService.Heartbeat:Wait()
        end
        if myRoot then myRoot.CFrame = currentPos myRoot.Velocity = Vector3.zero
end
        task.wait(1.2)
    else
        task.wait(0.5)
    end
end
    local char = Player.Character
    local root = char and char:FindFirstChild("HumanoidRootPart")
    if root then root.Velocity = Vector3.zero end
end)
else
    loopKillEnabled = false
end
end
end
}))

```

```

TargetGroup.AddToggle("LoopKickToggle", {
    Text = "ループキック (クラブ+ブロブ)",
    Default = false,
    Callback = function(on)
        kickLoopEnabled = on
        local target = selectedKickPlayer
        if on and not target then
            if Toggles.LoopKickToggle then Toggles.LoopKickToggle:SetValue(false) end
            return
        end
        local char = Player.Character
        local hum = char and char:FindFirstChild("Humanoid")
        local seat = hum and hum.SeatPart
        if on and (not seat or seat.Parent.Name ~= "CreatureBlobman") then
            if Toggles.LoopKickToggle then Toggles.LoopKickToggle:SetValue(false) end
            return
        end
    end
})

```

```

end
if not on then kickLoopEnabled = false return end
task.spawn(function()
    local RS = game:GetService("ReplicatedStorage")
    local GE = RS:WaitForChild("GrabEvents")
    local RunService = game:GetService("RunService")
    local blob = seat.Parent
    local blobRoot = blob:FindFirstChild("HumanoidRootPart") or blob.PrimaryPart
    local scriptObj = blob:FindFirstChild("BlobmanSeatAndOwnerScript")
    local CG = scriptObj and scriptObj:FindFirstChild("CreatureGrab")
    local CD = scriptObj and scriptObj:FindFirstChild("CreatureDrop")
    local R_Det = blob:FindFirstChild("RightDetector")
    local R_Weld = R_Det and (R_Det:FindFirstChild("RightWeld") or
R_Det:FindFirstChildWhichIsA("Weld"))
    local SavedPos = blobRoot.CFrame
    local tChar = target.Character
    local tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
    if tRoot and blobRoot then
        local bringStart = tick()
        while tick() - bringStart < 0.35 do
            if not kickLoopEnabled then break end
            blobRoot.CFrame = tRoot.CFrame
            blobRoot.Velocity = Vector3.zero
            pcall(function()
                if CG and R_Det then CG:FireServer(R_Det, tRoot, R_Weld) end
                GE.CreateGrabLine:FireServer(tRoot, Vector3.zero, tRoot.Position, false)
                GE.SetNetworkOwner:FireServer(tRoot, blobRoot.CFrame)
            end)
            RunService.Heartbeat:Wait()
        end
        blobRoot.CFrame = SavedPos
        blobRoot.Velocity = Vector3.zero
        task.wait(0.05)
    end
    local packetTimer = 0
    while kickLoopEnabled do
        if not target or not target.Parent or not target.Character then break end
        local tChar = target.Character
        local tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
        local tHum = tChar and tChar:FindFirstChild("Humanoid")
        if tRoot and tHum and tHum.Health > 0 and blobRoot then
            blobRoot.CFrame = SavedPos
            blobRoot.Velocity = Vector3.zero
            local lockPos = SavedPos * CFrame.new(0,23,0)
            tRoot.CFrame = lockPos
            tRoot.Velocity = Vector3.zero
            tRoot.RotVelocity = Vector3.zero
            if tick() - packetTimer > 0.05 then

```

```

        packetTimer = tick()
        pcall(function()
            tHum.PlatformStand = true
            tHum.Sit = true
            GE.SetNetworkOwner:FireServer(tRoot, lockPos)
            if R_Det then
                local weld = R_Det:FindFirstChild("RightWeld") or
R_Det:FindFirstChildWhichIsA("Weld")
                if weld then CD:FireServer(weld) end
            end
            GE.DestroyGrabLine:FireServer(tRoot)
            if R_Det then CG:FireServer(R_Det, tRoot, R_Weld) end
            GE.CreateGrabLine:FireServer(tRoot, Vector3.zero, tRoot.Position, false)
        end)
    end
else
    blobRoot.CFrame = SavedPos
    blobRoot.Velocity = Vector3.zero
end
if not kickLoopEnabled then break end
RunService.Heartbeat:Wait()
end
kickLoopEnabled = false
if Toggles.LoopKickToggle then Toggles.LoopKickToggle:SetValue(false) end
if blobRoot then blobRoot.CFrame = SavedPos blobRoot.Velocity = Vector3.zero end
end)
end
})

```

```

TargetGroup.AddToggle("DualHandLoopKick", {
    Text = "両手ループキック",
    Default = false,
    Callback = function(on)
        loopKickDualActive = on
        if on then
            if not selectedKickPlayer then
                notify("エラー", "先にターゲットを選択してください", 3)
                Toggles.DualHandLoopKick:SetValue(false)
                return
            end
        end
        task.spawn(function()
            local lastTargetCharDual = nil
            local bp = nil
            while loopKickDualActive do
                local target = selectedKickPlayer
                local char = Player.Character
                local hum = char and char:FindFirstChild("Humanoid")
                local seat = hum and hum.SeatPart
            end
        end)
    end
})

```

```

    if not seat or not target or not target.Parent then task.wait(0.5) continue end
    local seatParent = seat.Parent
    local grab = seatParent:FindFirstChild("BlobmanSeatAndOwnerScript") and
seatParent.BlobmanSeatAndOwnerScript:FindFirstChild("CreatureGrab")
    local drop = seatParent:FindFirstChild("BlobmanSeatAndOwnerScript") and
seatParent.BlobmanSeatAndOwnerScript:FindFirstChild("CreatureDrop")
    if not grab or not drop then task.wait(0.5) continue end
    local leftDet = seatParent:FindFirstChild("LeftDetector")
    local rightDet = seatParent:FindFirstChild("RightDetector")
    local leftWeld = leftDet and leftDet:FindFirstChild("LeftWeld")
    local rightWeld = rightDet and rightDet:FindFirstChild("RightWeld")
    local hrp = char:FindFirstChild("HumanoidRootPart")
    local targetChar = target.Character
    local targetHRP = targetChar and
targetChar:FindFirstChild("HumanoidRootPart")
    local targetHum = targetChar and targetChar:FindFirstChild("Humanoid")
    if targetHRP and targetHum and targetHum.Health > 0 then
        if targetChar ~= lastTargetCharDual then
            lastTargetCharDual = targetChar
            if bp then bp:Destroy() bp = nil end
            if hrp then hrp.CFrame = targetHRP.CFrame * CFrame.new(0,25,0) end
            task.wait(0.2)
            grab:FireServer(leftDet, targetHRP, leftWeld)
            task.wait(0.3)
            drop:FireServer(leftWeld, targetHRP)
            task.wait(0.1)
            bp = Instance.new("BodyPosition")
            bp.Position = Vector3.new(0,999999,0)
            bp.MaxForce = Vector3.new(math.huge,math.huge,math.huge)
            bp.Parent = targetHRP
            grab:FireServer(leftDet, targetHRP, leftWeld)
            task.wait(0.2)
            drop:FireServer(leftWeld, targetHRP)
        end
        grab:FireServer(leftDet, targetHRP, leftWeld)
        task.wait()
        drop:FireServer(leftWeld, targetHRP)
        task.wait()
        grab:FireServer(rightDet, targetHRP, rightWeld)
        task.wait()
        drop:FireServer(rightWeld, targetHRP)
        task.wait()
        grab:FireServer(leftDet, targetHRP, leftWeld)
        grab:FireServer(rightDet, targetHRP, rightWeld)
        task.wait()
        drop:FireServer(leftWeld, targetHRP)
        drop:FireServer(rightWeld, targetHRP)
        task.wait()
    end

```

})

```

TargetGroup:AddToggle("PlayerFlingBtn", {
    Text = "フリング",
    Default = false,
    Callback = function(on)
        playerFlingActive = on
        if on then
            if not selectedKickPlayer then
                notify("システム", "先にターゲットを選択してください", 3)
                Toggles.PlayerFlingBtn:SetValue(false)
            return
        end
        local RunService = game:GetService("RunService")
        local MyChar = Player.Character
        local MyRoot = MyChar and MyChar:FindFirstChild("HumanoidRootPart")
        if MyRoot then originalPos = MyRoot.CFrame end
        notify("フリング", "起動中。動かないでください。", 3)
        task.spawn(function()
            while playerFlingActive do
                local target = selectedKickPlayer
                local char = Player.Character
                local hrp = char and char:FindFirstChild("HumanoidRootPart")
                local hum = char and char:FindFirstChild("Humanoid")
                if not hrp or not hum then task.wait(0.5) continue end
                if target and target.Parent then
                    local tChar = target.Character
                    local tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
                    local tHum = tChar and tChar:FindFirstChild("Humanoid")
                    if tRoot and tHum and tHum.Health > 0 then
                        if not flingBAV or flingBAV.Parent ~= hrp then
                            if flingBAV then flingBAV:Destroy() end
                            flingBAV = Instance.new("BodyAngularVelocity")
                            flingBAV.Name = "MaestroSpin"
                            flingBAV.MaxTorque = Vector3.new(math.huge,math.huge,math.huge)
                            flingBAV.AngularVelocity = Vector3.new(0,10000,0)
                            flingBAV.P = 10000
                            flingBAV.Parent = hrp
                        end
                    end
                end
            end
        end)
    end
})

```

```

        end
        for _, part in pairs(char:GetDescendants()) do
            if part:IsA("BasePart") then part.CanCollide = false end
        end
        local loop = RunService.Heartbeat:Connect(function()
            if not playerFlingActive or not tRoot or not tRoot.Parent then return end
            hrp.CFrame = tRoot.CFrame
            hrp.Velocity = Vector3.zero
        end)
        local startTime = tick()
        while tick() - startTime < 1.5 do
            if not playerFlingActive or not tRoot.Parent then break end
            task.wait(0.1)
        end
        if loop then loop:Disconnect() end
    else
        task.wait(0.2)
    end
else
    playerFlingActive = false
    Toggles.PlayerFlingBtn:SetValue(false)
end
task.wait(0.1)
end
if flingBAV then flingBAV:Destroy() flingBAV = nil end
local char = Player.Character
if char then
    for _, part in pairs(char:GetDescendants()) do
        if part:IsA("BasePart") then part.CanCollide = true end
    end
    local hrp = char:FindFirstChild("HumanoidRootPart")
    if hrp then
        hrp.RotVelocity = Vector3.zero
        hrp.Velocity = Vector3.zero
        if originalPos then hrp.CFrame = originalPos end
    end
end
end)
else
    playerFlingActive = false
    if flingBAV then flingBAV:Destroy() flingBAV = nil end
    local char = Player.Character
    local hrp = char and char:FindFirstChild("HumanoidRootPart")
    if hrp then hrp.RotVelocity = Vector3.zero hrp.Velocity = Vector3.zero end
end
end
end
})

```

```

_G.AutoSitBlobZ = true
BlobGroup:AddToggle("AutoSitZ", {Text="自動着席 [Z]", Default=true,
Callback=function(Value) _G.AutoSitBlobZ = Value end})
UserInputService.InputBegan:Connect(function(input, processed)
    if not processed and input.KeyCode == Enum.KeyCode.Z and _G.AutoSitBlobZ then
        local plr = game.Players.LocalPlayer
        local char = plr.Character
        local hrp = char and char:FindFirstChild("HumanoidRootPart")
        local hum = char and char:FindFirstChild("Humanoid")
        if not hrp or not hum then return end
        local folderName = plr.Name .. "SpawnedInToys"
        local folder = workspace:FindFirstChild(folderName)
        local blob = folder and folder:FindFirstChild("CreatureBlobman")
        if not blob then
            task.spawn(function() pcall(function()
game.ReplicatedStorage.MenuToys.SpawnToyRemoteFunction:InvokeServer("CreatureBlob
man", hrp.CFrame, Vector3.zero) end) end)
                if not folder then folder = workspace:WaitForChild(folderName, 5) end
                if folder then blob = folder:WaitForChild("CreatureBlobman", 5) end
            end
            if blob then
                local seat = blob:WaitForChild("VehicleSeat", 5)
                if seat then
                    local t = tick()
                    repeat
                        if not hum.SeatPart then
                            hrp.CFrame = seat.CFrame + Vector3.new(0,1,0)
                            hrp.Velocity = Vector3.zero
                            seat:Sit(hum)
                        end
                        game:GetService("RunService").Heartbeat:Wait()
                    until hum.SeatPart == seat or tick() - t > 1.5
                end
            end
        end
    end)

```

```

-- Blob Fly
local blobMasterSwitch = true
local blobFlyActive = false
local bvInstance, bgInstance
local blobFlySpeed = 50
UserInputService.InputBegan:Connect(function(input, gameProcessed)
    if not gameProcessed and input.KeyCode == Enum.KeyCode.R then
        if blobMasterSwitch then
            blobFlyActive = not blobFlyActive
            if not blobFlyActive then
                if bvInstance then bvInstance:Destroy() bvInstance = nil end

```

```

        if bgInstance then bgInstance:Destroy() bgInstance = nil end
    end
end
end)
local function GetBlobRoot()
    local char = Player.Character
    local hum = char and char:FindFirstChild("Humanoid")
    if hum and hum.SeatPart and hum.SeatPart.Parent and hum.SeatPart.Parent.Name ==
"CreatureBlobman" then
        return hum.SeatPart.Parent:FindFirstChild("HumanoidRootPart") or
hum.SeatPart.Parent.PrimaryPart
    end
    local folder = workspace:FindFirstChild(Player.Name.."SpawnedInToys")
    if folder then
        local blob = folder:FindFirstChild("CreatureBlobman")
        if blob then return blob:FindFirstChild("HumanoidRootPart") or blob.PrimaryPart end
    end
    return nil
end
R.Heartbeat:Connect(function()
    if not blobFlyActive or not blobMasterSwitch then
        if bvInstance then bvInstance:Destroy() bvInstance = nil end
        if bgInstance then bgInstance:Destroy() bgInstance = nil end
        return
    end
    local root = GetBlobRoot()
    if root then
        if not root:FindFirstChild("BlobFlyVelocity") then
            bvInstance = Instance.new("BodyVelocity")
            bvInstance.Name = "BlobFlyVelocity"
            bvInstance.MaxForce = Vector3.new(math.huge, math.huge, math.huge)
            bvInstance.P = 10000
            bvInstance.Parent = root
        else bvInstance = root.BlobFlyVelocity end
        if not root:FindFirstChild("BlobFlyGyro") then
            bgInstance = Instance.new("BodyGyro")
            bgInstance.Name = "BlobFlyGyro"
            bgInstance.MaxTorque = Vector3.new(math.huge, math.huge, math.huge)
            bgInstance.P = 20000
            bgInstance.D = 100
            bgInstance.Parent = root
        else bgInstance = root.BlobFlyGyro end
        local cam = workspace.CurrentCamera
        local moveDir = Vector3.zero
        if UserInputService:IsKeyDown(Enum.KeyCode.W) then moveDir = moveDir +
cam.CFrame.LookVector end
    end
end)

```

```

        if UserInputService.IsKeyDown(Enum.KeyCode.S) then moveDir = moveDir -
cam.CFrame.LookVector end
        if UserInputService.IsKeyDown(Enum.KeyCode.A) then moveDir = moveDir -
cam.CFrame.RightVector end
        if UserInputService.IsKeyDown(Enum.KeyCode.D) then moveDir = moveDir +
cam.CFrame.RightVector end
        if UserInputService.IsKeyDown(Enum.KeyCode.Space) then moveDir = moveDir +
Vector3.new(0,1,0) end
        if UserInputService.IsKeyDown(Enum.KeyCode.LeftControl) then moveDir = moveDir -
Vector3.new(0,1,0) end
        if bvInstance then bvInstance.Velocity = moveDir * blobFlySpeed end
        if bgInstance then bgInstance.CFrame = cam.CFrame end
    else
        if bvInstance then bvInstance:Destroy() bvInstance = nil end
        if bgInstance then bgInstance:Destroy() bgInstance = nil end
    end
end)

```

```

TargetGroup.AddToggle("DestroyTargetGucci", {
    Text = "グッチ破壊 (着席)",
    Default = false,
    Callback = function(Value)
        DestroyTargetGucciActive = Value
        if Value then
            if not selectedKickPlayer then
                notify("エラー", "ターゲットを選択してください", 3)
                Toggles.DestroyTargetGucci:SetValue(false)
                return
            end
            local char = Player.Character
            local root = char and char:FindFirstChild("HumanoidRootPart")
            if not root then return end
            local SafeSpot = root.CFrame
            local RunService = game:GetService("RunService")
            local folderName = selectedKickPlayer.Name .. "SpawnedInToys"
            notify("システム", "フォルダ待機中: " .. folderName, 3)
            task.spawn(function()
                while DestroyTargetGucciActive do
                    if not selectedKickPlayer or not selectedKickPlayer.Parent then
                        notify("システム", "プレイヤーが退出しました", 3)
                        DestroyTargetGucciActive = false
                        Toggles.DestroyTargetGucci:SetValue(false)
                        break
                    end
                    local toysFolder = workspace:FindFirstChild(folderName)
                    if not toysFolder then task.wait(1) else
                        local foundBlob = false
                        for _, obj in ipairs(toysFolder:GetChildren()) do

```

```

        if not DestroyTargetGucciActive then break end
        if obj.Name == "CreatureBlobman" then
            foundBlob = true
            local seat = obj:FindFirstChild("VehicleSeat") or
obj:FindFirstChildWhichIsA("VehicleSeat", true)
            if seat then
                local myChar = Player.Character
                local myRoot = myChar and
myChar:FindFirstChild("HumanoidRootPart")
                local myHum = myChar and myChar:FindFirstChild("Humanoid")
                if myRoot and myHum then
                    if myHum.SeatPart ~= seat then
                        notify("ターゲット", "破壊中", 1)
                        local magnetConnection
                        magnetConnection = RunService.Stepped:Connect(function()
                            if myRoot and seat then
                                myRoot.CFrame = seat.CFrame
                                myRoot.Velocity = Vector3.zero
                                if obj.PrimaryPart then
                                    obj.PrimaryPart.Velocity = Vector3.zero
                                    obj.PrimaryPart.RotVelocity = Vector3.zero
                                end
                            end
                        end)
                        local sitStart = tick()
                        while tick() - sitStart < 1 do
                            if not DestroyTargetGucciActive then break end
                            if myHum.SeatPart == seat then break end
                            seat:Sit(myHum)
                            task.wait()
                        end
                        if magnetConnection then magnetConnection:Disconnect() end
                        if myHum.SeatPart == seat then
                            task.wait(0.3)
                            myHum.Sit = false
                            myHum.Jump = true
                            task.wait(0.05)
                            myRoot.CFrame = SafeSpot
                            myRoot.Velocity = Vector3.zero
                            notify("成功", "破壊完了", 1)
                            task.wait(0.5)
                        else
                            myRoot.CFrame = SafeSpot
                        end
                    end
                end
            end
        end
    end
end
end

```

```

        end
    end
    task.wait(1)
end
end)
else
    DestroyTargetGucciActive = false
    notify("システム", "グッチ破壊 停止", 2)
end
end
end
})

```

```

TargetGroup.AddButton({
    Text = "引き寄せ",
    Func = function()
        if not selectedKickPlayer then return end
        local char = Player.Character
        local hum = char and char:FindFirstChild("Humanoid")
        local seat = hum and hum.SeatPart
        if not seat or seat.Parent.Name ~= "CreatureBlobman" then return end
        local blob = seat.Parent
        local blobRoot = blob:FindFirstChild("HumanoidRootPart")
        local scriptObj = blob:FindFirstChild("BlobmanSeatAndOwnerScript")
        if not blobRoot or not scriptObj then return end
        local CG = scriptObj:FindFirstChild("CreatureGrab")
        local CD = scriptObj:FindFirstChild("CreatureDrop")
        local R_Det = blob:FindFirstChild("RightDetector")
        local R_Weld = R_Det and R_Det:FindFirstChild("RightWeld")
        local tChar = selectedKickPlayer.Character
        local tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
        if not tRoot then return end
        local home = blobRoot.CFrame
        blobRoot.CFrame = tRoot.CFrame
        blobRoot.Velocity = Vector3.new()
        blobRoot.RotVelocity = Vector3.new()
        task.wait(0.3)
        pcall(function() CG:FireServer(R_Det, tRoot, R_Weld) end)
        task.wait(0.5)
        blobRoot.CFrame = home
        blobRoot.Velocity = Vector3.new()
        blobRoot.RotVelocity = Vector3.new()
        task.wait(0.05)
        for i = 1, 12 do
            tRoot.CFrame = home * CFrame.new(0,3,0)
            tRoot.Velocity = Vector3.new()
            tRoot.RotVelocity = Vector3.new()
            task.wait(0.03)
        end
    end
end

```

```

    for i = 1, 8 do
        local weld = R_Det:FindFirstChild("RightWeld")
        if weld then pcall(function() CD:FireServer(weld) end) end
        task.wait(0.03)
    end
end
end
}))

TargetGroup:AddToggle("DestroyAntiKickToggle", {
    Text = "アンチキック奪取",
    Default = false,
    Callback = function(Value)
        antiAntiKickActive = Value
        if Value then
            task.spawn(function()
                local SetNetOwner =
game:GetService("ReplicatedStorage").GrabEvents.SetNetworkOwner
                local LocalPlayer = game.Players.LocalPlayer
                local function invis_touch(part, cf) SetNetOwner:FireServer(part, cf) end
                local function CheckAndYeet(toy)
                    local part = toy:FindFirstChild("SoundPart")
                    if part then
                        invis_touch(part, part.CFrame)
                        if part:FindFirstChild("PartOwner") and part.PartOwner.Value ==
LocalPlayer.Name then
                            part.CFrame = CFrame.new(0,1000,0)
                        end
                    end
                end
                while antiAntiKickActive do
                    local target = selectedKickPlayer
                    if target then
                        local spawned = workspace:FindFirstChild(target.Name.."SpawnedInToys")
                        if spawned then
                            if spawned:FindFirstChild("NinjaKunai") then
                                CheckAndYeet(spawned.NinjaKunai) end
                                if spawned:FindFirstChild("NinjaShuriken") then
                                    CheckAndYeet(spawned.NinjaShuriken) end
                                if spawned:FindFirstChild("AntiKick") then
                                    CheckAndYeet(spawned.AntiKick) end
                                end
                            end
                        end
                        task.wait(0.1)
                    end
                end
            end)
        else
            antiAntiKickActive = false
        end
    end
end

```

```

end
}))

TargetGroup:AddToggle("AntiAntiInputLag", {
    Text = "アンチ入力ラグ対策",
    Default = false,
    Callback = function(on)
        antiAntiLagEnabled = on
        if not on then antiAntiLagEnabled = false return end
        task.spawn(function()
            local plr = game.Players.LocalPlayer
            local char = plr.Character
            local hrp = char:FindFirstChild("HumanoidRootPart")
            if not hrp then return end
            local burgers = {}
            for _, v in ipairs(workspace:GetDescendants()) do
                if v.Name == "FoodHamburger" and v:IsA("Model") and
v:FindFirstChild("HoldPart") then
                    burgers[#burgers+1] = v
                end
            end
            workspace.DescendantAdded:Connect(function(obj)
                if obj.Name == "FoodHamburger" and obj:IsA("Model") then
                    task.spawn(function()
                        local hp = obj:WaitForChild("HoldPart", 3)
                        if hp then burgers[#burgers+1] = obj end
                    end)
                end
            end)
            while antiAntiLagEnabled do
                for i = #burgers, 1, -1 do
                    local b = burgers[i]
                    if not b or not b.Parent or not b:FindFirstChild("HoldPart") then
                        table.remove(burgers, i)
                    else
                        local hp = b.HoldPart
                        pcall(function() hp.HoldItemRemoteFunction:InvokeServer(b, char) end)
                        task.wait()
                        pcall(function() hp.DropItemRemoteFunction:InvokeServer(b,
CFrame.new(hrp.Position + Vector3.new(0,-2000,0)), Vector3.zero) end)
                    end
                end
                task.wait()
            end
        end)
    end
}))

```

```

-- ===== 上下キック =====
local updownKickToggle = BlobGroup:AddToggle("UpDownKick", {
    Text = "上下キック",
    Default = false,
    Callback = function(on)
        updownKickActive = on
        if not on then
            if updownKickTask then
                task.cancel(updownKickTask)
                updownKickTask = nil
            end
            return
        end
        if not selectedKickPlayer then
            notify("エラー", "先にターゲットを選択してください", 3)
            updownKickToggle:SetValue(false)
            updownKickActive = false
            return
        end
        local function mountBlobman()
            local char = Player.Character
            if not char then return false end
            local hum = char:FindFirstChild("Humanoid")
            if not hum then return false end
            if hum.SeatPart and hum.SeatPart.Parent and hum.SeatPart.Parent.Name ==
"CreatureBlobman" then
                return true
            end
            local blob = nil
            local folderName = Player.Name .. "SpawnedInToys"
            local folder = workspace:FindFirstChild(folderName)
            if folder then
                blob = folder:FindFirstChild("CreatureBlobman")
            end
            if not blob then
                pcall(function()

game.ReplicatedStorage.MenuToys.SpawnToyRemoteFunction:InvokeServer("CreatureBlob
man", char.HumanoidRootPart.CFrame, Vector3.zero)
                end)
            if not folder then
                folder = workspace:WaitForChild(folderName, 5)
            end
            if folder then
                blob = folder:WaitForChild("CreatureBlobman", 5)
            end
            if not blob then return false end
        end
    end
}

```

```

        local seat = blob:FindFirstChild("VehicleSeat") or
blob:FindFirstChildWhichIsA("Seat")
        if not seat then return false end
        local root = char:FindFirstChild("HumanoidRootPart")
        if root then
            root.CFrame = seat.CFrame + Vector3.new(0,1,0)
            root.Velocity = Vector3.zero
            seat:Sit(hum)
            local t = tick()
            repeat
                task.wait(0.05)
            until hum.SeatPart == seat or tick() - t > 1.5
            return hum.SeatPart == seat
        end
        return false
    end

    if not mountBlobman() then
        notify("エラー", "ブロブマンに乗れませんでした", 3)
        updownKickToggle:SetValue(false)
        updownKickActive = false
        return
    end

    updownKickTask = task.spawn(function()
        local char = Player.Character
        local hum = char and char:FindFirstChild("Humanoid")
        local seat = hum and hum.SeatPart
        if not seat or seat.Parent.Name ~= "CreatureBlobman" then
            notify("エラー", "ブロブマンに乗っていません", 3)
            updownKickActive = false
            updownKickToggle:SetValue(false)
            return
        end
        local GE = ReplicatedStorage:WaitForChild("GrabEvents")
        local blob = seat.Parent
        local blobRoot = blob:FindFirstChild("HumanoidRootPart") or blob.PrimaryPart
        local scriptObj = blob:FindFirstChild("BlobmanSeatAndOwnerScript")
        local CG = scriptObj and scriptObj:FindFirstChild("CreatureGrab")
        local CD = scriptObj and scriptObj:FindFirstChild("CreatureDrop")
        local R_Det = blob:FindFirstChild("RightDetector")
        local R_Weld = R_Det and (R_Det:FindFirstChild("RightWeld") or
R_Det:FindFirstChildWhichIsA("Weld"))
        if not blobRoot or not CG or not CD or not R_Det or not R_Weld then
            notify("エラー", "ブロブマンに必要なパーツがありません", 3)
            updownKickActive = false
            updownKickToggle:SetValue(false)
            return
        end
    end)

```

```

end
local SavedPos = blobRoot.CFrame
local target = selectedKickPlayer
local tChar = target.Character
local tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
if tRoot and blobRoot then
    local bringStart = tick()
    while tick() - bringStart < 0.15 do
        if not updownKickActive then break end
        blobRoot.CFrame = tRoot.CFrame
        blobRoot.Velocity = Vector3.zero
        pcall(function()
            CG:FireServer(R_Det, tRoot, R_Weld)
            GE.CreateGrabLine:FireServer(tRoot, Vector3.zero, tRoot.Position, false)
            GE.SetNetworkOwner:FireServer(tRoot, blobRoot.CFrame)
        end)
        RunService.Heartbeat:Wait()
    end
    blobRoot.CFrame = SavedPos
    blobRoot.Velocity = Vector3.zero
    task.wait(0.05)
end
end

```

```

local packetTimer = 0
local cycleTime = 0.02

```

```

while updownKickActive do
    if not target or not target.Parent or not target.Character then break end
    if not blobRoot or not blobRoot.Parent then break end
    tChar = target.Character
    tRoot = tChar and tChar:FindFirstChild("HumanoidRootPart")
    local tHum = tChar and tChar:FindFirstChild("Humanoid")
    if tRoot and tHum and tHum.Health > 0 then
        blobRoot.CFrame = SavedPos
        blobRoot.Velocity = Vector3.zero
        local phase = math.floor(tick() / cycleTime) % 2
        local offsetY = (phase == 0) and 12 or -5
        local lockPos = SavedPos * CFrame.new(0, offsetY, -5)
        tRoot.CFrame = lockPos
        tRoot.Velocity = Vector3.zero
        tRoot.RotVelocity = Vector3.zero
        if tick() - packetTimer > 0.05 then
            packetTimer = tick()
            pcall(function()
                tHum.PlatformStand = true
                tHum.Sit = true
                GE.SetNetworkOwner:FireServer(tRoot, lockPos)
                if R_Det then

```

```

                local weld = R_Det:FindFirstChild("RightWeld") or
R_Det:FindFirstChildWhichIsA("Weld")
                if weld then
                    CD:FireServer(weld)
                end
            end
            GE.DestroyGrabLine:FireServer(tRoot)
            CG:FireServer(R_Det, tRoot, R_Weld)
            GE.CreateGrabLine:FireServer(tRoot, Vector3.zero, tRoot.Position, false)
        end)
    end
else
    if blobRoot and blobRoot.Parent then
        blobRoot.CFrame = SavedPos
        blobRoot.Velocity = Vector3.zero
    end
end
RunService.Heartbeat:Wait()
end
updownKickActive = false
if updownKickToggle then updownKickToggle:SetValue(false) end
if blobRoot and blobRoot.Parent then
    blobRoot.CFrame = SavedPos
    blobRoot.Velocity = Vector3.zero
end
end)
end
})

```

```

WhitelistGroup:AddDropdown("MultiWhitelist", {Values = getPlayerList(), Default = {}, Multi =
true, Text = "ホワイトリスト"})
WhitelistGroup:AddButton({Text = "🔄 リスト更新", Func = function()
Options.MultiWhitelist:SetValues(getPlayerList()) end})

```

```

local notifyActive = false
local notifyConnection = nil
WhitelistGroup:AddToggle("JoinedNotifyBtn", {
    Text = "ターゲット参加通知",
    Default = false,
    Callback = function(on)
        notifyActive = on
        if on then
            notify("レーダー", "ターゲット監視中...", 3)
            if notifyConnection then notifyConnection:Disconnect() end
            notifyConnection = PS.PlayerAdded:Connect(function(newPlayer)
                if not notifyActive then return end
                local detected = false
                local reason = ""

```

```

local whitelistTable = Options.MultiWhitelist.Value
for nameString, isSelected in pairs(whitelistTable) do
    if isSelected then
        local actualName = nameString:match("%((.-)%)")
        if actualName == newPlayer.Name then
            detected = true
            reason = "[ホワイトリスト]"
            break
        end
    end
end
if not detected and Options.KickPlayerDropdown and
Options.KickPlayerDropdown.Value then
    local selection = Options.KickPlayerDropdown.Value
    local selectedName = selection:match("%((.-)%)")
    if selectedName and selectedName == newPlayer.Name then
        detected = true
        reason = "[メインターゲット]"
    end
end
if detected then
    notify("ターゲット参加", reason .. " プレイヤー: " .. newPlayer.Name, 8)
    local sound = Instance.new("Sound", workspace)
    sound.SoundId = "rbxassetid://4590662766"
    sound.Volume = 2
    sound:Play()
    game:GetService("Debris"):AddItem(sound, 3)
end)
else
    if notifyConnection then notifyConnection:Disconnect() notifyConnection = nil end
    notify("レーダー", "監視停止", 2)
end
end
end
})

```

```

-- =====
-- Grab Tab (掴み)
-- =====
local GrabGroup = Tabs.Grab:AddLeftGroupbox("👉 掴みカスタマイズ")
_G.strength = 750
local strengthConnection
GrabGroup:AddSlider("ThrowPowerSlider", {Text="投擲力", Default=750, Min=1,
Max=20000, Rounding=0, Callback=function(value) _G.strength = value end})
GrabGroup:AddToggle("ThrowStrengthToggle", {Text="投擲強化", Default=false,
Callback=function(enabled)
    if enabled then
        strengthConnection = workspace.ChildAdded:Connect(function(model)

```

```

    if model.Name == "GrabParts" then
        local partToImpulse = model.GrabPart.WeldConstraint.Part1
        if partToImpulse then
            local velocityObj = Instance.new("BodyVelocity", partToImpulse)
            model:GetPropertyChangedSignal("Parent"):Connect(function()
                if not model.Parent then
                    if UserInputService:GetLastInputType() ==
Enum.UserInputType.MouseButton2 then
                        velocityObj.MaxForce = Vector3.new(math.huge, math.huge,
math.huge)
                        velocityObj.Velocity = workspace.CurrentCamera.CFrame.LookVector *
_G.strength
                        game:GetService("Debris"):AddItem(velocityObj, 1)
                    else
                        velocityObj:Destroy()
                    end
                end
            end)
        end
    end
    elseif strengthConnection then strengthConnection:Disconnect() end
end})

```

```

local killGrabEnabled = false
local function killGrabFunction()
    workspace.ChildAdded:Connect(function(v)
        if v:IsA("Model") and v.Name == "GrabParts" and killGrabEnabled then
            task.wait(0.05)
            local grabPart = v:FindFirstChild("GrabPart")
            if grabPart and grabPart:FindFirstChild("WeldConstraint") then
                local part1 = grabPart.WeldConstraint.Part1
                if part1 and part1.Parent and part1.Parent ~= Player.Character then
                    local targetChar = part1.Parent
                    local targetHum = targetChar:FindFirstChildOfClass("Humanoid")
                    if targetHum and targetChar then
                        pcall(function() targetHum.Health = 0 targetChar:BreakJoints() end)
                    end
                end
            end
        end
    end)
end
killGrabFunction()
GrabGroup:AddToggle("KillGrabToggle", {Text="キルGrab", Default=false,
Callback=function(Value) killGrabEnabled = Value end})

```

```

-- =====

```

```

-- Player Tab (プレイヤー)
-- =====
local PlayerView = Tabs.Player:AddLeftGroupbox(" 👤 視点 & 移動")
local PlayerESP = Tabs.Player:AddRightGroupbox(" 🌈 ESP")
local PlayerEnv = Tabs.Player:AddLeftGroupbox(" 🌍 環境")
local PlayerPerf = Tabs.Player:AddRightGroupbox(" ⚡ パフォーマンス")

local RainbowESP = {Enabled=false, Boxes={}, Connections={}, Hue=0, Speed=0.5,
Transparency=0.3, UpdateInterval=0.05}
local function GetRainbowColor() return Color3.fromHSV(RainbowESP.Hue,1,1) end
task.spawn(function()
    while true do
        if RainbowESP.Enabled then
            RainbowESP.Hue = (RainbowESP.Hue + 0.005 * RainbowESP.Speed) % 1
            for _, box in pairs(RainbowESP.Boxes) do
                if box and box.Parent then pcall(function() box.Color3 = GetRainbowColor() end)
            end
        end
        task.wait(RainbowESP.UpdateInterval)
    end
end)
local targetNames = {"partesp", "playercharacterlocationdetector"}
local function IsTarget(obj)
    if not obj:IsA("BasePart") then return false end
    for _, name in ipairs(targetNames) do
        if string.lower(obj.Name) == string.lower(name) then return true end
    end
    return false
end
local function RemoveAllRainbowBoxes()
    for obj, box in pairs(RainbowESP.Boxes) do if box then pcall(function() box:Destroy() end)
end end
    RainbowESP.Boxes = {}
    for _, conn in ipairs(RainbowESP.Connections) do if conn and conn.Connected then
pcall(function() conn:Disconnect() end) end end
    RainbowESP.Connections = {}
end

PlayerESP:AddToggle("BoxESPWhite", {
    Text = " 🌈 レインボーESP",
    Default = false,
    Callback = function(Value)
        RainbowESP.Enabled = Value
        if Value then
            RemoveAllRainbowBoxes()
            for _, obj in ipairs(workspace:GetDescendants()) do
                if RainbowESP.Enabled and IsTarget(obj) then

```

```

        if not RainbowESP.Boxes[obj] then
            local box = Instance.new("BoxHandleAdornment")
            box.Adornee = obj
            box.AlwaysOnTop = true
            box.ZIndex = 5
            box.Color3 = GetRainbowColor()
            box.Transparency = RainbowESP.Transparency
            box.Size = obj.Size
            box.Parent = game.CoreGui
            RainbowESP.Boxes[obj] = box
        end
    end
end
local descConn = workspace.DescendantAdded:Connect(function(obj)
    if RainbowESP.Enabled and IsTarget(obj) then
        if not RainbowESP.Boxes[obj] then
            local box = Instance.new("BoxHandleAdornment")
            box.Adornee = obj
            box.AlwaysOnTop = true
            box.ZIndex = 5
            box.Color3 = GetRainbowColor()
            box.Transparency = RainbowESP.Transparency
            box.Size = obj.Size
            box.Parent = game.CoreGui
            RainbowESP.Boxes[obj] = box
        end
    end
end)
table.insert(RainbowESP.Connections, descConn)
else
    RemoveAllRainbowBoxes()
end
end
}))

local rainbowNicknames = {}
PlayerESP:AddToggle("NicknameESP", {
    Text = "🌈 ニックネームESP",
    Default = false,
    Callback = function(Value)
        if Value then
            local function createRainbowESP(plr)
                if plr == Player then return end
                if plr.Character and plr.Character:FindFirstChild("HumanoidRootPart") then
                    local hrp = plr.Character.HumanoidRootPart
                    if hrp:FindFirstChild("RainbowNameESP") then
                        hrp.RainbowNameESP:Destroy() end
                    local billboard = Instance.new("BillboardGui")

```

```

    billboard.Name = "RainbowNameESP"
    billboard.Adornee = hrp
    billboard.Size = UDim2.new(0,150,0,40)
    billboard.StudsOffset = Vector3.new(0,3.5,0)
    billboard.AlwaysOnTop = true
    billboard.Parent = hrp
    local textLabel = Instance.new("TextLabel")
    textLabel.Size = UDim2.new(1,0,1,0)
    textLabel.BackgroundTransparency = 1
    textLabel.Text = plr.DisplayName
    textLabel.TextColor3 = GetRainbowColor()
    textLabel.TextStrokeTransparency = 0
    textLabel.TextScaled = true
    textLabel.Font = Enum.Font.GothamBold
    textLabel.Parent = billboard
    table.insert(rainbowNicknames, billboard)
    task.spawn(function()
        while billboard and billboard.Parent do
            task.wait(0.1)
            if textLabel and textLabel.Parent then
                pcall(function() textLabel.TextColor3 = GetRainbowColor() end)
            end
        end
    end)
end
end
for _, plr in pairs(PS:GetPlayers()) do
    createRainbowESP(plr)
    plr.CharacterAdded:Connect(function() createRainbowESP(plr) end)
end
PS.PlayerAdded:Connect(function(plr)
    plr.CharacterAdded:Connect(function() createRainbowESP(plr) end)
end)
else
    for _, gui in pairs(rainbowNicknames) do if gui then pcall(function() gui:Destroy() end)
end end
rainbowNicknames = {}
for _, plr in pairs(PS:GetPlayers()) do
    if plr.Character and plr.Character:FindFirstChild("HumanoidRootPart") then
        local hrp = plr.Character.HumanoidRootPart
        if hrp:FindFirstChild("RainbowNameESP") then pcall(function()
hrp.RainbowNameESP:Destroy() end) end
    end
end
end
end
end
})

```

```

local function enableThirdPerson()
    Player.CameraMode = Enum.CameraMode.Classic
    Camera.CameraType = Enum.CameraType.Custom
    Camera.CameraSubject = Player.Character:WaitForChild("Humanoid")
    Player.CameraMaxZoomDistance = 16456456546
    Player.CameraMinZoomDistance = 0.5
end
local function disableThirdPerson()
    Player.CameraMode = Enum.CameraMode.LockFirstPerson
    Camera.CameraType = Enum.CameraType.Custom
    Camera.CameraSubject = Player.Character:WaitForChild("Humanoid")
    Player.CameraMaxZoomDistance = 0
    Player.CameraMinZoomDistance = 0
end
PlayerView.AddToggle("ThirdPersonToggle", {Text="三人称視点", Default=false,
Callback=function(Value) if Value then enableThirdPerson() else disableThirdPerson() end
end})

local spinningConnection
local spinSpeed = 5
PlayerView.AddToggle("SpinToggle", {Text="回転", Default=false, Callback=function(Value)
    if Value then
        spinningConnection = R.Heartbeat:Connect(function()
            local character = Player.Character
            local root = character and character:FindFirstChild("HumanoidRootPart")
            if root then root.CFrame = root.CFrame * CFrame.Angles(0, math.rad(spinSpeed), 0)
        end)
    else
        if spinningConnection then spinningConnection:Disconnect() spinningConnection = nil
        end
    end
end})
PlayerView.AddSlider("SpinSpeed", {Text="回転速度", Default=5, Min=1, Max=50,
Rounding=0, Callback=function(Value) spinSpeed = Value end})

local infJump = false
PlayerView.AddToggle("infJumpToggle", {Text="無限ジャンプ", Default=false,
Callback=function(Value) infJump = Value end})
UserInputService.JumpRequest:Connect(function()
    if infJump then
        local character = Player.Character
        if character and character:FindFirstChildOfClass("Humanoid") then

character:FindFirstChildOfClass("Humanoid"):ChangeState(Enum.HumanoidStateType.Jumping)
        end
    end
end

```

```

end)

local oldProperties = {}
PlayerPerf:AddButton({Text=" FPSブースト", Func=function()
    local Lighting = game:GetService("Lighting")
    for _, v in pairs(Workspace:GetDescendants()) do
        if v:IsA("BasePart") then
            if not oldProperties[v] then oldProperties[v] = {Material = v.Material, Reflectance =
v.Reflectance, CastShadow = v.CastShadow} end
            v.Material = Enum.Material.Plastic v.Reflectance = 0 v.CastShadow = false
        elseif v:IsA("ParticleEmitter") or v:IsA("Trail") or v:IsA("Smoke") or v:IsA("Fire") then
            if not oldProperties[v] then oldProperties[v] = {Enabled = v.Enabled} end
            v.Enabled = false
        end
    end
    for _, plr in pairs(PS:GetPlayers()) do
        if plr.Character then
            for _, part in pairs(plr.Character:GetDescendants()) do
                if part:IsA("BasePart") and part.Name ~= "HumanoidRootPart" then
                    if not oldProperties[part] then oldProperties[part] = {Material = part.Material,
Reflectance = part.Reflectance, CastShadow = part.CastShadow} end
                    part.Material = Enum.Material.Plastic part.Reflectance = 0 part.CastShadow =
false
                end
            end
        end
    end
    if not oldProperties["Lighting"] then oldProperties["Lighting"] = {GlobalShadows =
Lighting.GlobalShadows, FogEnd = Lighting.FogEnd, Brightness = Lighting.Brightness} end
    Lighting.GlobalShadows = false Lighting.FogEnd = 100000 Lighting.Brightness = 2
end})
PlayerPerf:AddButton({Text=" FPSブースト解除", Func=function()
    local Lighting = game:GetService("Lighting")
    for obj, props in pairs(oldProperties) do
        if typeof(obj) == "Instance" and obj.Parent then
            for prop, value in pairs(props) do obj[prop] = value end
            elseif obj == "Lighting" then
                for prop, value in pairs(props) do Lighting[prop] = value end
            end
        end
    end
    oldProperties = {}
end})

-- =====
-- Misc Tab (その他)
-- =====
local MiscGroup = Tabs.Misc:AddLeftGroupbox(" その他機能")
local mouse = Player:GetMouse()

```

```

local tpToolConn
MiscGroup:AddToggle("TPToggle", {Text="テレポート [T]", Default=false,
Callback=function(Value)
    if Value then
        if tpToolConn then tpToolConn:Disconnect() end
        tpToolConn = UserInputService.InputBegan:Connect(function(input, gameProcessed)
            if gameProcessed then return end
            if input.KeyCode == Enum.KeyCode.T then
                local character = Player.Character
                if character and character:FindFirstChild("HumanoidRootPart") then
                    local hrp = character.HumanoidRootPart
                    local targetPos = mouse.Hit.Position
                    hrp.CFrame = CFrame.new(targetPos + Vector3.new(0,3,0))
                end
            end
        end)
    else
        if tpToolConn then tpToolConn:Disconnect() tpToolConn = nil end
    end
end})

```

```

local waterParts = {}
task.spawn(function()
    if workspace:FindFirstChild("Map") and
workspace.Map:FindFirstChild("AlwaysHereTweenedObjects") then
        local oceanModel =
workspace.Map.AlwaysHereTweenedObjects.Ocean.Object.ObjectModel
        for _, v in pairs(oceanModel:GetChildren()) do
            if v:IsA("Part") or v:IsA("UnionOperation") or v:IsA("BasePart") or v:IsA("MeshPart")
then
                table.insert(waterParts, {part = v, originalCollide = v.CanCollide})
            end
        end
    end
end)
MiscGroup:AddToggle("WaterWalkToggle", {Text="水上歩行", Default=false,
Callback=function(on)
    for _, item in pairs(waterParts) do if item.part then item.part.CanCollide = on end end
end})

```

```

local Triggerbot = {Enabled=false, Connection=nil, canGrab=true, maxDistance=20,
preGrabDelay=0.00001, postGrabDelay=0.05, lastTarget=nil, lastHitTime=0,
targetMemoryDuration=0.1, checkThrottle=0.008, lastCheck=0}
local rayParams = RaycastParams.new()
rayParams.FilterType = Enum.RaycastFilterType.Exclude
task.spawn(function()
    local success, result = pcall(function() return
RS.GamepassEvents.CheckForGamepass:InvokeServer(20837132) end)

```

```

    if success and result then Triggerbot.maxDistance = 29.3 end
end)
if RS:FindFirstChild("GamepassEvents") and
RS.GamepassEvents:FindFirstChild("FurtherReachBoughtNotifier") then
    RS.GamepassEvents.FurtherReachBoughtNotifier.OnClientEvent:Connect(function()
Triggerbot.maxDistance = 29.3 end)
end
function Triggerbot:GetTarget()
    local c = Player.Character
    if not c or not c:FindFirstChild("HumanoidRootPart") then return end
    if Workspace:FindFirstChild("GrabParts") then return end
    local origin, dir = Camera.CFrame.Position, Camera.CFrame.LookVector
    rayParams.FilterDescendantsInstances = {c, Workspace.Terrain}
    local result = Workspace:Raycast(origin, dir * 1000, rayParams)
    if not result then
        local dirs = {dir, (dir + Vector3.new(0,0.075,0)).Unit, (dir - Vector3.new(0,0.075,0)).Unit}
        for _, d in ipairs(dirs) do
            result = Workspace:Raycast(origin, d * 1000, rayParams)
            if result then break end
        end
    end
    if not result then return end
    local hit = result.Instance
    local model = hit:FindFirstAncestorOfClass("Model")
    if not model or not model:FindFirstChildOfClass("Humanoid") or model == c then return
end
    local hum = model:FindFirstChildOfClass("Humanoid")
    if hum.Health <= 0 then return end
    local root = model:FindFirstChild("HumanoidRootPart")
    if not root then return end
    local dist = (c.HumanoidRootPart.Position - root.Position).Magnitude
    if dist > self.maxDistance then return end
    return model
end
function Triggerbot:OnHeartbeat()
    if not self.Enabled or not self.canGrab then return end
    if UserInputService:GetFocusedTextBox() then return end
    if tick() - self.lastCheck < self.checkThrottle then return end
    self.lastCheck = tick()
    local t = self:GetTarget()
    if t then self.lastTarget = t self.lastHitTime = tick()
    elseif self.lastTarget and tick() - self.lastHitTime > self.targetMemoryDuration then
self.lastTarget = nil end
    local c = Player.Character
    local root = self.lastTarget and self.lastTarget:FindFirstChild("HumanoidRootPart")
    if not (self.lastTarget and c and c:FindFirstChild("HumanoidRootPart") and root) then
return end

```

```

    if (c.HumanoidRootPart.Position - root.Position).Magnitude > self.maxDistance then
self.lastTarget = nil return end
    if self.lastTarget then
        self.canGrab = false
        task.spawn(function()
            task.wait(self.preGrabDelay)
            pcall(mouse1press)
            local t0 = tick()
            repeat task.wait(0.02) until not Workspace:FindFirstChild("GrabParts") or tick() - t0 >
1.6
                task.wait(self.postGrabDelay)
                self.canGrab = true
                self.lastTarget = nil
            end)
        end
    end
end
MiscGroup:AddToggle("TriggerbotToggle", {Text="トリガーボット",
Default=Triggerbot.Enabled, Callback=function(value)
    Triggerbot.Enabled = value
    if Triggerbot.Enabled and not Triggerbot.Connection then
        Triggerbot.Connection = R.Heartbeat:Connect(function() Triggerbot:OnHeartbeat() end)
    elseif not Triggerbot.Enabled and Triggerbot.Connection then
        Triggerbot.Connection:Disconnect()
        Triggerbot.Connection = nil
    end
end})

local PacketSpamAmount = 100
MiscGroup:AddSlider("PacketAmountSlider", {Text="パケット量", Default=100, Min=10,
Max=5000, Rounding=0, Callback=function(Value) PacketSpamAmount = Value end})
MiscGroup:AddToggle("PacketLagToggle", {Text="パケットラグ", Default=false,
Callback=function(Value)
    _G.PacketLagActive = Value
    if Value then
        task.spawn(function()
            for i, e in pairs(game.Players:GetPlayers()) do if e.Name == "MaybeFlashh" then
return end end
                local RS = game:GetService("ReplicatedStorage")
                local GrabEvent = RS:WaitForChild("GrabEvents"):WaitForChild("ExtendGrabLine")
                while _G.PacketLagActive do
                    pcall(function() GrabEvent:FireServer(string.rep("Balls Balls Balls Balls",
PacketSpamAmount)) end)
                    task.wait()
                end
            end)
        else
            _G.PacketLagActive = false
        end
    end
end

```

```
end}})
```

```
local autoResetEnabled = false
MiscGroup:AddToggle("AutoResetToggle", {Text="自動リセット", Default=false,
Callback=function(on)
    autoResetEnabled = on
    if not on then autoResetEnabled = false return end
    task.spawn(function()
        local plr = game.Players.LocalPlayer
        while autoResetEnabled do
            local char = plr.Character
            local hum = char and char:FindFirstChild("Humanoid")
            if hum and hum.Health > 0 then hum.Health = 0 end
            task.wait(0.5)
        end
    end)
end})
```

```
MiscGroup:AddSlider("FOVSlider", {Text="視野角(FOV)", Default=90, Min=1, Max=120,
Rounding=0, Suffix="°", Callback=function(value)
game.Workspace.CurrentCamera.FieldOfView = value end})
```

```
-- レインボーエフェクト
```

```
local RainbowEffect = {Enabled=true, Hue=0, Speed=0.8}
local function GetRainbowColorLemon() return Color3.fromHSV(RainbowEffect.Hue,1,1) end
local function UpdateRainbowLemon()
    while RainbowEffect.Enabled do
        RainbowEffect.Hue = (RainbowEffect.Hue + 0.005 * RainbowEffect.Speed) % 1
        task.wait(0.01)
    end
end
task.spawn(UpdateRainbowLemon)
```

```
-- =====
```

```
-- LagKick Tab (ラグキック)
```

```
-- =====
```

```
local LagKickGroup = Tabs.LagKick:AddLeftGroupbox("🕒 ラグキック操作")
local LagKick = {Enabled=false, SelectedHeight="Spawn", Thread=nil, Running=false,
LineLagEnabled=false, LineLagThread=nil}
local function getAllPlayers()
    local players = {}
    for _, plr in pairs(Players:GetPlayers()) do if plr ~= LocalPlayer then table.insert(players,
plr) end end
    return players
end
local GrabEvents = ReplicatedStorage:FindFirstChild("GrabEvents")
local function spamOwnership(hrp)
    if not GrabEvents then return end
```

```

    local setOwner = GrabEvents:FindFirstChild("SetNetworkOwner")
    if setOwner and hrp then pcall(function() setOwner:FireServer(hrp, hrp.CFrame) end) end
end
local function teleportToPlayer(myHrp, targetHrp)
    if not myHrp or not targetHrp then return end
    pcall(function() myHrp.CFrame = targetHrp.CFrame * CFrame.new(0,5,5)
myHrp.AssemblyLinearVelocity = Vector3.zero end)
end
local function destroyLineOnPlayer(hrp)
    if not GrabEvents then return end
    local createLine = GrabEvents:FindFirstChild("CreateGrabLine")
    local destroyLine = GrabEvents:FindFirstChild("DestroyGrabLine")
    if not createLine or not destroyLine then return end
    pcall(function() createLine:FireServer(hrp, CFrame.new(0,1e9,0)) task.wait()
destroyLine:FireServer(hrp) end)
end
local function startLineLag()
    if LagKick.LineLagEnabled then return end
    LagKick.LineLagEnabled = true
    LagKick.LineLagThread = coroutine.create(function()
        if not GrabEvents then return end
        local createLine = GrabEvents:FindFirstChild("CreateGrabLine")
        if not createLine then return end
        while LagKick.LineLagEnabled do
            local spawnLocation = Workspace:FindFirstChild("SpawnLocation") or
Workspace:FindFirstChild("Spawn") or (LocalPlayer.Character and
LocalPlayer.Character:FindFirstChild("HumanoidRootPart"))
            if spawnLocation then
                local randomX = math.random(-1e9,1e9)
                local randomZ = math.random(-1e9,1e9)
                local directions = {CFrame.new(randomX,0,randomZ),
CFrame.new(-randomX,0,-randomZ), CFrame.new(randomX,0,-randomZ),
CFrame.new(-randomX,0,randomZ)}
                for _, pos in pairs(directions) do createLine:FireServer(spawnLocation, pos) end
            end
            task.wait()
        end
    end)
    coroutine.resume(LagKick.LineLagThread)
end
local function stopLineLag()
    LagKick.LineLagEnabled = false
    if LagKick.LineLagThread then coroutine.close(LagKick.LineLagThread);
LagKick.LineLagThread = nil end
end
LagKickGroup:AddDropdown({Text="高さモード", Values={"地上", "天界"}, Default=1,
Callback=function(Value) LagKick.SelectedHeight = (Value == "天界") and "Heaven" or
"Spawn" end})

```

```

LagKickGroup:AddButton({Text="🚀 サーバー破壊", Func=function()
    if LagKick.Running then return end
    LagKick.Running = true
    task.spawn(function()
        showHackMessage("△ システムキック検出 △", Color3.fromRGB(255,0,0), 2)
        screenFlash(Color3.fromRGB(255,0,0), 0.3)
        shakeScreen(5,0.3)
        task.wait(0.5)
        local height = (LagKick.SelectedHeight == "Heaven") and 1e9 or 35
        startLineLag()
        task.wait(1)
        local players = getAllPlayers()
        if #players == 0 then
            stopLineLag()
            LagKick.Running = false
            notify("ラグキック", "プレイヤーが見つかりません", 3)
            return
        end
        showHackMessage("ターゲット取得: "..#players.." 人", Color3.fromRGB(0,255,255), 1.5)
        local myChar = LocalPlayer.Character
        local myHrp = myChar and myChar:FindFirstChild("HumanoidRootPart")
        if not myHrp then stopLineLag() LagKick.Running = false return end
        local playerData = {}
        for _, plr in ipairs(players) do
            local char = plr.Character
            local hrp = char and char:FindFirstChild("HumanoidRootPart")
            if hrp then table.insert(playerData, {player=plr, hrp=hrp}) end
        end
        for _, data in ipairs(playerData) do
            teleportToPlayer(myHrp, data.hrp)
            task.wait(0.2)
            spamOwnership(data.hrp)
            task.wait()
        end
        local radius = 40
        local angleStep = (math.pi * 2) / #playerData
        for idx, data in ipairs(playerData) do
            local angle = (idx - 1) * angleStep
            local x = math.cos(angle) * radius
            local z = math.sin(angle) * radius
            pcall(function()
                data.hrp.CFrame = CFrame.new(x, height, z)
                data.hrp.AssemblyLinearVelocity = Vector3.zero
            end)
            local bp = Instance.new("BodyPosition")
            bp.MaxForce = Vector3.new(1e9,1e9,1e9)
            bp.P = 40000000
            bp.Position = Vector3.new(x, height, z)
        end
    end)
end)

```

```

        bp.Parent = data.hrp
        task.delay(2, function() pcall(function() bp:Destroy() end) end)
        task.wait()
    end
    for i = 1, 8 do
        for _, data in ipairs(playerData) do destroyLineOnPlayer(data.hrp) end
        if i % 2 == 0 then screenFlash(Color3.fromRGB(255,0,255), 0.05) end
        task.wait(0.3)
    end
    LagKick.Running = false
    showHackMessage("✓ キック完了", Color3.fromRGB(0,255,0), 2)
    screenFlash(Color3.fromRGB(0,255,0), 0.2)
    if myHrp and myHrp.Parent then
        createLightningEffect(myHrp.Position, 8)
    end
    notify("ラグキック", "破壊完了！ラグ継続中", 2)
end)
end})
LagKickGroup:AddButton({Text="🟡 ラグ停止", Func=function()
    stopLineLag()
    LagKick.Running = false
    showHackMessage("△ システム復旧", Color3.fromRGB(255,255,0), 1.5)
    notify("ラグキック", "ラグ停止", 2)
end})

-- =====
-- Build Tab (ビルド)
-- =====
if Tabs.Build then
    local BuildGroup = Tabs.Build:AddLeftGroupbox("🔧 おもしろ機能")
    local I_Connection = nil
    BuildGroup:AddToggle("LShown", {
        Text = "L表示",
        Default = false,
        Callback = function(Value)
            local Players = game:GetService("Players")
            local RunService = game:GetService("RunService")
            local player = Players.LocalPlayer
            local char = player.Character or player.CharacterAdded:Wait()
            local torso = char:FindFirstChild("Torso") or char:FindFirstChild("HumanoidRootPart")
            if not torso then return end
            local folderName = player.Name .. "SpawnedInToys"
            local folder = workspace:FindFirstChild(folderName)
            local toy = folder and folder:FindFirstChild("TetracubeJ")
            local main = toy and toy:FindFirstChild("Main")
            if not main then return end
            for _, v in ipairs(main.Parent:GetDescendants()) do
                if v:IsA("BasePart") then v.CanCollide = false v.CanTouch = false end
            end
        end
    })
end

```

```

end
local bp = main:FindFirstChild("L_BP") or Instance.new("BodyPosition")
bp.Name = "L_BP"
bp.Parent = main
bp.P = 6000
bp.D = 150
local bg = main:FindFirstChild("L_BG") or Instance.new("BodyGyro")
bg.Name = "L_BG"
bg.Parent = main
bg.P = 5000
bg.D = 200
if I_Connection then I_Connection:Disconnect() end
if Value then
    bp.MaxForce = Vector3.new(1e6,1e6,1e6)
    bg.MaxTorque = Vector3.new(1e6,1e6,1e6)
    local t = 0
    I_Connection = RunService.RenderStepped:Connect(function(dt)
        if not main.Parent then if I_Connection then I_Connection:Disconnect() end
return end
        t = t + dt
        local cf = torso.CFrame
        local offset = math.sin(t * 30) * 9
        bp.Position = torso.Position + cf.LookVector * (11 + offset)
        bg.CFrame = cf * CFrame.Angles(0, math.rad(180), 0)
    end)
else
    bp.MaxForce = Vector3.zero
    bg.MaxTorque = Vector3.zero
end
end
end
})
end

```

```

-- =====
-- Lemon Kill (れもに一キル)
-- =====
local LemonKill = {}
LemonKill.isRunning = false
LemonKill.isKillAura = false
LemonKill.isSelectedKill = false
LemonKill.selectedPlayer = nil
LemonKill.currentBlobman = nil
LemonKill.killAuraConnection = nil
LemonKill.selectedKillConnection = nil
LemonKill.selectedPlayerConnection = nil
LemonKill.selectedKillAuraConnection = nil

local TP_WAIT = 0.02

```

```
local GRAB_WAIT = 0.005
local RETRY_WAIT = 0.005
local MAX_RETRIES = 5
local MAX_BLOBBMAN_DISTANCE = 500
local SELECTED_AURA_RANGE = 40
local AURA_RANGE = 40
```

```
local function GetSeatedBlobman()
    local char = LocalPlayer.Character
    if not char then return nil end
    local humanoid = char:FindFirstChildOfClass("Humanoid")
    if not humanoid then return nil end
    local seat = humanoid.SeatPart
    if not seat or not seat:IsA("VehicleSeat") then return nil end
    local obj = seat
    while obj do
        if obj:IsA("Model") and obj.Name == "CreatureBlobman" then return obj end
        obj = obj.Parent
    end
    return nil
end
```

```
function LemonKill.SpawnBlobman()
    local seatedBlobman = GetSeatedBlobman()
    if seatedBlobman then LemonKill.currentBlobman = seatedBlobman return
    seatedBlobman end
    if LemonKill.currentBlobman and LemonKill.currentBlobman.Parent then
        local blobmanPos = nil
        if LemonKill.currentBlobman.PrimaryPart then blobmanPos =
        LemonKill.currentBlobman.PrimaryPart.Position
        else local part = LemonKill.currentBlobman:FindFirstChildWhichIsA("BasePart") if part
        then blobmanPos = part.Position end end
        local character = LocalPlayer.Character
        local rootPart = character and character:FindFirstChild("HumanoidRootPart")
        local localPos = rootPart and rootPart.Position
        if blobmanPos and localPos and (blobmanPos - localPos).Magnitude <
        MAX_BLOBBMAN_DISTANCE then
            local seat = LemonKill.currentBlobman:FindFirstChild("VehicleSeat")
            if seat then
                local humanoid = character and character:FindFirstChildOfClass("Humanoid")
                if humanoid then seat:Sit(humanoid) task.wait(0.05) end
            end
            return LemonKill.currentBlobman
        else
            pcall(function() LemonKill.currentBlobman:Destroy() end)
            LemonKill.currentBlobman = nil
        end
    end
end
```

```

local character = LocalPlayer.Character
if not character then return nil end
local rootPart = character:FindFirstChild("HumanoidRootPart")
if not rootPart then return nil end
local spawnPos = rootPart.CFrame * CFrame.new(0,0,-5)
pcall(function()
ReplicatedStorage.MenuToys.SpawnToyRemoteFunction:InvokeServer("CreatureBlobman",
spawnPos, Vector3.new(0,127,0)) end)
local toyFolderName = LocalPlayer.Name.."SpawnedInToys"
local blobman = nil
local startTime = tick()
repeat
    local toyFolder = Workspace:FindFirstChild(toyFolderName)
    if toyFolder then blobman = toyFolder:FindFirstChild("CreatureBlobman") end
    if blobman then break end
    task.wait()
until tick() - startTime > 2
if not blobman then return nil end
LemonKill.currentBlobman = blobman
local seat = blobman:FindFirstChild("VehicleSeat")
if seat then
    local humanoid = character:FindFirstChildOfClass("Humanoid")
    if humanoid then seat:Sit(humanoid) end
end
task.wait(0.05)
return blobman
end

```

```

function LemonKill.KillPlayer(targetPlayer)
    if not targetPlayer or not targetPlayer.Character then return false end
    local humanoid = targetPlayer.Character:FindFirstChildOfClass("Humanoid")
    if not humanoid then return false end
    for _ = 1, MAX_RETRIES do
        local success = pcall(function()
            humanoid.BreakJointsOnDeath = false
            humanoid:ChangeState(Enum.HumanoidStateType.Dead)
        end)
        if success and humanoid.Health <= 0 then
            showHackMessage("ターゲット排除", Color3.fromRGB(0,255,0), 1.5)
            screenFlash(Color3.fromRGB(0,255,0), 0.1)
            return true
        end
        task.wait(RETRY_WAIT)
    end
    return false
end

```

```

function LemonKill.GrabRelease(blobman, targetRoot)

```

```

if not blobman or not targetRoot then return end
pcall(function()
    local script = blobman:FindFirstChild("BlobmanSeatAndOwnerScript")
    if script then
        script.CreatureGrab:FireServer(blobman.LeftDetector, targetRoot,
blobman.LeftDetector.LeftWeld)
        script.CreatureRelease:FireServer(blobman.LeftDetector.LeftWeld)
    end
end)
end

```

```

function LemonKill.ProcessPlayer(targetPlayer)
    if not targetPlayer or not targetPlayer.Character then return false end
    local humanoid = targetPlayer.Character:FindFirstChildOfClass("Humanoid")
    if not humanoid or humanoid.Health <= 0 then return false end
    local targetRoot = targetPlayer.Character:FindFirstChild("HumanoidRootPart")
    if not targetRoot then return false end
    local localChar = LocalPlayer.Character
    if not localChar then return false end
    local myRoot = localChar:FindFirstChild("HumanoidRootPart")
    if not myRoot then return false end
    local originalCFrame = myRoot.CFrame
    local originalVel = myRoot.AssemblyLinearVelocity
    local originalAngVel = myRoot.AssemblyAngularVelocity
    pcall(function()
        myRoot.CFrame = targetRoot.CFrame
        myRoot.AssemblyLinearVelocity = Vector3.zero
        myRoot.AssemblyAngularVelocity = Vector3.zero
        RunService.Heartbeat:Wait()
        humanoid.BreakJointsOnDeath = false
        humanoid:ChangeState(Enum.HumanoidStateType.Dead)
        local blobman = GetSeatedBlobman()
        if blobman then LemonKill.GrabRelease(blobman, targetRoot) end
    end)
    if myRoot and myRoot.Parent then
        myRoot.CFrame = originalCFrame
        myRoot.AssemblyLinearVelocity = originalVel or Vector3.zero
        myRoot.AssemblyAngularVelocity = originalAngVel or Vector3.zero
        myRoot.Velocity = Vector3.zero
        myRoot.RotVelocity = Vector3.zero
    end
    return true
end

```

```

function LemonKill.ProcessAllPlayers()
    local localChar = LocalPlayer.Character
    if not localChar or not localChar:FindFirstChild("HumanoidRootPart") then return end
    local rootPart = localChar.HumanoidRootPart

```

```

local blobman = LemonKill.SpawnBlobman()
if not blobman then return end
local targets = {}
for _, player in ipairs(Players:GetPlayers()) do
    if player ~= LocalPlayer and player.Character and
player.Character:FindFirstChild("HumanoidRootPart") then
        table.insert(targets, player)
    end
end
for _, player in ipairs(targets) do
    if not LemonKill.isRunning then break end
    local targetChar = player.Character
    if not targetChar then continue end
    local humanoid = targetChar:FindFirstChildOfClass("Humanoid")
    if not humanoid or humanoid.Health <= 0 then continue end
    local targetRoot = targetChar:FindFirstChild("HumanoidRootPart")
    if not targetRoot then continue end
    rootPart.CFrame = targetRoot.CFrame
    task.wait(TP_WAIT)
    LemonKill.KillPlayer(player)
    for _ = 1, 2 do
        LemonKill.GrabRelease(blobman, targetRoot)
        task.wait(GRAB_WAIT)
    end
end
end
end

function LemonKill.SetupKillAura()
    if LemonKill.killAuraConnection then LemonKill.killAuraConnection:Disconnect() end
    LemonKill.killAuraConnection = RunService.Heartbeat:Connect(function()
        if not LemonKill.isKillAura then return end
        local localChar = LocalPlayer.Character
        if not localChar or not localChar:FindFirstChild("HumanoidRootPart") then return end
        local localRoot = localChar.HumanoidRootPart
        if not LemonKill.currentBlobman or not LemonKill.currentBlobman.Parent then
            LemonKill.currentBlobman = LemonKill.SpawnBlobman()
            if not LemonKill.currentBlobman then return end
        end
        for _, player in ipairs(Players:GetPlayers()) do
            if player ~= LocalPlayer and player.Character and
player.Character:FindFirstChild("HumanoidRootPart") then
                local targetRoot = player.Character.HumanoidRootPart
                if (localRoot.Position - targetRoot.Position).Magnitude <= AURA_RANGE then
                    LemonKill.KillPlayer(player)
                    LemonKill.GrabRelease(LemonKill.currentBlobman, targetRoot)
                end
            end
        end
    end
end
end

```

```
end)
end
```

```
function LemonKill.UpdateKillAuraConnection()
    if LemonKill.isKillAura then
        if not LemonKill.killAuraConnection then LemonKill.SetupKillAura() end
    else
        if LemonKill.killAuraConnection then
            LemonKill.killAuraConnection:Disconnect()
            LemonKill.killAuraConnection = nil
        end
    end
end
```

```
local function StartSelectedKillAura()
    if LemonKill.selectedKillAuraConnection then
        LemonKill.selectedKillAuraConnection:Disconnect() end
    if not LemonKill.selectedPlayer then return end
    LemonKill.selectedKillAuraConnection = RunService.Heartbeat:Connect(function()
        if not LemonKill.isSelectedKill or not LemonKill.selectedPlayer then return end
        local targetPlayer = LemonKill.selectedPlayer
        if not targetPlayer.Parent then return end
        local localChar = LocalPlayer.Character
        if not localChar then return end
        local localRoot = localChar:FindFirstChild("HumanoidRootPart")
        if not localRoot then return end
        local targetChar = targetPlayer.Character
        if not targetChar then return end
        local targetRoot = targetChar:FindFirstChild("HumanoidRootPart")
        if not targetRoot then return end
        if (localRoot.Position - targetRoot.Position).Magnitude <= SELECTED_AURA_RANGE
then
            local blobman = GetSeatedBlobman()
            if not blobman then blobman = LemonKill.SpawnBlobman() end
            if blobman then
                LemonKill.KillPlayer(targetPlayer)
                LemonKill.GrabRelease(blobman, targetRoot)
            end
        end
    end)
end
```

```
function LemonKill.StartSelectedKillLoop()
    if LemonKill.selectedKillConnection then LemonKill.selectedKillConnection:Disconnect()
end
    if LemonKill.selectedPlayerConnection then
        LemonKill.selectedPlayerConnection:Disconnect() end
    if not LemonKill.selectedPlayer then return end
```

```

task.spawn(function()
    while LemonKill.isSelectedKill do
        if LemonKill.selectedPlayer and LemonKill.selectedPlayer.Parent then
            pcall(LemonKill.ProcessPlayer, LemonKill.selectedPlayer)
        end
        RunService.Heartbeat:Wait()
    end
end)
LemonKill.selectedPlayerConnection =
LemonKill.selectedPlayer.CharacterAdded:Connect(function()
    if LemonKill.isSelectedKill then
        task.spawn(function() pcall(LemonKill.ProcessPlayer, LemonKill.selectedPlayer) end)
    end
end)
StartSelectedKillAura()
end

```

```

local function StopSelectedKill()
    LemonKill.isSelectedKill = false
    if LemonKill.selectedKillConnection then LemonKill.selectedKillConnection:Disconnect()
end
    if LemonKill.selectedPlayerConnection then
LemonKill.selectedPlayerConnection:Disconnect() end
    if LemonKill.selectedKillAuraConnection then
LemonKill.selectedKillAuraConnection:Disconnect() end
end

```

```

local LemonTab = Window:AddTab("🍋 Kill", "crosshair")
local LemonGroup = LemonTab:AddLeftGroupbox("🍋 れもに一キル")

```

```

local RainbowEffectLemon = {Enabled=true, Hue=0, Speed=0.8}
local function GetRainbowColorLemon2() return
Color3.fromHSV(RainbowEffectLemon.Hue,1,1) end
task.spawn(function()
    while RainbowEffectLemon.Enabled do
        RainbowEffectLemon.Hue = (RainbowEffectLemon.Hue + 0.005 *
RainbowEffectLemon.Speed) % 1
        task.wait(0.01)
    end
end)
LemonGroup:AddToggle("LemonRainbowToggle", {Text="🍋 レインボー効果", Default=true,
Callback=function(Value)
    RainbowEffectLemon.Enabled = Value
    Library.Notify({Title="🍋", Description=Value and "レインボー: ON" or "レインボー: OFF",
Time=2})
end})

```

```

local function GetTargetablePlayerNames()

```

```

local names = {}
for _, player in ipairs(Players:GetPlayers()) do
    if player ~= LocalPlayer then table.insert(names, player.DisplayName.."
(@"..player.Name.."") end
end
table.sort(names, function(a,b) return a:lower() < b:lower() end)
return names
end
LemonGroup:AddDropdown("LemonTargetPlayer", {Text="🍋 ターゲット選択",
Values=GetTargetablePlayerNames(), Default=1, Callback=function(Value) end})
LemonGroup:AddToggle("LemonKillAll", {Text="🍋 全員キル", Default=false,
Callback=function(Value)
    LemonKill.isRunning = Value
    if Value then
        Library:Notify({Title="🍋", Description="全員キル: 起動", Time=2})
        task.spawn(function() while LemonKill.isRunning do LemonKill.ProcessAllPlayers()
task.wait() end end)
    else
        Library:Notify({Title="🍋", Description="全員キル: 停止", Time=2})
    end
end})
LemonGroup:AddToggle("LemonKillAura", {Text="🍋 キルオーラ", Default=false,
Callback=function(Value)
    LemonKill.isKillAura = Value
    if Value then LemonKill.SpawnBlobman() Library:Notify({Title="🍋", Description="キルオー
ラ: 起動", Time=2})
    else Library:Notify({Title="🍋", Description="キルオーラ: 停止", Time=2}) end
    LemonKill.UpdateKillAuraConnection()
end})
LemonGroup:AddToggle("LemonSelectedKill", {Text="🍋 選択キル", Default=false,
Callback=function(Value)
    if Value then
        local selected = Options.LemonTargetPlayer.Value
        if type(selected) == "string" then
            local username = selected:match("%(@(.+)%)$")
            if username then
                LemonKill.selectedPlayer = Players:FindFirstChild(username)
                if LemonKill.selectedPlayer then
                    LemonKill.isSelectedKill = true
                    LemonKill.StartSelectedKillLoop()
                    Library:Notify({Title="🍋", Description="選択キル: "..username.." に起動",
Time=3})
                else
                    Library:Notify({Title="🍋", Description="プレイヤーが見つかりません", Time=2})
                    Toggles.LemonSelectedKill:SetValue(false)
                end
            end
        else
    end

```

```

        Library:Notify({Title="🍋", Description="先にプレイヤーを選択してください",
Time=2})
        Toggles.LemonSelectedKill:SetValue(false)
    end
else
    Library:Notify({Title="🍋", Description="先にプレイヤーを選択してください", Time=2})
    Toggles.LemonSelectedKill:SetValue(false)
end
else
    StopSelectedKill()
    Library:Notify({Title="🍋", Description="選択キル: 停止", Time=2})
end
end}}

```

```

-- =====
-- Plot Break (プロット破壊)
-- =====
local PlotBreak = {Enabled=false, SelectedPlots={}, SpawnedShurikens={}, Task=nil}
local PB_Remote = {SetNetworkOwner=nil, SpawnToyRemote=nil, DestroyToyRemote=nil,
StickyPartEvent=nil}
for _, v in pairs(ReplicatedStorage:GetDescendants()) do
    if v:IsA("RemoteEvent") then
        if v.Name == "SetNetworkOwner" then PB_Remote.SetNetworkOwner = v
        elseif v.Name == "DestroyToy" then PB_Remote.DestroyToyRemote = v end
        elseif v:IsA("RemoteFunction") and v.Name == "SpawnToyRemoteFunction" then
PB_Remote.SpawnToyRemote = v end
    end
    pcall(function() PB_Remote.StickyPartEvent =
ReplicatedStorage:WaitForChild("PlayerEvents"):WaitForChild("StickyPartEvent") end)

local function PB_cleanupShurikens()
    if PB_Remote.DestroyToyRemote then
        for _, shuriken in pairs(PlotBreak.SpawnedShurikens) do
            if shuriken and shuriken.Parent then pcall(function()
PB_Remote.DestroyToyRemote:FireServer(shuriken) end) end
        end
        PlotBreak.SpawnedShurikens = {}
    end
end
local function PB_getHRP()
    if LocalPlayer.Character and LocalPlayer.Character:FindFirstChild("HumanoidRootPart")
then return LocalPlayer.Character.HumanoidRootPart
    else local character = LocalPlayer.CharacterAdded:Wait() return
character:WaitForChild("HumanoidRootPart") end
end
local function PB_CheckForHome()
    if not Workspace.PlotItems.PlayersInPlots:FindFirstChild(LocalPlayer.Name) then return
false end

```

```

for _, v in pairs(Workspace.Plots:GetChildren()) do
    if v:FindFirstChild("PlotSign") then
        local sign = v.PlotSign
        local owners = sign:FindFirstChild("ThisPlotsOwners")
        if owners then
            for _, b in pairs(owners:GetChildren()) do
                if b.Value == LocalPlayer.Name then
                    local folder = Workspace.PlotItems:FindFirstChild(v.Name)
                    if folder then return true, folder end
                end
            end
        end
    end
end
return false
end

local function PB_startLoop()
    PB_cleanupShurikens()
    local plr = LocalPlayer
    if not plr then return end
    local canSpawnObj = plr:FindFirstChild("CanSpawnToy")
    if not canSpawnObj then warn("[PlotBreak] CanSpawnToy not found") return end
    while PlotBreak.Enabled do
        local validPlots = {}
        for _, plotName in pairs(PlotBreak.SelectedPlots) do
            local targetPlot = Workspace.Plots:FindFirstChild(plotName)
            local plotArea = targetPlot and targetPlot:FindFirstChild("PlotArea")
            if plotArea then table.insert(validPlots, {Name=plotName, Area=plotArea}) end
        end
        local requiredCount = #validPlots
        if requiredCount == 0 then task.wait(1) continue end
        local boolik, house = PB_CheckForHome()
        local inv = Workspace:FindFirstChild(plr.Name.."SpawnedInToys")
        local targetContainer = (boolik and house) or inv
        local activeOwnShurikens = {}
        for _, s in pairs(PlotBreak.SpawnedShurikens) do if s and s.Parent then
            table.insert(activeOwnShurikens, s) end end
        PlotBreak.SpawnedShurikens = activeOwnShurikens
        local currentOwnCount = #PlotBreak.SpawnedShurikens
        if currentOwnCount < requiredCount then
            local neededSpawns = requiredCount - currentOwnCount
            for i = 1, neededSpawns do
                if not PlotBreak.Enabled then break end
                local preExisting = {}
                if targetContainer then
                    for _, child in pairs(targetContainer:GetChildren()) do
                        if child.Name == "NinjaShuriken" then table.insert(preExisting, child) end
                    end
                end
            end
        end
    end
end

```

```

end
local t = tick()
while not canSpawnObj.Value do
    if not PlotBreak.Enabled then break end
    if tick() - t > 3 then break end
    task.wait(0.01)
end
if not PlotBreak.Enabled then break end
local currentHRP = PB_getHRP()
if currentHRP and PB_Remote.SpawnToyRemote then
    task.spawn(function()
        pcall(function() PB_Remote.SpawnToyRemote:InvokeServer("NinjaShuriken",
currentHRP.CFrame * CFrame.new(0,2,8), Vector3.zero) end)
    end)
end
local newShuriken = nil
if targetContainer then
    local searchStart = tick()
    while tick() - searchStart < 2 do
        for _, child in pairs(targetContainer:GetChildren()) do
            if child.Name == "NinjaShuriken" and not table.find(preExisting, child) and
not table.find(PlotBreak.SpawnedShurikens, child) then
                newShuriken = child
                break
            end
        end
        if newShuriken then
            if PB_Remote.SetNetworkOwner then
                local soundPart = newShuriken:FindFirstChild("SoundPart")
                if soundPart then
                    task.spawn(function() pcall(function()
PB_Remote.SetNetworkOwner:FireServer(soundPart, soundPart.CFrame) end) end)
                end
            end
            break
        end
    end
    task.wait()
end
if newShuriken then
    table.insert(PlotBreak.SpawnedShurikens, newShuriken)
    local targetPlotData = validPlots[#PlotBreak.SpawnedShurikens]
    if targetPlotData and newShuriken:FindFirstChild("StickyPart") and
PB_Remote.StickyPartEvent then
        pcall(function()
            PB_Remote.StickyPartEvent:FireServer(newShuriken.StickyPart,
targetPlotData.Area,
CFrame.new(999999999600,999999999600,999999999600,1,0,0,0,1,0,0,0,1))

```

```

        end)
    end
end
task.wait(0.05)
end
end
if not PlotBreak.Enabled then PB_cleanupShurikens() break end
local waitTime = 0.5
local elapsed = 0
while elapsed < waitTime do
    if not PlotBreak.Enabled then PB_cleanupShurikens() break end
    task.wait(0.05)
    elapsed = elapsed + 0.05
end
end
end
end

```

```

local PlotBreakTab = Tabs.PlotBreak
local PlotSelectGroup = PlotBreakTab:AddLeftGroupbox("🏠 プロット選択")
local plotDropdown = PlotSelectGroup:AddDropdown("PlotBreakSelect",
{Values={"Plot1","Plot2","Plot3","Plot4","Plot5"}, Default={}, Multi=true, Text="プロット選択",
Callback=function(Options)
    PlotBreak.SelectedPlots = {}
    for _, plot in pairs(Options) do table.insert(PlotBreak.SelectedPlots, plot) end
end})
local PlotControlGroup = PlotBreakTab:AddRightGroupbox("🎮 コントロール")
local plotBreakToggle = PlotControlGroup:AddToggle("PlotBreakToggle", {Text="🏠 プロット破壊", Default=false, Callback=function(Value)
    PlotBreak.Enabled = Value
    if PlotBreak.Enabled then
        if #PlotBreak.SelectedPlots == 0 then
            notify("エラー", "少なくとも1つのプロットを選択してください", 3)
            PlotBreak.Enabled = false
            if plotBreakToggle and plotBreakToggle.SetValue then
                plotBreakToggle:SetValue(false) end
            return
        end
        notify("プロット破壊", "起動しました", 3)
        if PlotBreak.Task then task.cancel(PlotBreak.Task) PlotBreak.Task = nil end
        PlotBreak.Task = task.spawn(PB_startLoop)
    else
        if PlotBreak.Task then task.cancel(PlotBreak.Task) PlotBreak.Task = nil end
        PB_cleanupShurikens()
        notify("プロット破壊", "停止しました", 3)
    end
end})
PlotControlGroup:AddButton({Text="🗡️ 手裏剣クリーンアップ", Func=function()
PB_cleanupShurikens() notify("クリーンアップ", "全ての手裏剣を削除しました", 3) end})

```

```

PlotSelectGroup:AddButton({Text=" プロットリスト更新", Func=function()
    local plotNames = {"Plot1","Plot2","Plot3","Plot4","Plot5"}
    local existingPlots = {}
    for _, name in pairs(plotNames) do if Workspace.Plots:FindFirstChild(name) then
table.insert(existingPlots, name) end end
    if #existingPlots == 0 then existingPlots = plotNames end
    plotDropdown:SetValues(existingPlots)
    notify("プロット", "リストを更新しました", 2)
end})

-- =====
-- Backpack (おんぶ)
-- =====

local BackpackTab = Tabs.Backpack
local BackpackLeftGroup = BackpackTab:AddLeftGroupbox(" ターゲット選択")
local BackpackRightGroup = BackpackTab:AddRightGroupbox(" おんぶ")
local backpackActive = false
local backpackTask = nil
local backpackTargetName = ""
local BP_HEAD_POS = Vector3.new(0,1.5,0)
local BP_LARM_POS = Vector3.new(-1.5,0.5,-0.5)
local BP_RARM_POS = Vector3.new(1.5,0.5,-0.5)
local BP_LLEG_POS = Vector3.new(-1,-1.7,-0.7)
local BP_RLEG_POS = Vector3.new(1,-1.7,-0.7)
local BP_HEAD_ANG = Vector3.new(0,0,0)
local BP_LARM_ANG = Vector3.new(90,0,0)
local BP_RARM_ANG = Vector3.new(90,0,0)
local BP_LLEG_ANG = Vector3.new(80,45,-35)
local BP_RLEG_ANG = Vector3.new(80,-45,35)

local function GetBackpackPlayerList()
    local opts = {}
    for _, p in pairs(PS:GetPlayers()) do if p ~= LocalPlayer then table.insert(opts,
p.DisplayName.." ("..p.Name..")" end end
    return opts
end
local function GetBackpackUserName(displayString)
    if not displayString or displayString == "" then return nil end
    local startPos = string.find(displayString, "%(")
    if startPos then return string.sub(displayString, startPos+1, -2) end
    return nil
end
local backpackDropdown = BackpackLeftGroup:AddDropdown("BackpackTargetSelect",
{Text="プレイヤー選択", Default="", Values=GetBackpackPlayerList(),
Callback=function(selected)
    local userName = GetBackpackUserName(selected)
    if userName then backpackTargetName = userName end
end})

```

```

local function UpdateBackpackList()
backpackDropdown:SetValues(GetBackpackPlayerList()) end
PS.PlayerAdded:Connect(function() task.wait(0.5) UpdateBackpackList() end)
PS.PlayerRemoving:Connect(function() task.wait(0.2) UpdateBackpackList() end)
task.spawn(function() task.wait(1) UpdateBackpackList() end)

local function BackpackClaimNetwork(part) pcall(function()
RS.GrabEvents.SetNetworkOwner:FireServer(part, part.CFrame) end) end
local backpackNoclipConnection = nil
local function BackpackEnableNoclip(targetChar)
    if backpackNoclipConnection then backpackNoclipConnection:Disconnect() end
    if not targetChar then return end
    for _, part in pairs(targetChar:GetDescendants()) do if part:IsA("BasePart") then
part.CanCollide = false end end
    backpackNoclipConnection = targetChar.DescendantAdded:Connect(function(part) if
part:IsA("BasePart") then part.CanCollide = false end end)
end
local function BackpackDisableNoclip(targetChar)
    if backpackNoclipConnection then backpackNoclipConnection:Disconnect() end
    if not targetChar then return end
    for _, part in pairs(targetChar:GetDescendants()) do if part:IsA("BasePart") then
part.CanCollide = true end end
end
local function BackpackMainLoop()
    while backpackActive do
        local target = PS:FindFirstChild(backpackTargetName)
        if not target then task.wait(0.5) continue end
        local targetChar = target.Character
        if not targetChar then task.wait(0.1) continue end
        local tHRP = targetChar:FindFirstChild("HumanoidRootPart")
        local tHum = targetChar:FindFirstChild("Humanoid")
        if not tHRP or not tHum or tHum.Health <= 0 then task.wait(0.1) continue end
        BackpackEnableNoclip(targetChar)
        local myChar = LocalPlayer.Character
        local myHRP = myChar and myChar:FindFirstChild("HumanoidRootPart")
        if not myHRP then task.wait(0.1) continue end
        while backpackActive do
            local target = PS:FindFirstChild(backpackTargetName)
            if not target then break end
            local tChar = target.Character
            if not tChar then break end
            local tHRP = tChar:FindFirstChild("HumanoidRootPart")
            local tHum = tChar:FindFirstChild("Humanoid")
            if not tHRP or not tHum then break end
            if tHum.Health <= 0 then break end
            BackpackEnableNoclip(tChar)
            local myChar = LocalPlayer.Character
            local myHRP = myChar and myChar:FindFirstChild("HumanoidRootPart")

```

```

        if not myHRP then break end
        local baseCF = myHRP.CFrame * CFrame.new(0,1,1.5)
        tHRP.CFrame = baseCF
        tHRP.Velocity = Vector3.zero
        local head = tChar:FindFirstChild("Head")
        if head then head.CFrame = baseCF *
CFrame.new(BP_HEAD_POS.X,BP_HEAD_POS.Y,BP_HEAD_POS.Z) *
CFrame.Angles(math.rad(BP_HEAD_ANG.X),math.rad(BP_HEAD_ANG.Y),math.rad(BP_H
EAD_ANG.Z)) end
        local leftArm = tChar:FindFirstChild("Left Arm")
        if leftArm then leftArm.CFrame = baseCF *
CFrame.new(BP_LARM_POS.X,BP_LARM_POS.Y,BP_LARM_POS.Z) *
CFrame.Angles(math.rad(BP_LARM_ANG.X),math.rad(BP_LARM_ANG.Y),math.rad(BP_L
ARM_ANG.Z)) end
        local rightArm = tChar:FindFirstChild("Right Arm")
        if rightArm then rightArm.CFrame = baseCF *
CFrame.new(BP_RARM_POS.X,BP_RARM_POS.Y,BP_RARM_POS.Z) *
CFrame.Angles(math.rad(BP_RARM_ANG.X),math.rad(BP_RARM_ANG.Y),math.rad(BP_R
ARM_ANG.Z)) end
        local leftLeg = tChar:FindFirstChild("Left Leg")
        if leftLeg then leftLeg.CFrame = baseCF *
CFrame.new(BP_LLEG_POS.X,BP_LLEG_POS.Y,BP_LLEG_POS.Z) *
CFrame.Angles(math.rad(BP_LLEG_ANG.X),math.rad(BP_LLEG_ANG.Y),math.rad(BP_LL
EG_ANG.Z)) end
        local rightLeg = tChar:FindFirstChild("Right Leg")
        if rightLeg then rightLeg.CFrame = baseCF *
CFrame.new(BP_RLEG_POS.X,BP_RLEG_POS.Y,BP_RLEG_POS.Z) *
CFrame.Angles(math.rad(BP_RLEG_ANG.X),math.rad(BP_RLEG_ANG.Y),math.rad(BP_R
LEG_ANG.Z)) end
        BackpackClaimNetwork(tHRP)
        RunService.Heartbeat:Wait()
    end
    BackpackDisableNoclip(targetChar)
    task.wait(0.1)
end
end
BackpackRightGroup:AddToggle("BackpackToggle", {Text="🎒 おんぶ", Default=false,
Callback=function(Value)
    backpackActive = Value
    if Value then
        if backpackTargetName and backpackTargetName ~= "" then
            backpackTask = task.spawn(BackpackMainLoop)
            Library:Notify({Title="🎒 おんぶ", Description="開始: "..backpackTargetName,
Duration=3})
        else
            backpackActive = false
            Toggles.BackpackToggle:SetValue(false)
        end
    end
end
end

```

```

        Library:Notify({Title="エラー", Description="先にターゲットを選択してください",
Duration=3})
    end
    else
        if backpackTask then task.cancel(backpackTask) backpackTask = nil end
        local target = PS:FindFirstChild(backpackTargetName)
        if target and target.Character then BackpackDisableNoclip(target.Character) end
        Library:Notify({Title="🎒 おんぶ", Description="停止", Duration=2})
    end
end}})

```

```

-- =====
-- UI Settings (UI設定)
-- =====

```

```

local MenuGroup = Tabs["UI Settings"]:AddLeftGroupbox("⚙️ メニュー設定")
MenuGroup:AddButton("アンロード", function() Library:Unload() end)
MenuGroup:AddLabel("メニューキーバインド"):AddKeyPicker("MenuKeybind",
{Default="RightShift", NoUI=true, Text="メニューキー"})
Library.ToggleKeybind = Options.MenuKeybind
ThemeManager:SetLibrary(Library)
SaveManager:SetLibrary(Library)
SaveManager:IgnoreThemeSettings()
SaveManager:SetIgnoreIndexes({"MenuKeybind"})
ThemeManager:SetFolder("LemoneeHub")
SaveManager:SetFolder("LemoneeHub/Configs")
SaveManager:BuildConfigSection(Tabs["UI Settings"])
ThemeManager:ApplyToTab(Tabs["UI Settings"])

```

```

-- =====
-- BlackHole & Kick 検出 (緑フラッシュ + 雷エフェクト)
-- =====

```

```

local variants =
{"BlackHole","Black_Hole","Blackhole","Black-Hole","BHole","BH","VoidHole","Void","VoidSp
here","DarkHole","DarkSphere","DarkOrb","GravityHole","GravityOrb","SpaceHole","SpaceO
rb","Singularity","SingularityOrb","EventHorizon","BlackSphere","Anomaly","AnomalyHole","S
upermassiveHole","QuantumHole"}
local kickVariants =
{"Kick","KickObject","KickPart","KickEffect","Kick_Effect","KickEvent","KickNotify","KickBlob"}

```

```

local function isBlackHole(obj)
    for _,v in ipairs(variants) do if obj.Name:lower() == v:lower() then return true end end
    return false
end

```

```

local function isKickObject(obj)
    for _,v in ipairs(kickVariants) do if obj.Name:lower() == v:lower() then return true end end
    return false
end

```

```

local function getObjectPosition(obj)
    if obj:IsA("BasePart") then return obj.Position end
    local part = obj:FindFirstChildWhichIsA("BasePart", true)
    if part then return part.Position end
    return nil
end

```

```

local function getClosestPlayer(pos)
    local closest = nil
    local dist = math.huge
    for _,plr in pairs(Players:GetPlayers()) do
        local hrp = plr.Character and plr.Character:FindFirstChild("HumanoidRootPart")
        if hrp then
            local d = (hrp.Position - pos).Magnitude
            if d < dist then dist = d closest = plr.Name end
        end
    end
    return closest or "不明"
end

```

```

local function createLightningEffect(position, count)
    count = count or 5
    local camera = workspace.CurrentCamera
    local origin = camera.CFrame.Position

    for i = 1, count do
        task.spawn(function()
            local direction = (position - origin).Unit + Vector3.new(
                (math.random() - 0.5) * 30,
                (math.random() - 0.5) * 20,
                (math.random() - 0.5) * 30
            )
            local endPos = position + direction * (10 + math.random() * 20)

            local beam = Instance.new("Beam")
            beam.Color = ColorSequence.new(Color3.fromRGB(0, 255, 50))
            beam.Width0 = 0.5
            beam.Width1 = 0.5
            beam.Transparency = NumberSequence.new(0)
            beam.LightEmission = 1
            beam.LightInfluence = 1
            beam.FaceCamera = true

            local att1 = Instance.new("Attachment")
            local att2 = Instance.new("Attachment")
            att1.Position = Vector3.zero
            att2.Position = endPos - origin
        end)
    end
end

```

```

local dummy = Instance.new("Part")
dummy.Anchored = true
dummy.CanCollide = false
dummy.Transparency = 1
dummy.Size = Vector3.one
dummy.CFrame = CFrame.new(origin)
dummy.Parent = workspace

att1.Parent = dummy
att2.Parent = dummy
beam.Attachment0 = att1
beam.Attachment1 = att2
beam.Parent = dummy

local start = tick()
while tick() - start < 0.3 do
    local alpha = (tick() - start) / 0.3
    beam.Transparency = NumberSequence.new(alpha)
    task.wait(0.02)
end
dummy:Destroy()
end)
end

workspace.ChildAdded:Connect(function(obj)
    local isBH = isBlackHole(obj)
    local isKO = isKickObject(obj)
    if isBH or isKO then
        task.wait(0.05)
        local pos = getObjectPosition(obj)
        if not pos then return end
        local closest = getClosestPlayer(pos)
        local title = isBH and "キック通知 (ブラックホール)" or "キック通知 (キックオブジェクト)"
        Library.Notify({Title=title, Description="キックされた: "..closest, Time=6.5})
        screenFlash(Color3.fromRGB(0, 255, 0), 0.5)
        createLightningEffect(pos, 6)
    end
end)

-- =====
-- Heart Sparkler (ハート)
-- =====
local heartHighRun = false
local heartConnection = nil
local heartToy = nil
MiscGroup:AddToggle("HeartSparklerHigh", {Text="💖 ハート", Default=false,
Callback=function(Value)

```

```

heartHighRun = Value
local RS = game:GetService("ReplicatedStorage")
local RunService = game:GetService("RunService")
local player = game.Players.LocalPlayer
if Value then
    task.spawn(function()
        if not player.Character then return end
        local hrp = player.Character:FindFirstChild("HumanoidRootPart")
        if not hrp then return end
        pcall(function()
            RS.MenuToys.SpawnToyRemoteFunction:InvokeServer("FireworkSparkler", hrp.CFrame *
            CFrame.new(0,50,0), Vector3.zero) end)
        local folderName = player.Name.."SpawnedInToys"
        local folder = workspace:WaitForChild(folderName, 5)
        if not folder then return end
        heartToy = folder:WaitForChild("FireworkSparkler", 5)
        if not heartToy then return end
        local part = heartToy:FindFirstChild("Handle") or
        heartToy:FindFirstChildWhichIsA("BasePart")
        if not part then return end
        task.wait(0.2)
        for _, v in pairs(heartToy:GetDescendants()) do
            if v:IsA("BasePart") then v.Anchored = false v.CanCollide = false v.Massless = true
        end
        end
        part:BreakJoints()
        local bp = Instance.new("BodyPosition")
        bp.MaxForce = Vector3.new(math.huge,math.huge,math.huge)
        bp.P = 20000
        bp.D = 500
        bp.Parent = part
        local bg = Instance.new("BodyGyro")
        bg.MaxTorque = Vector3.new(math.huge,math.huge,math.huge)
        bg.P = 3000
        bg.CFrame = CFrame.new()
        bg.Parent = part
        local t = 0
        if heartConnection then heartConnection:Disconnect() end
        heartConnection = RunService.Heartbeat:Connect(function(dt)
            if not heartHighRun or not part or not part.Parent then
                if heartConnection then heartConnection:Disconnect() end
                if heartToy then pcall(function() heartToy:Destroy() end) end
                return
            end
            local currentHrp = player.Character and
            player.Character:FindFirstChild("HumanoidRootPart")
            if not currentHrp then return end

```

```

        pcall(function() RS.GrabEvents.SetNetworkOwner:FireServer(part, part.CFrame)
end)
    t = t + (8 * dt)
    local scale = 1.5
    local x = 16 * math.sin(t)^3
    local y = 13 * math.cos(t) - 5 * math.cos(2*t) - 2 * math.cos(3*t) - math.cos(4*t)
    local relPos = Vector3.new(x*scale, (y*scale)+25, 3)
    local finalPos = currentHrp.CFrame:PointToWorldSpace(relPos)
    bp.Position = finalPos
    bg.CFrame = currentHrp.CFrame
end)
end)
else
    if heartConnection then heartConnection:Disconnect() heartConnection = nil end
    if heartToy then pcall(function() heartToy:Destroy() end) heartToy = nil end
end
end})

```

```

-- =====
-- Anchor Object (アンカー)
-- =====
MiscGroup:AddLabel("アンカーキーバインド"):AddKeyPicker("AnchorObjectKey", {
    Default = "G",
    Text = "アンカー",
    NoUI = false,
    Callback = function()
        local original = workspace:FindFirstChild("GrabParts")
        if not original then return end
        local grabPart = original:FindFirstChild("GrabPart", true)
        if not grabPart or not grabPart:IsA("BasePart") then return end
        local wasCollide = grabPart.CanCollide
        grabPart.CanCollide = true
        task.wait(0.1)
        local targetModel = nil
        local touchingParts = grabPart:GetTouchingParts()
        if #touchingParts == 0 then grabPart.CanCollide = wasCollide return end
        for _, part in ipairs(touchingParts) do
            if not part:IsDescendantOf(original) then
                local current = part
                while current and current ~= workspace do
                    if current:IsA("Model") then targetModel = current break end
                    current = current.Parent
                end
                if targetModel then break end
            end
        end
        grabPart.CanCollide = wasCollide
        if not targetModel then return end
    end
end

```

```

if not targetModel.Parent then
    local found = false
    local connection
    connection = targetModel.AncestryChanged:Connect(function(_, parent)
        if parent then found = true connection:Disconnect() end
    end)
    local startTime = tick()
    while not found and tick() - startTime < 2 do task.wait(0.1) end
    if not found then return end
end
local existing = targetModel:FindFirstChild("CleanedGrabParts")
if existing then
    local existingHighlight = targetModel:FindFirstChild("AnchorHighlight")
    if existingHighlight then existingHighlight:Destroy() end
    existing:Destroy()
    return
end
local clone = original:Clone()
clone.Name = "CleanedGrabParts"
for _, desc in ipairs(clone:GetDescendants()) do
    if desc:IsA("BasePart") then
        desc.Transparency = 1
        desc.CanCollide = false
        local beam = desc:FindFirstChild("GrabBeam")
        if beam then beam:Destroy() end
        for _, sName in
            ipairs({"AttachSound1", "AttachSound", "BeamSound", "BeamSound1"}) do
                local sound = desc:FindFirstChild(sName)
                if sound then sound:Destroy() end
            end
        end
    end
end
clone.Parent = targetModel
local hl = Instance.new("Highlight")
hl.Name = "AnchorHighlight"
hl.FillColor = Color3.fromRGB(0,85,255)
hl.FillTransparency = 0.4
hl.OutlineColor = Color3.fromRGB(0,170,255)
hl.OutlineTransparency = 0.7
hl.Adornee = targetModel
hl.Parent = targetModel
local connection
connection = game:GetService("RunService").Heartbeat:Connect(function()
    if not clone or not clone.Parent or not targetModel or not targetModel.Parent then
        if connection then connection:Disconnect() end
        return
    end
    if hl and hl.Parent then hl.Adornee = targetModel

```

```

        else connection:Disconnect() end
    end)
end
})

-- =====
-- クリーンアップ関数
-- =====
local function disableAllFeatures()
    LemonKill.isRunning = false
    LemonKill.isKillAura = false
    LemonKill.isSelectedKill = false
    if LemonKill.killAuraConnection then LemonKill.killAuraConnection:Disconnect() end
    if LemonKill.selectedKillConnection then LemonKill.selectedKillConnection:Disconnect()
end
    if LemonKill.selectedPlayerConnection then
LemonKill.selectedPlayerConnection:Disconnect() end
        if LemonKill.selectedKillAuraConnection then
LemonKill.selectedKillAuraConnection:Disconnect() end

    RainbowEffect.Enabled = false
    RainbowESP.Enabled = false
    RemoveAllRainbowBoxes()

    backpackActive = false
    if backpackTask then task.cancel(backpackTask) backpackTask = nil end

    PlotBreak.Enabled = false
    if PlotBreak.Task then task.cancel(PlotBreak.Task) PlotBreak.Task = nil end
    PB_cleanupShurikens()

    updownKickActive = false
    if updownKickTask then task.cancel(updownKickTask) updownKickTask = nil end

    Library:Unload()

    for _, v in pairs(CoreGui:GetChildren()) do
        if v:IsA("ScreenGui") then
            v:Destroy()
        end
    end

    notify("🔄 アンロード", "れもに一HUBを手動で停止しました。", 5)
end

-- =====
-- 制限時間なし(無期限)
-- =====

```

```
print("🕒 制限時間なし: 無期限で使用可能です。")
```

```
-- =====
```

```
-- 終了時クリーンアップ
```

```
-- =====
```

```
game:BindToClose(function()
    LemonKill.isRunning = false
    LemonKill.isKillAura = false
    LemonKill.isSelectedKill = false
    if LemonKill.killAuraConnection then LemonKill.killAuraConnection:Disconnect() end
    if LemonKill.selectedKillConnection then LemonKill.selectedKillConnection:Disconnect()
end
    if LemonKill.selectedPlayerConnection then
LemonKill.selectedPlayerConnection:Disconnect() end
    if LemonKill.selectedKillAuraConnection then
LemonKill.selectedKillAuraConnection:Disconnect() end
    RainbowEffect.Enabled = false
    RainbowESP.Enabled = false
    RemoveAllRainbowBoxes()
    backpackActive = false
    if backpackTask then task.cancel(backpackTask) backpackTask = nil end
    PlotBreak.Enabled = false
    if PlotBreak.Task then task.cancel(PlotBreak.Task) PlotBreak.Task = nil end
    PB_cleanupShurikens()
    updownKickActive = false
    if updownKickTask then task.cancel(updownKickTask) updownKickTask = nil end
end)
```

```
print("👉 れもにーHUB V2 (再起動防止ブロッカー付き) 完全ロード完了！")
```

```
print("🔒 パスワード認証は削除されました")
```

```
print("💜 キルエフェクトは完全に削除(メッセージのみ)")
```

```
print("👉 おんぶ・プロットブレイク・各種防御機能が有効です")
```

```
print("✅ 上下キック機能を追加しました")
```

```
print("⚡ ブラックホール & キック検出時に緑フラッシュ + 雷エフェクトを発動します。")
```

```
print("🕒 制限時間なし: 無期限で使用可能です。")
```

```
print("🚫 2回目の実行はブロックされます。")
```

```
print("🇯🇵 UIは完全日本語化されています。")
```