

# Quiz 5: Relational Algebra Quiz

**Due** Feb 19 at 2:59am**Points** 100**Questions** 18**Available** Feb 7 at 2:59am - Feb 25 at 2:59am 18 days**Time Limit** None**Allowed Attempts** Unlimited

## Instructions

## Instructions

A self check on basic relational algebra concepts.

[Take the Quiz Again](#)

## Attempt History

	Attempt	Time	Score
KEPT	<a href="#">Attempt 4</a>	13 minutes	85 out of 100
LATEST	<a href="#">Attempt 4</a>	13 minutes	85 out of 100
	<a href="#">Attempt 3</a>	96 minutes	65 out of 100
	<a href="#">Attempt 2</a>	4 minutes	20 out of 100
	<a href="#">Attempt 1</a>	299 minutes	15 out of 100

! Correct answers are hidden.

Score for this attempt: **85** out of 100

Submitted Feb 18 at 3:56pm

This attempt took 13 minutes.

### Question 1

**15 / 15 pts**

Identify these Relational Algebra operators

$\sigma$

SELECT

 $\pi$ 

PROJECT

 $\bowtie$ 

JOIN



## Question 2

5 / 5 pts

Which query best represents this relational algebra statement:

$$\Pi_{d,f}(\sigma_{Foo.x="Bear"}((Foo \bowtie_{Foo.x=Bar.z} Bar) \bowtie_{Foo.x=Baz.z} Baz))$$

SELECT Foo.d, Foo.f FROM Foo

INNER JOIN Bar ON Foo.x = Bar.z

INNER JOIN Baz ON Foo.x = Baz.z

☐ WHERE Foo.x = "Bear";

SELECT d, f FROM Bar

INNER JOIN Baz ON Foo.x = Baz.z

INNER JOIN Foo ON Foo.x = Bar.z

☐ WHERE Foo.x = "Bear";

SELECT d, f FROM Foo

INNER JOIN Bar ON Foo.x = Bar.z

INNER JOIN Baz ON Foo.x = Baz.z

☒ WHERE Foo.x = "Bear";

SELECT \* FROM Bar

INNER JOIN Baz ON Foo.x = Baz.z

INNER JOIN Foo ON Foo.x = Bar.z

☐ WHERE Foo.x = "Bear";

**Question 3****5 / 5 pts**

Which query best represents this relational algebra statement:

$$\sigma_{Foo.a < 100} (Foo \bowtie_{Foo.b = Bar.c} Bar)$$

SELECT Foo.a FROM Foo

INNER JOIN Bar ON Foo.b = Bar.c

☐ WHERE Foo.a < 100;

SELECT a FROM Foo

INNER JOIN Bar

☐ WHERE Foo.a < 100;

SELECT Foo.a FROM Foo

INNER JOIN Bar

☐ WHERE Foo.a < 100;

SELECT \* FROM Foo

INNER JOIN Bar ON Foo.b = Bar.c

☒ WHERE Foo.a < 100;

**Question 4****5 / 5 pts**

Which relational algebra command creates a new table where only certain columns are to be included?

☒ PROJECT

☐ SELECT

☐ DELETE

☐ PROGRAM

**Question 5****5 / 5 pts**

Which command contains all rows that are similar in two different tables?

☒ INTERSECT

☐ JOIN

☐ DIFFERENCE

☐ UNION

**Incorrect****Question 6****0 / 5 pts**

Two tables are \_\_\_\_\_ compatible if they have the same number of columns with the same types of corresponding data?

☒ INTERSECTION

☐ JOIN

☐ DIFFERENCE

☐ UNION

**Question 7****5 / 5 pts**

Based on this table:

```
Vehicle(vehicle_id, year, make_id, model_id)
```

Which command will list all information from Vehicle with the vehicle\_id of the value '3'?

- ☐ SELECT Vehicle '3' GIVING Answer
- ☒ SELECT Vehicle WHERE vehicle\_id=3 GIVING Answer
- ☐ SELECT Vehicle GIVING Answer WHERE vehicle\_id='3'
- ☐ SELECT Vehicle WHERE vehicle\_id='3' RESULTS Answer

Incorrect

### Question 8

0 / 5 pts

Based on the table:

```
Vehicle(vehicle_id, year, make_id, model_id)
```

Which command creates a new table named 'Make' that contains the fields 'make\_id' and 'year'?

- ☐ JOIN Vehicle WITH (make\_id, year) GIVING Make
- ☒ INNER JOIN Vehicle FROM Make WITH (make\_id, year)
- ☐ PROJECT Vehicle OVER (make\_id, year) GIVING Make

- ☐ SELECT Vehicle OVER (make\_id, year) GIVING Make

**Question 9****5 / 5 pts**

Based on the following tables:

Vehicle(vehicle\_id, year, make\_id, year, model\_id)

Make(make\_id, make\_name, country)

Which command creates a new table named Inventory that combines Vehicle and Make tables based on make\_id?



JOIN Vehicle Make WHERE Vehicle.make\_id=Make.make\_id GIVING Inventory



SELECT Vehicle Make WHERE Vehicle.make\_id=Make.make\_id MAKING Inventory



UNION Vehicle Make JOIN Vehicle.make\_id=Make.make\_id GIVING Inventory



PROJECT Vehicle Make WHERE Vehicle.make\_id=Make.make\_id MAKING Inventory

Incorrect

**Question 10****0 / 5 pts**

Which query below will return a number of row(s) where make\_id field contains '1' from Vehicle and provides a total of the price field?

- ☐ SELECT COUNT(\*), SUM(price) FROM Vehicle WHERE make\_id='1';
- ☐ SELECT FROM Vehicle SUM(price) WHERE make\_id='1' COUNT(\*);
- ☐ SELECT FROM Vehicle COUNT(price) SUM(\*) WHERE make\_id='1';
- ☒ SELECT COUNT(\*) WHERE make\_id='1' SUM(price) FROM Vehicle;

**Question 11****5 / 5 pts**

Which query will return the row(s) with the make\_id field containing '1' from the table Vehicle?

- ☐ SELECT FROM Vehicle COUNT(\*) WHERE make\_id='1';
- ☐ SELECT COUNT(\*) WHERE make\_id='1' FROM Vehicle;
- ☒ SELECT COUNT(\*) FROM Vehicle WHERE make\_id='1';
- ☐ SELECT FROM Vehicle WHERE make\_id='1' COUNT(\*);

**Question 12****5 / 5 pts**

When using SQL, the SELECT condition is typically specified in which clause of a query?

☒ WHERE

☐ IF

☐ FROM

☐ NOT

### Question 13

5 / 5 pts

Relational Algebra Identification Equations: Identify the best equation

PROJECT Inventory WHERE price is less than 8500

☐  $\pi ( \text{price} < 8500 ) \sigma \text{Inventory}$

☒  $\pi ( \sigma ( \text{price} < 8500 ) \text{Inventory} )$

☐  $\pi ( \sigma \text{Inventory} ( \text{price} < 8500 ) )$

☐  $\pi_{\text{Inventory}} ( \sigma_{\text{price} < 8500} )$

### Question 14

5 / 5 pts

Relational Algebra Identification Equations: Identify the best equation



JOIN make\_id (Vehicle, Make) NEW MakeInfo

- ☐ MakeInfo =  $\sigma_{\text{Vehicle}} \bowtie \sigma_{\text{Make}}$
- ☐ Vehicle  $\bowtie$  Make  $\pi_{\text{MakeInfo}}$
- ☐ Vehicle  $\bowtie$  Make  $\pi_{\text{MakeInfo}}$
- ☒ MakeInfo := Vehicle  $\bowtie$  Make

### Question 15

5 / 5 pts

Relational Algebra Identification Equations: Identify the best equation

SELECT Vehicle WHERE vehicle\_id=3

- ☐  $\sigma_{\text{make\_id}, 3}(\text{Vehicle})$
- ☐  $\bowtie_{\text{vehicle\_id} = "3"}(\text{Vehicle})$
- ☐  $\sigma_{\text{Vehicle}} = 3(\text{vehicle\_id})$
- ☒  $\sigma_{\text{vehicle\_id} = "3"}(\text{Vehicle})$

### Question 16

5 / 5 pts

Relational Algebra Identification Equations: Identify the best equation

```
SELECT Make WHERE make_id=2
```

☒  $\sigma_{\text{make\_id} = "2"}(\text{Make})$

☐  $\sigma_{\text{Make} = 2}(\text{make\_id})$

☐  $\pi_{\text{make\_id} = "2"}(\sigma_{\text{Make}})$

☐  $\sigma_{\text{make\_id} \bowtie 2}(\text{Make})$

### Question 17

5 / 5 pts

Relational Algebra Identification Equations: Identify the best equation

```
PROJECT Vehicle OVER (make_id, year)
```

☐  $\pi_{\text{Vehicle}}(\text{make\_id, year})$

☒  $\pi_{\text{make\_id, year}}(\text{Vehicle})$

☐  $\pi_{\text{make\_id, year}} \sigma_{\text{Vehicle}}$

☐  $\sigma_{\text{make\_id, year}} \pi_{\text{Vehicle}}$

### Question 18

5 / 5 pts

If we wanted to retrieve data from an employee database for all employees that work in department # 5.

Which single relational algebra expression would be best matched to display the employees first name, last name, and total salary using the following EMPLOYEE table headings?

empid	lastname	firstname	department	salaryrate	salary
-------	----------	-----------	------------	------------	--------

☐

$\sigma \text{ } \textit{firstname, lastname, salary} (\pi \textit{ department} = 5 (\textit{EMPLOYEE}))$

☒

$\pi \textit{ firstname, lastname, salary} (\sigma \textit{ department} = 5 (\textit{EMPLOYEE}))$

☐

$\Theta \textit{ firstname, lastname, salary} (\sigma \textit{ department} = 5 (\textit{EMPLOYEE}))$

☐

$\pi \textit{ firstname, lastname, salary} (\sigma \textit{ EMPLOYEE, department} = 5)$

Quiz Score: **85** out of 100